



Cypress Semiconductor Corporation, 198 Champion Court San Jose, CA 95134. Tel: (408) 943-2600

PRODUCT CHANGE NOTIFICATION

PCN: PCN175004

Date: December 21, 2017

Subject: Qualification of Fab 25 as an Additional Wafer Fab Site and Test 25 as an Additional Wafer Sort Site for 3V/5V 1Mb Parallel nvSRAM Products

To: FUTURE ELECTRONICS
FUTURE ELE
pcn.system2@future.ca

Change Type: Major

Description of Change:

Cypress announces the qualification of Fab 25 in Austin, Texas as an additional wafer fab site and Test 25 in Austin, Texas as an additional wafer sort site for 3V/5V 1Mb Parallel nvSRAM products. No design or test program changes were made during this fab transfer. There is no change to product datasheets.

Benefit of Change:

Qualification of alternate manufacturing sites is part of the ongoing flexible manufacturing initiative announced by Cypress. The goal of the flexible manufacturing initiative is to provide the means for Cypress to continue to meet delivery commitments through dynamic, changing market conditions.

Affected Part Numbers: 61

See the attached 'Affected Parts List' file for a list of all part numbers affected by this change. Note that any new parts that are introduced after the publication of this PCN will include all changes outlined in this PCN.

Qualification Status:

This new wafer fabrication site has been qualified through a series of tests identified in the Qualification Test Plan (QTP) Report #170803. This new wafer sort site has been qualified through a series of tests identified in the Qualification Test Plan (QTP) Report #171610. The QTP reports can be found as attachments to this notification or by visiting www.cypress.com, typing the QTP number in the keyword search window.

Sample Status:

Qualification samples may not be built ahead of time for all part numbers affected by this change. Please review the attached 'Affected Parts List' file for a list of affected part numbers with their associated Fab 25 sample ordering part numbers. Samples are available now unless there is an indication that the sample ordering part numbers are subject to lead times. If you

require qualification samples, please contact your local Cypress sales representative as soon as possible, preferably within 30 days of the date of this PCN, to place any sample orders.

Approximate Implementation Date:

Effective 90 days from the date of this notification, all shipments of the affected part numbers will be fabricated at either SkyWater or Fab 25 and sorted at either SkyWater or Test 25.

Anticipated Impact:

Products fabricated at Fab 25 and sorted at Test 25 are completely compatible with existing product from a form, fit, functional, parametric and quality performance perspective.

Cypress also recommends that customers take this opportunity to review these changes against current application notes, system design considerations and customer environment conditions to assess impact (if any) to their application.

Method of Identification:

Cypress maintains traceability of product to wafer level, including wafer fabrication location, through the lot number marked on the package.

Response Required:

No response is required.

For additional information regarding this change, contact your local sales representative or contact the PCN Administrator at pcn_adm@cypress.com.

Sincerely,

Cypress PCN Administration

Item	Marketing Part Number	Sample Order Part Number
1	CY14101V-1XWI	CY14101V2-1XWI Subject to lead time
2	CY14B101KA-SP25XI	CY14B101KA2-SP25XI Subject to lead time
3	CY14B101KA-SP25XIT	CY14B101KA2-SP25XI Subject to lead time
4	CY14B101KA-SP45XI	CY14B101KA2-SP45XI Subject to lead time
5	CY14B101KA-SP45XIT	CY14B101KA2-SP45XI Subject to lead time
6	CY14B101KA- S25XI	CY14B101KA2- S25XI Subject to lead time
7	CY14B101KA- S25XIT	CY14B101KA2- S25XI Subject to lead time
8	CY14B101KA- S45XI	CY14B101KA2- S45XI
9	CY14B101KA- S45XIT	CY14B101KA2- S45XI
10	CY14B101LA-BA25XI	CY14B101LA2-BA25XI Subject to lead time
11	CY14B101LA-BA25XIT	CY14B101LA2-BA25XI Subject to lead time
12	CY14B101LA-BA45XI	CY14B101LA2-BA45XI
13	CY14B101LA-BA45XIT	CY14B101LA2-BA45XI
14	CY14B101LA-SP25XI	CY14B101LA2-SP25XI
15	CY14B101LA-SP25XIT	CY14B101LA2-SP25XI
16	CY14B101LA-SP45XI	CY14B101LA2-SP45XI
17	CY14B101LA-SP45XIT	CY14B101LA2-SP45XI
18	CY14B101LA-S 25XI	CY14B101LA2-S 25XI
19	CY14B101LA-S 25XIT	CY14B101LA2-S 25XI
20	CY14B101LA-S 45XI	CY14B101LA2-S 45XI
21	CY14B101LA-S 45XIT	CY14B101LA2-S 45XI
22	CY14B101LA- S20XI	CY14B101LA2- S20XI Subject to lead time
23	CY14B101LA- S20XIT	CY14B101LA2- S20XI Subject to lead time
24	CY14B101LA- S25XI	CY14B101LA2- S25XI Subject to lead time
25	CY14B101LA- S25XIT	CY14B101LA2- S25XI Subject to lead time
26	CY14B101LA- S45XI	CY14B101LA2- S45XI
27	CY14B101LA- S45XIT	CY14B101LA2- S45XI
28	CY14B101NA- S25XI	CY14B101NA2- S25XI Subject to lead time
29	CY14B101NA- S25XIT	CY14B101NA2- S25XI Subject to lead time
30	CY14B101NA- S45XI	CY14B101NA2- S45XI
31	CY14B101NA- S45XIT	CY14B101NA2- S45XI
32	CY14B101Q2-LHXI	CY14B101Q22-LHXI
33	CY14B101Q2-LHXIT	CY14B101Q22-LHXI
34	CY14B101Q3-SFXI	CY14B101Q32-SFXI Subject to lead time
35	CY14B256KA-SP25XI	CY14B256KA2-SP25XI Subject to lead time
36	CY14B256KA-SP25XIT	CY14B256KA2-SP25XI Subject to lead time
37	CY14B256KA-SP45XI	CY14B256KA2-SP45XI Subject to lead time
38	CY14B256KA-SP45XIT	CY14B256KA2-SP45XI Subject to lead time
39	CY14B256LA-SP25XI	CY14B256LA2-SP25XI Subject to lead time
40	CY14B256LA-SP25XIT	CY14B256LA2-SP25XI Subject to lead time
41	CY14B256LA-SP45XI	CY14B256LA2-SP45XI Subject to lead time
42	CY14B256LA-SP45XIT	CY14B256LA2-SP45XI Subject to lead time
43	CY14B256LA-S 25XI	CY14B256LA2-S 25XI
44	CY14B256LA-S 25XIT	CY14B256LA2-S 25XI
45	CY14B256LA-S 45XI	CY14B256LA2-S 45XI
46	CY14B256LA-S 45XIT	CY14B256LA2-S 45XI

47	CY14B256LA- S25XI	CY14B256LA2- S25XI Subject to lead time
48	CY14B256LA- S25XIT	CY14B256LA2- S25XI Subject to lead time
49	CY14B256Q2-LHXI	CY14B256Q22-LHXI Subject to lead time
50	CY14E256LA-S 25XI	CY14E256LA2-S 25XI
51	CY14E256LA-S 25XIT	CY14E256LA2-S 25XI
52	CY14E256LA-S 45XI	CY14E256LA2-S 45XI
53	CY14E256LA-S 45XIT	CY14E256LA2-S 45XI
54	CY14E256LA-S 45XQ	CY14E256LA2-S 45XQ Subject to lead time
55	CY14E256LA-S 45XQT	CY14E256LA2-S 45XQ Subject to lead time
56	CG7299AT	CG7299BT Subject to lead time
57	CG7299ATT	CG7299BT Subject to lead time
58	CG7702AA	CG7702BA Subject to lead time
59	CG7702AAT	CG7702BA Subject to lead time
60	CG7956AA	CG7956BA Subject to lead time
61	CG7956AAT	CG7956BA Subject to lead time

Cypress Semiconductor Corporation

CY14B101x nvSRAM Characterization Report

Design Engineering Director

David Still

dstl@cypress.com

Product Engineering Director

Shailesh Chauhan

svc@cypress.com

Product Engineer

Gokul Kumar S

gkus@cypress.com

Applications Engineer

Shivendra Singh

zsk@cypress.com

Marketing Engineer

Douglas Mitchell

dmit@cypress.com



www.cypress.com

198 Champion Ct.
San Jose, CA 95134 USA

Tel: (408) 943 2600

Fax: (408) 943 4730

Company Confidential

A printed copy of this document is considered uncontrolled. Refer to online copy for latest revision.



1.0 Table of Contents


1.0 Table of Contents.....	2
2.0 Introduction	3
2.1 General Description – CY14B101K/L/M/N	3
2.2 General Description – CY14B101P/Q	4
2.3 Pin Definitions	5
2.4 Datasheets	9
2.5 Application Notes	9
2.6 White Papers	9
2.7 Qualification Reports	9
3.0 Characterization Hardware and Setup.....	10
3.1 ATE Characterization Hardware	10
3.2 Characterization Conditions.....	10
4.0 Characterization Data	11
4.1 DC Parameters (CY14B101K/L/M/N Devices)	11
4.2 DC Parameters (CY14B101P/Q Device)	12
4.3 AC Parameters (CY14B101K/L/M/N Devices)	12
4.4 AC Parameters (CY14B101P/Q Device)	13
4.5 Store/Recall Parameters.....	13
4.6 RTC Parameters	14
Document History Page.....	15

2.0 Introduction

2.1 General Description – CY14B101K/L/M/N

The Cypress CY14B101K/L/M/N combines a 1-Mbit nonvolatile static RAM (nvSRAM) with a full-featured RTC in a monolithic integrated circuit. The embedded nonvolatile elements incorporate Quantum Trap technology producing the world's most reliable nonvolatile memory. The SRAM is read and written infinite number of times, while independent nonvolatile data resides in the nonvolatile elements. The CY14B101K and CY14B101M have the RTC function which provides an accurate clock with leap year tracking and a programmable, high accuracy oscillator. The alarm function is programmable for periodic minutes, hours, days, or months alarms. There is also a programmable watchdog timer for process control.


Figure 1: Logic Block Diagram



2.2 General Description – CY14B101P/Q

The Cypress CY14B101P/Q combines a 1-Mbit nonvolatile static RAM (nvSRAM) with a full-featured RTC in a monolithic integrated circuit with serial SPI interface. The memory is organized as 128K words of 8 bits each. The embedded nonvolatile elements incorporate Quantum Trap technology producing the world's most reliable nonvolatile memory. The SRAM is read and written infinite number of times, while independent nonvolatile data resides in the nonvolatile elements. The CY14B101P has the RTC function which provides an accurate clock with leap year tracking and a programmable, high accuracy oscillator. The alarm function is programmable for periodic minutes, hours, days, or months alarms. There is also a programmable watchdog timer for process control.

Figure 2: Logic Block Diagram



2.3 Pin Definitions

Figure 3: CY14B101K and CY14B101M – 44 TSOPII, 54TSOP II and 48-pin SSOP




Figure 4: CY14B101L and CY14B101N – 44 TSOPII




Figure 5: CY14B101L and CY14B101N – 48 SSOP & 32 SOIC




Figure 6: CY14B101L and CY14B101N – 48 FBGA & 54 TSOP II




Figure 7: CY14B101P– 16 SOIC




Figure 8: CY14B101Q– 8 DFN





Figure 9: CY14B101Q– 16 SOIC



2.4 Datasheets

The 1M-bit nvSRAM devices meet all datasheet specifications.

Device	RTC?	Datasheet
CY14B101K/M	Yes	001-42880
CY14B104L/N	No	001-42879
CY14B101P	Yes	001-44109
CY14B101Q	No	001-50091

2.5 Application Notes

Following are some of the application notes associated with the 1M-bit nvSRAM products:

- [AN43380](#) - HSB Operation in nvSRAMs
- [AN43593](#) - Storage Capacitor (VCAP) options for Cypress NVSRAM
- [AN53313](#) - Real Time Clock Calibration in Cypress nvSRAM
- [AN61546](#) - NVSRAM RTC Design guidelines and Best practices

2.6 White Papers

Following are the white papers associated with the 4M-bit/2M-bit/8M-bit nvSRAM products:

- [Nonvolatile SRAM \(NVSRAM\) basics](#)
- [NVSRAM as write journal in RAID storage systems](#)
- [Using Cypress NVSRAM as Program Memory](#)
- [Probability of Occurrence of a Soft Sequence in Asynchronous nvSRAMs](#)
- [Data Retention Performance of 130-nm nvSRAM](#)

2.7 Qualification Reports

The CY14B101x device is qualified under QTP 170803. The qualification reports are available from the Cypress website at <http://www.cypress.com> (Specific website URL is TBD).

3.0 Characterization Hardware and Setup

3.1 ATE Characterization Hardware

Temperature Forcing System

The Temptronic XStream 4300 was used to force all the required temperatures.

ATE Testers

Advantest T5581 tester was used to characterize the DC, AC, SPI and Store/Recall parameters.

Nextest Magnum1 tester was used to characterize the RTC parameters.

3.2 Characterization Conditions

All units were tested across 2.7V to 3.6V in addition to a +/- 100mV guardband. The temperature range for the characterization was from -45C to 90C. A guardband of +/-5C was used.

4.0 Characterization Data

This characterization report compares devices from the FAB4 (SkyWater) which is the old Cypress fab at Bloomington, MN, U.S.A. to the new FAB25 (Cypress) at Austin, TX, U.S.A.

4.1 DC Parameters (CY14B101K/L/M/N Devices)

Parameter	Name	Test Conditions	Datasheet			Fab4		Fab25		Unit
			Min	Typ	Max	Min	Max	Min	Max	
ICC1	Average VCC current	tRC = 20 ns, Values obtained without output loads (IOUT = 0 mA)	-	-	70	30.00	40.00	39.90	42.80	mA
		tRC = 25 ns, Values obtained without output loads (IOUT = 0 mA)	-	-	70	26.40	35.60	36.80	39.60	mA
		tRC = 45 ns, Values obtained without output loads (IOUT = 0 mA)	-	-	52	20.80	28.00	29.20	31.20	mA
ICC2	Average VCC current during STORE	All inputs don't care, VCC = Max. Average current for duration tSTORE	-	-	10	3.20	6.00	3.20	4.80	mA
ICC3	Average VCC current at tRC=200ns, VCC (Typ), 25 °C	All inputs cycling at CMOS Levels. Values obtained without output loads (IOUT = 0 mA).	-	35	-	14.80	20.80	21.60	23.60	mA
ICC4 ^[1]	Average VCAP current during AutoStore cycle	All inputs don't care. Average current for duration tSTORE	-	-	5	4.20	4.80	3.60	4.40	mA
ISB	VCC standby current	CE# > (VCC – 0.2 V). VIN < 0.2 V or > (VCC – 0.2 V). 'W' bit set to '0'. Standby current level after nonvolatile cycle is complete. Inputs are static. f = 0 MHz.	-	-	5	1.20	4.00	1.20	2.56	mA
IIX ^[2]	Input leakage current (except HSB#)	VCC = Max, VSS < VIN < VCC	-1	-	1	-0.04	0.10	-0.02	0.02	uA
	Input leakage current (for HSB#)	VCC = Max, VSS < VIN < VCC	-100	-	1	-31.6	0.38	-34.7	0.18	uA
IOZ	Off state output leakage current	VCC = VCC(Max), VSS < VOUT < VCC, CE# or OE# > VIH or BLE#, BHE# > VIH or WE# < VIL	-1	-	1	-0.02	0.04	-0.02	0.02	uA
VIH	Input HIGH voltage		2	-	Vcc+0.5	1.64	1.75	1.68	1.74	V
VIL	Input LOW voltage		Vss-0.5	-	0.8	1.08	1.12	1.06	1.09	V
VOH	Output HIGH voltage	IOUT=-2mA	2.4	-	-	2.56	2.57	2.47	2.49	V
VOL	Output LOW voltage	IOUT=4mA	-	-	0.4	0.19	0.20	0.10	0.12	V

Notes:

1. These parameters are guaranteed by design but not tested.
2. The HSB pin has IOUT = -2 uA for VOH of 2.4 V when both active HIGH and LOW drivers are disabled. When they are enabled standard VOH and VOL are valid. This parameter is characterized but not tested.

4.2 DC Parameters (CY14B101P/Q Device)

Parameter	Name	Test Conditions	Datasheet			Fab4		Fab25		Unit
			Min	Typ	Max	Min	Max	Min	Max	
ICC1	Average VCC current	At fSCK = 40 MHz. Values obtained without output loads (Iout = 0 mA)	-	-	10	5.60	7.20	4.80	6.00	mA
ISB	VCC standby current	CS > (VCC – 0.2 V). VIN < 0.2 V or > (VCC – 0.2 V). W bit set to '0'. Standby current level after nonvolatile cycle is complete. Inputs are static. f = 0 MHz.	-	-	5	1.20	1.60	0.80	1.60	mA
VIH	Input HIGH voltage		2	-	Vcc+0.5	1.62	1.68	1.33	1.72	V
VIL	Input LOW voltage		Vss-0.5	-	0.8	0.98	1.01	1.00	1.04	V
VOH	Output HIGH voltage	IOUT=-2mA	2.4	-	-	2.53	2.54	2.53	2.54	V
VOL	Output LOW voltage	IOUT=4mA	-	-	0.4	0.21	0.22	0.24	0.25	V

4.3 AC Parameters (CY14B101K/L/M/N Devices)

Parameter ^[1]	Name	Datasheet			Fab4		Fab25		Unit
		Min	Typ	Max	Min	Max	Min	Max	
tACE	Chip enable access time	-	-	20	14.69	17.81	15.38	16.44	ns
tAA ^[2]	Address access time	-	-	20	15.06	15.38	15.31	16.37	ns
tDOE	Output enable to data valid	-	-	10	6.69	7.88	7.00	7.44	ns
tOHA ^[2]	Output hold after address change	3	-	-	6.63	9.56	6.88	12.31	ns
tDBE	Byte enable to data valid	-	-	10	5.13	7.69	6.88	7.25	ns
tPWE	Write pulse width	15	-	-	9.13	11.81	10.56	11.75	ns
tSCE	Chip enable to end of write	15	-	-	9.19	11.19	9.81	11.00	ns
tSD	Data setup to end of write	8	-	-	5.81	6.88	6.99	7.55	ns
tHD	Data hold after end of write	0	-	-	-4.63	-3.94	-6.12	-4.93	ns
tAW	Address setup to end of write	15	-	-	11.50	12.06	12.07	13.76	ns
tSA	Address setup to start of write	0	-	-	-9.06	-7.19	-8.06	-7.12	ns
tHA	Address hold after end of write	0	-	-	-12.56	-9.75	-11.80	-10.50	ns
tBW	Byte enable to end of write	15	-	-	8.00	11.44	9.06	10.31	ns

Notes:

- Test conditions assume signal transition time of 3 ns or less, timing reference levels of VCC/2, input pulse levels of 0 to VCC (typ) and output loading of the specified IOL/IOH and load capacitance
- Device is continuously selected with CE#, OE# and BLE# / BHE# LOW.

4.4 AC Parameters (CY14B101P/Q Device)

Parameter ^[1]	Name	Datasheet			Fab4		Fab25		Unit
		Min	Typ	Max	Min	Max	Min	Max	
tCL	Clock pulse width LOW	11	-	-	3.00	3.00	3.00	3.00	ns
tCH	Clock pulse width HIGH	11	-	-	3.38	4.88	3.31	3.75	ns
tCS	CS# HIGH time	20	-	-	16.00	16.00	16.00	16.00	ns
tCSS	CS# setup time	20	-	-	0.38	0.56	0.06	0.99	ns
tCSH	CS# hold time	10	-	-	3.00	3.00	3.00	3.00	ns
tSD	Data in setup time	5	-	-	0.50	1.31	1.00	1.25	ns
tHD	Data in hold time	5	-	-	-0.18	0.31	-0.38	-0.19	ns
tCO	Output valid	-	-	9	5.94	6.81	5.06	5.5	ns
tOH	Output hold time	0	-	-	3.94	4.88	3.94	4.25	ns

4.5 Store/Recall Parameters

AutoStore/Power-UP RECALL Characteristics

Parameter	Name	Datasheet			Fab4		Fab25		Unit
		Min	Typ	Max	Min	Max	Min	Max	
tHRECALL ^[1]	Power-Up RECALL duration	-	-	20	14.20	18.70	13.70	17.70	ms
tSTORE ^[2]	STORE cycle duration	-	-	8	4.60	6.20	5.40	6.80	ms
tDELAY ^[3]	Time allowed to complete SRAM write cycle	-	-	25	19.00	19.00	19.00	19.00	ns
VSWITCH	Low voltage trigger level	-	-	2.65	2.52	2.58	2.40	2.53	V

Software Controlled STORE and RECALL Characteristics

Parameter ^[4,5]	Name	Datasheet			Fab4		Fab25		Unit
		Min	Typ	Max	Min	Max	Min	Max	
tSA	Address setup time	0	-	-	-5.13	-3.81	-5.12	-3.87	ns
tCW	Clock pulse width	15	-	-	7.44	9.19	7.81	9.00	ns
tHA	Address hold time	0	-	-	-5.00	-2.81	-4.18	-2.81	ns

tRECALL	RECALL duration	-	-	200	66.00	90.00	75.00	95.00	us
---------	-----------------	---	---	-----	-------	-------	-------	-------	----

Hardware STORE Characteristics

Parameter	Name	Datasheet			Fab4		Fab25		Unit
		Min	Typ	Max	Min	Max	Min	Max	
tDHSB	HSB# to output active time when write latch not set	-	-	25	17.00	18.00	17.00	18.00	ns
tPHSB	Hardware STORE pulse width	15	-	-	3.50	5.00	4.00	4.70	ns
tSS ^[6,7]	Soft sequence processing time	-	-	100	50.00	70.00	60.00	75.00	us

Notes:

1. tHRECALL starts from the time VCC rises above VSWITCH.
2. If an SRAM write has not taken place since the last NV cycle, no AutoStore or Hardware STORE takes place.
3. On a Hardware STORE and AutoStore initiation, SRAM write operation continues to be enabled for time tDELAY.
4. The software sequence is clocked with CE# controlled or OE# controlled reads.
5. The six consecutive addresses must be read in the order listed. WE# must be HIGH during all six cycles.
6. This is the amount of time it takes to take action on a soft sequence command. VCC power must remain HIGH to effectively register command.
7. Commands such as STORE and RECALL lock out I/O until complete which further increases this time.

4.6 RTC Parameters

Parameter	Name	Datasheet			Fab4		Fab25		Unit
		Min	Typ	Max	Min	Max	Min	Max	
V _{RTCbat}	RTC battery pin voltage	1.8	3	3.6	1.37	1.55	1.47	1.50	V
V _{RTCCap} ^[1]	RTC capacitor pin voltage	1.6	-	3.6	1.36	1.55	1.47	1.50	V
I _{BAK} ^[2]	RTC backup current	-	-	0.5	0.36	0.42	0.22	0.44	uA
tOCS	RTC oscillator time to start	-	1	2	0.24	0.42	0.14	0.31	s
t _{RTCP}	RTC processing time from end of 'W' bit set to '0'	-	-	350	162.00	164.00	146.00	166.00	us
RBKCHG	RTC backup capacitor charge current-limiting resistor	350	-	850	554.41	579.40	436.06	602.68	Ω

Notes:

1. If V_{RTCCap} > 0.5 V or if no capacitor is connected to V_{RTCCap} pin, the oscillator starts in tOCS time. If a backup capacitor is connected and V_{RTCCap} < 0.5 V, the capacitor must be allowed to charge to 0.5 V for oscillator to start.
2. From either V_{RTCCap} or V_{RTCbat}.



Document History Page

Rev.	ECN No.	Orig. of Change	Description of Change
**	5978108	ARAV/YSR	New Characterization Report.

Sales, Solutions, and Legal Information

Worldwide Sales and Design Support

Cypress maintains a worldwide network of offices, solution centers, manufacturer's representatives, and distributors. To find the office closest to you, visit us at cypress.com/sales.

Products

PSoC psoc.cypress.com
Clocks & Buffers clocks.cypress.com
Wireless wireless.cypress.com
Memories memory.cypress.com
Image Sensors image.cypress.com

PSoC Solutions

General psoc.cypress.com/solutions
Low Power/Low Voltage psoc.cypress.com/low-power
Precision Analog psoc.cypress.com/precision-analog
LCD Drive psoc.cypress.com/lcd-drive
CAN 2.0b psoc.cypress.com/can
USB psoc.cypress.com/usb

© Cypress Semiconductor Corporation, 2017. The information contained herein is subject to change without notice. Cypress Semiconductor Corporation assumes no responsibility for the use of any circuitry other than circuitry embodied in a Cypress product. Nor does it convey or imply any license under patent or other rights. Cypress products are not warranted nor intended to be used for medical, life support, lifesaving, critical control or safety applications, unless pursuant to an express written agreement with Cypress. Furthermore, Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress products in life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

Any Source Code (software and/or firmware) is owned by Cypress Semiconductor Corporation (Cypress) and is protected by and subject to worldwide patent protection (United States and foreign).

United States copyright laws and international treaty provisions. Cypress hereby grants to licensee a personal, non-exclusive, non-transferable license to copy, use, modify, create derivative works of, and compile the Cypress Source Code and derivative works for the sole purpose of creating custom software and/or firmware in support of licensee product to be used only in conjunction with a Cypress integrated circuit as specified in the applicable agreement. Any reproduction, modification, translation, compilation, or representation of this Source Code except as specified above is prohibited without the express written permission of Cypress.

Disclaimer: CYPRESS MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Cypress reserves the right to make changes without further notice to the materials described herein. Cypress does not assume any liability arising out of the application or use of any product or circuit described herein. Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress' product in a life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges. Use may be limited by and subject to the applicable Cypress software license agreement.

All products and company names mentioned in this document may be the trademarks of their respective holders.

Cypress Semiconductor Sort Site Qualification Report

**QTP# 171610 VERSION *A
September 2017**

Cypress Test 25, Austin, Texas

Sort Site for S8 Technology

MPD / MCD Devices

FOR ANY QUESTIONS ON THIS REPORT, PLEASE CONTACT
reliability@cypress.com or via a CYLINK CRM CASE

Prepared By:
Honesto Sintos
Reliability Engineer

Reviewed By:
Lorena Zapanta
Reliability Manager

Approved By:
David Hoffman
Reliability Director

PACKAGE/PRODUCT QUALIFICATION HISTORY

QTP Number	Description of Qualification Purpose	Date
151907	Cypress Test 25, Austin, Texas Sort Site Qualification for S4 Technology	June 2015
171610	Cypress Test 25, Austin, Texas Sort Site Qualification for S8 Technology	April 2017

QUALIFICATION COVERAGE RANGE

MARKETING PART NUMBER	DEVICE DESCRIPTION
CY8C4013 / CY8C4014 / CY8CMBR3002 / CY8CMBR3102 / CY8CMBR3110	CapSense® MBR3
CY8CMBR31 / CY8C4013 / CY8C4014	PSoC® 4000
CY8C4014	Automotive PSoC® 4000
CY8C4124 / CY8C4125 / CY8C4244 / CY8C4245	PSoC® 4100 & PSoC® 4200
CY8C4124 / CY8C4125 / CY8C4244 / CY8C4245	Automotive PSoC® 4100 & PSoC® 4200
CY8CEBIKE	PSoC® 4100 & PSoC® 4200
CY8C4125 / CY8C4126 / CY8C4127	PSoC® 4100M & PSoC® 4200M M Series
CY8C4245 / CY8C4246 / CY8C4247	PSoC® 4100M & PSoC® 4200M M Series
CY8C4246 / CY8C4247 / CY8C4248	PSoC® 4200L L-Series
CY8C4127 / CY8C4247	PSoC® 4 BLE 128K
CYBL1016 / CYBL10162 / CYBL10163	PRoCTM-BLE 128K
CYBL10461 / CYBL10462 / CYBL10463	PRoCTM-BLE 128K
CYBL10561 / CYBL10562 / CYBL10563	PRoCTM-BLE 128K
CYBL10999	PRoCTM-BLE 128K
CY8C4128 / CY8C4248	PSoC® 4 BLE 256K
CYBL10573	PRoCTM-BLE 256K
CY8C3244 / CY8C3245 / CY8C3246 / CY8C3444	Automotive PSoC® 3
CY8C3445 / CY8C3446 / CY8C3645 / CY8C3646 CY8C3665 / CY8C3666 / CY8C3846 / CY8C3866 /	Automotive PSoC® 3
CY8C3244 / CY8C3245 / CY8C3246 / CY8C3444	PSoC® 3
CY8C3445 / CY8C3446 / CY8C3665 / CY8C3666 / CY8C3846 / CY8C3865 / CY8C3866 / CY8C3MFIDOCK / CY8C3USBAUDIO	PSoC® 3
CY8C5267 / CY8C5268 / CY8C5287 / CY8C5288 / CY8C5467 / CY8C5468 / CY8C5488 / CY8C5666 CY8C5667 / CY8C5668 / CY8C5688 / CY8C5866 / CY8C5867 / CY8C5868 / CY8C5888	PSoC® 5LP
CY8CTMA1036 / CY8CTMA460 / CY8CTMA461 / CY8CTMA768	Automotive True Touch® Gen4 Touchscreen Controller

QUALIFICATION COVERAGE RANGE

MARKETING PART NUMBER	DEVICE DESCRIPTION
CYTMA445A / CYTMA525A / CYTT21100 CYTT21401 / CYTT21402 / CYTT21403	True Touch® Gen6M Touchscreen Controller
CYTT21100 / CYTT21401 / CYTT21402 CYTT21403 / CYTT31401 / CYTT31702 CYTT31802 / CYTT32302	True Touch® Gen6L Touchscreen Controller
CYAT81682 / CYAT81685 / CYAT81688	Automotive True Touch® Gen6XL Touchscreen Controller
CYFPA1I	True Touch® Fingerprint
CYPD1103 / CYPD1104 / CYPD1105 CYPD1120 / CYPD1121 / CYPD1122 CYPD1134	EZ-PDTM CCG1 USB Type-C PD Controller
CYPD2103 / CYPD2104 / CYPD2105 CYPD2119 / CYPD2120 / CYPD2134	EZ-PDTM CCG2 USB Type-C PD Controller
CY7C65210 / CY7C65211 / CY7C65213 CY7C65215 / CY7C65217 / CY7C65221	USB-Serial Bridge Controller
CY14B064 / CY14E064 / CY14MB064 / CY14ME064	64Kb Serial nvSRAM
CY14B256 / CY14E256	256Kb Serial nvSRAM
CY14B512	512Kb Serial nvSRAM
CY14B101 / CY14E101	1Mb Serial nvSRAM
CY14V101	1Mb Quad SPI nvSRAM
CY14B256 / CY14E256 / CY14U256 / CY14V256	256Kb Parallel nvSRAM
CY14101V / CY14B101 / CY14V101	1Mb Parallel nvSRAM
CY14B102NS	2Mb Parallel nvSRAM
CY14104V / CY14B104 / CY14V104	4Mb Parallel nvSRAM
CY14B108 / CYATB108	8Mb Parallel nvSRAM
CY14B116 / CY14V116 / CY14E116	16Mb Parallel nvSRAM
CY27410F / CY27410L	4-PLL Spread-Spectrum Clock Generator

Reliability Test Data

QTP #: 151907

<i>Device</i>	<i>Fab Lot #</i>	<i>Assembly Lot#</i>	<i>Test Loc</i>	<i>Yield</i>
<i>SORT TEST: CORRELATION</i>				
Sort Yield:				
8C24094AC	4446219 w2, w4, w5	N/A	CMI-FAB25	Correlated
8A24094AC	4510997 w5, w6, w7	N/A	CMI-FAB25	Correlated
8A24094AC	4506339 w6, w7, w8	N/A	CMI-FAB25	Correlated
Bin Movement:				
8C24094AC	4446219 w2	N/A	CMI-FAB25	Correlated
8A24094AC	4510997 w5	N/A	CMI-FAB25	Correlated
8A24094AC	4506339 w6	N/A	CMI-FAB25	Correlated
Fishers Exact:				
8C24094AC	4446219 w2, w4, w5	N/A	CMI-FAB25	>0.05
8A24094AC	4510997 w5, w6, w7	N/A	CMI-FAB25	>0.05
8A24094AC	4506339 w6, w7, w8	N/A	CMI-FAB25	>0.05

Reliability Test Data**QTP #: 171610**

Device	Fab Lot #	Assembly Lot#	Test Loc	Yield
---------------	------------------	----------------------	-----------------	--------------

SORT TEST: CORRELATION**Sort Yield:**

8A20680BB	3639013 w21	N/A	FAB25	Correlated
-----------	-------------	-----	-------	------------

Bin Movement:

8A20680BB	3639013 w21	N/A	FAB25	<2%
-----------	-------------	-----	-------	-----

Document History Page

Document Title: QTP#171610: Cypress Test 25, Austin, Texas Sort Site for S8 Technology
Document Number: 002-19700

Rev.	ECN No.	Orig. of Change	Description of Change
**	5747717	HSTO	Initial Spec Release
*A	5874099	GKUS	1. Rearranged the nvSRAM parts as per the density & interface. 2. Included CY14B101 in the 1Mb Serial nvSRAM row which was missed in the last revision.

Cypress Semiconductor Product Qualification Report

QTP# 170803 VERSION**
December 2017

1MB nvSRAM Device Family S8TNV1-5 Technology, Fab 25	
CY14B101KA*	3V 1-Mbit (128K x 8) nvSRAM with RTC
CY14B101LA*	3V 1-Mbit (128K x 8) nvSRAM
CY14B101M*	3V 1-Mbit (64K x 16) nvSRAM with RTC
CY14B101NA*	3V 1-Mbit (64K x 16) nvSRAM
CY14B256KA*	3V 256-Kbit (32K x 8) nvSRAM with RTC
CY14B256LA*	3V 256-Kbit (32K x 8) nvSRAM
CY14E256LA*	5V 256-Kbit (32K x 8) nvSRAM
CY14B101Q*	3V 1-Mbit (128K x 8) SPI nvSRAM
CY14B256Q*	3V 256-Kbit (32K x 8) SPI nvSRAM
CY14101V*	1-Mbit (128K x 8/64K x 16) nvSRAM Die

FOR ANY QUESTIONS ON THIS REPORT, PLEASE CONTACT
reliability@cypress.com or via a CYLINK CRM CASE

Prepared By:
Josephine Pineda (JYF)
Staff Reliability Engineer

Reviewed By:
Sandhya Chandrashekhar (SANC)
Principal Reliability Engineer

Approved By:
David Hoffman (DHH)
Reliability Director

PRODUCT QUALIFICATION HISTORY

QTP Number	Description of Qualification Purpose	Date
151008	Qualification of S8* Technology in Fab 25 using TSG6M Device	December 2015
163004	S8TNV Fab Transfer Qualification at Fab 25 using 4M Parallel nvSRAM Device	September 2017
170803	Qualification of 1M nvSRAM Device at Fab 25 using S8TNV1-5 Technology	December 2017

PRODUCT DESCRIPTION (for qualification)	
Qualification Purpose: To qualify 1M nvSRAM device at Fab 25 using S8TNV1-5 technology	
Marketing Part #:	CY14B101KA*/ CY14B101LA*/ CY14B101M*/ CY14B101NA*/ CY14B256KA* CY14B256LA*/ CY14E256LA*/ CY14B101Q*/ CY14B256Q*/ CY14101V*
Device Description:	1M nvSRAM
Cypress Division:	Cypress Semiconductor – Memory Products Division (MPD)

TECHNOLOGY/FAB PROCESS DESCRIPTION			
Number of Metal Layers:	Proprietary	Metal Composition:	Proprietary
Passivation Type and Thickness:	Proprietary		
Generic Process Technology/Design Rule (μ -drawn):	Proprietary		
Gate Oxide Material/Thickness (MOS):	Proprietary		
Name/Location of Die Fab (prime) Facility:	Fab 25		
Die Fab Line ID/Wafer Process ID:	S8TNV1-5		

MAJOR PACKAGE INFORMATION USED IN THIS QUALIFICATION

Package Designation:	ZW44
Package Outline, Type, or Name:	44L TSOP II (400 mils)
Mold Compound Name/Manufacturer:	KE G6000/Kyocera
Mold Compound Flammability Rating:	V-0 / UL94
Oxygen Rating Index: >28%	>28%
Lead Frame Designation:	FMP
Lead Frame Material:	Copper
Lead Finish, Composition / Thickness:	NiPdAu
Die Backside Preparation Method/Metallization:	Backgrind
Die Separation Method:	Saw Process
Die Attach Supplier:	Henkel
Die Attach Material:	QMI-509
Bond Diagram Designation	001-67276
Wire Bond Method:	Thermosonic
Wire Material/Size:	Cu/0.8 mil
Thermal Resistance Theta JA °C/W:	41.74°C/W
Package Cross Section Yes/No:	Yes
Assembly Process Flow:	11-21099
Name/Location of Assembly (prime) facility:	CML-RA
MSL Level	3
Reflow Profile	260C

ELECTRICAL TEST / FINISH DESCRIPTION

Test Location:	CML - R
----------------	---------

MAJOR PACKAGE INFORMATION USED IN THIS QUALIFICATION

Package Designation:	SP48
Package Outline, Type, or Name:	48L SSOP (300 mils)
Mold Compound Name/Manufacturer:	KE G3000/Kyocera
Mold Compound Flammability Rating:	V-0 / UL94
Oxygen Rating Index: >28%	>28%
Lead Frame Designation:	FMP
Lead Frame Material:	Copper
Lead Finish, Composition / Thickness:	NiPdAu
Die Backside Preparation Method/Metallization:	Backgrind
Die Separation Method:	Saw Process
Die Attach Supplier:	Henkel
Die Attach Material:	QMI-509
Bond Diagram Designation	001-85628
Wire Bond Method:	Thermosonic
Wire Material/Size:	Cu/0.8 mil
Thermal Resistance Theta JA °C/W:	46.16°C/W
Package Cross Section Yes/No:	Yes
Assembly Process Flow:	11-21099
Name/Location of Assembly (prime) facility:	CML-RA
MSL Level	3
Reflow Profile	260C

ELECTRICAL TEST / FINISH DESCRIPTION

Test Location:	CML - R
----------------	---------

MAJOR PACKAGE INFORMATION USED IN THIS QUALIFICATION	
Package Designation:	SZ32
Package Outline, Type, or Name:	32L SOIC (300 mils)
Mold Compound Name/Manufacturer:	EME-G712/ Sumitomo
Mold Compound Flammability Rating:	V-0 / UL94
Oxygen Rating Index: >28%	> 28%
Lead Frame Designation:	FMP
Lead Frame Material:	Copper
Lead Finish, Composition / Thickness:	Pure Sn
Die Backside Preparation Method/Metallization:	Backgrind
Die Separation Method:	Saw Process
Die Attach Supplier:	Ablebond
Die Attach Material:	8600
Bond Diagram Designation	001-97384
Wire Bond Method:	Thermosonic
Wire Material/Size:	Au/1.0 mil
Thermal Resistance Theta JA °C/W:	45.12°C/W
Package Cross Section Yes/No:	Yes
Assembly Process Flow:	001-85398
Name/Location of Assembly (prime) facility:	UTL-Thailand (UT)
MSL Level	3
Reflow Profile	260C

ELECTRICAL TEST / FINISH DESCRIPTION	
Test Location:	CML - R

MAJOR PACKAGE INFORMATION USED IN THIS QUALIFICATION

Package Designation:	LH08
Package Outline, Type, or Name:	8-Pin DFN (5x6x0.75mm)
Mold Compound Name/Manufacturer:	GE7470LA/Nitto
Mold Compound Flammability Rating:	V-0 / UL94
Oxygen Rating Index: >28%	>28%
Lead Frame Designation:	FMP
Lead Frame Material:	Copper
Lead Finish, Composition / Thickness:	NiPdAu-Ag
Die Backside Preparation Method/Metallization:	Backgrind
Die Separation Method:	Saw Process
Die Attach Supplier:	Henkel
Die Attach Material:	AMK-06
Bond Diagram Designation	001-51523
Wire Bond Method:	Thermosonic
Wire Material/Size:	Au/0.8 mil
Thermal Resistance Theta JA °C/W:	17.7°C/W
Package Cross Section Yes/No:	Yes
Assembly Process Flow:	001-20659
Name/Location of Assembly (prime) facility:	Amkor-Phils (MB)
MSL Level	3
Reflow Profile	260C

ELECTRICAL TEST / FINISH DESCRIPTION

Test Location:	CML - R
----------------	---------

MAJOR PACKAGE INFORMATION USED IN THIS QUALIFICATION

Package Designation:	SZ16
Package Outline, Type, or Name:	16L SOIC (300 mils)
Mold Compound Name/Manufacturer:	G600/Sumitomo
Mold Compound Flammability Rating:	V-0 / UL94
Oxygen Rating Index: >28%	>28%
Lead Frame Designation:	FMP
Lead Frame Material:	Copper
Lead Finish, Composition / Thickness:	Pure Sn
Die Backside Preparation Method/Metallization:	Backgrind
Die Separation Method:	Saw Process
Die Attach Supplier:	Ablestik
Die Attach Material:	8290
Bond Diagram Designation	001-51384
Wire Bond Method:	Thermosonic
Wire Material/Size:	Cu/0.8 mil
Thermal Resistance Theta JA °C/W:	55.17°C/W
Package Cross Section Yes/No:	Yes
Assembly Process Flow:	49-24999
Name/Location of Assembly (prime) facility:	Amkor-Phils (M)
MSL Level	3
Reflow Profile	260C

ELECTRICAL TEST / FINISH DESCRIPTION

Test Location:	CML - R
----------------	---------

MAJOR PACKAGE INFORMATION USED IN THIS QUALIFICATION

Package Designation:	BK48
Package Outline, Type, or Name:	48-Ball FBGA (6x10x1.2mm)
Mold Compound Name/Manufacturer:	KMC3580LVA/Shinetsu
Mold Compound Flammability Rating:	V-0 / UL94
Oxygen Rating Index: >28%	> 40%
Substrate Material:	BT Resin
Solder Ball Finish:	SAC105
Die Backside Preparation Method/Metallization:	Backgrind
Die Separation Method:	Saw Process
Die Attach Supplier:	Sumitomo
Die Attach Material:	CRM-1577DB
Bond Diagram Designation	001-99291
Wire Bond Method:	Thermosonic
Wire Material/Size:	CuPd/0.8 mil
Thermal Resistance Theta JA °C/W:	48.19 °C/W
Package Cross Section Yes/No:	Yes
Assembly Process Flow:	001-97055
Name/Location of Assembly (prime) facility:	Bangkok-Thailand (SB)
MSL Level	3
Reflow Profile	260C

ELECTRICAL TEST / FINISH DESCRIPTION

Test Location:	CML - R
----------------	---------

PACKAGE AVAILABILITY

PACKAGE	ASSEMBLY FACILITY SITE	WIRE MATERIAL	QTP#
44L TSOP II	CML-RA	Cu	121406
48L SSOP	CML-RA	Cu	125201
16L SOIC	M-Phils	Cu	124706
32L SOIC	UT-Thailand	Au	153005
8-Pin DFN	MB-Phils	Au	093102
48-Ball FBGA	SB-Thailand	CuPd	160703

RELIABILITY TESTS PERFORMED PER SPECIFICATION REQUIREMENTS

Stress/Test	Test Condition (Temp/Bias)	Result P/F
Acoustic Microscopy	J-STD-020 Precondition: JESD22 Moisture Sensitivity Level (192 Hrs., 30 °C, 60% RH, 260°C Reflow)	P
Age Bond Strength	200□C, 4HRS MIL-STD-883, Method 883-2011	P
Data Retention	150°C/175°C, No Bias JESD22-A117 and JESD22-A103	P
Electrostatic Discharge Charge Device Model (ESD-CDM)	500V/750V/1,000V/1,250V/1,500V/1,750V/2,000V JESD22-C101	P
Electrostatic Discharge Human Body Model (ESD-HBM)	1,100V/2,200V /3,300V/4,000V/5,000V/6,000V/7,000V/8,000V JESD22, Method A114	P
Endurance Test	MIL-STD-883, Method 883-1033/ JESD22-A117	P
High Accelerated Saturation Test (HAST)	JEDEC STD 22-A110: 130°C, 85% RH, 3.3V/5.5V Precondition: JESD22 Moisture Sensitivity Level (192 Hrs., 30 °C, 60% RH, 260°C Reflow)	P
High Temperature Operating Life Early Failure Rate – Regulator On	Dynamic Operating Condition, Vcc Max=3.3V,150°C JESD22-A-108	P
High Temperature Operating Life Early Failure Rate – Regulator Off	Dynamic Operating Condition, Vcc Max=2.07V/3.3V,150°C JESD22-A-108	P
High Temperature Operating Life Latent Failure Rate	Dynamic Operating Condition, Vcc Max=2.0V/3.3V,150°C JESD22-A-108	P
High Temperature Storage	JESD22-A103:150°C No bias	P
Low Temperature Operating Life	Dynamic Operating Condition, -40°C JESD22-A108	P
Pressure Cooker	JESD22-A102:121°C /100%RH, 15 PSIG Precondition: JESD22 Moisture Sensitivity Level (192 Hrs., 30 °C, 60% RH, 260°C Reflow)	P
Pre/Post LFR AC/DC Char	AC/DC Critical Parameter Char at 0 hour/500hrs	P
Soft Error (Alpha Particle)	JESD89	P
Soft Error (Neutron)	JESD89	P
Static Latch-up	85°C, +/- 140mA, +/- 200mA, +/-300mA 125°C, +/-100mA, +/-140mA JESD 78	P
Temperature Cycle	MIL-STD-883, Method 1010, Condition C, -65°C to 150°C Precondition: JESD22 Moisture Sensitivity Level (192 Hrs., 30 °C, 60% RH, 260°C Reflow)	P

RELIABILITY FAILURE RATE SUMMARY

Stress/Test	Device Tested/ Device Hours	# Fails	Activation Energy	Thermal AF ³	Failure Rate
High Temperature Operating Life Early Failure Rate	1,598 Devices	0	N/A	N/A	0 PPM ⁽¹⁾
High Temperature Operating Life Long Term Failure Rate	338,000 DHRs	0	0.7	170	16 FIT ⁽²⁾

1. Early Failure Rate was computed from QTP# 170803.
2. Long Term Failure Rate was computed from QTP#151008, QTP# 163004 and QTP# 170803 LFR data.

¹ Assuming an ambient temperature of 55°C and a junction temperature rise of 15°C.

² Chi-squared 60% estimations used to calculate the failure rate.

³ Thermal Acceleration Factor is calculated from the Arrhenius equation

$$AF = \exp \left[\frac{E_A}{k} \left[\frac{1}{T_2} - \frac{1}{T_1} \right] \right]$$

where:

E_A = The Activation Energy of the defect mechanism.

K = Boltzmann's constant = 8.62x10⁻⁵ eV/Kelvin.

T₁ is the junction temperature of the device under stress and T₂ is the junction temperature of the device at use conditions.

Reliability Test Data

QTP #: 151008

Device	Fab Lot #	Assy Lot #	Assy Loc	Duration	Samp	Rej	Failure Mechanism
STRESS: ACOUSTIC, MSL3							
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	COMP	15	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	COMP	15	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	COMP	15	0	
STRESS: DATA RETENTION, PLASTIC, 150C							
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	500	80	0	
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	1000	80	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	500	80	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	1000	80	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	500	80	0	
STRESS: DATA RETENTION, PLASTIC, 175C							
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	76	80	0	
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	152	79	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	76	80	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	152	80	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	76	80	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	152	80	0	
STRESS: HIGH TEMP DYNAMIC OPERATING LIFE-EARLY FAILURE RATE (150C, 2.07V, Vcc Max)							
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	48	1490	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	48	1510	0	
CYTT214032 (8CP206101)	4545249	611537364	CML-RA	48	1547	0	
STRESS: ENDURANCE							
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	168	78	0	
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	500	78	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	168	80	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	500	80	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	168	80	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	500	80	0	
STRESS: ESD-CHARGE DEVICE MODEL							
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	500	9	0	
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	750	3	0	
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	1000	3	0	
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	1250	3	0	
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	1500	3	0	
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	1750	3	0	

Reliability Test Data

QTP #: 151008

Device	Fab Lot #	Assy Lot #	Assy Loc	Duration	Samp	Rej	Failure Mechanism
STRESS: ESD-CHARGE DEVICE MODEL							
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	500	9	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	750	3	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	1000	3	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	1250	3	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	1500	3	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	1750	3	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	500	9	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	750	3	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	1000	3	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	1250	3	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	1500	3	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	1750	3	0	
STRESS: ESD-HUMAN BODY MODEL PER JESD22, METHOD A114							
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	1100	3	0	
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	2200	8	0	
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	3300	3	0	
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	4000	3	0	
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	5000	3	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	1100	3	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	2200	8	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	3300	3	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	4000	3	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	1100	3	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	2200	8	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	3300	3	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	4000	3	0	
STRESS: HI-ACCEL SATURATION TEST (130C, 85%RH, 5.5V), PRE COND 192 HR 30C/60%RH (MSL3)							
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	96	30	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	96	30	0	
STRESS: HIGH TEMP DYNAMIC OPERATING LIFE-LATENT FAILURE RATE (150C, 2.07V, Vcc Max)							
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	80	116	0	
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	500	116	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	80	120	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	500	120	0	

Reliability Test Data

QTP #: 151008

Device	Fab Lot #	Assy Lot #	Assy Loc	Duration	Samp	Rej	Failure Mechanism
STRESS: LOW TEMPERATURE OPERATING LIFE, -40C							
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	160	40	0	
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	380	40	0	
STRESS: PRESSURE COOKER TEST (121C, 100%RH), 15 Psig, PRE COND 192 HR 30C/60%RH (MSL3)							
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	168	75	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	168	78	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	168	80	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	288	80	0	
STRESS: PRE/POST LFR PARAMETER ASSESSMENT							
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	COMP	10+2	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	COMP	10+2	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	COMP	10+2	0	
STRESS: STATIC LATCH-UP (85C, 140mA)							
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	COMP	6	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	COMP	6	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	COMP	6	0	
STRESS: STATIC LATCH-UP (85C, 200mA)							
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	COMP	3	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	COMP	3	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	COMP	3	0	
STRESS: STATIC LATCH-UP (85C, 300mA)							
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	COMP	3	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	COMP	3	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	COMP	3	0	
STRESS: SEM CROSS SECTION							
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	COMP	1	0	
STRESS: TC COND. C -65C TO 150C, PRE COND 192 HRS 30C/60%RH (MSL3)							
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	500	80	0	
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	1000	80	0	
CYTT214032 (8CP206101)	4540145	611534709	CML-RA	500	80	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	500	79	0	
CY8C42452 (8CP44200)	4537464	611531543	CML-RA	1000	79	0	
STRESS: THERMAL JUNCTION MEASUREMENT							
CYTT214032 (8CP206101)	4539372	611534008	CML-RA	COMP	1	0	

Reliability Test Data

QTP #: 163004

Device	Fab Lot	Assy Lot #	Assy Loc	Duration	Samp	Rej	Failure Mechanism
STRESS: ACOUSTIC, MSL3							
CY14B104NA2 (7CC1404B6D)	4647620	611645509	CML-RA	COMP	22	0	
CY14B104K2 (7C1404B1D)	4652108	611703935	CML-RA	COMP	22	0	
CY14B104NA2 (7CC1404B6D)	4652108	611703705	G-TAIWAN	COMP	22	0	
CY14B104NA2 (7CC1404B6D)	3721074	611723439	CML-RA	COMP	22	0	
CY14B104NA2 (7C1404B6D)	4715938	611723536	CML-RA	COMP	22	0	
STRESS: AGED BOND STRENGTH							
CY14B104K2 (7CC1404B1D)	4647620	611645506	CML-RA	COMP	3	0	
STRESS: DATA RETENTION, PLASTIC, 150C							
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	1000	80	0	
STRESS: ENDURANCE							
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA CYCLING		80	0	
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	168	80	0	
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	500	80	0	
STRESS: ESD-CHARGE DEVICE MODEL							
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	500	9	0	
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	750	3	0	
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	1000	3	0	
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	1250	3	0	
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	1500	3	0	
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	1750	3	0	
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	2000	3	0	
CY14B104NA2 (7CC1404B6D)	4652108	611703705	G-TAIWAN	500	9	0	
CY14B104NA2 (7CC1404B6D)	4652108	611703705	G-TAIWAN	750	3	0	
CY14B104NA2 (7CC1404B6D)	4652108	611703705	G-TAIWAN	1000	3	0	
CY14B104NA2 (7CC1404B6D)	4652108	611703705	G-TAIWAN	1250	3	0	
CY14B104NA2 (7CC1404B6D)	4652108	611703705	G-TAIWAN	1500	3	0	
CY14B104NA2 (7CC1404B6D)	4652108	611703705	G-TAIWAN	1750	3	0	
CY14B104NA2 (7CC1404B6D)	4652108	611703705	G-TAIWAN	2000	3	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	500	9	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	750	3	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	1000	3	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	1250	3	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	1500	3	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	1750	3	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	2000	3	0	

Reliability Test Data

QTP #: 163004

Device	Fab Lot	Assy Lot #	Assy Loc	Duration	Samp	Rej	Failure Mechanism
STRESS: ESD-CHARGE DEVICE MODEL							
CY14B104M2 (7C1404B2D)	4652108	611705462	GM-TAIWAN	500	9	0	
CY14B104M2 (7C1404B2D)	4652108	611705462	GM-TAIWAN	750	3	0	
CY14B104M2 (7C1404B2D)	4652108	611705462	GM-TAIWAN	1000	3	0	
CY14B104M2 (7C1404B2D)	4652108	611705462	GM-TAIWAN	1250	3	0	
CY14B104M2 (7C1404B2D)	4652108	611705462	GM-TAIWAN	1500	3	0	
CY14B104M2 (7C1404B2D)	4652108	611705462	GM-TAIWAN	1750	3	0	
CY14B104M2 (7C1404B2D)	4652108	611705462	GM-TAIWAN	2000	3	0	
CY14B104M2 (7C1404B2D)	3720073	611726034	GM-TAIWAN	500	9	0	
CY14B104M2 (7C1404B2D)	3720073	611726034	GM-TAIWAN	750	3	0	
CY14B104M2 (7C1404B2D)	3720073	611726034	GM-TAIWAN	1000	3	0	
CY14B104M2 (7C1404B2D)	3720073	611726034	GM-TAIWAN	1250	3	0	
CY14B104M2 (7C1404B2D)	3720073	611726034	GM-TAIWAN	1500	3	0	
CY14B104M2 (7C1404B2D)	3720073	611726034	GM-TAIWAN	1750	3	0	
CY14B104M2 (7C1404B2D)	3720073	611726034	GM-TAIWAN	2000	3	0	
CY14B104NA2 (7CP1404B6D)	3720073	611728313	GM-TAIWAN	500	9	0	
CY14B104NA2 (7CP1404B6D)	3720073	611728313	GM-TAIWAN	750	3	0	
CY14B104NA2 (7CP1404B6D)	3720073	611728313	GM-TAIWAN	1000	3	0	
CY14B104NA2 (7CP1404B6D)	3720073	611728313	GM-TAIWAN	1250	3	0	
CY14B104NA2 (7CP1404B6D)	3720073	611728313	GM-TAIWAN	1500	3	0	
CY14B104NA2 (7CP1404B6D)	3720073	611728313	GM-TAIWAN	1750	3	0	
CY14B104NA2 (7CP1404B6D)	3720073	611728313	GM-TAIWAN	2000	3	0	
STRESS: ESD-HUMAN BODY MODEL PER JESD22, METHOD A114							
CY14B104K2 (7CC1404B1D)	4647620	611645506	CML-RA	1100	3	0	
CY14B104K2 (7CC1404B1D)	4647620	611645506	CML-RA	2200	8	0	
CY14B104K2 (7CC1404B1D)	4647620	611645506	CML-RA	3300	3	0	
CY14B104K2 (7CC1404B1D)	4647620	611645506	CML-RA	4000	3	0	
CY14B104K2 (7CC1404B1D)	4647620	611645506	CML-RA	5000	3	0	
CY14B104K2 (7CC1404B1D)	4647620	611645506	CML-RA	6000	3	0	
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	1100	3	0	
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	2200	8	0	
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	3300	3	0	
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	4000	3	0	
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	5000	3	0	
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	6000	3	0	
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	7000	3	0	

Reliability Test Data

QTP #: 163004

Device	Fab Lot	Assy Lot #	Assy Loc	Duration	Samp	Rej	Failure Mechanism
STRESS: ESD-HUMAN BODY MODEL PER JESD22, METHOD A114							
CY14B104K2 (7C1404B1D)	4652108	611703935	CML-RA	1100	3	0	
CY14B104K2 (7C1404B1D)	4652108	611703935	CML-RA	2200	8	0	
CY14B104K2 (7C1404B1D)	4652108	611703935	CML-RA	3300	3	0	
CY14B104K2 (7C1404B1D)	4652108	611703935	CML-RA	4000	3	0	
CY14B104K2 (7C1404B1D)	4652108	611703935	CML-RA	5000	3	0	
CY14B104K2 (7C1404B1D)	4652108	611703935	CML-RA	6000	3	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	1100	3	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	2200	8	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	3300	3	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	4000	3	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	5000	3	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	6000	3	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	7000	3	0	
STRESS: HI-ACCEL SATURATION TEST (130C, 85%RH, 3.3V), PRE COND 192 HR 30C/60%RH (MSL3)							
CY14B104K2 (7CC1404B1D)	4647620	611645506	CML-RA	96	30	0	
CY14B104K2 (7C1404B1D)	4652108	611703935	CML-RA	96	30	0	
CY14B104NA2 (7CC1404B6D)	4652108	611703705	G-TAIWAN	96	30	0	
STRESS: HIGH TEMP DYNAMIC OPERATING LIFE-EARLY FAILURE RATE, REG-ON (150C, 3.3V, Vcc Max)							
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	48	50	0	
STRESS: HIGH TEMP DYNAMIC OPERATING LIFE-EARLY FAILURE RATE, REG-OFF (150C, 3.3V, Vcc Max)							
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	48	3400	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	48	3399	0	
CY14B104NA2 (7A1404B6D)	3721074	611722753	JT-CHINA	48	1489	0	
STRESS: HIGH TEMP DYNAMIC OPERATING LIFE-LATENT FAILURE RATE (150C, 3.3V, Vcc Max)							
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	80	120	0	
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	500	120	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	80	120	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	500	120	0	
CY14B104NA2 (7A1404B6D)	4703546	611706560	JT-CHINA	80	120	0	
CY14B104NA2 (7A1404B6D)	4703546	611706560	JT-CHINA	500	120	0	
STRESS: PRESSURE COOKER TEST (121C, 100%RH), 15 Psig, PRE COND 192 HR 30C/60%RH (MSL3)							
CY14B104K2 (7C1404B1D)	4652108	611703935	CML-RA	96	80	0	
CY14B104K2 (7C1404B1D)	4652108	611703935	CML-RA	168	79	0	
CY14B104K2 (7C1404B1D)	4652108	611703935	CML-RA	288	79	0	
CY14B104NA2 (7CC1404B6D)	4652108	611703705	G-TAIWAN	168	80	0	
CY14B104NA2 (7CC1404B6D)	3721074	611723439	CML-RA	168	80	0	
CY14B104NA2 (7C1404B6D)	4715938	611723536	CML-RA	168	80	0	

Reliability Test Data

QTP #: 163004

Device	Fab Lot	Assy Lot #	Assy Loc	Duration	Samp	Rej	Failure Mechanism
STRESS: PRE/POST LFR PARAMETER ASSESSMENT							
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	0	10+2	0	
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	500	10+2	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	0	10+2	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	500	10+2	0	
CY14B104NA2 (7A1404B6D)	4703546	611706560	JT-CHINA	0	10+2	0	
CY14B104NA2 (7A1404B6D)	4703546	611706560	JT-CHINA	500	10+2	0	
STRESS: STATIC LATCH-UP (125C, 100mA)							
CY14B104K2 (7CC1404B1D)	4647620	611645506	CML-RA	COMP	3	0	
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	COMP	3	0	
CY14B104K2 (7C1404B1D)	4652108	611703935	CML-RA	COMP	3	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	COMP	3	0	
STRESS: STATIC LATCH-UP (125C, 140mA)							
CY14B104K2 (7CC1404B1D)	4647620	611645506	CML-RA	COMP	3	0	
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	COMP	3	0	
CY14B104K2 (7C1404B1D)	4652108	611703935	CML-RA	COMP	3	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	COMP	3	0	
STRESS: STATIC LATCH-UP (85C, 140mA)							
CY14B104K2 (7CC1404B1D)	4647620	611645506	CML-RA	COMP	3	0	
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	COMP	3	0	
CY14B104K2 (7C1404B1D)	4652108	611703935	CML-RA	COMP	3	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	COMP	3	0	
STRESS: STATIC LATCH-UP (85C, 200mA)							
CY14B104K2 (7CC1404B1D)	4647620	611645506	CML-RA	COMP	3	0	
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	COMP	3	0	
CY14B104K2 (7C1404B1D)	4652108	611703935	CML-RA	COMP	3	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	COMP	3	0	
STRESS: STATIC LATCH-UP (85C, 300mA)							
CY14B104K2 (7CC1404B1D)	4647620	611645506	CML-RA	COMP	3	0	
CY14B104NA2 (7A1404B6D)	4647620	611646995	JT-CHINA	COMP	3	0	
CY14B104K2 (7C1404B1D)	4652108	611703935	CML-RA	COMP	3	0	
CY14B104NA2 (7A1404B6D)	4652108	611705917	JT-CHINA	COMP	3	0	
STRESS: SER – ALPHA PARTICLE SEL							
CY14B104K2 (7CC1404B1D)	4647620	611645506	CML-RA	COMP	3	0	
STRESS: SER – NEUTRON SEL							
CY14B104K2 (7CC1404B1D)	4647620	611645506	CML-RA	COMP	3	0	

Reliability Test Data

QTP #: 163004

<i>Device</i>	<i>Fab Lot</i>	<i>Assy Lot #</i>	<i>Assy Loc</i>	<i>Duration</i>	<i>Samp</i>	<i>Rej</i>	<i>Failure Mechanism</i>
STRESS: TC COND. C -65C TO 150C, PRE COND 192 HRS 30C/60%RH (MSL3)							
CY14B104NA2 (7CC1404B6D)	4647620	611645509	CML-RA	500	80	0	
CY14B104NA2 (7CC1404B6D)	4647620	611645509	CML-RA	1000	80	0	
CY14B104K2 (7C1404B1D)	4652108	611703935	CML-RA	500	80	0	
CY14B104K2 (7C1404B1D)	4652108	611703935	CML-RA	1000	80	0	
CY14B104NA2 (7CC1404B6D)	4652108	611703705	G-TAIWAN	500	79	0	
CY14B104NA2 (7CC1404B6D)	3721074	611723439	CML-RA	500	79	0	
STRESS: THERMAL JUNCTION MEASUREMENT							
CY14B104K2 (7CC1404B1D)	4647620	611645506	CML-RA	COMP	1	0	

Reliability Test Data

QTP #: 170803

Device	Fab Lot	Assy Lot #	Assy Loc	Duration	Samp	Rej	Failure Mechanism
STRESS: ACOUSTIC, MSL3							
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	COMP	22	0	
STRESS: DATA RETENTION, PLASTIC, 150C							
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	500	80	0	
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	1000	80	0	
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	1500	80	0	
STRESS: ENDURANCE							
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	CYCLING	80	0	
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	168	80	0	
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	500	80	0	
STRESS: ESD-CHARGE DEVICE MODEL							
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	500	9	0	
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	750	3	0	
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	1000	3	0	
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	1500	3	0	
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	1750	3	0	
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	2000	3	0	
CY14B101LA2 (7CC1401B8D)	3726089	611731311	CML-RA	500	9	0	
CY14B101LA2 (7CC1401B8D)	3726089	611731311	CML-RA	750	3	0	
CY14B101LA2 (7CC1401B8D)	3726089	611731311	CML-RA	1000	3	0	
CY14B101LA2 (7CC1401B8D)	3726089	611731311	CML-RA	1250	3	0	
CY14B101LA2 (7CC1401B8D)	3726089	611731311	CML-RA	1500	3	0	
CY14B101LA2 (7CC1401B8D)	3726089	611731311	CML-RA	1750	3	0	
CY14B101LA2 (7CC1401B8D)	3726089	611731311	CML-RA	2000	3	0	
CY14B256LA2 (7C1418B8D)	3726089	611731972	UT-Thailand	500	9	0	
CY14B256LA2 (7C1418B8D)	3726089	611731972	UT-Thailand	750	3	0	
CY14B256LA2 (7C1418B8D)	3726089	611731972	UT-Thailand	1000	3	0	
CY14B256LA2 (7C1418B8D)	3726089	611731972	UT-Thailand	1250	3	0	
CY14B256LA2 (7C1418B8D)	3726089	611731972	UT-Thailand	1500	3	0	
CY14B256LA2 (7C1418B8D)	3726089	611731972	UT-Thailand	1750	3	0	
CY14B256LA2 (7C1418B8D)	3726089	611731972	UT-Thailand	2000	3	0	
CY14B101Q22 (7C1401B5D)	3726089	611731510	MB-Phils	500	9	0	
CY14B101Q22 (7C1401B5D)	3726089	611731510	MB-Phils	750	3	0	
CY14B101Q22 (7C1401B5D)	3726089	611731510	MB-Phils	1000	3	0	
CY14B101Q22 (7C1401B5D)	3726089	611731510	MB-Phils	1250	3	0	
CY14B101Q22 (7C1401B5D)	3726089	611731510	MB-Phils	1500	3	0	
CY14B101Q22 (7C1401B5D)	3726089	611731510	MB-Phils	1750	3	0	
CY14B101Q22 (7C1401B5D)	3726089	611731510	MB-Phils	2000	3	0	

Reliability Test Data

QTP #: 170803

<i>Device</i>	<i>Fab Lot</i>	<i>Assy Lot #</i>	<i>Assy Loc</i>	<i>Duration</i>	<i>Samp</i>	<i>Rej</i>	<i>Failure Mechanism</i>
CY14B101Q32 (7CC1401B4D)	3734080	611736254	M-Phils	500	9	0	
CY14B101Q32 (7CC1401B4D)	3734080	611736254	M-Phils	750	3	0	
CY14B101Q32 (7CC1401B4D)	3734080	611736254	M-Phils	1000	3	0	
CY14B101Q32 (7CC1401B4D)	3734080	611736254	M-Phils	1250	3	0	
CY14B104NA2 (7CC1401B4D)	3734080	611736254	M-Phils	1500	3	0	
CY14B104NA2 (7CC1401B4D)	3734080	611736254	M-Phils	1750	3	0	
CY14B104NA2 (7CC1401B4D)	3734080	611736254	M-Phils	2000	3	0	
CY14B101LA2 (7CP1401B8D)	3734080	611740662	SB-Thailand	500	9	0	
CY14B101LA2 (7CP1401B8D)	3734080	611740662	SB-Thailand	750	3	0	
CY14B101LA2 (7CP1401B8D)	3734080	611740662	SB-Thailand	1000	3	0	
CY14B101LA2 (7CP1401B8D)	3734080	611740662	SB-Thailand	1250	3	0	
CY14B101LA2 (7CP1401B8D)	3734080	611740662	SB-Thailand	1500	3	0	
CY14B101LA2 (7CP1401B8D)	3734080	611740662	SB-Thailand	1750	3	0	
CY14B101LA2 (7CP1401B8D)	3734080	611740662	SB-Thailand	2000	3	0	
STRESS: ESD-HUMAN BODY MODEL PER JESD22, METHOD A114							
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	1100	3	0	
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	2200	8	0	
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	3300	3	0	
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	4000	3	0	
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	5000	3	0	
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	6000	3	0	
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	7000	3	0	
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	8000	3	0	
CY14B101LA2 (7CC1401B8D)	3726089	611731311	CML-RA	1100	3	0	
CY14B101LA2 (7CC1401B8D)	3726089	611731311	CML-RA	2200	8	0	
CY14B101LA2 (7CC1401B8D)	3726089	611731311	CML-RA	3300	3	0	
CY14B101LA2 (7CC1401B8D)	3726089	611731311	CML-RA	4000	3	0	
CY14B101LA2 (7CC1401B8D)	3726089	611731311	CML-RA	5000	3	0	
CY14B101LA2 (7CC1401B8D)	3726089	611731311	CML-RA	6000	3	0	
CY14B101LA2 (7CC1401B8D)	3726089	611731311	CML-RA	7000	3	0	
CY14B101LA2 (7CC1401B8D)	3726089	611731311	CML-RA	8000	3	0	
CY14B101Q32 (7CC1401B4D)	3734080	611736254	M-Phils	1100	3	0	
CY14B101Q32 (7CC1401B4D)	3734080	611736254	M-Phils	2200	8	0	
CY14B101Q32 (7CC1401B4D)	3734080	611736254	M-Phils	3300	3	0	
CY14B101Q32 (7CC1401B4D)	3734080	611736254	M-Phils	4000	3	0	
CY14B101Q32 (7CC1401B4D)	3734080	611736254	M-Phils	5000	3	0	
CY14B101Q32 (7CC1401B4D)	3734080	611736254	M-Phils	6000	3	0	
CY14B101Q32 (7CC1401B4D)	3734080	611736254	M-Phils	7000	3	0	
CY14B101Q32 (7CC1401B4D)	3734080	611736254	M-Phils	8000	3	0	

Reliability Test Data

QTP #: 170803

Device	Fab Lot	Assy Lot #	Assy Loc	Duration	Samp	Rej	Failure Mechanism
STRESS: HIGH TEMP DYNAMIC OPERATING LIFE-EARLY FAILURE RATE, REG-OFF (150C, 3.3V, Vcc Max)							
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	48	1598	0	
STRESS: HIGH TEMP DYNAMIC OPERATING LIFE-EARLY FAILURE RATE, REG-ON (150C, 3.3V, Vcc Max)							
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	48	49	0	
STRESS: HIGH TEMP DYNAMIC OPERATING LIFE-LATENT FAILURE RATE (150C, 3.3V, Vcc Max)							
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	500	80	0	
STRESS: HIGH TEMPERATURE STORAGE, PLASTIC, 150C							
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	500	80	0	
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	1000	80	0	
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	1500	80	0	
STRESS: PRE/POST LFR PARAMETER ASSESSMENT							
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	0	10+2	0	
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	500	10+2	0	
STRESS: PRESSURE COOKER TEST (121C, 100%RH), 15 Psig, PRE COND 192 HR 30C/60%RH (MSL3)							
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	96	80	0	
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	168	80	0	
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	288	80	0	
STRESS: STATIC LATCH-UP (125C, 100mA)							
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	COMP	3	0	
CY14B101NA2 (7CC1401B8D)	3726089	611731311	CML-RA	COMP	3	0	
CY14B101Q32 (7CC1401B4D)	3734080	611736254	M-Phils	COMP	3	0	
CY14E101LA2 (7C1401E8)	3734080	0	CSJ	COMP	3	0	
STRESS: STATIC LATCH-UP (125C, 140mA)							
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	COMP	3	0	
CY14B101NA2 (7CC1401B8D)	3726089	611731311	CML-RA	COMP	3	0	
CY14B101Q32 (7CC1401B4D)	3734080	611736254	M-Phils	COMP	3	0	
CY14E101LA2 (7C1401E8)	3734080	0	CSJ	COMP	3	0	
STRESS: STATIC LATCH-UP (85C, 140mA)							
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	COMP	3	0	
CY14B101NA2 (7CC1401B8D)	3726089	611731311	CML-RA	COMP	3	0	
CY14B101Q32 (7CC1401B4D)	3734080	611736254	M-Phils	COMP	3	0	
CY14E101LA2 (7C1401E8)	3734080	0	CSJ	COMP	3	0	
STRESS: STATIC LATCH-UP (85C, 200mA)							
CY14B101NA2 (7CC1401B6D)	3726089	611727206	CML-RA	COMP	3	0	
CY14B101NA2 (7CC1401B8D)	3726089	611731311	CML-RA	COMP	3	0	
CY14B101Q32 (7CC1401B4D)	3734080	611736254	M-Phils	COMP	3	0	
CY14E101LA2 (7C1401E8)	3734080	0	CSJ	COMP	3	0	

Reliability Test Data

QTP #: 170803

Device	Fab Lot	Assy Lot #	Assy Loc	Duration	Samp	Rej	Failure Mechanism
STRESS: STATIC LATCH-UP (85C, 300mA)							
CY14B101NA2 (7CC1401B6D)	3726089	611727206		CML-RA	COMP	3	0
CY14B101LA2 (7CC1401B8D)	3726089	611731311		CML-RA	COMP	3	0
CY14B101Q32 (7CC1401B4D)	3734080	611736254		M-Phils	COMP	3	0
CY14E101LA2 (7C1401E8)	3734080	0		CSJ	COMP	3	0
STRESS: TC COND. C -65C TO 150C, PRE COND 192 HRS 30C/60%RH (MSL3)							
CY14B101NA2 (7CC1401B6D)	3726089	611727206		CML-RA	500	80	0
CY14B101NA2 (7CC1401B6D)	3726089	611727206		CML-RA	1000	80	0
STRESS: THERMAL JUNCTION MEASUREMENT							
CY14B101NA2 (7CC1401B6D)	3726089	611727206		CML-RA	COMP	1	0



Document History Page

Document Title: QTP# 170803: 1MB nvSRAM Device Family, S8TNV1-5 Technology, Fab 25
Document Number: 002-22266

Rev.	ECN No.	Orig. of Change	Description of Change
**	5982878	JYF	Initial spec release.