



## Product Change Notification / SYST-29QVJG807

---

### Date:

30-Nov-2021

### Product Category:

Clock and Timing - High Speed Communication

### PCN Type:

Document Change

### Notification Subject:

Data Sheet - SY87700AL Data Sheet Document Revision

### Affected CPNs:

[SYST-29QVJG807\\_Affected\\_CPN\\_11302021.pdf](#)

[SYST-29QVJG807\\_Affected\\_CPN\\_11302021.csv](#)

### Notification Text:

SYST-29QVJG807

Microchip has released a new Product Documents for the SY87700AL Data Sheet of devices. If you are using one of these devices please read the document located at [SY87700AL Data Sheet](#).

**Notification Status:** Final

#### Description of Change:

- 1) Converted Micrel document SY87700AL to Microchip data sheet DS20006628A.
- 2) Removed all reference to the EOL'd 28-Lead SOIC package option.
- 3) Minor text changes throughout.

**Impacts to Data Sheet:** See above details.

**Reason for Change:** To Improve Productivity

**Change Implementation Status:** Complete

**Date Document Changes Effective:** 30 Nov 2021

**NOTE:** Please be advised that this is a change to the document only the product has not been changed.

Markings to Distinguish Revised from Unrevised Devices: N/A

## Attachments:

[SY87700AL Data Sheet](#)

Please contact your local [Microchip sales office](#) with questions or concerns regarding this notification.

## Terms and Conditions:

If you wish to receive Microchip PCNs via email please register for our PCN email service at our [PCN home page](#) select register then fill in the required fields. You will find instructions about registering for Microchips PCN email service in the [PCN FAQ](#) section.

If you wish to change your PCN profile, including opt out, please go to the [PCN home page](#) select login and sign into your myMicrochip account. Select a profile option from the left navigation bar and make the applicable selections.

Affected Catalog Part Numbers (CPN)

SY87700ALHG

SY87700ALHG-TR

---

## Low-Power, 3.3V, 32 Mbps to 208 Mbps AnyRate<sup>®</sup> Clock and Data Recovery

---

### Features

- 3.3V Power Supply
- SONET/SDH/ATM Compatible
- Clock and Data Recovery from 32 Mbps Up to 208 Mbps NRZ Data Stream; Clock Generation from 32 Mbps to 208 Mbps
- Two On-Chip PLLs: One for Clock Generation and Another for Clock Recovery
- Selectable Reference Frequencies
- Differential PECL High-Speed Serial I/O
- Line Receiver Input: No External Buffering Needed
- Link Fault Indication
- 100K ECL-Compatible I/O
- Industrial Temperature Range: -40°C to +85°C
- Low Power: Fully Compatible SY87700V, but Consumes 30% Less Power
- Available in a 32-Lead ePAD TQFP Package

### Applications

- SONET/SDH/ATM OC-1 and OC-3
- Fast Ethernet, SMPTE 259
- Proprietary Architecture Up to 208 Mbps

### General Description

The SY87700AL is a complete clock recovery and data re-timing integrated circuit for data rates from 32 Mbps up to 208 Mbps NRZ. The device is ideally suited for SONET/SDH/ATM applications and other high-speed data transmission systems.

Clock recovery and data re-timing is performed by synchronizing the on-chip VCO directly to the incoming data stream. The VCO center frequency is controlled by the reference clock frequency and the selected divide ratio. On-chip clock generation is performed through the use of a frequency multiplier PLL with a byte rate source as reference.

The SY87700AL also includes a link fault detection circuit.

# SY87700AL

## 1.0 ELECTRICAL CHARACTERISTICS

### Absolute Maximum Ratings †

Supply Voltage ( $V_{CC}$ )	.....	-0.5V to +4.0V
Input Voltage ( $V_{IN}$ )	.....	-0.5V to $V_{CC}$
Output Current ( $I_{OUT}$ )		
Continuous	.....	±50 mA
Surge	.....	±100 mA

### Operating Ratings ‡

Input Voltage ( $V_{CC}$ )	.....	-3.15V to +3.45V
----------------------------	-------	------------------

† **Notice:** Stresses above those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. This is a stress rating only and functional operation of the device at those or any other conditions above those indicated in the operational sections of this specification is not intended. Exposure to maximum rating conditions for extended periods may affect device reliability.

‡ **Notice:** The device is not guaranteed to function outside its operating ratings.

## DC ELECTRICAL CHARACTERISTICS

Parameter	Symbol	Min.	Typ.	Max.	Units	Conditions
Power Supply Voltage	$V_{CC}$	3.15	3.3	3.45	V	—
Power Supply Current	$I_{CC}$	—	120	160	mA	—

## PECL 100K DC ELECTRICAL CHARACTERISTICS

**Electrical Characteristics:**  $V_{CC} = V_{CCO} = V_{CCA} = 3.3V \pm 5\%$ ;  $T_A = -40^\circ C$  to  $+85^\circ C$ , unless otherwise noted.

Parameter	Symbol	Min.	Typ.	Max.	Units	Conditions
Input HIGH Voltage	$V_{IH}$	$V_{CC} - 1.165$	—	$V_{CC} - 0.880$	V	—
Input LOW Voltage	$V_{IL}$	$V_{CC} - 1.810$	—	$V_{CC} - 1.475$	V	—
Output HIGH Voltage	$V_{OH}$	$V_{CC} - 1.075$	—	$V_{CC} - 0.830$	V	$50\Omega$ to $V_{CC} - 2V$
Output LOW Voltage	$V_{OL}$	$V_{CC} - 1.860$	—	$V_{CC} - 1.570$	V	$50\Omega$ to $V_{CC} - 2V$
Input LOW Current	$I_{IL}$	0.5	—	—	$\mu A$	$V_{IN} = V_{IL(MIN)}$

## TTL DC ELECTRICAL CHARACTERISTICS

**Electrical Characteristics:**  $V_{CC} = V_{CCO} = V_{CCA} = 3.3V \pm 5\%$ ;  $T_A = -40^\circ C$  to  $+85^\circ C$ , unless otherwise noted.

Parameter	Symbol	Min.	Typ.	Max.	Units	Conditions
Input HIGH Voltage	$V_{IH}$	2.0	—	$V_{CC}$	V	—
Input LOW Voltage	$V_{IL}$	—	—	0.8	V	—
Output HIGH Voltage	$V_{OH}$	2.0	—	—	V	$I_{OH} = -0.4$ mA
Output LOW Voltage	$V_{OL}$	—	—	0.5	V	$I_{OL} = 4$ mA
Input HIGH Current	$I_{IH}$	-175	—	—	$\mu A$	$V_{IN} = 2.7V$ , $V_{CC} = \text{Max.}$
		—	—	100	$\mu A$	$V_{IN} = V_{CC}$ , $V_{CC} = \text{Max.}$
Input LOW Current	$I_{IL}$	-300	—	—	$\mu A$	$V_{IN} = 0.5V$ , $V_{CC} = \text{Max.}$
Output Short-Circuit Current	$I_{OS}$	-15	—	-100	mA	$V_{OUT} = 0V$ , (Max., 1 sec.)

## AC ELECTRICAL CHARACTERISTICS

**Electrical Characteristics:**  $V_{CC} = V_{CCO} = V_{CCA} = 3.3V \pm 5\%$ ;  $T_A = -40^{\circ}C$  to  $+85^{\circ}C$ , unless otherwise noted.

Parameter	Symbol	Min.	Typ.	Max.	Units	Conditions
VCO Center Frequency	$f_{VCO}$	750	—	1250	MHz	$f_{REFCLK} \times \text{Byte Rate}$
VCO Center Frequency Tolerance	$\Delta f_{VCO}$	—	5	—	%	Nominal
Acquisition Lock Time	$t_{ACQ}$	—	—	15	$\mu s$	$50\Omega$ to $V_{CC} - 2$
REFCLK Pulse Width HIGH	$t_{CPWH}$	4	—	—	ns	$50\Omega$ to $V_{CC} - 2$
REFCLK Pulse Width LOW	$t_{CPWL}$	4	—	—	ns	$V_{IN} = V_{IL}$ (Min.)
REFCLK Input Rise Time	$t_{IR}$	—	0.5	2	ns	—
Output Duty Cycle (RCLK/TCLK)	$t_{ODC}$	45	—	55	% of UI	—
ECL Output Rise/Fall Time (20% to 80%)	$t_r/t_f$	100	—	400	ps	$50\Omega$ to $V_{CC} - 2$
Recovered Clock Skew	$t_{SKEW}$	-200	—	200	ps	—
Data Valid	$t_{DV}$	$1/(2 \times f_{RCLK}) - 200$	—	—	ps	—
Data Hold	$t_{DH}$	$1/(2 \times f_{RCLK}) - 200$	—	—	ps	—


## TEMPERATURE SPECIFICATIONS (Note 1)

Parameters	Sym.	Min.	Typ.	Max.	Units	Conditions
<b>Temperature Ranges</b>						
Ambient Temperature Range	$T_A$	-40	—	+85	$^{\circ}C$	—
Lead Temperature	—	—	—	+260	$^{\circ}C$	Soldering, 20 sec.
Storage Temperature	$T_S$	-65	—	+150	$^{\circ}C$	—
<b>Package Thermal Resistance</b>						
Thermal Resistance, TQFP 32-Ld, Note 2	$\theta_{JA}$	—	27.6	—	$^{\circ}C/W$	0 lfpm airflow
	$\theta_{JA}$	—	22.6	—	$^{\circ}C/W$	200 lfpm airflow
	$\theta_{JA}$	—	20.7	—	$^{\circ}C/W$	500 lfpm airflow

**Note 1:** The maximum allowable power dissipation is a function of ambient temperature, the maximum allowable junction temperature and the thermal resistance from junction to air (i.e.,  $T_A$ ,  $T_J$ ,  $\theta_{JA}$ ). Exceeding the maximum allowable power dissipation will cause the device operating junction temperature to exceed the maximum +85 $^{\circ}C$  rating. Sustained junction temperatures above +85 $^{\circ}C$  can impact the device reliability.

**2:** Using JEDEC standard test boards with die attach pad soldered to PCB. See [www.amkor.com](http://www.amkor.com) for additional package details.


## Timing Waveforms



# SY87700AL

## 2.0 PIN DESCRIPTIONS

### Package Type



The descriptions of the pins are listed in [Table 2-1](#).

**TABLE 2-1: PIN FUNCTION TABLE**

Pin Number	Pin Name	Description
<b>Inputs</b>		
2 3	RDINP RDINN	Serial Data Input. Differential PECL: These built-in line receiver inputs are connected to the differential receive serial data stream. An internal receive PLL recovers the embedded clock (RCLK) and data (RDOUT) information. The incoming data rate can be within one of eight frequency ranges depending on the state of the FREQSEL pins. See "Frequency Selection" Table.
5	REFCLK	Reference Clock. TTL Input: This input is used as the reference for the internal frequency synthesizer and the "training" frequency for the receiver PLL to keep it centered in the absence of data coming in on the RDIN inputs
26	CD	Carrier Detect. PECL Input: This input controls the recovery function of the Receive PLL and can be driven by the carrier detect output of optical modules or from external transition detection circuitry. When this input is HIGH the input data stream (RDIN) is recovered normally by the Receive PLL. When this input is LOW the data on the inputs RDIN will be internally forced to a constant LOW, the data outputs RDOUT will remain LOW, the Link Fault Indicator output LFIN forced LOW and the clock recovery PLL forced to lock onto the clock frequency generated from REFCLK.
4 6 7	FREQSEL1 FREQSEL2 FREQSEL3	Frequency Select. TTL Inputs: These inputs select the output clock frequency range as shown in the "Frequency Selection" Table.
32 25	DIVSEL1 DIVSEL2	Divider Select. TTL Inputs: These inputs select the ratio between the output clock frequency (RCLK/TCLK) and the REFCLK input frequency as shown in the "Reference Frequency Selection" Table.
16	CLKSEL	Clock Select. TTL Input: This input is used to select either the recovered clock of the receiver PLL (CLKSEL = HIGH) or the clock of the frequency synthesizer (CLKSEL = LOW) to the TCLK outputs.

TABLE 2-1: PIN FUNCTION TABLE


Pin Number	Pin Name	Description
<b>Outputs</b>		
31	LFIN	Link Fault Indicator. TTL Output: This output indicates the status of the input data stream RDIN. Active HIGH signal is indicating when the internal clock recovery PLL has locked onto the incoming data stream. LFIN will go HIGH if CD is HIGH and RDIN is within the frequency range of the Receive PLL (1000 ppm). LFIN is an asynchronous output.
24 23	RDOUTP RDOUTN	Receive Data Output. Differential PECL: These ECL 100k outputs represent the recovered data from the input data stream (RDIN). This recovered data is specified against the rising edge of RCLK.
21 20	RCLKP RCLKN	Clock Output. Differential PECL: These ECL 100k outputs represent the recovered clock used to sample the recovered data (RDOUT).
18 17	TCLKP TCLKN	Clock Output. Differential PECL: These ECL 100k outputs represent either the recovered clock (CLKSEL = HIGH) used to sample the recovered data (RDOUT) or the transmit clock of the frequency synthesizer (CLKSEL = LOW).
9 10	PLLSP PLLSN	Clock Synthesis PLL Loop Filter: External loop filter pins for the clock synthesis PLL.
15 14	PLLRP PLLRN	Clock Recovery PLL Loop Filter: External loop filter pins for the receiver PLL.
<b>Power and Ground</b>		
27, 28	VCC	Supply Voltage( <a href="#">Note 1</a> )
29, 30	VCCA	Analog Supply Voltage( <a href="#">Note 1</a> )
19, 22	VCCO	Output Supply Voltage( <a href="#">Note 1</a> )
12, 13	GND	Ground.
1, 8	NC	No connect.
11	GNDA	Analog Ground.

**Note 1:** VCC, VCCA, VCCO must be the same value.



## 3.0 FUNCTIONAL DESCRIPTION

### Functional Block Diagram



### 3.1 Clock Recovery

Clock recovery, as shown in the block diagram, generates a clock that is at the same frequency as the incoming data bit rate at the serial data input. The clock is phase aligned by a PLL so that it samples the data in the center of the data eye pattern.

The phase relationship between the edge transitions of the data and those of the generated clock are compared by a phase/frequency detector. Output pulses from the detector indicate the required direction of phase correction. These pulses are smoothed by an integral loop filter. The output of the loop filter controls the frequency of the Voltage Controlled Oscillator (VCO), which generates the recovered clock.

Frequency stability, without incoming data, is guaranteed by an alternate reference input (REFCLK) that the PLL locks onto when data is lost. If the frequency of the incoming signal varies by greater than approximately 1000 ppm with respect to the synthesizer frequency, the PLL will be declared out of lock, and the PLL will lock to the reference clock.

The loop filter transfer function is optimized to enable the PLL to track the jitter, yet tolerate the minimum transition density expected in a received SONET data signal. This transfer function yields a 30  $\mu$ s data stream of continuous 1's or 0's for random incoming NRZ data.

### 3.2 Lock Detect

The SY87700AL contains a link fault indication circuit, which monitors the integrity of the serial data inputs. If the received serial data fails the frequency test, then the PLL will be forced to lock to the local reference clock. This will maintain the correct frequency of the recovered clock output under loss of signal or loss of lock conditions. If the recovered clock frequency deviates from the local reference clock frequency by more than approximately 1000 ppm, the PLL will be declared out of lock. The lock detect circuit will poll the input data stream in an attempt to reacquire lock to data. If the recovered clock frequency is determined to be within approximately 1000 ppm, the PLL will be declared in lock and the lock detect output will go active.

During the interval when the CDR is not locked onto the RDIN input, the LFIN output will not be a static LOW, but will be changing.

**TABLE 3-1: FREQUENCY SELECTION TABLE**


FREQSEL1	FREQSEL2	FREQSEL3	$f_{VCO}/f_{RCLK}$	$f_{RCLK}$ Data Rates
0	1	1	6	125 Mbps to 208 Mbps
1	0	0	8	94 Mbps to 156 Mbps
1	0	1	12	63 Mbps to 104 Mbps
1	1	0	16	47 Mbps to 78 Mbps
1	1	1	24	32 Mbps to 52 Mbps
0	1	0	—	Undefined
0	0	X (Note 2)	—	Undefined

**Note 1:** SY87700AL operates from 32 MHz to 208 MHz. For higher speed applications, the SY87701AL operates from 28 MHz to 1300 MHz.


**2:** X is a Don't Care.

**TABLE 3-2: REFERENCE FREQUENCY SELECTION**

DIVSEL1	DIVSEL2	$f_{RCLK}/f_{REFCLK}$
0	0	8
0	1	10
1	0	16
1	1	20



**FIGURE 3-1:** Loop Filter Components.




**FIGURE 3-2:** Application Example: AC-Coupled I/O.

TABLE 3-3: BILL OF MATERIALS (AC-COUPLED)

Item	Part Number	Manufacturer	Description	Qty.
C6	293D685X0025B2T	Vishay	6.8 $\mu$ F, 25V, Tantalum Capacitor, Size B	1
C7	VJ206Y103JXJAT	Vishay	0.01 $\mu$ F Ceramic Capacitor, Size 1206, X7R Dielectric	1
C10, C11	VJ0603Y105JXJAT	Vishay	1.0 $\mu$ F Ceramic Capacitor, Size 0603, X7R Dielectric	2
C12 - C15, C18, C19, C27, C28	VJ0402Y104JXJAT	Vishay	0.1 $\mu$ F Ceramic Capacitor, Size 0402, X7R Dielectric	8
C20 - C26	VJ0402Y104JXJAT	Vishay	0.01 $\mu$ F Ceramic Capacitor, Size 1206, X7R Dielectric	7
D1	P301-ND	Panasonic	LED Diode, T-1 3/4, Red Clear	1
D2	P300-ND/P301-ND	Vishay	T-1 3/4, Red LED	1
J2, J3, J4, J6	111-0702-001	Johnson Components	Red, Insulated Thumb Nut Binding Post (Jumped Together)	4
J5	BLM21A102F	Murata	Black, Insulated Thumb Nut Binding Post, GND (Jumped to $V_{EE}$ )	1
Q1	459-2598-5-ND	NTE	2N2222A Buffer/Driver Transistor, NPN	1
R1	CRCW04023500F	Vishay	350 $\Omega$ Resistor, 2%, Size 0402	1
R2	CRCW04026800F	Vishay	680 $\Omega$ Resistor, 2%, Size 0402	1
R3 - R10	CRCW04021001F	Vishay	1 k $\Omega$ Pull-up Resistor, 2%, Size 1206	8
R11 - R16, R28 - R30, R32	CRCW04021820F	Vishay	182 $\Omega$ Resistor, 2%, Size 0402	10
R21	CRCW06031300F	Vishay	130 $\Omega$ Resistor, 2%, Size 0603	1
R22	CRCW04021820F	Vishay	12.1 k $\Omega$ Resistor, 2%, Size 1206	1
R23, R24	CRCW04022825F	Vishay	82 $\Omega$ Resistor, 2%, Size 0402	2
R25, R26	CRCW04021300F	Vishay	130 $\Omega$ Resistor, 2%, Size 0402	2
R27	CRCW040200R0F	Vishay	0 $\Omega$ Resistor, 2%, Size 0402	1
R31	CRCW04025000F	Vishay	50 $\Omega$ Resistor, 2%, Size 0402	1
SMA1 - SMA10	142-0701-851	Johnson Components	End Launch SMA Jack	10
SP1 - SP6	—	—	Solder Jump Option	6
SW1	CT2068-ND	CTS	8-Position, Top Actuated Slide Dip Switch	1
U1	SY87700AL	Microchip	Low-Power 3.3V 28 Mbps to 216 Mbps AnyRate® Clock and Data Recovery	1
U2	SY89322V	Microchip	3.3/5V Dual LVTTTL/LVCMOS-to-Differential LVPECL Translator	1

# SY87700AL



**FIGURE 3-3:** Application Example: DC-Coupled I/O.

TABLE 3-4: BILL OF MATERIALS (DC-COUPLED)


Item	Part Number	Manufacturer	Description	Qty.
C6	293D685X0025B2T	Vishay	6.8 $\mu$ F, 25V, Tantalum Capacitor, Size B	1
C7	VJ206Y103JXJAT	Vishay	0.01 $\mu$ F Ceramic Capacitor, Size 1206, X7R Dielectric	1
C10, C11	VJ0603Y105JXJAT	Vishay	1.0 $\mu$ F Ceramic Capacitor, Size 0603, X7R Dielectric	2
C12 - C15, C18, C19, C27, C28	VJ0402Y104JXJAT	Vishay	0.1 $\mu$ F Ceramic Capacitor, Size 0402, X7R Dielectric	8
C20 - C26	VJ0402Y104JXJAT	Vishay	0.01 $\mu$ F Ceramic Capacitor, Size 1206, X7R Dielectric	7
D1	P301-ND	Panasonic	LED Diode, T-1 3/4, Red Clear	1
D2	P300-ND/P301-ND	Vishay	T-1 3/4, Red LED	1
J2, J3, J4, J6	111-0702-001	Johnson Components	Red, Insulated Thumb Nut Binding Post (Jumped Together)	4
J5	BLM21A102F	Murata	Black, Insulated Thumb Nut Binding Post, GND (Jumped to $V_{EE}$ )	1
Q1	459-2598-5-ND	NTE	2N2222A Buffer/Driver Transistor, NPN	1
R1	CRCW04023500F	Vishay	350 $\Omega$ Resistor, 2%, Size 0402	1
R2	CRCW04026800F	Vishay	680 $\Omega$ Resistor, 2%, Size 0402	1
R3 - R10	CRCW04021001F	Vishay	1 k $\Omega$ Pull-up Resistor, 2%, Size 1206	8
R15, R16, R30, R32	CRCW04021820F	Vishay	182 $\Omega$ Resistor, 2%, Size 0402	4
R21	CRCW06031300F	Vishay	130 $\Omega$ Resistor, 2%, Size 0603	1
R22	CRCW04021820F	Vishay	12.1 k $\Omega$ Resistor, 2%, Size 1206	1
R23, R24	CRCW04022825F	Vishay	82 $\Omega$ Resistor, 2%, Size 0402	2
R27	CRCW040200R0F	Vishay	0 $\Omega$ Resistor, 2%, Size 0402	1
R31	CRCW04025000F	Vishay	50 $\Omega$ Resistor, 2%, Size 0402	1
SMA1 - SMA10	142-0701-851	Johnson Components	End Launch SMA Jack	10
SP1 - SP6	—	—	Solder Jump Option	6
SW1	CT2068-ND	CTS	8-Position, Top Actuated Slide Dip Switch	1
U1	SY87700AL	Microchip	Low-Power 3.3V 28 Mbps to 216 Mbps AnyRate <sup>®</sup> Clock and Data Recovery	1
U2	SY89322V	Microchip	3.3/5V Dual LVTTTL/LVC MOS-to-Differential LVPECL Translator	1

## 4.0 LAYOUT AND GENERAL SUGGESTIONS

- Establish controlled impedance stripline, microstrip, or coplanar construction techniques.
- Signal paths should have approximately the same width as the device pads.
- All differential paths are critical timing paths, where skew should be matched to within  $\pm 10$  ps.
- Signal trace impedance should not vary more than  $\pm 5\%$ . If in doubt, perform TDR analysis of all high-speed signal traces.
- Maintain compact filter networks as close to filter pins as possible. Provide ground plane relief under filter path to reduce stray capacitance. Be careful of crosstalk coupling into the filter network.
- Maintain low jitter on the REFCLK input. Isolate the XTAL oscillator from power supply noise by adequately decoupling. Keep XTAL oscillator close to device, and minimize capacitive coupling from adjacent signals.
- Higher speed operation may require use of fundamental-tone (third-overtone typically has more jitter) crystal-based oscillator for optimum performance. Evaluate and compare candidates by measuring TXCLK jitter.
- All unused outputs must be terminated. To conserve power, unused PECL outputs can be terminated with a 1 k $\Omega$  resistor to  $V_{EE}$ .

## 5.0 PACKAGING INFORMATION

### 5.1 Package Marking Information



<b>Legend:</b>	<p>XX...X Product code or customer-specific information</p> <p>Y Year code (last digit of calendar year)</p> <p>YY Year code (last 2 digits of calendar year)</p> <p>WW Week code (week of January 1 is week '01')</p> <p>NNN Alphanumeric traceability code</p> <p>(e3) Pb-free JEDEC® designator for Matte Tin (Sn)</p> <p>* This package is Pb-free. The Pb-free JEDEC designator ((e3)) can be found on the outer packaging for this package.</p> <p>•, ▲, ▼ Pin one index is identified by a dot, delta up, or delta down (triangle mark).</p>
<b>Note:</b>	<p>In the event the full Microchip part number cannot be marked on one line, it will be carried over to the next line, thus limiting the number of available characters for customer-specific information. Package may or may not include the corporate logo.</p> <p>Underbar ( _ ) and/or Overbar ( ¯ ) symbol may not be to scale.</p>




# SY87700AL

## 32-Lead TQFP Package Outline and Recommended Land Pattern

### TITLE


32 LEAD TQFP 7X7 mm EPAD PACKAGE OUTLINE & RECOMMENDED LAND PATTERN




## TITLE

32 LEAD TQFP 7X7 mm EPAD PACKAGE OUTLINE & RECOMMENDED LAND PATTERN


DRAWING #	TQFPEP7X7-32LD-PL-2	UNIT	MM [INCH]
Lead Frame	Copper	Lead Finish	Matte Tin




TOP VIEW



BOTTOM VIEW




SIDE VIEW



DETAIL "A"

### NOTES:

1. DIMENSIONS ARE IN MM(INCHES).
2. CONTROLLING DIMENSION: MM.
3. DIMENSION DOES NOT INCLUDE MOLD FLASH OR PROTRUSIONS, EITHER OF WHICH SHALL NOT EXCEED 0.254 [0.010].
4. LEAD DIMENSION DOES NOT INCLUDE DAMBAR PROTRUSION.
5. MAXIMUM AND MINIMUM SPECIFICATIONS ARE INDICATED AS FOLLOWS: MAX/MIN.
6. THESE DIMENSIONS TO BE DETERMINED AT DATUM PLANE [H].
7. PACKAGE TOP DIMENSIONS ARE SMALLER THAN BOTTOM DIMENSIONS AND TOP OF PACKAGE WILL NOT OVERHANG BOTTOM OF PACKAGE.
8. EXPOSED PAD SHALL BE COPLANAR WITH PACKAGE BOTTOM WITHIN 0.05mm.
9. EXPOSED PAD: Cu WITH Sn/Pb PLATING.
10. RED CIRCLES IN LAND PATTERN REPRESENT THERMAL VIAS. RECOMMENDED SIZE IS 0.30MM DIAMETER, CONNECT TO GND.



RECOMMENDED LAND PATTERN

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>.

# SY87700AL

---

NOTES:

## APPENDIX A: REVISION HISTORY

### Revision A (November 2021)

- Converted Micrel document SY87700AL to Microchip data sheet DS20006628A.
- Removed all reference to the EOL'd 28-Lead SOIC package option.
- Minor text changes throughout.

# SY87700AL

---

NOTES:

## PRODUCT IDENTIFICATION SYSTEM

To order or obtain information, e.g., on pricing or delivery, contact your local Microchip representative or sales office.

<u>PART No.</u>	X	X	X	-XX
Device	Supply Voltage	Package	Temperature Range	Media Type
<div> <div> <b>Device:</b> SY87700A: Low-Power, 3.3V, 32 Mbps to 208 Mbps AnyRate<sup>®</sup> Clock and Data Recovery </div> <div> <b>Supply Voltage:</b> L = 3.3V </div> <div> <b>Package:</b> H = 32-Lead TQFP </div> <div> <b>Temperature Range:</b> G = -40°C to +85°C </div> <div> <b>Media Type:</b> (blank)= 250/Tray TR = 1,000/Reel </div> </div>				
<b>Examples:</b> <div> a) SY87700ALHG: SY87700A, 3.3V Supply Voltage, 32-Lead TQFP, -40°C to +85°C Temp. Range, 250/Tray </div> <div> b) SY87700ALHG-TR: SY87700A, 3.3V Supply Voltage, 32-Lead TQFP, -40°C to +85°C Temp. Range, 1,000/Reel </div>				
<b>Note 1:</b> Tape and Reel identifier only appears in the catalog part number description. This identifier is used for ordering purposes and is not printed on the device package. Check with your Microchip Sales Office for package availability with the Tape and Reel option.				

# SY87700AL

---

NOTES:

---

**Note the following details of the code protection feature on Microchip products:**

- Microchip products meet the specifications contained in their particular Microchip Data Sheet.
  - Microchip believes that its family of products is secure when used in the intended manner, within operating specifications, and under normal conditions.
  - Microchip values and aggressively protects its intellectual property rights. Attempts to breach the code protection features of Microchip product is strictly prohibited and may violate the Digital Millennium Copyright Act.
  - Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code protection does not mean that we are guaranteeing the product is “unbreakable”. Code protection is constantly evolving. Microchip is committed to continuously improving the code protection features of our products.
- 

This publication and the information herein may be used only with Microchip products, including to design, test, and integrate Microchip products with your application. Use of this information in any other manner violates these terms. Information regarding device applications is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. Contact your local Microchip sales office for additional support or, obtain additional support at <https://www.microchip.com/en-us/support/design-help/client-support-services>.

THIS INFORMATION IS PROVIDED BY MICROCHIP “AS IS”. MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, OR CONSEQUENTIAL LOSS, DAMAGE, COST, OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP’S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION.

Use of Microchip devices in life support and/or safety applications is entirely at the buyer’s risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

For information regarding Microchip’s Quality Management Systems, please visit [www.microchip.com/quality](http://www.microchip.com/quality).

**Trademarks**

The Microchip name and logo, the Microchip logo, Adaptec, AnyRate, AVR, AVR logo, AVR Freaks, BesTime, BitCloud, CryptoMemory, CryptoRF, dsPIC, flexPWR, HELDO, IGLOO, JukeBlox, KeeLoq, Klear, LANCheck, LinkMD, maxStylus, maxTouch, MediaLB, megaAVR, Microsemi, Microsemi logo, MOST, MOST logo, MPLAB, OptoLyzer, PIC, picoPower, PICSTART, PIC32 logo, PolarFire, Prochip Designer, QTouch, SAM-BA, SenGenuity, SpyNIC, SST, SST Logo, SuperFlash, Symmetricom, SyncServer, Tachyon, TimeSource, tinyAVR, UNI/O, Vectron, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

AgileSwitch, APT, ClockWorks, The Embedded Control Solutions Company, EtherSynch, Flashtec, Hyper Speed Control, HyperLight Load, IntelliMOS, Libero, motorBench, mTouch, Powermite 3, Precision Edge, ProASIC, ProASIC Plus, ProASIC Plus logo, QuietWire, SmartFusion, SyncWorld, Temux, TimeCesium, TimeHub, TimePictra, TimeProvider, TrueTime, WinPath, and ZL are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, AnyIn, AnyOut, Augmented Switching, BlueSky, BodyCom, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, Espresso T1S, EtherGREEN, GridTime, IdealBridge, In-Circuit Serial Programming, ICSP, INICnet, Intelligent Paralleling, Inter-Chip Connectivity, JitterBlocker, Knob-on-Display, maxCrypto, maxView, memBrain, Mindi, MiWi, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, NVm Express, NVMe, Omniscient Code Generation, PICDEM, PICDEM.net, PICKit, PICtail, PowerSmart, PureSilicon, QMatrix, REAL ICE, Ripple Blocker, RTAX, RTG4, SAM-ICE, Serial Quad I/O, simpleMAP, SimpliPHY, SmartBuffer, SmartHLS, SMART-I.S., storClad, SQI, SuperSwitcher, SuperSwitcher II, Switchtec, SynchroPHY, Total Endurance, TSHARC, USBCheck, VariSense, VectorBlox, VeriPHY, ViewSpan, WiperLock, XpressConnect, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

The Adaptec logo, Frequency on Demand, Silicon Storage Technology, Symmcom, and Trusted Time are registered trademarks of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2021, Microchip Technology Incorporated and its subsidiaries.

All Rights Reserved.

ISBN: 978-1-5224-9384-6



## Worldwide Sales and Service

### AMERICAS

**Corporate Office**  
2355 West Chandler Blvd.  
Chandler, AZ 85224-6199  
Tel: 480-792-7200  
Fax: 480-792-7277  
Technical Support:  
<http://www.microchip.com/support>  
Web Address:  
[www.microchip.com](http://www.microchip.com)

**Atlanta**  
Duluth, GA  
Tel: 678-957-9614  
Fax: 678-957-1455

**Austin, TX**  
Tel: 512-257-3370

**Boston**  
Westborough, MA  
Tel: 774-760-0087  
Fax: 774-760-0088

**Chicago**  
Itasca, IL  
Tel: 630-285-0071  
Fax: 630-285-0075

**Dallas**  
Addison, TX  
Tel: 972-818-7423  
Fax: 972-818-2924

**Detroit**  
Novi, MI  
Tel: 248-848-4000

**Houston, TX**  
Tel: 281-894-5983

**Indianapolis**  
Noblesville, IN  
Tel: 317-773-8323  
Fax: 317-773-5453  
Tel: 317-536-2380

**Los Angeles**  
Mission Viejo, CA  
Tel: 949-462-9523  
Fax: 949-462-9608  
Tel: 951-273-7800

**Raleigh, NC**  
Tel: 919-844-7510

**New York, NY**  
Tel: 631-435-6000

**San Jose, CA**  
Tel: 408-735-9110  
Tel: 408-436-4270

**Canada - Toronto**  
Tel: 905-695-1980  
Fax: 905-695-2078

### ASIA/PACIFIC

**Australia - Sydney**  
Tel: 61-2-9868-6733

**China - Beijing**  
Tel: 86-10-8569-7000

**China - Chengdu**  
Tel: 86-28-8665-5511

**China - Chongqing**  
Tel: 86-23-8980-9588

**China - Dongguan**  
Tel: 86-769-8702-9880

**China - Guangzhou**  
Tel: 86-20-8755-8029

**China - Hangzhou**  
Tel: 86-571-8792-8115

**China - Hong Kong SAR**  
Tel: 852-2943-5100

**China - Nanjing**  
Tel: 86-25-8473-2460

**China - Qingdao**  
Tel: 86-532-8502-7355

**China - Shanghai**  
Tel: 86-21-3326-8000

**China - Shenyang**  
Tel: 86-24-2334-2829

**China - Shenzhen**  
Tel: 86-755-8864-2200

**China - Suzhou**  
Tel: 86-186-6233-1526

**China - Wuhan**  
Tel: 86-27-5980-5300

**China - Xian**  
Tel: 86-29-8833-7252

**China - Xiamen**  
Tel: 86-592-2388138

**China - Zhuhai**  
Tel: 86-756-3210040

### ASIA/PACIFIC

**India - Bangalore**  
Tel: 91-80-3090-4444

**India - New Delhi**  
Tel: 91-11-4160-8631

**India - Pune**  
Tel: 91-20-4121-0141

**Japan - Osaka**  
Tel: 81-6-6152-7160

**Japan - Tokyo**  
Tel: 81-3-6880-3770

**Korea - Daegu**  
Tel: 82-53-744-4301

**Korea - Seoul**  
Tel: 82-2-554-7200

**Malaysia - Kuala Lumpur**  
Tel: 60-3-7651-7906

**Malaysia - Penang**  
Tel: 60-4-227-8870

**Philippines - Manila**  
Tel: 63-2-634-9065

**Singapore**  
Tel: 65-6334-8870

**Taiwan - Hsin Chu**  
Tel: 886-3-577-8366

**Taiwan - Kaohsiung**  
Tel: 886-7-213-7830

**Taiwan - Taipei**  
Tel: 886-2-2508-8600

**Thailand - Bangkok**  
Tel: 66-2-694-1351

**Vietnam - Ho Chi Minh**  
Tel: 84-28-5448-2100

### EUROPE

**Austria - Wels**  
Tel: 43-7242-2244-39  
Fax: 43-7242-2244-393

**Denmark - Copenhagen**  
Tel: 45-4485-5910  
Fax: 45-4485-2829

**Finland - Espoo**  
Tel: 358-9-4520-820

**France - Paris**  
Tel: 33-1-69-53-63-20  
Fax: 33-1-69-30-90-79

**Germany - Garching**  
Tel: 49-8931-9700

**Germany - Haan**  
Tel: 49-2129-3766400

**Germany - Heilbronn**  
Tel: 49-7131-72400

**Germany - Karlsruhe**  
Tel: 49-721-625370

**Germany - Munich**  
Tel: 49-89-627-144-0  
Fax: 49-89-627-144-44

**Germany - Rosenheim**  
Tel: 49-8031-354-560

**Israel - Ra'anana**  
Tel: 972-9-744-7705

**Italy - Milan**  
Tel: 39-0331-742611  
Fax: 39-0331-466781

**Italy - Padova**  
Tel: 39-049-7625286

**Netherlands - Drunen**  
Tel: 31-416-690399  
Fax: 31-416-690340

**Norway - Trondheim**  
Tel: 47-7288-4388

**Poland - Warsaw**  
Tel: 48-22-3325737

**Romania - Bucharest**  
Tel: 40-21-407-87-50

**Spain - Madrid**  
Tel: 34-91-708-08-90  
Fax: 34-91-708-08-91

**Sweden - Gothenberg**  
Tel: 46-31-704-60-40

**Sweden - Stockholm**  
Tel: 46-8-5090-4654

**UK - Wokingham**  
Tel: 44-118-921-5800  
Fax: 44-118-921-5820