



PRODUCT CHANGE NOTIFICATION (PCN)

ISSUE DATE: 03.03.2022
MODIFICATION / REVISION DATE: 03.03.2022

AKSNT/x BLACK Jumper Connector

CHANGE NOTIFICATION: PCN 20220303_AKSNTxBLACK

DESCRIPTION OF CHANGES: CHANGE OF PRODUCT LOCATION
CHANGE OF DATA SHEET
New Draw.-No. ASS_1004_COrev04

REASON FOR CHANGE: CHANGE OF PRODUCT LOCATION
CHANGE OF PRODUCT DIMENSIONS, TOLERANCES AND/OR PROPERTIES

KEY CHARACTERISTICS OF CHANGE: Details see page 3

PRODUCTS AFFECTED: AKSNT/x BLACK

DATE OF CHANGE AND IMPLEMENTATION: CHANGE: WEEK 10 / YEAR 2022
IMPLEMENTATION: 03.03.2022

RESPONSE: NO RESPONSE TO THIS NOTIFICATION IS REQUIRED

PRODUCT CHANGE NOTIFICATION (PCN)

page 2/

PRODUCT CHANGE NOTIFICATION (PCN)

ISSUE DATE: 03.03.2022
MODIFICATION / REVISION DATE: 03.03.2022

AKSNT/x BLACK OLD VERSION	AKSNT/x BLACK NEW VERSION
NOTES: 1. Insulation: 30% Glass Filled PBT, UL94V-0, Color Black 2. Contact : Brass 3. Current Rating: 3A Max 4. Dielectric Voltage: 1000V rms / 1 minute 5. Insulation Resistance: 1000M ohm Min. 6. Contact Resistance: 30m ohm Max. 7. Operating and Storage Temperature: -40°C ~ +105°C ③ 8. Matlng Cycles: 10 Min. AKSNT/x BLACK — Contact Area Plating: ③ G: Gold Flash Z: Tinned	NOTES: 1. Insulator: PBT+30% G.F,UL94V-0,Black ④ 2. Contact : Phosphor Bronze,Au or Sn over Ni 3. Current Rating: 3.0AMP 4. Dielectric Withstanding Voltage: 1000V AC/ minute ④ 5. Insulation Resistance: 500MΩ Min. ④ 6. Contact Resistance: 20mΩ Max. 7. Operating Temperature: -40°C ~ +105°C ③ AKSNT/x BLACK — Contact Area Plating: ③ G: Gold Flash Z: Tinned
FOR DETAIL, PLEASE TAKE ATTACHED NEW DRAWING: FOR REFERENCE	

PCN REVISION HISTORY:

DATE OF REVISION: 03.03.2022

REVISION NUMBER: 00

page 3/

AFFECTED PART NUMBERS

AKSNT/G BLACK

AKSNT/X BLACK