



EDITION 6

Sensor Solutions Guide

SENSE • CONNECT • CONTROL

www.FutureElectronics.com/Sensors





**WHEN YOU'RE CREATING
ENERGY EFFICIENT DEVICES THAT
SENSE CONNECT AND CONTROL**

THINK ON



ON Semiconductor®

ON Semiconductor's industry leading portfolio of image sensors enable and address the demanding needs of 'Vision IoT' applications within automotive, industrial, consumer, and medical segments. A broad portfolio of pixel resolutions and sizes, combined with technology leadership in global shutter, HDR (High Dynamic Range), Near-IR, LED Flicker Mitigation, etc., provides unmatched choice in picking the right sensor for your application. When you want to innovate, THINK ON.

onsemi.com/IoT

ACCELEROMETERS

Analog Output	5
Digital Output	8
Shock Sensor	10

ACOUSTIC

Ultrasonic Sensors	15
MEMS Microphone	15

AIR QUALITY

Air Quality Sensor – VOC	17
CO2 Sensor	19
Dust Sensor	21

BIOSENSORS

Biosensor	23
Biopotential AFE	23
Optical AFE	24

ENVIRONMENTAL COMBO

Humidity, Temperature and Pressure Sensor Combo	27
Humidity, Temperature, Pressure and VOC Sensor Combo	27

FLOW

Mass Air Flow Meter	29
Ultrasonic Flow Converter	29

GYRO – ANGULAR RATE

Gyro – Angular Rate Sensor	31
--------------------------------------	----

HUMIDITY

Humidity Sensor	35
---------------------------	----

IMAGE

CMOS Image Sensor	39
CCD Image Sensor	44
Image Sensor Module	45
Thermal Image Sensor	46
3D Image Sensor (Time of Flight)	47

INERTIAL COMBO

Digital Compass	51
Inertial Measurement Unit (IMU)	52
9-DoF / 9-Axis Combo Sensor	53
Sensor HUB	53

LIGHT – COLOR

Ambient Light Sensor – Analog	57
Ambient Light Sensor – Digital	58
Color Sensor	60
Photo Detector	61
UV Sensor	61
Spectral Sensor	61

MAGNETIC – HALL

Current Sensor	65
Hall Switch – Latch	66
Linear Hall IC	77
Magnetometer	78
AMR Sensors	79

OCCUPANCY – MOTION

Passive Infrared Motion Sensor	81
IR Thermal Sensor Array	83
Radar	83
Time of Flight (3D Image)	84

OPTICAL COMBO

Ambient Light and Proximity	87
Gesture, Color, Proximity and Ambient Light	89

POSITION – SPEED

3D Magnetic Position Sensor	91
Magnetic Rotational Speed Sensor	97
Magnetic Speed Sensor	97
Optical Switch	98
Industrial Magnetic Rotary Encoder	98
Automotive Certified Magnetic Rotary Encoder	98
Industrial Magnetic Linear Encoder	99
Magnetic Angular Position Sensor	100
Passive Position Sensor	102

PRESSURE

Pressure Sensor – Analog	105
Pressure Sensor – Digital	117
Barometer	121

PROXIMITY

Touch Controller – Capacitive	123
Touch Controller – Resistive	123
IR Reflective Proximity Sensor	124
Optical Sensor	124
Radar Sensor	125
Time-of-Flight Laser Range Sensor	125

TEMPERATURE

Analog Infrared Thermopile	127
Digital Infrared Thermometer	128
Temperature Sensor – Analog	131
Temperature Sensor – Digital	131
Thermistor	133
Thermistor – Inrush Current Limiter	137
PTC Thermistor - Overheat Detection	139
RTD Platinum Element	139

SENSOR EVALUATION TOOLS

Evaluation Tools	141
----------------------------	-----



ACCELEROMETERS

Analog Output	5
Digital Output	8
Shock Sensor	10



BOSCH
Invented for life

muRata
INNOVATOR IN ELECTRONICS



AUTHORIZED DISTRIBUTOR



Part Number	Sensing Range (g)	Sensing Axis	Sensitivity Typ. (mV/g)	Zero-g Offset (V)	Bandwidth Typ. (Hz)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
KXTC9-2050	±2*	X, Y, Z	660	1.65	50*	3.3	0.24	-40 to +85	LGA-10 3 x 3 x 0.9
KX220-1071	±20*	X, Y, Z	66	1.65	8000 (x,y)* 5100 (z)*	3.3	0.24	-40 to +85	LGA-10 3 x 3 x 0.9
KX220-1072	±40*	X, Y, Z	33	1.65	8000 (x,y)* 5100 (z)*	3.3	0.24	-40 to +85	LGA-10 3 x 3 x 0.9
KXR94-2050	±2*	X, Y, Z	660	1.65	800*	3.3	0.95	-40 to +85 (+125 Optional)	DFN-14 5 x 5 x 1.2
KXR94-2283	±2*	X, Y, Z	1000	2.5	800*	5.0	0.95	-40 to +85 (+125 Optional)	DFN-14 5 x 5 x 1.2
KXD94-2802	±10*	X, Y, Z	200	2.5	800*	5.0	1.2	-40 to +85 (+125 Optional)	DFN-14 5 x 5 x 1.2

*Factory Programmable



Part Number	Sensing Range (g)	Sensing Axis	Sensitivity Typ. (mV/g)	Zero-g Offset (V)	Bandwidth Typ. (Hz)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
SCA610-E23H1A	±1.5	X, Y	1.33V/g	±125mg*	50	5.0	—	-40 to +125	11.33 x 15.58 x 5.08
SCA610-E28H1A	±1.7	X, Y	1.2V/g	±125mg*	50	5.0	—	-40 to +125	11.33 x 15.58 x 5.08
SCA620-EF1V1B	0 to +2	Z	2V/g	±125mg*	50	5.0	—	-40 to +125	11.33 x 15.58 x 5.08
SCA620-EF6H1A	±1.7	Z	1.2V/g	±125mg*	50	5.0	—	-40 to +125	11.33 x 15.58 x 5.08
SCA630-EDCV18	-12.3 to +13.3	Y	0.15V/g	±870mg*	400	5.0	—	-40 to +125	11.33 x 15.58 x 5.08

* Total offset over time and temperature



Part Number	Sensing Range (g)	Sensing Axis	Sensitivity Typ. (mV/g)	Zero-g Offset (V)	Bandwidth Typ. (Hz)	Supply Voltage (V)	Supply Current	Operating Temperature (°C)	Package Type / Size (mm)
FXLN8361	±2, ±8	X, Y, Z	229 (2g), 57.25 (8g)	0.75	1.1kHz (X&Y), 600Hz (Z)	1.95 to 3.6	180µA (Active), 30nA (Shutdown)	-40 to +105	QFN 3 x 3 x 1
FXLN8362	±4, ±16	X, Y, Z	114.5 (4g), 28.62 (16g)	0.75	1.1kHz (X&Y), 600Hz (Z)	1.95 to 3.6	180µA (Active), 30nA (Shutdown)	-40 to +105	QFN 3 x 3 x 1

Part Number	Sensing Range (g)	Sensing Axis	Sensitivity Typ. (mV/g)	Zero-g Offset (V)	Bandwidth Typ. (Hz)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
LIS344ALHTR	±2; ±6	X, Y, Z	660	1.65	1800	3.3	0.68	-40 to +85	LLGA 16 4 x 4 x 1.5

Part Number	Sensing Range (g)	Sensing Axis	Sensitivity Typ. (mV/g)	Zero-g Offset (V)	Bandwidth Typ. (Hz)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
3038-0050	±50	Z	2	±0.025	0 to 1000	2 to 10	—	-54 to +125	LCC-8
3038-0100	±100	Z	1	±0.025	0 to 1200	2 to 10	—	-54 to +125	LCC-8
3038-0200	±200	Z	0.9	±0.025	0 to 1400	2 to 10	—	-54 to +125	LCC-8
3038-0500	±500	Z	0.4	±0.025	0 to 2000	2 to 10	—	-54 to +125	LCC-8
3038-2000	±2000	Z	0.16	±0.025	0 to 4500	2 to 10	—	-54 to +125	LCC-8
3038-6000	±6000	Z	0.1	±0.025	0 to 5000	2 to 10	—	-54 to +125	LCC-8
4030-002-120	±2	X, Y, Z	1000	2.5	0 to 200	5 to 30	—	-40 to +85	70.5 x 40 housing
4030-006-120	±6	X, Y, Z	333	2.5	0 to 200	5 to 30	—	-40 to +85	70.5 x 40 housing
805-0050	±50	Z	100	—	1 to 8000	18 to 30	2 to 10	-40 to +100	T0-5
805-0500	±500	Z	10	—	1 to 8000	18 to 30	2 to 10	-40 to +100	T0-5
805M1-0020	±20	Z	100	2.5	1 to 8000	3.0 to 5.5	<0.80	-40 to +100	T0-5
805M1-0200	±200	Z	10	2.5	1 to 8000	3.0 to 5.5	<0.80	-40 to +100	T0-5
832M1-0025	±25	X, Y, Z	50	2.5	2 to 6000	3.0 to 5.5	0.022	-40 to +125	18.50 x 14.48 housing
832M1-0050	±50	X, Y, Z	25	2.5	2 to 6000	3.0 to 5.5	0.022	-40 to +125	18.50 x 14.48 housing
832M1-0100	±100	X, Y, Z	12.5	2.5	2 to 6000	3.0 to 5.5	0.022	-40 to +125	18.50 x 14.48 housing
832M1-0200	±200	X, Y, Z	6.25	2.5	2 to 6000	3.0 to 5.5	0.022	-40 to +125	18.50 x 14.48 housing
832M1-0500	±500	X, Y, Z	2.5	2.5	2 to 6000	3.0 to 5.5	0.022	-40 to +125	18.50 x 14.48 housing
834M1-2000	±2000	X, Y, Z	0.62	2.5	2 to 6000	3.0 to 5.5	0.022	-40 to +125	18.50 x 14.48 housing
834M1-6000	±6000	X, Y, Z	0.2	2.5	2 to 6000	3.0 to 5.5	0.022	-40 to +125	18.50 x 14.48 housing
3038-0050	±50	Z	2	±0.025	0 to 1000	2 to 10	—	-54 to +125	LCC-8
3038-0100	±100	Z	1	±0.025	0 to 1200	2 to 10	—	-54 to +125	LCC-8
3038-0200	±200	Z	0.9	±0.025	0 to 1400	2 to 10	—	-54 to +125	LCC-8
3038-0500	±500	Z	0.4	±0.025	0 to 2000	2 to 10	—	-54 to +125	LCC-8
3038-2000	±2000	Z	0.16	±0.025	0 to 4500	2 to 10	—	-54 to +125	LCC-8
3038-6000	±6000	Z	0.1	±0.025	0 to 5000	2 to 10	—	-54 to +125	LCC-8
4030-002-120	±2	X, Y, Z	1000	2.5	0 to 200	5 to 30	—	-40 to +85	70.5 x 40 housing



AUTHORIZED DISTRIBUTOR

Part Number	Sensing Range (g)	Sensing Axis	Sensitivity Typ. (mV/g)	Zero-g Offset (V)	Bandwidth Typ. (Hz)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
4030-006-120	±6	X, Y, Z	333	2.5	0 to 200	5 to 30	—	-40 to +85	70.5 x 40 housing
805-0050	±50	Z	100	—	1 to 8000	18 to 30	2 to 10	-40 to +100	T0-5
805-0500	±500	Z	10	—	1 to 8000	18 to 30	2 to 10	-40 to +100	T0-5
805M1-0020	±20	Z	100	2.5	1 to 8000	3.0 to 5.5	<0.80	-40 to +100	T0-5
805M1-0200	±200	Z	10	2.5	1 to 8000	3.0 to 5.5	<0.80	-40 to +100	T0-5
832M1-0025	±25	X, Y, Z	50	2.5	2 to 6000	3.0 to 5.5	0.022	-40 to +125	18.50 x 14.48 housing
832M1-0050	±50	X, Y, Z	25	2.5	2 to 6000	3.0 to 5.5	0.022	-40 to +125	18.50 x 14.48 housing
832M1-0100	±100	X, Y, Z	12.5	2.5	2 to 6000	3.0 to 5.5	0.022	-40 to +125	18.50 x 14.48 housing
832M1-0200	±200	X, Y, Z	6.25	2.5	2 to 6000	3.0 to 5.5	0.022	-40 to +125	18.50 x 14.48 housing
832M1-0500	±500	X, Y, Z	2.5	2.5	2 to 6000	3.0 to 5.5	0.022	-40 to +125	18.50 x 14.48 housing
834M1-2000	±2000	X, Y, Z	0.62	2.5	2 to 6000	3.0 to 5.5	0.022	-40 to +125	18.50 x 14.48 housing
834M1-6000	±6000	X, Y, Z	0.2	2.5	2 to 6000	3.0 to 5.5	0.022	-40 to +125	18.50 x 14.48 housing

LPS22HH MEMS piezo-resistive absolute pressure sensor is so accurate and stable that manufacturers can eliminate one-point calibration (OPC) after soldering to increase throughput and efficiency. With a pressure noise equivalent to 5cm, the **LPS22HH** enhances controls such as collision avoidance for drones or other unmanned vehicles. Its superior accuracy also enhances features of smartphones and sport watches, such as indoor navigation.



life.augmented

www.st.com



BOSCH
Invented for life

Part Number	Sensing Range (g)	Sensing Axis	Sensitivity (LSB/g)	Output Interface	Bandwidth (Hz)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
BMA253	±2, ±4, ±8, ±16	X, Y, Z	1024, 512, 256, 128	SPI, I ² C, 2 digital interrupt pins	8 to 1000z	V _{DD} 1.62 to 3.6 V _{DDIO} 1.2 to 3.6	6.5 µA @40 Hz data rate (low-power mode) 130µA @2kHz data rate (full operation)	-40 to +85	2.0 × 2.0 × 0.95
BMA280	±2, ±4, ±8, ±16	X, Y, Z	4096, 2048, 1024, 512	SPI, I ² C, 2 digital interrupt pins	8 to 500	V _{DD} 1.62 to 3.6 V _{DDIO} 1.2 to 3.6	6.5 µA @40 Hz data rate (low-power mode) 130µA @2kHz data rate (full operation)	-40 to +85	2.0 × 2.0 × 0.95
BMA400	±2, ±4, ±8, ±16	X, Y, Z	1024, 512, 256, 128	SPI, I ² C, 2 digital interrupt pins	0.24 x ODR or 0.48 x ODR (ODR from 12.5... 800 Hz)	V _{DD} 1.71 to 3.6 V _{DDIO} 1.2 to 3.6	14 µA (max. performance) <8 µA (typical use case) < 4 µA Independent of ODR (lower power mode)	-40 to +85	2.0 × 2.0 × 0.95
BMA423	±2, ±4, ±8, ±16	X, Y, Z	1024, 512, 256, 128	SPI, I ² C, 2 digital interrupt pins	1.5 to 1600	V _{DD} 1.62 to 3.6 V _{DDIO} 1.2 to 3.6	13 µA @50 Hz data rate (low-power mode) 150 µA (full operation)	-40 to +85	2.0 × 2.0 × 0.95
BMA456	±2, ±4, ±8, ±16	X, Y, Z	16384, 8192, 4096, 2048	SPI, I ² C, 2 digital interrupt pins	5 to 684 (ODR: 0.8 to 1600)	V _{DD} 1.62 to 3.6 V _{DDIO} 1.2 to 3.6	13 µA @50 Hz data rate (low-power mode) 150 µA (full operation)	-40 to +85	2.0 × 2.0 × 0.65



Kionix®

Part Number	Sensing Range (g)	Sensing Axis	Sensitivity (LSB/g)	Output Interface	Bandwidth (Hz)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
KXTJ3-1057	±2, ±4, ±8, ±16	X, Y, Z	1024, 512, 256, 128	I ² C (1 Interrupt)	800	1.71 to 3.60	0.0015 to 0.155	-40 to +85	LGA-12 2 x 2 x 0.9
KX003-1077	±2, ±4, ±8, ±16	X,Y,Z	1024, 512, 256, 128	I ² C (1 Interrupt)	800	1.71 to 3.60	0.0015 to 0.155	-40 to +85	LGA-12 2 x 2 x 0.9
KX122-1037	±2, ±4, ±8	X, Y, Z	16384, 8192, 4096	I ² C, SPI, (2 Interrupts)	3000 (x,y) 1800 (z)	1.71 to 3.60	0.0018 to 0.145	-40 to +85	LGA 12-Pin 2.0 x 2.0 x 0.9
KX124-1051	±2, ±4, ±8	X, Y, Z	16384, 8192, 4096	I ² C, SPI, (2 Interrupts)	3000 (x,y) 1800 (z)	1.71 to 3.60	0.0018 to 0.145	-40 to +85	LGA 16-Pin 3.0 x 3.0 x 0.9
KX126-1063	±2, ±4, ±8	X, Y, Z	16384, 8192, 4096	I ² C, SPI, (2 Interrupts)	3000 (x,y) 1800 (z)	1.71 to 3.60	0.0018 to 0.145	-40 to +85	LGA 12-Pin 2.0 x 2.0 x 0.9
KX127-1068	±2, ±4, ±8	X,Y,Z	16384, 8192, 4096	I ² C, SPI, (2 Interrupts)	800	1.71 to 3.60	0.0018 to 0.145	-40 to +85	LGA-12 2 x 2 x 0.9
KX112-1042	±2, ±4, ±8	X, Y, Z	16384, 8192, 4096	I ² C, SPI, (2 Interrupts)	3000 (x,y) 1800 (z)	1.71 to 3.60	0.0018 to 0.145	-40 to +85	LGA 12-Pin 2.0 x 2.0 x 0.6
KXCJB-1041	±2, ±4, ±8	X, Y, Z	1024, 512, 256	I ² C (1 Interrupt)	800	1.71 to 3.60	0.0017 to 0.120	-40 to +85	LGA 10-Pin 3.0 x 3.0 x 0.45
KX222-1054	±8, ±16, ±32	X, Y, Z	4096, 2048, 1024	I ² C, SPI, (2 Interrupts)	8000 (x,y) 5100 (z)	1.71 to 3.60	0.0018 to 0.145	-40 to +85	LGA 12-Pin 2.0 x 2.0 x 0.9
KX224-1053	±8, ±16, ±32	X, Y, Z	4096, 2048, 1024	I ² C, SPI, (2 Interrupts)	8000 (x,y) 5100 (z)	1.71 to 3.60	0.0018 to 0.145	-40 to +85	LGA 16-Pin 3.0 x 3.0 x 0.9

Part Number	Sensing Range (g)	Sensing Axis	Sensitivity (LSB/g)	Output Interface	Bandwidth (Hz)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
SCA820-D04	±2	Z	900	SPI	50	3.3	5.0	-40 to +125	7.0 x 8.6 x 3.3
SCA830-D06	±2	Y	900	SPI	50	3.3	5.0	-40 to +125	7.0 x 8.6 x 3.3
SCA830-D07	±1	Y	32000	SPI	6	3.3	5.0	-40 to +125	7.0 x 8.6 x 3.3
SCA2120-D06	±2	Y, Z	900	SPI	45	3.3	5.0	-40 to +125	7.0 x 8.6 x 3.3
SCA3300-D01	±1.5, ±3, ±6	X, Y, Z	5400, 2700, 1350	SPI	88	3.3	1.2	-40 to +125	7.0 x 8.6 x 3.3
SCA3100-D04	±2	X, Y, Z	900	SPI	45	3.3	3.0	-40 to +125	7.0 x 8.6 x 3.3
SCA3100-D07	±6	X, Y, Z	650	SPI	45	3.3	3	-40 to +125	7.0 x 8.6 x 3.3



Part Number	Sensing Range (g)	Sensing Axis	Sensitivity (LSB/g)	Output Interface	Bandwidth (Hz)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
FXLS8962AF	±2, ±4, ±8, ±16	X, Y, Z	1024, 512, 256, 128	SPI, I²C	1.6 kHz (X&Y), 700 Hz (Z)	1.71 to 3.6	0.65 µA to 137µA (Active), 0.6 µA (Standby), 50nA (Hibernate)	-40 to +105	DFN-10 2 x 2 x 0.95
MMA8451	±2, ±4, ±8	X, Y, Z	4096, 2048, 1024	I²C	Up to 400 Hz	1.95 to 3.6	6 µA to 165 µA (Active), 1.8 µA (Standby)	-40 to +105	QFN-16 3 x 3 x 1
MMA8491	±8	X, Y, Z	1024	I²C	Up to 400 Hz	1.71 to 3.6	400 nA/Hz (One Shot), 1.8 nA (Shutdown)	-40 to +105	QFN-12 3 x 3 x 1
MMA8652	±2, ±4, ±8	X, Y, Z	1024, 512, 256	I²C	Up to 400 Hz	1.95 to 3.6	6 µA to 185 µA (Active), 1.4 µA (Standby)	-40 to +105	DFN-10 2 x 2 x 1
FXLS8471	±2, ±4, ±8	X, Y, Z	4096, 2048, 1024	SPI, I²C	Up to 400 Hz	1.95 to 3.6	8 µA to 240 µA (Active), 2 µA (Standby)	-40 to +105	QFN-16 3 x 3 x 1
MMA68xx	±20 to ±120	X, Y	4.88-20.47 (X), 4.09 to 9.76 (Y)	SPI	Up to 1 kHz	3.3 or 5	4 - 9	-40 to +125	QFN-16 6 x 6 x 1.98
MMA65xx	±80, ±105, ±120	X, Y	24 (80 g), 18.2 (105 g), 16 (120 g)	SPI	Up to 1 kHz	3.3 or 5	4 - 8	-40 to +125	QFN-16 6 x 6 x 1.98
MMA6900/10	±3.5	X, Y	291	SPI	50 kHz	3.3 or 5	Up to 8	-40 to +125	QFN-16 6 x 6 x 1.98



Part Number	Sensing Range (g)	Sensing Axis	Sensitivity (LSB/g)	Output Interface	Bandwidth (Hz)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
LIS2DW12TR	±2, ±4, ±8, ±16	X, Y, Z	0.244mg/digit to 7.808 mg/digit	SPI/I²C 2x digital interrupt pins	0.4 - 3200	1.62 - 3.6	0.00038	-40 to +85	LGA 12 2 x 2 x 0.7
LIS2DS12TR	±2, ±4, ±8, ±16	X, Y, Z	0.061 mg/digit to 0.488 mg/digit	SPI/I²C 2x digital interrupt pins	11 - 3200	1.62 - 1.98	0.0025	-40 to +85	LGA 12 2 x 2 x 0.86
LIS2DH12TR	±2, ±4, ±8, ±16	X, Y, Z	1 mg/digit to 192 mg/digit	SPI/I²C 2x digital interrupt pins	0.11 - 2688	1.71 - 3.6	0.002	-40 to +85	LGA 12 2 x 2 x 1.0

ACCELEROMETER / Digital Output



life.augmented

Part Number	Sensing Range (g)	Sensing Axis	Sensitivity (LSB/g)	Output Interface	Bandwidth (Hz)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
LIS2HH12TR	± 2, ± 4, ± 8	X, Y, Z	0.061 mg/digit to 0.244 mg/digit	SPI / I ² C 2x digital interrupt pins	50 to 400	1.71 to 3.6	0.05	-40 to +85	LGA 12 2 x 2 x 1.0
AIS328DQTR	±2, ±4, ±8	X, Y, Z	0.98 mg/digit to 3.91 mg/digit	SPI / I ² C 2x digital interrupt pins	0.25 to 500	2.4 to 3.6	0.01	-40 to +105	QFN 24 4 x 4 x 1.8
AIS3624DQTR	±6, ±12, ±24	X, Y, Z	2.9 mg/digit to 11.7 mg/digit	SPI / I ² C 2x digital interrupt pins	0.25 to 500	2.4 to 3.6	0.01	-40 to +105	QFN 24 4 x 4 x 1.8
MIS2DHTR	±2, ±4, ±8, ±16	X, Y, Z	0.98 mg/digit to 188 mg/digit	SPI / I ² C 2x digital interrupt pins	0.11 to 2688	1.7 to -3.6	0.002	-40 to +85	LGA 12 2 x 2 x 1.0
IIS2DHTR	±2, ±4, ±8, ±16	X, Y, Z	1 mg/digit to 188 mg/digit	SPI / I ² C 2x digital interrupt pins	0.11 to 2688	1.71 to 3.6	0.002	-40 to +85	LGA 12 2 x 2 x 1.0
H3LIS100DLTR	±100	X, Y, Z	780 mg/digit	SPI / I ² C 2x digital interrupt pins	0.25 to 200	2.16 to 3.6	0.01	-40 to +85	TFLGA 16 3 x 3 x 1.0
H3LIS200DLTR	±100, ±200	X, Y, Z	780 mg/digit to 1560 mg/digit	SPI / I ² C 2x digital interrupt pins	0.25 to 500	2.16 to 3.6	0.01	-40 to +85	TFLGA 16 3 x 3 x 1.0
H3LIS331DLTR	±100, ±200, ±400	X, Y, Z	49 mg/digit to 195 mg/digit	SPI / I ² C 2x digital interrupt pins	0.25 to 500	2.16 to 3.6	0.01	-40 to +85	TFLGA 16 3 x 3 x 1.0
LIS2DE12TR	±2, ±4, ±8, ±16	X, Y, Z	15 mg/digit to 188 mg/digit	SPI / I ² C 2x digital interrupt pins	0.5 to 2688	1.71 to 3.6	0.002	-40 to +85	LGA 12 2 x 2 x 1.0
LIS3DSHTR	±2, ±4, ±6, ±8, ±16	X, Y, Z	0.06 mg/digit to 0.73 mg/digit	SPI / I ² C 2x digital interrupt pins	50 to 800	1.71 to 3.6	0.011	-40 to +85	LGA 16 3 x 3 x 1
LIS3DHHTR	±2.5	X, Y, Z	0.076 mg/digit	SPI 2x digital interrupt pins	235 or 440	1.71 to 3.6	2.5	-40 to +85	LGA 16 5 x 5 x 1.7
IIS3DHHCTR	±2.5	X, Y, Z	0.076 mg/digit	SPI 2x digital interrupt pins	235 or 440	1.71 to 3.6	2.5	-40 to +85	LGA 16 5 x 5 x 1.7
IIS2DLPCTR	±2, ±4, ±8, ±16	X, Y, Z	0.244mg/digit to 7.808 mg/digit	SPI/I ² C 2x digital interrupt pins	0.4 to 3200	1.62 to 3.6	0.00038	-40 to +85	LGA 12 2 x 2 x 0.7
IIS328DQ	±2, ±4, ±8	X, Y, Z	0.98, 1.95, 3.91 mg/digit	SPI/I ² C 2x digital interrupt pins	25 to 500 (ODR/2)	2.16 to 3.6	0.01	-40 to +85	4 x 4 x 1.8

ACCELEROMETER / Shock Sensor



INNOVATOR IN ELECTRONICS

Part Number	Primary Axis Inclined Angle	Sensitivity (pC/g)	Capacitance (pF)	Insulation Resistance (min)	Resonant Frequency (kHz)	Non-Linearity (Typ.)	Shock Resistance (g)	Operating Temperature (°C)
PKGS-00GXP1-R	0°	0.35	390	500M ohms	31	1%	3000 (0.3ms duration)	-40 to +85
PKGS-25SXAP1-R	25°	0.35	740	100M ohms	27	1%	3000 (0.3ms duration)	-40 to +85
PKGS-25WXP1-R	25°	0.168	550	100M ohms	42	1%	3000 (0.3ms duration)	-40 to +85



AUTHORIZED DISTRIBUTOR

Part Number	Primary Axis Inclined Angle	Sensitivity (pC/g)	Capacitance (pF)	Insulation Resistance (min)	Resonant Frequency (kHz)	Non-Linearity (Typ.)	Shock Resistance (g)	Operating Temperature (°C)
705	Z	8	600	100 MOhm	46	1%	10000	-73 to +200

ACCELERATING SENSOR INNOVATION FOR AUTOMOTIVE AND INDUSTRIAL



Our portfolio matches market requirements with devices for:

- Medical applications and electronic inhalers
- Wearable and IoT end nodes
- Car keyfob and infotainment
- Tire pressure monitoring systems
- Inertial navigation systems

www.nxp.com/sensors





ACOUSTIC

Ultrasonic Sensors 15

MEMS Microphone 15






Infineon XENSIV™ – sensing the world

From the world leader in sensing technology, XENSIV™ sensors enable “things” to “see”, “hear”, “feel” and “understand” their environment. Thanks to proven quality and outstanding reliability, customers can rely on XENSIV™ for system stability, durability and integrity. Providing exceptional accuracy and best-in-class measurement performance, XENSIV™ sensors add extraordinary value to customer applications.

With more than 40 years' experience in sensing solutions and a deep-rooted system understanding, we offer the broadest portfolio of ready-to-use sensor solutions on the market. Ecosystem partners and our customers partner with us for leading technologies, perfect-fit solutions and continuous innovation.

Discover our broad portfolio at
www.infineon.com/sensors





Hear nothing but your favorite beats!

With XENSIV™ MEMS microphones, you can define the benchmark in active noise cancellation for a new user experience

The popularity of active noise cancellation headsets is increasing dramatically. However, the signal- to- noise ratio and matching performance of microphones often limits the potential of today's cutting-edge devices.

Not any more!

Our XENSIV™ MEMS microphones introduce a new performance class of digital MEMS microphones that overcomes existing audio chain limitations. Infineon's IM69D130 provides premium digital audio raw data, perfect to combine with advanced audio signal processing algorithms for best noise attenuation experience in any environment.

- › Noise free audio raw data: 69 dB [A] signal to noise ratio
- › Distortion free audio signal capture: <1% total harmonic distortion up to 128 dB SPL
- › Microphone matching: < ±1 dB sensitivity and < ±2° phase response variations
- › Digital PDM interface: ultra-low group delay for latency-critical applications (6 µs at 1 kHz)
- › Wide frequency response: 28 Hz to 20 kHz



Part Number	Description	Resonance Frequency (KHz)	Directivity (deg)	Sound Pressure Level (dB)	Capacitance (pF)	Max Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
MA40S4R	Ultrasonic Receiver	40	80 deg. (typ.)	—	2,550 ±20%	—	-40 to +85	9.9 x 7.1
MA40S4S	Ultrasonic Transmitter	40	80 deg. (typ.)	120dB typ. (0dB=0.02mPa)	2,550 ±20%	20V p-p	-40 to +85	9.9 x 7.1

Part Number	Output	SNR (dB)	Sensitivity (dB)	Frequency Response	Supply (V)	Supply Current (µA)	Port Location	Package Type / Size (mm)
IM69D130	Digital (PDM)	69	-36	Flat, with roll-off at 28Hz	1.62 to 3.6	800 Normal Mode 300 Low Power Mode	Bottom	4 x 3 x 1.2
IM69D120	Digital (PDM)	69	-26	Flat, with roll-off at 28Hz	1.62 to 3.6	800 Normal Mode 300 Low Power Mode	Bottom	4 x 3 x 1.2

Part Number	Output	SNR (dB)	Sensitivity (dB)	Frequency Response	Supply (V)	Supply Current (µA)	Port Location	Package Type / Size (mm)
MP34DT05TR-A	Digital	64	-26	20Hz - 20Khz	1.64 to 3.6	600	Top	HCLGA 4 x 3 x 1.0 4LD
IMP34DT05TR	Digital	64	-26	20Hz - 20Khz	1.64 to 3.6	600	Top	HCLGA 4 x 3 x 1.0 4LD
MP34DT06JTR	Digital	64	-26	20Hz - 20Khz	1.6 to 3.6	650	Top	HCLGA 4 x 3 x 1.0 4LD
MP23ABS1	Analog	64	-38 to ±1	20Hz - 20Khz	1.52 to 3.6	120 (150 Max)	Bottom	Metal 3.5 x 2.65 x 0.98



AIR QUALITY

Air Quality Sensor – VOC	17
CO2 Sensor	19
Dust Sensor	21



Amphenol
Advanced Sensors



BOSCH
Invented for life

SENSIRION
THE SENSOR COMPANY

Part Number	Description	Output Interface	Measurement Range	Power Consumption	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
MICS-VZ-89TE	VOC	I ² C, PWM	400-2000 ppm equivalent CO2 0-1000 ppb isobutylene equivalent TVOCs	125mW	3.3VDC regulated ±5%	0 to +50	22.9 x 14 x 3.15



Part Number	Description	Output Interface	Measurement Range	Power Consumption	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
AS-MLV-P2	Gas sensor component specifically designed for a broad detection of reducing gases such as VOCs and CO associated with bad air quality.	Analog Rs	—	34mW	3	0 to +50	Surface Mount Custom PCB / 9.1 x 9.1 x 4.53
IAQ-Core	Measure VOC levels and provide CO2 equivalent and TVOC equivalent predictions	I ² C	—	IAQ-core-C: 66 mW (1/1s) IAQ-core-P: 9 mW (1/10s)	3.3	0 to +50	Surface Mount Custom PCB / 15.24 x 17.78 x 1.7
CCS811	Ultra-low power digital gas sensor solution which integrates a metal oxide (MOX) gas sensor for monitoring indoor air quality (IAQ)	I ² C	—	46mW 1s mode <1.3mW 60s mode	1.8 to 3.6	-5 to +50	LGA package 10-lead 2.7 x 4.0


BOSCH
 Invented for life

Part Number	Description	Output Interface	Measurement Range	Power Consumption	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
BME680	The unit integrates for the first time low-power and highly accurate gas, pressure, humidity and temperature sensors in one tiny package.	I ² C, SPI	Gas 0 to 500 IAQ (equivalent to 0.2 to 20 mg/m ³ TVOC levels); Humidity 0 to 100 % rH; Pressure 300 to 1100 hPa; Temperature -40 to 85°C	Sleep mode 0.15 µA 2.1 µA @ 1Hz (H,T) 3.1 µA @ 1Hz (P, T) 3.7 µA @ 1 Hz (H, P, T) 0.09 -12 mA (P/H/T/Gas) depending on operation mode	V _{DDIO} 1.2 to 3.6 V _{DD} 1.71 to 3.6	-40 to +85	3.0 x 3.0 x 0.93



Part Number	Description	Output Interface	Measurement Range	Power Consumption	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
SGP30	MEMS metal-oxide gas sensor for measuring volatile organic compounds	Digital, I ² C	0 - 1,000 ppm	0.086 W	1.8	-40 to +85	2.45 x 2.45 x 0.9
SGPC3	MEMS metal-oxide gas sensor for measuring volatile organic compounds - Consumer version	Digital, I ² C	0 - 1,000 ppm	LP:1.8 mW, ULP:0.12mW	1.8	-40 to +85	2.45 x 2.45 x 0.9



SENSE THE FUTURE WITH ROHM

CURRENT SENSORS | ACCELEROMETERS
GEOMAGNETIC | HALL ICs
LOW POWER WIRELESS MODULES
PROXIMITY | HEART RATE | COLOR
AMBIENT LIGHT | BAROMETRIC PRESSURE
TEMPERATURE | IR



ROHM.COM

Part Number	Measurement Range (ppm)	Output Interface	Response Time	Power Consumption	Supply Voltage (V)	Operating Conditions	Package Type / Size (mm)
T6613	0 to 2,000	UART, I ² C, PWM	< 2 minutes for 90% step change typical	0.90 watts peak, 0.165 watts average	5V _{DC} regulated (±5%)	0 to +50 (0 to 95% RH, non condensing)	57.15 x 34.67 x 15.24
T6613-5K	0 to 5,000	UART, I ² C, PWM	< 2 minutes for 90% step change typical	0.90 watts peak, 0.165 watts average	5V _{DC} regulated (±5%)	0 to +50 (0 to 95% RH, non condensing)	57.15 x 34.67 x 15.24
T6613-5KC	0 to 5,000	UART, I ² C, PWM	< 2 minutes for 90% step change typical	0.90 watts peak, 0.165 watts average	5V _{DC} regulated (±5%)	0 to +50 (0 to 95% RH, non condensing)	57.15 x 34.67 x 15.24
T6613-5KF	0 to 5,000	UART, I ² C, PWM	< 2 minutes for 90% step change typical	0.90 watts peak, 0.165 watts average	5V _{DC} regulated (±5%)	0 to +50 (0 to 95% RH, non condensing)	57.15 x 34.67 x 15.24
T6613-C	0 to 2,000	UART, I ² C, PWM	< 2 minutes for 90% step change typical	0.90 watts peak, 0.165 watts average	5V _{DC} regulated (±5%)	0 to +50 (0 to 95% RH, non condensing)	57.15 x 34.67 x 15.24
T6613-F	0 to 2,000	UART, I ² C, PWM	< 2 minutes for 90% step change typical	0.90 watts peak, 0.165 watts average	5V _{DC} regulated (±5%)	0 to +50 (0 to 95% RH, non condensing)	57.15 x 34.67 x 15.24
T6613-R12	0 to 2,000	UART, I ² C, PWM	< 2 minutes for 90% step change typical	0.90 watts peak, 0.165 watts average	5V _{DC} regulated (±5%)	0 to +50 (0 to 95% RH, non condensing)	57.15 x 34.67 x 15.24
T6615	0 to 2,000	UART	< 2 minutes for 90% step change typical	0.90 watts peak, 0.165 watts average	5V _{DC} regulated (±5%)	0 to +50 (0 to 95% RH, non condensing)	57.15 x 34.67 x 15.24
T6615-10K	0 to 10,000	UART	< 2 minutes for 90% step change typical	0.90 watts peak, 0.165 watts average	5V _{DC} regulated (±5%)	0 to +50 (0 to 95% RH, non condensing)	57.15 x 34.67 x 15.24
T6615-10KF	0 to 10,000	UART	< 2 minutes for 90% step change typical	0.90 watts peak, 0.165 watts average	5V _{DC} regulated (±5%)	0 to +50 (0 to 95% RH, non condensing)	57.15 x 34.67 x 15.24
T6615-50K	0 to 50,000	UART	< 2 minutes for 90% step change typical	0.90 watts peak, 0.165 watts average	5V _{DC} regulated (±5%)	0 to +50 (0 to 95% RH, non condensing)	57.15 x 34.67 x 15.24
T6615-50KF	0 to 50,000	UART	< 2 minutes for 90% step change typical	0.90 watts peak, 0.165 watts average	5V _{DC} regulated (±5%)	0 to +50 (0 to 95% RH, non condensing)	57.15 x 34.67 x 15.24
T6615-5K	0 to 5,000	UART	< 2 minutes for 90% step change typical	0.90 watts peak, 0.165 watts average	5V _{DC} regulated (±5%)	0 to +50 (0 to 95% RH, non condensing)	57.15 x 34.67 x 15.24
T6615-5KF	0 to 5,000	UART	< 2 minutes for 90% step change typical	0.90 watts peak, 0.165 watts average	5V _{DC} regulated (±5%)	0 to +50 (0 to 95% RH, non condensing)	57.15 x 34.67 x 15.24
T6615-F	0 to 2,000	UART	< 2 minutes for 90% step change typical	0.90 watts peak, 0.165 watts average	5V _{DC} regulated (±5%)	0 to +50 (0 to 95% RH, non condensing)	57.15 x 34.67 x 15.24
T6615-R12	0 to 2,000	UART	< 2 minutes for 90% step change typical	0.90 watts peak, 0.165 watts average	5V _{DC} regulated (±5%)	0 to +50 (0 to 95% RH, non condensing)	57.15 x 34.67 x 15.24
T6713	0 to 2,000	UART, I ² C, PWM	< 3 minutes for 90% step change	25mA	4.5 to 5.5V _{DC}	-10 to +60 (0 to 95% RH, non-condensing)	30 x 15.6 x 8.6
T6713-5k	0 to 5,000	UART, I ² C, PWM	< 3 minutes for 90% step change	25mA	4.5 to 5.5V _{DC}	-10 to +60 (0 to 95% RH, non-condensing)	30 x 15.6 x 8.6
T6713-6H	0 to 2,000	UART, I ² C, PWM	< 3 minutes for 90% step change	25mA	4.5 to 5.5V _{DC}	-10 to +60 (0 to 95% RH, non-condensing)	30 x 15.6 x 8.6
T8031	0 to 2,000	24V nominal supply	< 3 minutes for 90% step change	1.65 watts peak, 0.65 watts average	0 to 10 analog	0 to +50 (0 to 95% RH, non condensing)	3.83 in + 0.74 in mounting tab x 1.17in x 0.94 in
T8031-5V	0 to 2,000	24V nominal supply	< 3 minutes for 90% step change	1.65 watts peak, 0.65 watts average	1 to 10 analog	0 to +50 (0 to 95% RH, non condensing)	3.83 in + 0.74 in mounting tab x 1.17in x 0.94 in
T8031-1M	0 to 2,000	24V nominal supply	< 3 minutes for 90% step change	1.65 watts peak, 0.65 watts average	2 to 10 analog	0 to +50 (0 to 95% RH, non condensing)	3.83 in + 0.74 in mounting tab x 1.17in x 0.94 in
T8031-1M-5V	0 to 2,000	24V nominal supply	< 3 minutes for 90% step change	1.65 watts peak, 0.65 watts average	3 to 10 analog	0 to +50 (0 to 95% RH, non condensing)	3.83 in + 0.74 in mounting tab x 1.17in x 0.94 in

TELAIRE**NOVA**
SENSORTHERMOMETRICS
A COMMITMENT TO EXCELLENCE**Amphenol**
Advanced Sensors

EMBEDDED SENSING TECHNOLOGIES *for*

Transportation, Healthcare & Industrial Applications

TEMPERATURE

- NTC and PTC thermistors
- Non-contact infrared (IR) temperature sensors
- Inrush current limiting thermistors

PRESSURE / MEMS

- MEMS-based piezoresistive pressure sensors
- Senstable® technology for world-class accuracy and low drift
- Low pressure 2" H₂O to 3000 PSI

CARBON DIOXIDE (CO₂)

- Non-dispersive infrared (NDIR)
- Patented self-calibrating with lifetime calibration warranty
- Small footprint

HUMIDITY

- Various calibrated outputs (digital and analog)
- Fully-integrated humidity and temperature transmitters
- Harsh environment probes

NEW!

Filtration Air Restriction
Sensor (FAR)



NovaSensor FMA Series

DUST

- Laser and LED versions
- PM 2.5 and PM 10 measurements
- Analog and digital outputs



www.amphenol-sensors.com

Part Number	Measurement Range (ppm)	Output Interface	Response Time	Power Consumption	Supply Voltage (V)	Operating Conditions	Package Type / Size (mm)
T8031-3M	0 to 2,000	24V nominal supply	< 3 minutes for 90% step change	1.65 watts peak, 0.65 watts average	4 to 10 analog	0 to +50 (0 to 95% RH, non condensing)	3.83 in + 0.74 in mounting tab x 1.17in x 0.94 in
T8031-3M-5V	0 to 2,000	24V nominal supply	< 3 minutes for 90% step change	1.65 watts peak, 0.65 watts average	5 to 10 analog	0 to +50 (0 to 95% RH, non condensing)	3.83 in + 0.74 in mounting tab x 1.17in x 0.94 in
T3031-2-10K-24-P	0 to 10,000	0-10V	<200 sec for 63% change	0.90 watts peak, 0.165 watts average	18-30VAC RMS, 50/60Hz, or 18 to 42 V _{DC} , polarity protected	-20 to +50	70 x 68 x 45 approx. overall, IP67
T3031-2-2k-24-P	0 to 2,000	0-10V	<200 sec for 63% change	0.90 watts peak, 0.165 watts average	18-30VAC RMS, 50/60Hz, or 18 to 42 V _{DC} , polarity protected	-20 to +50	70 x 68 x 45 approx. overall, IP67
T3031-2-5K-24-P	0 to 5,000	0-10V	<200 sec for 63% change	0.90 watts peak, 0.165 watts average	18-30VAC RMS, 50/60Hz, or 18 to 42 V _{DC} , polarity protected	-20 to +50	70 x 68 x 45 approx. overall, IP67
T3032-2-10K-24-P	0 to 10,000	4-20 mA	<200 sec for 63% change	0.90 watts peak, 0.165 watts average	18-30VAC RMS, 50/60Hz, or 18 to 42 V _{DC} , polarity protected	-20 to +50	70 x 68 x 45 approx. overall, IP67
T3032-2-10K-24-P-CM	0 to 10,000	4-20 mA	<200 sec for 63% change	0.90 watts peak, 0.165 watts average	18-30VAC RMS, 50/60Hz, or 18 to 42 V _{DC} , polarity protected	-20 to +50	70 x 68 x 45 approx. overall, IP67
T3032-2-2K-24-P	0 to 2,000	4-20 mA	<200 sec for 63% change	0.90 watts peak, 0.165 watts average	18-30VAC RMS, 50/60Hz, or 18 to 42 V _{DC} , polarity protected	-20 to +50	70 x 68 x 45 approx. overall, IP67
T3032-2-5K-24-P	0 to 5,000	4-20 mA	<200 sec for 63% change	0.90 watts peak, 0.165 watts average	18-30VAC RMS, 50/60Hz, or 18 to 42 V _{DC} , polarity protected	-20 to +50	70 x 68 x 45 approx. overall, IP67


SENSIRION
 THE SENSOR COMPANY

Part Number	Measurement Range (ppm)	Output Interface	Response Time	Power Consumption	Supply Voltage (V)	Operating Conditions	Package Type / Size (mm)
SCD30	0 to 40,000	UART/ I ² C	τ63% 20s	2mW @ 1 measurement per minute	3.3 to 5.5	0 to -50°C, 0 to 95%RH	35 x 23 x 7

Part Number	Measurement Range	Output Interface	Power-Up Time	Power Consumption	Supply Voltage (VDC)	Operating Conditions (°C)	Package Type / Size (mm)
SM-PWM-01C	0.01 to 3000 ug/m ³	PWM	90s	<100 mA	4.5 to 5.5	-10 to +60, <85%RH	59 x 46 x 18

SENSIRION
 THE SENSOR COMPANY

Part Number	Measurement Range	Output Interface	Power-Up Time	Power Consumption	Supply Voltage (VDC)	Operating Conditions (°C)	Package Type / Size (mm)
SPS30	0.1 to 1000 ug/m ³	UART / I ² C	<8s	0.44 W	4.5 to 5.5	-10 to +60, <85%RH	41 x 41 x 12



BIOSENSORS

Biosensor	23
Biopotential AFE	23
Optical AFE	24



Part Number	Integrated LEDs	Integrated LED Driver Current (mA)	Sensor Spectrum Bandwidth ($\lambda_{0.5}$ nm)	ADC Resolution (Bit)	Output Interface	Supply Current (uA)	Standby Current (uA)	Supply Voltage (V)	I ² C Bus Voltage Range (V)	Package Type / Size (mm)
MAX30101EFD+T	Red, IR, Green	50	—	18	I ² C	600	0.7	1.7 to 2.0	1.7 to 5.0	OLGA, 14-pin, 3.3 x 5.6 x 1.55
MAX30102EFD+T	Red, IR	50	—	18	I ² C	600	0.7	1.7 to 2.0	1.7 to 5.0	OLGA, 14-pin, 3.3 x 5.6 x 1.55



Part Number	Integrated LEDs	Integrated LED Driver Current (mA)	Sensor Spectrum Bandwidth ($\lambda_{0.5}$ nm)	ADC Resolution (Bit)	Output Interface	Supply Current (uA)	Standby Current (uA)	Supply Voltage (V)	I ² C Bus Voltage Range (V)	Package Type / Size (mm)
BH1792GLC	NO	2 x 63mA	550nm, 790nm	16bit	I ² C	200	0.8	2.5 to 3.6	2.5 to 3.6	WGA010V28 2.8 x 2.8 x 1.0

BIOSENSORS / Biopotential AFE


Part Number	Features / Applications	Data Converter Resolution (bits)	Input Impedance (MOhm)	CMRR (dB)	DC Offset Range (mV)	Supply Current	Shutdown Mode Supply Current (uA)	Supply Voltage	Package Type / Size (mm)
MAX30001CWV+	ECG, R-R Detection, BioZ, Pace	18;15.5 effective (ECG) 20, 17 effective (BioZ)	1500 (Differential) 45000 (Common-mode)	115	±300 at 1.1V ±650 at 1.8V	205 at 1.1V 232 at 1.8V 242 at 2.0V	0.58	1.1 to 2.0 (AVDD, DVDD) 1.65 to 3.6 (OVDD)	WLP, 30-pin, 2.74 x 2.926
MAX30003CTI+T	ECG, R-R Detection	18;15.5 effective (ECG)	1500 (Differential) 45000 (Common-mode)	115	±300 at 1.1V ±650 at 1.8V	76 at 1.1V 100 at 1.8V 109 at 2.0V	0.51	1.1 to 2.0 (AVDD, DVDD) 1.65 to 3.6 (OVDD)	TQFN, 28-pin, 5 x 5 x 0.75
MAX30004CWV+T	R-R Detection	18;15.5 effective (ECG)	1500 (Differential) 45000 (Common-mode)	115	±300 at 1.1V ±650 at 1.8V	76 at 1.1V 100 at 1.8V 109 at 2.0V	0.51	1.1 to 2.0 (AVDD, DVDD) 1.65 to 3.6 (OVDD)	WLP, 30-pin, 2.74 x 2.926

Part Number	Output Interface	Receiver Channels	Transceiver Channels (LED Driver)	Integrated LED Driver Current (mA)	ADC Resolution (Bit)	Standby Current (uA)	Supply Voltage (V)	Package Type / Size (mm)
MAX86140ENP+	SPI	1	3 (up to 6 with external Mux)	124	19	0.6	1.7 to 2.0	WLP, 20-pin, 2.048 x 1.848
MAX86141ENP+	SPI	2	3 (up to 6 with external Mux)	124	19	0.6	1.7 to 2.0	WLP, 20-pin, 2.048 x 1.848
MAX30112EWG+	I ² C	1	2	200	19	1.6	1.7 to 2.0	WLP, 24-pin, 2.8 x 2.0
MAX30110EWG+	SPI	1	2	200	19	1.6	1.7 to 2.0	WLP, 24-pin, 2.8 x 2.0

RSL10-SENSE-GEVK: ULTRA-LOW POWER MULTI-SENSOR DEVELOPMENT KIT



ON Semiconductor®



THINK ON

onsemi.com/IoT

Experts in Environmental Sensing

VOC


PM2.5

RH/T

CO₂

www.FutureElectronics.com/Sensors

SENSIRION
THE SENSOR COMPANY



ENVIRONMENTAL COMBO

Humidity, Temperature and Pressure Sensor Combo. . . . 27

Humidity, Temperature, Pressure and
VOC Sensor Combo. 27



BOSCH
Invented for life

SENSIRION
THE SENSOR COMPANY

ENVIRONMENTAL COMBO / Humidity, Temperature and Pressure Sensor Combo



BOSCH

Invented for life

Part Number	Description	Output Interface	Sensing Range	Accuracy	Supply Current	Supply Voltage (V)	Package Type / Size (mm)
BME280	The unit combines individual high linearity, high accuracy sensors for pressure, humidity and temperature.	I ² C, SPI	H: 0 to 100 %RH P: 300 to 1100 hPa P: 1100 to 1250 hPa T: 0 to 65°C	H: ±3% RH P: -20 to 0 @ ±1.7 hPa P: 0 to 65 @ ±1.0 hPa P: 25 to 40 @ ±1.5 hPa T: ±1.0°C	Sleep mode 0.1 µA 1.8 µA @ 1Hz (H,T) 2.8 µA @1Hz (P, T) 3.6 µA @ 1Hz (H, P, T)	V _{DDIO} 1.2 to 3.6 V _{DD} 1.71 to 3.6	2.5 x 2.5 x 0.93

G= Gas; T= Temperature; H= Humidity; P= Pressure

ENVIRONMENTAL COMBO / Humidity, Temperature, Pressure and VOC Sensor Combo



BOSCH

Invented for life

Part Number	Description	Output Interface	Measurement Range	Power Consumption	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
BME680	The unit integrates for the first time low-power and highly accurate gas, pressure, humidity and temperature sensors in one tiny package.	I ² C, SPI	G: 0 to 500 IAQ (equivalent to 0.2 to 20mg/m³ TVOC levels) T: -40 to 85°C H: 0 to 100 % rH P: 300 to 1100 hPa	Sleep mode 0.15 µA 2.1 µA @ 1Hz (H,T) 3.1 µA @ 1Hz (P, T) 3.7 µA @ 1 Hz (H, P, T) 0.09 to 12 mA (P/H/T/Gas) depending on operation mode	V _{DDIO} 1.2 to 3.6 V _{DD} 1.71 to 3.6	-40 to +85	3.0 x 3.0 x 0.93

V = Volatile Organic Compound (VOC); G= Gas; T= Temperature; H= Humidity; P= Pressure

SENSIRION
THE SENSOR COMPANY

Part Number	Description	Output Interface	Measurement Range	Power Consumption	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
SVM30	MEMS metal-oxide gas sensor for measuring volatile organic compounds - Consumer version	Digital, I ² C	0 - 1000 ppm	250mW	5	-20 to +85	39 x 15 x 6.5

V = Volatile Organic Compound (VOC); G= Gas; T= Temperature; H= Humidity; P= Pressure



FLOW

Mass Air Flow Meter..... 29

Ultrasonic Flow Converter 29

am 

SENSIRION
THE SENSOR COMPANY

Part Number	Output Interface	Flow Range (slm)	Pressure Drop (mbar)	Calibrated Gases	Max. Working Pressure (bar)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
SFM3000	Digital I ² C	-200 to 200	< 1 @ 60slm	Air, N ₂ , O ₂	1.3	5.0	-20 to +80	82 x 33
SFM3100	Analog	-24 to 240	< 3 @ 60slm	Air, N ₂ , O ₂	1.3	5.0	+5 to +60	57.5 x 31
SFM3200	Digital I ² C	-100 to 250	< 1 @ 60slm	Air, N ₂ , O ₂	1.07	5.0	+10 to +50	73 x 22
SFM3200-AW	Digital I ² C	-100 to 250	< 1 @ 60slm	Air, N ₂ , O ₂	1.07	5.0	+10 to +50	73 x 22
SFM3300-AW	Digital I ² C	-250 to 250	< 1.8 @ 60slm	Air, N ₂ , O ₂	1.1	5.0	+10 to +50	73 x 22
SFM3300-D	Digital I ² C	-250 to 250	< 1.8 @ 60slm	Air, N ₂ , O ₂	1.1	5.0	+10 to +50	69.3 x 22
SFM4100	Digital I ² C	0 to 20	< 25 @ 20slm	Air, N ₂ , O ₂ , N ₂ O, Ar, CO ₂	6.0	3.5 to 9.0	-20 to +80	93 x 11.91

FLOW / Ultrasonic Flow Converter

Part Number	Output Interface	Description	Integrated Functions	Resolution (ps)	Supply Voltage (V)	Current Consumption	Operating Temperature (°C)	Package Type / Size (mm)
TDC-GP21	SPI	2-channel Time-to-Digital Converter	Fire-pulse generator, zero-cross detection, analog switches	22	2.5 to 3.6	4 mA (during measurement)	-40 to +125	QFN-32; 5 x 5 x 0.9
TDC-GP22	SPI	2-channel Time-to-Digital Converter	Analog front end for flow meters, fire-pulse generator, zero-cross detection, analog switches, first-hit detection	22	2.5 to 3.6	4 mA (during measurement)	-40 to +125	QFN-32; 5 x 5 x 0.9
TDC-GP30 / TDC-GP30-F01	SPI	Ultrasonic Flow Converter	Analog frontend for driving and receiving piezos, amplitude measurement & CPU for flow calculation	11 avr	2.5 to 3.6	8.5µA @ 8Hz	-40 to +125	QFN-32; 5 x 5 x 0.9 QFN-40; 6 x 6 x 0.9

ams AS6200 Digital Temperature Sensor

- Ultra low power consumption at 6mA @ 4 samples/sec
- Industry's smallest integration size: WLCSP (1.6 x 1.0mm)





GYRO - ANGULAR RATE

Gyro - Angular Rate Sensor 31



BOSCH
Invented for life

muRata
INNOVATOR IN ELECTRONICS



ST
life.augmented


BOSCH

Invented for life

Part Number	Output Interface	Sensing Range (°/s)	Sensing Axis	Zero Rate Output (°/s)	Turn On Time (ms)	Supply Voltage (V)	Supply Current (µA)	Operating Temperature (°C)	Package Type / Size (mm)
BMG250	For primary UI IF: I ² C up to 1MHz 3w/4w SPI 2x digital interrupts for secondary OIS/EIS IF: 3w SPI up to 10MHz	±125, ±250, ±500, ±1000, ±2000	X, Y, Z	±3	Suspend to normal mode 55 ms (typical); Fast start-up to normal mode 10 ms (typical)	V _{DDO} 1.2 to 3.6 V _{DD} 1.7 to 3.6	Full operation 850 µA Suspend mode 3 µA Fast start-up 500 µA	-40 to +85	2.5 x 3 x 0.8

INNOVATOR IN ELECTRONICS

Part Number	Output Interface	Sensing Range (°/s)	Sensing Axis	Zero Rate Output (°/s)	Turn On Time (ms)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
SCR2100-D08	SPI	±125	X	0.8	620 - 750	3.3	3.3	-40 to +125	15.0 x 8.5 x 4.3

Part Number	Output Interface	Sensing Range (°/s)	Sensing Axis	Zero Rate Output (°/s)	Turn On Time (ms)	Supply Voltage (V)	Supply Current (µA)	Operating Temperature (°C)	Package Type / Size (mm)
FXAS21002CQR1	SPI, I ² C	±250, ±500, ±1000, ±2000	X, Y, Z	1.5	60	1.95 to 3.6	2.7	-40 to +85	QFN-24 4 x 4 x 1

life.augmented

Part Number	Output Interface	Sensing Range (°/s)	Sensing Axis	Zero Rate Output (°/s)	Turn On Time (ms)	Supply Voltage (V)	Supply Current (µA)	Operating Temperature (°C)	Package Type / Size (mm)
I3G4250DTR	Digital	±245, ±500, ±2000	Yaw, Pitch, Roll	±25	—	2.4 to 3.6	6.1	-40 to +125	LGA-16 4 x 4 x 1.1
A3G4250DTR	Digital	±245	Yaw, Pitch, Roll	±25	—	2.4 to 3.6	6.1	-40 to +125	LGA-16 4 x 4 x 1.1
L20G20IS	Digital	±100, ±200	Two-axis	±5	35	2.4 to 3.6	1.4	-40 to +125	LGA 2.0 x 2.0 x 0.7



SECURE SENSING FOR A SMARTER WORLD

To learn how our solutions are enabling secure connections for a smarter world, visit www.nxp.com/sensors

NXP, the NXP logo, and NXP Secure Connections for a Smarter World are trademarks of NXP B.V. All other product or service names are the property of their respective owners. © 2017 NXP B.V.



| SECURE CONNECTIONS
FOR A SMARTER WORLD |

SECURE SENSING FOR A SMARTER WORLD



With successful experiences over 30 years and over 3 billion sensors shipped worldwide, NXP is a leader serving applications in the automotive, medical and industrial market spaces. NXP's Sensor solutions include a breadth of accelerometers, gyroscopes, magneto-resistive and pressure sensor solutions covering different performance, sensing ranges and form factors. The portfolio is complemented with class leading development and enablement support spanning hardware tools, software tools and use case algorithms. It leverages secure computing and connectivity from the greater NXP portfolio to facilitate speedy sensor system development for the IoT.



To learn how our solutions are enabling secure connections for a smarter world, visit www.nxp.com/sensors

NXP

SECURE CONNECTIONS
FOR A SMARTER WORLD

NXP, the NXP logo, and NXP Secure Connections for a Smarter World are trademarks of NXP B.V. All other product or service names are the property of their respective owners.
© 2017 NXP B.V.

Stay on top of all the **latest and greatest** technologies with

FTM



Future Technology Magazine (FTM) is designed to be a modern, interesting and engaging magazine. It is highly response-oriented, with a written style and content that reflects an interactive and technical approach.

TARGET AUDIENCE

- Design Engineers

FORMAT AND FREQUENCY

- 7 to 8/year (minimum)

DISTRIBUTION

Global print circulation of 60,000 and 40,000 e-mail subscribers

- Future in-house list, purchased lists from industry publications, plus personal delivery to key customers. Future e-mail list.

OBJECTIVES

- Sell components, generate leads and responses
- Drive demand creation
- Offer readers technical expertise
- Focus on solutions sell
- Increase reader loyalty
- Particular focus on New Product Introductions (NPIs)

NEW PRODUCT INTRODUCTION (NPI) DEFINITION

Products released in the last 6 months.

- Small engineering quantities must be available for immediate shipment with data sheets, application notes, and development boards/evaluation kits (where applicable).

CALLS TO ACTION

- Compelling offers (e.g. development boards/evaluation kits)
- Endorsement of manufacturers' components
- All featured products will have links to web landing pages to provide more comprehensive information, data sheets and application notes.
- Landing pages will provide the option to purchase products online.

Don't miss an issue! Register today at
www1.futureelectronics.com/FTM/register.asp





HUMIDITY

Humidity Sensor 35



Amphenol
Advanced Sensors



Part Number	Output Interface	Humidity Accuracy (%)	Temperature Accuracy (°C)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
CC2D23	PC	±2	±0.3	3.3	0.75	-40 to +125	SMD
CC2D25	PC	±2	±0.3	5.0	0.75	-40 to +125	SMD
CC2D33	PC	±3	±0.3	3.3	0.75	-40 to +125	SMD
CC2D35	PC	±3	±0.3	5.0	0.75	-40 to +125	SMD
CC2A23	PDM	±2	±0.3	3.3	0.9	-40 to +125	SMD
CC2A25	PDM	±2	±0.3	5.0	0.9	-40 to +125	SMD
CC2A33	PDM	±3	±0.3	3.3	0.9	-40 to +125	SMD
CC2A35	PDM	±3	±0.3	5.0	0.9	-40 to +125	SMD
CC2D23-SIP	PC	±2	±0.3	3.3	0.75	-40 to +125	SIP
CC2D25-SIP	PC	±2	±0.3	5.0	0.75	-40 to +125	SIP
CC2D33-SIP	PC	±3	±0.3	3.3	0.75	-40 to +125	SIP
CC2D35-SIP	PC	±3	±0.3	5.0	0.75	-40 to +125	SIP
T9602-3-D	PDM	±2	±0.5	3.3	0.75	-20 to +70	Probe
T9602-5-D	PDM	±2	±0.5	5.0	0.75	-20 to +70	Probe
T9602-3-A	PDM	±2	±0.5	3.3	0.75	-20 to +70	Probe
T9602-5-A	PDM	±2	±0.5	5.0	0.75	-20 to +70	Probe

*PDM= Pulse Density Modulation

TELAIRE
NOVA
 SENSOR

 THERMOMETRICS
 A COMMITMENT TO EXCELLENCE

Amphenol
 Advanced Sensors


EMBEDDED SENSING TECHNOLOGIES for

TEMPERATURE

- NTC & PTC thermistors
- Non-contact infrared temperature sensors
- Inrush current limiting thermistors

CARBON DIOXIDE (CO₂)

- Non-dispersive infrared (NDIR)
- Patented self-calibrating with lifetime calibration warranty
- Small footprint

HUMIDITY

- Various calibrated outputs (digital and analog)
- Fully-integrated humidity and temperature transmitters
- Harsh environment probes

Transportation, Healthcare
and Industrial Applications

PRESSURE / MEMS

- MEMS-based piezoresistive pressure sensors
- Senstable[®] technology for world-class accuracy and low drift
- Low pressure 2" H₂O to 3000 PSI

DUST

- Laser and LED versions
- PM 2.5 and PM 10 measurements
- Analog and digital outputs



Part Number	Output Interface	Humidity Accuracy (%)	Temperature Accuracy (°C)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
ENS210	I ² C	±3.5	±0.2	1.71 to 3.6	Active current: 7.1 µA @ 1 Hz (1.8V) Standby current: 40 nA	-40 to +100	QFN-4 2 x 2 x 0.75



Part Number	Output Interface	Humidity Accuracy (%)	Temperature Accuracy (°C)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
SHT30-ARP-B	ARV*	±3.0	±0.3	2.4 to 5.5	0.22	-40 to +125	0.9 x 1.6
SHT30-DIS-B	I ² C	±2.0	±0.3	2.4 to 5.5	0.20	-40 to +125	0.9 x 1.6
SHT31-ARP-B	ARV*	±2.0	±0.2	2.4 to 5.5	0.22	-40 to +125	0.9 x 1.6
SHT31-DIS-B	I ² C	±2.0	±0.2	2.4 to 5.5	0.20	-40 to +125	0.9 x 1.6
SHT31-DIS-F	I ² C	±2.0	±0.2	2.4 to 5.5	0.20	-40 to +125	0.9 x 1.6
SHT31-DIS-P	I ² C	±2.0	±0.2	2.4 to 5.5	0.20	-40 to +125	0.9 x 1.6
SHT35-DIS-B	I ² C	±1.5	±0.1	2.4 to 5.5	0.20	-40 to +125	0.9 x 1.6
SHT35-DIS-F	I ² C	±1.5	±0.1	2.4 to 5.5	0.20	-40 to +125	0.9 x 1.6
SHTC1	I ² C	±3.0	±0.3	1.80	0.48	-40 to +125	2 x 2 x 0.75
SHTW2	I ² C	±3.0	±0.4	1.80	0.48	-40 to +125	1.3 x 0.7 x 0.5
SHT85	I ² C	±1.5	±0.1	-0.3 to 6.0	1.5	-40 to +105	17.8 x 4.9 x 2.2
SHTC3	I ² C	±2.0	±0.2	1.62 to 3.6	0.9	-40 to +125	2 x 2 x 0.75
SCC30-db	I ² C	±3.0	±0.2	2.4 to 5.5	0.8	-20 to +85	21.6 x 13.6 x 7.2

*ARV= Analog Ratiometric Voltage



Part Number	Output Interface	Humidity Accuracy (%)	Temperature Accuracy (°C)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
HTS221TR	SPI, I ² C, DRDY*	±3.5	±0.5	1.7 to 3.6	0.002	- 40 to +120	HLGA-6L 2 x 2 x 0.9

*DRDY= Data Ready

Part Number	Output Interface	Humidity Accuracy (%)	Temperature Accuracy (°C)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
HPP801A031	Analog	±5 (w/ Calibration)	—	—	—	-60 to +140	10 x 6
HPP808H031	Analog	±3	±0.5	5.0	1.00	-40 to +85	18 x 13 x 11
HPP805D033	Analog	±3	±0.8	5.0	3.00	-40 to +100	35 x 13 x 13
HPP809A031	Analog	±3	±0.3	5.0	1.00	-40 to +60	75 x 11
HPP809A033	Analog	±3	±0.3	5.0	1.00	-40 to +85	75 x 11
HPP805A031	Analog	±3	—	5.0	1.50	-40 to +60	11 x 58
HPP805C031	Analog	±2 (for RH<15%RH)	—	5.0	1.50	-40 to +60	11 x 58
HPP815A533	Analog	±3	±0.3	3.0	1.00	-40 to +85	27 x 12 x 6
HPP815A535	Analog	±3	±0.3	5.0	1.00	-40 to +85	27 x 12 x 6
HPP815F535	Analog	±3	±0.3	5.0	1.00	-40 to +85	27 x 12 x 6
HPP831A210	Analog	±2	±0.3	5.0	1.00	-40 to +85	27 x 12 x 6
HPP831A610	Analog	±2	±0.3	5.0	1.00	-40 to +85	27 x 12 x 6
HPP831F511	I²C	±2	±0.3	3.0	0.50	-40 to +85	27 x 12 x 6
HPP831E511	I²C	±2	±0.3	5.0	0.50	-40 to +85	27 x 12 x 6
HPP831E910	I²C	±2	±0.3	5.0	0.50	-40 to +85	27 x 12 x 6
HPP845E031	I²C	±2	±0.3	3.0	0.50	-40 to +125	3 x 3 x 0.9
HPP845E032	Analog	±2	±0.3	3.0	0.50	-40 to +125	3 x 3 x 0.9
HPP845E131	I²C	±2	±0.3	3.0	0.50	-40 to +125	3 x 3 x 0.9
HPP845E034	I²C	±3	±0.3	3.0	0.50	-40 to +125	3 x 3 x 0.9
HPP845E035	Analog	±3	±0.3	3.0	0.50	-40 to +125	3 x 3 x 0.9
HPP845E134	I²C	±3	±0.3	3.0	0.50	-40 to +125	3 x 3 x 0.9

Panasonic



Sensor Solutions

<https://na.industrial.panasonic.com/products/sensors>



IMAGE

CMOS Image Sensor	39
CCD Image Sensor	44
Image Sensor Module	45
Thermal Image Sensor	46
3D Image Sensor (Time of Flight)	47

am 

 **FLIR**[®]

Melexis 

ON Semiconductor[®]



Part Number / Series	Output Interface	Pixel Size (μm)	Optical Format	Shutter Type	Color Filter	Frame Rate @ Full Resolution (FPS)	Resolution (Megapixels)	SNR Max (dB)	Dynamic Range (dB)	Responsivity	Package Type / Size (mm)
CMV300	LVDS (4x)	7.4 x 7.4	1/3"	Global	optional	480	640 x 480	43	60	6 V/Lux-s	58 pins BGA
CMV2000	LVDS (16x)	5.5 x 5.5	2/3"	Global	optional	340	2048 x 1088	41.3	60	5.56 V/Lux-s	Ceramic 95-pins μPGA/LGA or 92-pins LCC
CMV4000	LVDS (16x)	5.5 x 5.5	1"	Global	optional	180	2048 x 2048	41.3	60	5.56 V/Lux-s	Ceramic 95-pins μPGA/LGA or 92-pins LCC
CMV8000	LVDS (16x)	5.5 x 5.5	4/3"	Global	optional	103	3360 x 2496	41.3	61	5.56 V/Lux-s	107-pins μPGA
CMV12000	LVDS (64x)	5.5 x 5.5	APS-like	Global	optional	300	4096 x 3072	41.3	60	4.64 V/Lux-s	237-pins μPGA
CMV20000	LVDS (16x)	6.4 x 6.4	35mm	Global	optional	30	5120 x 3840	41.7	66	8.3 V/Lux-s	143-pins PGA
CMV50000	LVDS (22x)	4.6 x 4.6	35mm	Global	optional	30	7920 x 6004	41.6	64	3.5 x10e7 DN/ (W.s/m2) (@ 550 nm)	141-pins PGA ceramic package
CHR71000	8 analog channels	3.1 x 3.1	35mm	Rolling	optional	3	10000 x 7096	—	63	1.24 V/Lux-s	65-pins Ceramic PGA
DR-2K7	4-wire SPI	7 x 7	Single-line or Dual-line	Global	no	80KHz	2048 x 1 or 2048 x 2	44	44	77 DN/nJ/cm2 (@12 bit)	LCC or INVAR
DR-4K7	4-wire SPI	7 x 7	Single-line or Dual-line	Global	no	80KHz	4096 x 1 or 4096 x 2	44	44	77 DN/nJ/cm2 (@12 bit)	INVAR
DR-4K3.5	4-wire SPI	3.5 x 3.5	Single-line or Dual-line	Global	no	80KHz	4096 x 1 or 4096 x 2	44	44	39 DN/nJ/cm2 (@12 bit)	LCC or INVAR
DR-6K7	4-wire SPI	7 x 7	Single-line	Global	no	80KHz	6144 x1	44	44	77 DN/nJ/cm2 (@12 bit)	LCC or INVAR
DR-8K7	4-wire SPI	7 x 7	Single-line or Dual-line	Global	no	80KHz	8192 x 1 or 8192 x 2"	44	44	77 DN/nJ/cm2 (@12 bit)	INVAR
DR-8K3.5	4-wire SPI	3.5 x 3.5	Single-line or Dual-line	Global	no	80KHz	8192 x 1 or 8192 x 2	44	44	39 DN/nJ/cm2 (@12 bit)	INVAR
DR-16K	4-wire SPI	3.5 x 3.5	Single-line	Global	no	80KHz	16384 x 1	44	44	39 DN/nJ/cm2 (@12 bit)	INVAR
4LS-10K	LVDS	5.6 x 5.6	4-line	Global	no	80KHz	10176 x 4	44	61 DN/nJ/cm2 (@12 bit)	61 DN/nJ/cm2 (@12 bit)	INVAR
4LS-15K	LVDS	5.6 x 5.6	4-line	Global	no	80KHz	15264 x 4	44B	62 DN/nJ/cm2 (@12bit)	61 DN/nJ/cm2 (@12bit)	INVAR

GS= Global Shutter; ERS= Electronic Rolling Shutter; GRR= Global Reset Release (ERS); FF= Full Frame; IT= Interleave

*NOTE: PEAK QE: wave length, CFA, microlens dependent (only Mono max stated, review datasheet for clarification)



Part Number / Series	Output Interface	Pixel Size (µm)	Optical Format	Shutter Type	Color Filter	Frame Rate @ Full Resolution (FPS)	Resolution (Megapixels)	SNR Max (dB)	Dynamic Range (dB)	Responsivity	Package Type / Size (mm)
AR0130CS	Parallel	3.75	1/3"	ERS	RGB, Mono	45	1	44	82	6.5 (mono) V/Lux-s	ILCC-48, PLCC-48
AR0132AT	HiSPi™, Parallel	3.75	1/3"	ERS	Mono, RCCC, RGB	45	1	44	115	5.48 V/Lux-s	IBGA-63
AR0134CS	HiSPi™, Parallel	3.75	1/3"	GS	RGB, Mono	54	1	38.4	64	6.1 (mono), 5.3 (color) V/Lux-s	IBGA-63, ILCC-48
AR0135AT	HiSPi™, Parallel	3.75	1/3"	GS	Mono	54	1	40.7	71.1	85 ke-/lux*sec (mono)	IBGA-63
AR0135CS	HiSPi™, Parallel	3.75	1/3"	GS	Mono	54	1	34	69	6.1 V/Lux-s	IBGA-63
AR0136AT	HiSPi™, Parallel	3.75	1/3"	ERS	RGB	54	1	43.9	120	6.3 V/Lux-s	IBGA-63
AR0140AT	HiSPi™, Parallel	3	1/4"	ERS	RGB	60	1	41	96	4 V/Lux-s	IBGA-63
AR0140CS	HiSPi™, Parallel	3	1/4"	ERS	RGB	60	1	41	96	4 V/Lux-s	IBGA-63
AR0141CS	HiSPi™, Parallel	3	1/4"	ERS	RGB, Mono	60	1	41	79	4 V/Lux-s	IBGA-63
AR0144CS	MIPI-2 lane, Parallel 12-bit	3	1/4"	GS	RGB, Mono	60	1	38	63.9	3.6 V/Lux-s	CSP-69, Bare die
AR0230AT	HiSPi™, Parallel	3	1/2.7"	ERS, GRR	RGB, Mono	30	2	41	80 / 96	4 V/Lux-s	IBGA-80
AR0230CS	HiSPi™, Parallel	3	1/2.7"	ERS, GRR	RGB	60	2	41	80 / 96	4 V/Lux-s	IBGA-80
AR0231AT	HiSPi™, Parallel	3	1/2.7"	ERS, GRR	RGB	40	2	42.8	120	34 ke-/Lux-s	IBGA-121
AR0237	HiSPi™, Parallel	3	1/2.7"	ERS, GRR	RGB Bayer, RGB-IR	60	2	41	96	4.0 V/Lux-s	IBGA-80, PLCC-48
AR0238	HiSPi™, Parallel	3	1/2.7"	ERS	RGB	60	2	41	96	4.0 V/Lux-s	PLCC-48
AR0238 RGB-IR	HiSPi™, Parallel	3	1/2.7"	ERS	RGB	60	2	41	96	4.0 V/Lux-s	PLCC-48
AR0239SR	HiSPi™, MIPI, Parallel	3	1/2.7"	ERS	RGB Bayer	60	2	43	83 / 128	28.6 ke-/Lux-s	IBGA-63
AR023Z	HiSPi™, Parallel	3	1/2.7"	ERS, GRR	RGB Bayer	60	2	41	80.5	4.0 V/Lux-s	IBGA-80
AR0261	MIPI	1.4	1/6"	ERS	RGB, Mono	60	2	37.5	66.5	0.75 V/Lux-s	Bare Die, CSP
AR0263	MIPI	1.4	1/6"	ERS	Mono	60	2	37.5	66.5	0.75 V/Lux-s	ODCSP-35
AR0330	HiSPi™, MIPI, Parallel	2.2	1/3"	ERS, GRR	RGB	60	3	39	69.5	2.0 V/Lux-s	CLCC-48, ODCSP-61, ODCSP-64, PLCC-48
AR0331SR	HiSPi™, Multi	2.2	1/3"	ERS, GRR	Bayer Color	60	3	39	100	1.9 V/Lux-s	IBGA-63, ILCC-48

GS = Global Shutter; ERS = Electronic Rolling Shutter; GRR = Global Reset Release (ERS); FF = Full Frame; IT = Interline Transfer

NOTE: PEAK QE: wave length, CFA, microlens dependent (only Mono max stated, review datasheet for clarification)



Part Number / Series	Output Interface	Pixel Size (µm)	Optical Format	Shutter Type	Color Filter	Frame Rate @ Full Resolution (FPS)	Resolution (Megapixels)	SNR Max (dB)	Dynamic Range (dB)	Responsivity	Package Type / Size (mm)
AR0521	HiSPi™, MIPI CSI-2	2.2	1/2.5"	ERS, GRR	RGB, Mono	60	5	40	74.3	18.8 ke-/Lux-s (RGB)	mPLCC, IBGA-63
AR0543	MIPI	1.4	1/4"	ERS	RGB Bayer	15	5	36.5	66	0.82 V/Lux-s	ODCSP-54
AR0833	HiSPi™, MIPI	1.4	1/3.2"	ERS	RGB	30	8	36	64	0.6 V/Lux-s	CLCC-48
AR0835HS	HiSPi™, MIPI	1.4	1/3.2"	ERS	RGB	42	8	36	64	0.6 V/Lux-s	CLCC-48
AR1335	MIPI	1.1	1/3.2"	ERS	RGB	30	13	37	69	4.7 ke-/Lux-s	CSP-63
AR1820HS	HiSPi™, MIPI	1.25	1/2.3"	ERS, GRR	RGB	24	18	36.3	65.8	0.62 V/Lux-s	IBGA-60
ARX342CS	Parallel	5.6	1/4"	ERS	Bayer RGB	60	VGA	46	87	16.5 V/Lux-s	IBGA-63
ARX550AT	HiSPi™, Parallel	3.75	1/5"	ERS	RGB, RCCC, RGBC	60	VGA	43.9	115	5.48 V/Lux-s	IBGA-63
AS0260	Parallel, MIPI	1.4	1/6"	ERS	RGB	30	2 Mp	33	65	0.64 V/Lux-s	ODCSP-54
ASX340AT	Parallel, NTSC, PAL	5.6	1/4"	ERS	RGB	30	VGA	46	87	16.5 V/Lux-s	IBGA-63
ASX340CS	Parallel, NTSC, PAL	5.6	1/4"	ERS	RGB	60	VGA	46	75.8	16.5 V/Lux-s	IBGA-63
ASX342AT	Parallel, NTSC, PAL	5.6	1/4"	ERS	RGB	60	VGA	46	87	16.5 V/Lux-s	IBGA-63
ASX344AT	Parallel, NTSC, PAL	5.6	1/4"	ERS	RGB	60	WVGA	46	84	16.5 V/Lux-s	IBGA-63
ASX350AT	Parallel, NTSC, PAL	3.75	1/5"	ERS	RGB	60	VGA	42.6	82.2	6.67 V/Lux-s	IBGA-63
ASX350CS	Parallel, NTSC, PAL	3.75	1/5"	ERS	RGB	60	VGA	42.6	82.2	6.67 V/Lux-s	IBGA-63
ASX370CS	Parallel, MIPI	3	1/7"	ERS	RGB Bayer	30	VGA	40	72.46	3.7 V/Lux-s	Bare Die; CSP
KAC-06040	LVDS	4.7	1"	Global Rolling	Bayer Color, Mono	160	6	—	—	—	CPGA-267
KAC-12040	LVDS	4.7	4/3"	Global Rolling	Bayer Color, Mono	70	12	—	—	—	CPGA-267
MT9F002	HiSPi™, Parallel	1.4	1/2.3"	ERS, GRR	RGB	13.7	15	35.5	65.3	0.724 V/Lux-s	ILCC-48
MT9J003	HiSPi™, Parallel	1.67	1/2.3"	ERS, GRR	RGB, Mono	15	10	34	65.2	0.31 V/Lux-s	ILCC-48
MT9M001	Parallel	5.2	1/2"	ERS	RGB, Mono	30	1	45	68.2	2.1 V/Lux-s	CLCC-48
MT9M024	HiSPi™, Parallel	3.75	1/3"	ERS	RGB, Mono	45	1	43.9	120	5.48 V/Lux-s	IBGA-63
MT9M025	HiSPi™, Parallel	3.75	1/3"	ERS	RGB, Mono	45	1	43.9	120	5.48 V/Lux-s	IBGA-63
MT9M034	Parallel	3.75	1/3"	ERS	RGB, Mono	45	1	43.9	120	5.48 V/Lux-s	ILCC-48
MT9M114	Parallel, MIPI	1.9	1/6"	ERS	RGB	30	1	30	70.8	2.24 V/Lux-s	ODCSP-55

GS = Global Shutter; ERS = Electronic Rolling Shutter; GRR = Global Reset Release (ERS); FF = Full Frame; IT = Interline Transfer

NOTE: PEAK QE: wave length, CFA, microlens dependent (only Mono max stated, review datasheet for clarification)



Part Number / Series	Output Interface	Pixel Size (µm)	Optical Format	Shutter Type	Color Filter	Frame Rate @ Full Resolution (FPS)	Resolution (Megapixels)	SNR Max (dB)	Dynamic Range (dB)	Responsivity	Package Type / Size (mm)
MT9P001	Parallel	2.2	1/2.5"	ERS, GRR	RGB	15	5	38.1	70.1	1.4 V/Lux-s	ILCC-48
MT9P006	Parallel	2.2	1/2.5"	ERS	RGB	15	5	38.5	67.74	1.76 V/Lux-s	ILCC-48
MT9P031	Parallel	2.2	1/2.5"	ERS	RGB, Mono	15	5	38.1	70.1	1.4 V/Lux-s	ILCC-48
MT9P401	Parallel	2.2	1/2.5"	ERS	RGB	15	5	38.1	70.1	1.4 V/Lux-s	ILCC-48
MT9V022	LVDS, Parallel	6	1/3"	GS	RGB, Mono	60	WVGA	37.3	55 / 100	4.8 V/Lux-s	IBGA-52
MT9V023	—	6	1/3"	GS	RGB, Mono	60	WVGA	—	110	4.8 V/Lux-s	IBGA-52
MT9V024	LVDS, Parallel	6	1/3"	GS	Mono, RCCC, RGB	60	WVGA	—	55 / 100	4.8 V/Lux-s	IBGA-52
MT9V032	LVDS, Parallel	6	1/3"	GS	RGB, Mono	60	WVGA	37.3	55 / 100	4.8 V/Lux-s	CLCC-48
MT9V034	LVDS, Parallel	6	1/3"	GS	RGB, Mono	60	WVGA	37.3	55 / 100	4.8 V/Lux-s	CLCC-48
MT9V111	—	5.6	1/4"	ERS	RGB	90	VGA	35.2	62	0.68 V/Lux-s	IBGA-52
MT9V113	Parallel, MIPI	2.2	1/11"	ERS	RGB	30	VGA	34	63.5	1.15 V/Lux-s	Bare Die
MT9V115	Parallel, MIPI	1.75	1/13"	ERS	RGB	30	VGA	34.1	64	1.88 V/Lux-s	ODCSP-25
MT9V124	LVDS, Parallel	1.75	1/13"	ERS	RGB	30	VGA	—	—	1.65 V/Lux-s	ODCSP-25
MT9V125	—	5.6	1/4"	ERS	RGB	30	VGA	38.5	71.7	5.0 V/Lux-s	IBGA-52
MT9V126	—	5.6	1/4"	ERS	RGB	30	VGA	45	74.6	11.9 V/Lux-s	IBGA-63
MT9V127	—	5.6	1/4"	ERS	RGB	30	VGA	45	74.6	11.9 V/Lux-s	IBGA-63
MT9V128	—	5.6	1/4"	ERS	RGB	60	VGA	46	74.8	16.5 V/Lux-s	IBGA-63
PYTHON10K	LVDS	4.5	4/3"	GS Trigger, Pipeline	Bayer Color, Mono, NIR	175	10	—	—	—	CPGA-355
PYTHON12K	LVDS	4.5	4/3"	GS Trigger, Pipeline	Bayer Color, Mono, NIR	160	12	41	59	—	CPGA-355
PYTHON1300	LVDS, Parallel	4.8	1/2"	GS Trigger, Pipeline	Bayer Color, Mono, NIR	210	1	40	60	7.7 V/Lux-s	LCC-48
PYTHON16K	LVDS	4.5	APS-H	GS Trigger, Pipeline	Bayer Color, Mono, NIR	120	16	41	59	—	CPGA-355
PYTHON2000	LVDS, Parallel	4.8	2/3"	GS Trigger, Pipeline	Bayer Color, Mono, NIR	225	2	40	60	7.5 V/Lux-s	LCC-84
PYTHON25K	LVDS	4.5	APS-H	GS Trigger, Pipeline	Bayer Color, Mono, NIR	80	25	41	59	—	CPGA-355
PYTHON300	LVDS, Parallel	4.8	1/4"	GS Trigger, Pipeline	Bayer Color, Mono, NIR	815	VGA	40	60	7.7 V/Lux-s	LCC-48
PYTHON480	LVDS, Parallel	4.8	1/3.6"	GS Trigger, Pipeline	Bayer Color, Mono	120	VGA	40	59	—	ODCSP-67
PYTHON500	LVDS, Parallel	4.8	1/3"	GS Trigger, Pipeline	Bayer Color, Mono, NIR	545	VGA	40	60	7.7 V/Lux-s	LCC-48
PYTHON5000	LVDS, Parallel	4.8	1"	GS Trigger, Pipeline	Bayer Color, Mono, NIR	100	5	40	60	7.5 V/Lux-s	LCC-84

GS = Global Shutter; ERS = Electronic Rolling Shutter; GRR = Global Reset Release (ERS); FF = Full Frame; IT = Interline Transfer

NOTE: PEAK QE: wave length, CFA, microlens dependent (only Mono max stated, review datasheet for clarification)



Part Number / Series	Output Interface	Pixel Size (µm)	Optical Format	Shutter Type	Color Filter	Frame Rate @ Full Resolution (FPS)	Resolution (Megapixels)	SNR Max (dB)	Dynamic Range (dB)	Responsivity	Package Type / Size (mm)
STAR250	—	25	1"	ERS	Mono	29	0.25	—	74	5.5 V/Lux-s	JLDCC-84 Wafer
STAR1000	—	15	1"	ERS	Mono	11	1	—	64	2.7 V/Lux-s	JLDCC-84
VITA12K	LVDS	4.5	4/3"	GS(CMOS)	Bayer Color Mono	160	12.6	43.3	59.6	3.4 V/Lux-s	CPGA-355
VITA16K	LVDS	4.5	APS-H	GS(CMOS)	Bayer Color Mono	120	16	43.3	59.6	3.4 V/Lux-s	CPGA-355
VITA25K	LVDS	4.5	APS-H	GS Trigger, Pipeline	Bayer Color Mono	53	26.2	43.3	59.6	3.4 V/Lux-s	CPGA-355
VITA1300	LVDS Parallel	4.8	1/2"	GS(CMOS)	Color Mono	37 150	1.3	41	60	4.6 V/Lux-s	LCC-48
VITA2000	LVDS Parallel	4.8	2/3"	GS(CMOS)	Color Mono	23 92	2	41	60	4.6 V/Lux-s	LCC-52
VITA5000	LVDS	4.8	1"	GS(CMOS)	Color Mono	75	5.3	41	60	4.6 V/Lux-s	LCC-68
XGS 8000	HISPI™	3.2	1"	GS	Bayer Color Mono	75 130	8.8	—	67	—	CLGA-163
XGS 12000	HISPI™	3.2	1/1.1"	GS	Bayer Color Mono	27 90	12.6	—	67	—	CLGA-163

GS = Global Shutter; ERS = Electronic Rolling Shutter; GRR = Global Reset Release (ERS); FF = Full Frame; IT = Interline Transfer

NOTE: PEAK QE: wave length, CFA, microlens dependent (only Mono max stated, review datasheet for clarification)



THINK ON



ON Semiconductor®

ON Semiconductor provides a full suite of Image Sensor Evaluation Kits enabling customers to easily and quickly evaluate the performance of ON Semiconductor imaging devices without the need to develop a full camera design. When combined with ON Semiconductor DevSuite software, this evaluation system allows full control of the image sensor's register settings and enables video recording, still image capture, and image analysis.

onsemi.com/imagesensors



Part Number / Series	Output Interface	Pixel Size (µm)	Optical Format	Shutter Type	Color filter	Frame Rate @ Full Resolution (FPS)	Resolution (Mega-pixels)	Dynamic Range (dB)	Responsivity	Package Type / Size (mm)
KAE-02150	Analog	5.5	2/3"	GS	Bayer Color, Mono	30	2	68	*PEAK QE: 50%	CPGA-135, CPGA-143
KAE-02152	Analog	5.5	2/3"	GS	Bayer Color, Mono	30	2	68	*PEAK QE: 50%	CPGA-135, CPGA-143
KAE-04471	Analog	7.4	4/3"	GS	Bayer Color, Mono	30	4	72	*PEAK QE: 50%	CPGA-155
KAE-08151	Analog	5.5	4/3"	GS	Bayer RGB, Mono	14	8	66	*PEAK QE: 50%	CPGA-155
KAF-0261	Analog	20	1"	FF	Mono	15	VGA	87	*PEAK QE: 55%	CDIP-24
KAF-0402	Analog	9	1/2"	FF	Mono	20	WVGA	76	*PEAK QE: 77%	CDIP-24
KAF-09000	Analog	12	51.9 mm	FF	Mono	0.4	9	84	*PEAK QE: 64%	CDIP-34
KAF-09001	Analog	12	51.3 mm	FF	Mono	5	9	84	*PEAK QE: 64%	CDIP-34
KAF-1001	Analog	24	APS-H	FF	Mono	3	1	97	*PEAK QE: 55%	CDIP-26
KAF-1603	Analog	9	1"	FF	Mono	2.2	1	74	*PEAK QE: 77%	CDIP-24
KAF-16200	Analog	6	APS-H	FF	Bayer Color, Mono	1	16	—	*PEAK QE: 56%	CDIP-32
KAF-16801	Analog	9	52.1mm	FF	Mono	0.4	16	76	*PEAK QE: 67%	CDIP-34
KAF-16803	Analog	9	52.1mm	FF	Mono	0.2	16	80	*PEAK QE: 60%	CDIP-34
KAF-18500	Analog	6.8	35 mm	FF	Mono	0.8	20	68	*PEAK QE: 45%	CPGA
KAF-3200	Analog	6.8	4/3"	FF	Bayer Color	2.5	3	78	*PEAK QE: 80%	CDIP-24
KAF-40000	Analog	6	54.78 mm	FF	Bayer Color	1.3	40	70.2	*PEAK QE: 44%	CPGA-52
KAF-4320	Analog	24	70.7 mm	FF	Mono	2	4	87.5	*PEAK QE: 70%	CPGA-84
KAF-50100	Analog	6	61.3 mm	FF	Bayer Color, Mono	1	50	70.2	*PEAK QE: 62%	CPGA-52
KAF-6303	Analog	9	APS-H	FF	Mono	0.6	6	76	*PEAK QE: 68%	CDIP-26
KAF-8300	Analog	5.4	4/3"	FF	Mono	2.9	8	64.4	*PEAK QE: 56%	CDIP-32
KAI-01050	Analog	5.5	1/2"	IT	Bayer Color, Mono	120	1	64	*PEAK QE: 44%	CLCC-64 CPGA-68
KAI-01150	Analog	5.5	1/2"	IT	Bayer Color, Mono, Sparse CFA	147	1	64	*PEAK QE: 44%	CLCC-64 CPGA-68
KAI-02050	Analog	5.5	2/3"	IT	Bayer Color, Mono	64	2	64	*PEAK QE: 44%	CLCC-64 CPGA-68
KAI-02150	Analog	5.5	2/3"	IT	Bayer Color, Mono, Sparse CFA	64	2	64	*PEAK QE: 44%	CLCC-64 CPGA-68
KAI-02170	Analog	7.4	1"	IT	Bayer Color, Mono, Sparse CFA	60	2	82	*PEAK QE: 52%	CPGA-68
KAI-0330	Analog	9	1/2"	IT	Bayer Color, Mono	120	VGA	57	*PEAK QE: 36%	CDIP-20
KAI-0340	Analog	7.4	1/3"	IT	Bayer Color, Mono	210	VGA	69	*PEAK QE: 55%	CDIP-22
KAI-0373	Analog	11.6 x 13.6	2/3"	IT	Mono	30	WVGA	60	*PEAK QE: 35%	CDIP-24
KAI-04022	Analog	7.4	4/3"	IT	RGB	16	4	-	*PEAK QE: 50%	CDIP-34
KAI-04050	Analog	5.5	1"	IT	Bayer Color, Mono, Sparse CFA	32	4	64	*PEAK QE: 46%	CPGA-68
KAI-04070	Analog	7.4	4/3"	IT	Bayer Color, Mono, Sparse CFA	32	4	82	*PEAK QE: 52%	CPGA-68

GS= Global Shutter; ERS= Electronic Rolling Shutter; GRR= Global Reset Release (ERS); FF= Full Frame; IT= Interleave

*NOTE: PEAK QE: wave length, CFA, microlens dependent (only Mono max stated, review datasheet for clarification)



Part Number / Series	Output Interface	Pixel Size (µm)	Optical Format	Shutter Type	Color filter	Frame Rate @ Full Resolution (FPS)	Resolution (Mega-pixels)	Dynamic Range (dB)	Responsivity	Package Type / Size (mm)
KAI-08051	Analog	5.5	4/3"	IT	Bayer Color, Mono, Sparse CFA	16	8	66	*PEAK QE: 50%	CPGA-68
KAI-08052	Analog	5.5	4/3"	IT	Bayer Color, Mono, Sparse CFA	16	8	66	*PEAK QE: 50%	CPGA-68
KAI-08670	Analog	7.4	APS-H	IT	Bayer Color, Mono, Sparse CFA	12	8	82	*PEAK QE: 48%	CPGA-72
KAI-1003	Analog	12.8	4/3"	IT	Mono	30	1	72	*PEAK QE: 45%	CDIP-28
KAI-1010	Analog	9	1"	IT	Mono	30	1	60	*PEAK QE: 37%	CDIP-24
KAI-1020	Analog	7.4	2/3"	IT	RGB, Mono	50	1	58	*PEAK QE: 44%	CLCC-64; CPGA-68
KAI-11002	Analog	9	35 mm	IT	RGB, Mono	5	11	66	*PEAK QE: 50%	CDIP-40
KAI-16000	Analog	7.4	35 mm	IT	RGB, Mono	3	16	65	*PEAK QE: 45%	CPGA-40
KAI-16050	Analog	5.5	APS-H	IT	Bayer Color, Mono, Sparse CFA	8	16	64	*PEAK QE: 43%	CPGA-72
KAI-16070	Analog	7.4	35 mm	IT	Bayer Color, Mono, Sparse CFA	8	16	82	*PEAK QE: 48%	CPGA-72
KAI-2020	Analog	7.4	1"	IT	RGB, Mono	30	2	68	*PEAK QE: 55%	CDIP-32
KAI-29050	Analog	5.5	35 mm	IT	Bayer Color, Mono, Sparse CFA	4	29	64	*PEAK QE: 43%	CPGA-72
KAI-29052	Analog	5.5	35 mm	IT	Bayer Color, Mono, Sparse CFA	4	29	64	*PEAK QE: 43%	CPGA-72
KAI-47051	Analog	5.5	56.7 mm	IT	Bayer Color, Mono, Sparse CFA	7	47	—	*PEAK QE: 43%	CPGA-201
KLI-2104	Analog	14	Linear	Linear	RGB	20 MHz (linear)	Linear	80	16 V/uJ/cm ²	CDIP-32
KLI-2113	Analog	14	Linear	Linear	RGB, Mono	20 MHz (linear)	Linear	76	66 V/uJ/cm ²	CDIP-28
KLI-4104	Analog	10	Linear	Linear	RGB, Mono	30 MHz (linear)	Linear	60	33 V/uJ/cm ²	CDIP-46
KLI-8023	Analog	9	Linear	Linear	RGB, Mono	6 MHz (linear)	Linear	90	33 V/uJ/cm ²	CDIP-40

GS= Global Shutter; ERS= Electronic Rolling Shutter; GRR= Global Reset Release (ERS); FF= Full Frame; IT= Interleave

*NOTE: PEAK QE: wave length, CFA, microlens dependent (only Mono max stated, review datasheet for clarification)

IMAGE / Image Sensor Module



Part Number / Series	Output Interface	Optical Format	Shutter Type	Color filter	Frame Rate @ Full Resolution (FPS)	Resolution (Pixels)	SNR Max (dB)	Dynamic range (dB)	Responsivity	Package Type / Size (mm)
NanEye Module	LVDS	3 x 3 µm ²	1/15"	Rolling shutter	No	250 x 250	41	58	11.5 DN/nJ/cm ² @ max gain	Chip + Lens + Cable
NanEye-Stereo Module	LVDS	3 x 3 µm ²	1/15"	Rolling shutter	No	250 x 250	41	58	11.5 DN/nJ/cm ² @ max gain	2x (Chip + Lens + Cable)



Part Number / Series	Output Interface	Thermal Range (K)	FOV (degree)	Spectral Range (um)	Number of Pixels	Frame Rate (Hz)	Supply Voltage (V)	Current Consumption (mA)	Package Type / Size (mm)
500-0643-00 (Lepton 1.5)	Video over SPI	263 to 413	50° HFOV	8 to 14	80 x 60	9	2.8, 1.2, 2.5 to 3.1 IO	48 mA typical	8.47 x 9.67 x 5.62
500-0690-00 (Lepton 1.6)	Video over SPI	263 to 413	25° HFOV	8 to 14	80 x 60	9	2.8, 1.2, 2.5 to 3.1 IO	48 mA typical	8.47 x 9.69 x 8.84
500-0659-01 (Lepton 2.0)	Video over SPI	263 to 413	50° HFOV	8 to 14	80 x 60	9	2.8, 1.2, 2.5 to 3.1 IO	48 mA typical, shutter event (209 mA typical) at 3.1 VDC	10.78 x 11.70 x 6.68
500-0763-01 (Lepton 2.5)	Video over SPI	263 to 723	50° HFOV	8 to 14	80 x 60	9	2.8, 1.2, 2.5 to 3.1 IO	48 mA typical, shutter event 333 mA typical (at 3.1 V _{DC})	11.50 x 12.70 x 6.835
500-0726-01 (Lepton 3.0)	Video over SPI	263 to 413	57° HFOV	8 to 14	160 x 120	9	2.8, 1.2, 2.5 to 3.1 IO	48 mA typical, shutter event 333 mA typical (at 3.1 V _{DC})	11.50 x 12.70 x 6.835
500-0771-01 (Lepton 3.5)	Video over SPI	263 to 673	57° HFOV	8 to 14	160 x 120	9	2., 1.2, 2.5 to 3.1 IO	48 mA typical, shutter event 333 mA typical (at 3.1 V _{DC})	11.50 x 12.70 x 6.835

THERMAL INNOVATION COMES IN SMALL PACKAGES



Actual Size

The versatile, low-cost FLIR Lepton® micro thermal camera is ideal for products minimizing size, weight, power and cost without sacrificing performance. Consumer and industrial mobile platforms, drones, IoT and augmented reality devices, smart city and smart controls, all can be enhanced with Lepton – available with or without absolute temperature output.

Learn more at www.flir.com/lepton



Part Number / Series	Output Interface	Thermal Range (K)	FOV (degree)	Spectral Range (um)	Number of Pixels	Frame Rate (Hz)	Supply Voltage (V)	Current Consumption (mA)	Package Type / Size (mm)
MLX90621ESF-BAA-000	I ² C	233 to 573	120 x 25	7 to 13	16 x 4 (64)	0.5 to 64	2.5 to 3.3	9	TO-39 / 5.51(h) x 9.3(d)
MLX90621ESF-BAB-000	I ² C	233 to 573	60 x 15	7 to 13	16 x 4 (64)	0.5 to 64	2.5 to 3.4	9	TO-39 / 11.15(h) x 9.3(d)
MLX90621ESF-BAD-000	I ² C	233 to 573	40 x 10	7 to 13	16 x 4 (64)	0.5 to 64	2.5 to 3.5	9	TO-39 / 14.15(h) x 9.3(d)
MLX90640ESF-BAA-000	I ² C	233 to 573	110 x 75	7 to 13	32 x 24 (768)	0.5 to 64	2.9 to 3.6	15	TO-39 / 5.7(h) x 9.3(d)
MLX90640ESF-BAB-000	I ² C	233 to 573	55 x 40	7 to 13	32 x 24 (768)	0.5 to 64	2.9 to 3.6	15	TO-39 / 11.25(h) x 9.3(d)
MLX90641ESF-BCA-000	I ² C	233 to 573	110 x 75	7 to 13	16 x 12 (192)	0.5 to 64	3 to 3.6	12	TO-39 / 5.7(h) x 9.3(d)
MLX90641ESF-BCB-000	I ² C	233 to 573	55 x 40	7 to 13	16 x 12 (192)	0.5 to 64	3 to 3.6	12	TO-39 / 11.25(h) x 9.3(d)
MLX90641KSF-BCA-000*	I ² C	233 to 573	110 x 75	7 to 13	16 x 12 (192)	0.5 to 64	3 to 3.6	12	TO-39 / 5.7(h) x 9.3(d)
MLX90641KSF-BCB-000*	I ² C	233 to 573	55 x 40	7 to 13	16 x 12 (192)	0.5 to 64	3 to 3.6	12	TO-39 / 11.25(h) x 9.3(d)

*Note: * Automotive AEC-Q100

IMAGE / 3D Image Sensor (Time of Flight)

Product	Description	Resolution	Pixel Size (µm)	Frame Rate (fps)	Optical Format (inch)	Output Interface	Temperature (°C)	Sunlight Robustness (klux)	Modulation Frequency (MHz)	Package Type
MLX75023RTF-BAB-000	Automotive ToF Sensor, without cover tape	320 x 240	15 x 15	150	1/3"	Analog	-40 to +105	120	12 to 40	GBGA
MLX75023RTF-BAB-001	Automotive ToF Sensor, with cover tape	320 x 240	15 x 15	150	1/3"	Analog	-40 to +105	120	12 to 40	GBGA
MLX75023STF-BAB-000	ToF Sensor, without cover tap	320 x 240	15 x 15	150	1/3"	Analog	-20 to +85	120	12 to 40	GBGA
MLX75023STF-BAB-001	ToF Sensor, with cover tap	320 x 240	15 x 15	150	1/3"	Analog	-20 to +85	120	12 to 40	GBGA
MLX75024RTF-GAA-000	Automotive ToF Sensor, without cover tape	320 x 240	15 x 15	150	1/3"	Analog	-40 to +105	120	12 to 40	GBGA
MLX75024RTF-GAA-001	Automotive ToF Sensor, with cover tape	320 x 240	15 x 15	150	1/3"	Analog	-40 to +105	120	12 to 40	GBGA
MLX75024STF-GAA-000	ToF Sensor, without cover tap	320 x 240	15 x 15	150	1/3"	Analog	-20 to +85	120	12 to 40	GBGA
MLX75024STF-GAA-001	ToF Sensor, with cover tap	320 x 240	15 x 15	150	1/3"	Analog	-20 to +85	120	12 to 40	GBGA
MLX75123RLA-BAG-000-RE	Automotive ToF Companion Chip	320 x 240	—	150	1/3"	12-bit Parallel with I ² C for control	-40 to +105	120	12 to 40	AGFN
MLX75123SLA-BAG-000-RE	ToF Companion Chip	320 x 240	—	150	1/3"	12-bit Parallel with I ² C for control	-20 to +85	120	12 to 40	AGFN

THERMAL INNOVATION COMES IN SMALL PACKAGES



Actual Size

The versatile, low-cost FLIR Lepton® micro thermal camera is ideal for products minimizing size, weight, power and cost without sacrificing performance. Consumer and industrial mobile platforms, drones, IoT and augmented reality devices, smart city and smart controls, all can be enhanced with Lepton – available with or without absolute temperature output.

Learn more at www.flir.com/lepton



Murata Sensor Solutions

offers a wide selection of MEMS, ceramic and magnetoresistive options



Murata pursues sensing functions, making full use of MEMS, processing technology and magnetoresistive elements, including ceramic material technology, in order to develop highly efficient and highly reliable devices, modules and systems.

Murata Sensor products include MEMS sensors (accelerometers, inclinometers, gyro), IR, ultrasonic, thermistors (PTC & NTC), shock, AMR and rotary position to name a few.

A vast lineup of sensors respond to the various needs of automobile, industrial, wearable, IoT, medical care and health care applications.

So whether you need temperature/current sensing, detection, pressure, distance or angle measuring – **Murata has innovative sensing solutions to enable your next innovation.**



muRata

INNOVATOR IN ELECTRONICS



INERTIAL COMBO

Digital Compass	51
Inertial Measurement Unit (IMU)	52
9-DoF / 9-Axis Combo Sensor	53
Sensor HUB	53



BOSCH
Invented for life



Kionix®

muRata
INNOVATOR IN ELECTRONICS



life.augmented



Part Number	Sensing Axis	Sensitivity Range (g)	Wake Up Resolution	Output Type	Supply Voltage (V)	Current Consumption Typ (mA)	Current Consumption (Power-Down Mode) Typ (µA)	Operating Temperature (°C)	Package Type / Size (mm)
KMX62-1031	6 axis (3 axis Accel + 3 axis Mag)	Accel: $\pm 2, \pm 4, \pm 8, \pm 16$ Mag: $\pm 1,200\mu\text{T}$	Accel: 62mg Mag: 9.3uT	Digital I ² C (2 Interrupts) Accel: up to 1600kHz** Mag: up to 1600Hz**	1.7 to 3.6	0.0016 - 0.386	1.6	-40 to +85	LGA 3 x 3 x 0.9
KMX63-1055	6 axis (3 axis Accel + 3 axis Mag)	Accel: $\pm 8, \pm 16, \pm 32, \pm 64$ Mag: $\pm 1,200\mu\text{T}$	Accel: 250mg Mag: 9.3uT	Digital I ² C (2 Interrupts) Accel: up to 1600Hz** Mag: up to 1600Hz**	1.7 to 3.6	0.0016 - 0.386	1.6	-40 to +85	LGA/ 3 x 3 x 0.9

*1 Gauss = 100 μT

**Optional Higher ODR, Accel up to 25,600Hz, Mag up to 12,800Hz



Part Number	Sensing Axis	Sensitivity Range (g)	Magnetic Field Range	Output Type	Supply Voltage (V)	Current Consumption Typ (mA)	Current Consumption (Power-Down Mode) Typ (µA)	Operating Temperature (°C)	Package Type / Size (mm)
FX0S8700CQ	X, Y, Z	$\pm 2, \pm 4, \pm 8$	1200 μT	I ² C, SPI	1.95 to 3.6	0.5	2	-40 to +85	QFN-16 3 x 3 x 1.2



Part Number	Sensing Axis	Sensitivity Range (g)	Magnetic Field Range	Output Type	Supply Voltage (V)	Current Consumption Typ (mA)	Current Consumption (Power-Down Mode) Typ (µA)	Operating Temperature (°C)	Package Type / Size (mm)
LSM303AHTR	X, Y, Z	$\pm 2 \pm 4 \pm 8 \pm 16$	± 50 Gauss (typ)	Digital	1.71	1.98	0.0362	-40 to +85	LGA-12 2X2X1 (max)
LSM303AGRTR	X, Y, Z	$\pm 2 \pm 4 \pm 8 \pm 16$	± 50 Gauss (typ)	Digital	1.71	3.6	0.0212	-40 to +85	LGA-12 2X2X1 (max)
ISM303DACTR	X, Y, Z	$\pm 2 \pm 4 \pm 8 \pm 16$	± 50 Gauss (typ)	Digital	1.71	1.98	0.0362	-40 to +85	LGA-12 2X2X1 (max)

INERTIAL COMBO / Inertial Measurement Unit (IMU)



BOSCH

Invented for life

Part Number	Output Interface	Sensing Range	Sensing Axis	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
BMI055	I ² C, SPI, 4x digital interrupts	(A): ±2 g, ±4 g, ±8 g, ±16 g (G): ±125°/s, ±250°/s, ±500°/s, ±1000°/s, ±2000°/s	6-axis	V _{DD} 2.4 to 3.6 V _{DDIO} 1.2 to 3.6	Full operation: 5.15 mA Suspend mode: 6 µA	-40 to +85	3.0 x 4.5 x 0.95
BMI085	I ² C, SPI, 4x digital interrupts	(A): ±2 g, ±4 g, ±8 g, ±16 g (G): ±125°/s, ±250°/s, ±500°/s, ±1000°/s, ±2000°/s	6-axis	V _{DD} 2.4 to 3.6 V _{DDIO} 1.2 to 3.6	5.15	-40 to +85	3.0 x 4.5 x 0.95
BMI088	I ² C, SPI, 4x digital interrupts	(A): ±3 g, ±6 g, ±12 g, ±24 g (G): ±125°/s, ±250°/s, ±500°/s, ±1000°/s, ±2000°/s	6-axis	V _{DD} 2.4 to 3.6 V _{DDIO} 1.2 to 3.6	5.15	-40 to +85	3.0 x 4.5 x 0.95
BMI160*	I ² C, SPI, 4x digital interrupts	(A): ±2 g, ±4 g, ±8 g, ±16 g (G): ±125°/s, ±250°/s, ±500°/s, ±1000°/s, ±2000°/s	6-axis	V _{DD} 1.71 to 3.6 V _{DDIO} 1.2 to 3.6	Full operation: 950 µA Suspend mode: 3 µA	-40 to +85	2.5 x 3.0 x 0.8
BMI270 	I ² C, SPI, 2x digital interrupts	(A): ±2 g, ±4 g, ±8 g, ±16 g (G): ±125°/s, ±250°/s, ±500°/s, ±1000°/s, ±2000°/s	6-axis	V _{DD} 1.71 to 3.6 V _{DDIO} 1.2 to 3.6	Full operation: 685 µA Suspend mode: 3.5 µA	-40 to +85	2.5 x 3.0 x 0.8

*Queexo FingerSense Compatible

A= Accelerometer, G= Gyro



Part Number	Output Interface	Sensing Range	Sensing Axis	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
SCC2130-D08	SPI	±6g, ±125dps	XYZ accel, X gyro	3.3	31.5	-40 to +125	5.0 x 8.5 x 4.3
SCC2230-D08	SPI	±6g, ±125dps	XYZ accel, X gyro	3.3	31.5	-40 to +125	5.0 x 8.5 x 4.3
SCC2230-E02	SPI	±6g, ±125dps	XYZ accel, X gyro	3.3	31.5	-40 to +125	5.0 x 8.5 x 4.3



life.augmented

Part Number	Output Interface	Sensing Range	Sensing Axis	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
LSM6DSLTR	I ² C, SPI, I ³ C	125/±245/±500/±1000/±2000 dps ±2/±4/±8/±16 g	X, Y, Z, Yaw, Pitch, Roll	1.7 to 3.6	0.45mA (gyro + accel)	-40 to +85	LGA-16L 2.5 x 3 x 0.86
LSM6DSMTR	I ² C, SPI, I ³ C	125/±245/±500/±1000/±2000 dps ±2/±4/±8/±16 g	X, Y, Z, Yaw, Pitch, Roll	1.7 to 3.6	0.45mA (gyro + accel)	-40 to +85	LGA-16L 2.5 x 3 x 0.86
LSM6DSOTR	I ² C, SPI, I ³ C	125/±250/±500/±1000/±2000 dps ±2/±4/±8/±16 g	X, Y, Z, Yaw, Pitch, Roll	1.7 to 3.6	0.55mA (gyro + accel)	-40 to +85	LGA-16L 2.5 x 3 x 0.86
ASM330LHHTR	I ² C, SPI, I ³ C	125/±250/±500/±1000/±2000/±4000 dps ±2/±4/±8/±16 g	X, Y, Z, Yaw, Pitch, Roll	1.7 to 3.6	0.7mA (gyro + accel)	-40 to +85	LGA-16L 2.5 x 3 x 0.86
ISM330DLCTR	I ² C, SPI, I ³ C	125/±245/±500/±1000/±2000 dps	X, Y, Z, Yaw, Pitch, Roll	1.7 to 3.6	0.5mA (gyro + accel)	-40 to +85	LGA-16L 2.5 x 3 x 0.83

A= Accelerometer; G= Gyroscope



BOSCH
Invented for life

Part Number	Output Interface	Linear Acceleration Full Scale (g)	Angular Rate Full Scale (dps)	Magnetic Full Scale Range (gauss)	Resolution	Supply Voltage (V)	Supply Current (Acc+Mag+Gyro) (mA)	Operating Temperature (°C)	Package Type / Size (mm)
BMX055	I ² C, SPI	(A): ± 2, ± 4, ± 8, ± 16	(G): ± 125°/s, ± 250°/s, ± 500°/s, ± 1000°/s, ± 2000°/s	±1300 μT (x, y axis) ±2500 μT (z axis)	(A): 0.98 mg (G): 0.004 °/s (M): 0.3 μT	V _{DD} 2.4 to 3.6 V _{DDIO} 2.4 to 3.6	Gyro @ full operation; 5 mA; Acc @ full operation; 130 μA; Acc; @ wake-up mode; < 1 μA; Magnet sensor @ 10Hz ODR: 0.5	-40 to +85	3.0 × 4.5 × 0.95
BMX160	I ² C, SPI	(A): ± 2, ± 4, ± 8, ± 16	(G): ± 125°/s, ± 250°/s, ± 500°/s, ± 1000°/s, ± 2000°/s	±1300 μT (x, y axis) ±2500 μT (z axis)	(A): 0.061mg; (G): 0.004°/s (M): 0.3 μT	V _{DD} 1.71 to 3.6 V _{DDIO} 1.2 to 3.6	Gyro @ full operation; 850 μA; Gyro + Acc + Geomag: 1585 μA; Geomag @ full operation; 660 μA; Acc @ full operation; 180 μA Suspend mode; 5 μA; Significant motion; 30 μA; Step detector: 30 μA	-40 to +85	2.5 × 3.0 × 0.95

A= Accelerometer, G= Gyro

INERTIAL COMBO / Sensor Hub



BOSCH
Invented for life

Part Number	Integrated Processor	Software Library	Software	Output Interface	Sensing Range	Bandwidth Typ. (Hz)	Current Consumption (mA Typ. @100 Hz ODR)	Supply Voltage (V)	Package Type / Size (mm)
BHI160	32 bit floating-point ARC EM4 MCU running @ 10 MHz 96 kByte ROM, 48 kByte RAM	BSX 3.0 fusion Activity recognition, Gesture recognition Step detector, Step counter	—	I ² C up to 3.4 MBit/s 3 × GPIO, 1 × Host-INT	(A): ±2 g, ±4 g, ±8 g, ±16 g (G): ±125°/s, ±250°/s, ±500°/s, ±1000°/s, ±2000°/s	BSX3 (Fusion) output data rate: 200, 100, 50, 25, 12.5	Full 6DoF PDR: 1.3 mA; full 6DoF Fusion @ 100 Hz ODR: 1.2 mA; full 9DoF Fusion @ 100 Hz ODR: 1.3 mA; significant motion: 128 μA; step detector: 131 μA suspend mode: 11 μA	V _{DD} 1.71 to 3.6 V _{DDIO} 1.2 to 3.6	3.0 x 3.0 x 0.95
BHI260 	32 bit floating-point ARC EM4 CPU with (up to 3.6 CoreMark/MHz) 256 kByte SRAM, 144 kByte ROM	BSX 4.0 fusion Activity recognition, Gesture recognition Step detector, Step counter Custom Programmable	—	Host interface configurable as SPI or I ² C; 3 master interfaces (selectable out of 2 × SPI master and 2 × I ² C master); - Up to 25 GPIOs	(A): ±2 g, ±4 g, ±8 g, ±16 g (G): ±125°/s, ±250°/s, ±500°/s, ±1000°/s, ±2000°/s	BSX4 (Fusion) output data rate: 800, 400, 200, 100, 50, 25, 12.5, 6.25, 3.125, 1.5625	Fuser2 (running CoreMark) -long run mode (20 MHz): 950 μA; turbo mode (50 MHz): 2.8 mA; Sensor Fusion (Hub+IMU) operation (calculating Game Rotation Vector) 800 Hz ODR: 1.2 mA; 100 Hz ODR: 1.0 mA Standby current: 8 μA	1.8	4.1 x 3.6 x 0.83

A= Accelerometer, G= Gyro

THERMAL INNOVATION COMES IN SMALL PACKAGES

Learn more at www.flir.com/lepton




BOSCH

Invented for life

Part Number	Integrated Processor	Software Library	Software	Output Interface	Sensing Range	Bandwidth Typ. (Hz)	Current Consumption (mA Typ. @100 Hz ODR)	Supply Voltage (V)	Package Type / Size (mm)
BN0055	32 bit cortex M0+ microcontroller	BSX 3.0 full fusion	—	I ² C, UART, HID-I ² C	±2 g, ±4 g, ±8 g, ±16 g	BSX3 (Fusion) output data rate: 1000, 500, 250, 125, 63, 31, 16, 8	Suspend mode: 40 µA 9DOF @ 100 Output data rate: 12.3	V _{DD} 2.4 to 3.6 V _{DDIO} 1.7 to 3.6	3.8 × 5.2 × 1.13
BMF055	33 bit cortex M0+ microcontroller, 256kB Flash memory and 32kB SRAM memory	BSX fusion lite as additional lib. Custom Programmable.	—	I ² C, UART, HID-I ² C	±2 g, ±4 g, ±8 g, ±16 g	Depends on the custom specific sensor fusion	Depends on the custom specific sensor fusion	V _{DD} 2.4 to 3.6 V _{DDIO} 1.7 to 3.6	3.8 × 5.2 × 1.13
BHA250	32 bit floating-point ARC EM4 MCU running @ 10 MHz 1.6 DMIPS/MHz performance, 3.41 CoreMarks/MHz 96 kByte ROM, 48 kByte RAM shared RAM for FIFO, features & extensions optimized for ultra-low power sensor data fusion	BSX 3.0 fusion Activity recognition, Gesture recognition Step detector, Step counter	—	I ² C up to 3.4 MBit/s 3 × GPIO, 1 × Host-INT	±2 g, ±4 g, ±8 g, ±16 g	BSX3 (Fusion) output data rate: 200, 100, 50, 25, 12.	eCompass @ 100 ODR: 630 µA Hub+Acc @ 100 ODR: 430 µA Activity recognition: 200 µA Significant motion: 100 µA Step detector: 100 µA Suspend mode: 11 µA	V _{DD} 1.71 to 3.6 V _{DDIO} 1.2 to 3.6	2.2 x 2.2 x 0.95
BHA260 	32 bit floating-point ARC EM4 CPU with (up to 3.6 CoreMark/MHz) 256 kByte SRAM, 144 kByte ROM	BSX 4.0 fusion Activity recognition, Gesture recognition Step detector, Step counter Custom Programmable	—	- Host interface configurable as SPI or I ² C - 2 master interfaces (1 selectable SPI/I ² C and 1 I ² C) - Up to 12 GPIOs	±2 g, ±4 g, ±8 g, ±16 g	BSX4 (Fusion) output data rate: 800, 400, 200, 100, 50, 25, 12.5, 6.25, 3.125, 1.5625	Fuser2 (running CoreMark) - long run mode (20 MHz): 950 µA -turbo mode (50 MHz): 2.8 mA Sensor algorithm operation (incl. Sensor) -significant motion: 32 µA -step counter: 46 µA - activity recognition: 77 µA Standby current: 8 µA	1.8	2.7 x 2.6 x 0.8



BMX160 Absolute Orientation Sensor


BOSCH
Invented for life



BOSCH
Invented for life

Bosch MEMS sensors for hearable applications

BHI260 and BHA260

Smart Sensors

The combination of state-of-the-art MEMS sensors with an ultra-low power, high performance sensor coprocessor significantly extends battery life in mobile devices, such as hearables.



LIGHT - COLOR

Ambient Light Sensor - Analog	57
Ambient Light Sensor - Digital	58
Color Sensor	60
Photo Detector	61
UV Sensor	61
Spectral Sensor	61



ON Semiconductor®





Part Number	Sensing Range (Lux)	Output Type	Output Range (μA)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
LA0151C	100k	Analog	0 to 80	2.2	0.08	-30 to +85	ODCSP-4
LV0111CF	100k	Analog	0 to 30	2.3	0.021	-30 to +85	ODCSP-4J



Part Number	Sensing Range (Lux)	Output Type	Output Range (μA)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
BH1603FVC	0 to 100,000	Current (Sourced)	0 to 60	2.4 to 5.5	0.074	-40 to +85	WSOF6 (6-Pin) 3.0 x 1.6 x 0.75
BH1620FVC	0 to 100,000	Current (Sourced)	0 to 57	2.4 to 5.5	0.071	-40 to +85	WSOF5 (5-Pin) 1.6 x 1.6 x 0.6
BH1680FVC	0 to 50,000	Current (Sourced)	0 to 61	2.4 to 5.5	0.075	-40 to +85	WSOF5 (5-Pin) 1.6 x 1.6 x 0.6
BH1682FVC	1 to 55,000	Logarithmic Current (Source)	0 to 20	2.3 to 5.5	0.075	-40 to +85	WSOF5 (5-pin) 1.6 x 1.6 x 0.6



Part Number	Sensing Range (Lux)	Output Type	Output Range (μA)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
TEPT4400	0.01 to 167000	Analog	15 to 70	0.5 to 5	—	-40 to +85	T1, Ø 3mm
TEPT5600	0.01 to 167000	Analog	25 to 226	0.5 to 5	—	-40 to +85	T1¾, Ø 5mm
TEPT5700	0.01 to 167000	Analog	5.2 to 24	0.5 to 5	—	-40 to +85	T1¾, Ø 5mm, flat
TEMT6000X01	0.01 to 167000	Analog	3.5 to 16	0.5 to 5	—	-40 to +100	2 x 4 x 1H
TEMT6200FX01	0.01 to 167000	Analog	7.5 to 39	0.5 to 5	—	-40 to +100	1.2 x 2 x 0.85H
TEMD6010FX01	0.01 to 167000	Analog	0.03 to 0.09	0.5 to 5	—	-40 to +100	2 x 4 x 1H
TEMD5510FX01	0.01 to 167000	Analog	0.8 to 1.4	0.5 to 5	—	-40 to +100	4.2 x 5 x 1H



Part Number	Sensing Range (Lux)	Output Interface	Peak Wave Length (nm)	Power-Down Current (mA)	Supply Current (mA)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
TSL25721	10,000	I ² C	700	0.002	0.200	2.4 to 3.6	-30 to +70	DFN-6 2 x 2 x 0.65
TSL25723	10000	I ² C	700	0.002	0.200	2.7 to 3.6	-30 to +70	DFN-6 2 x 2 x 0.65
TSL25911	88,000	I ² C	650	0.002	0.275	2.7 to 3.6	-30 to +70	DFN-6 2 x 2.4 x 0.65
TSL25913	88,000	I ² C	650	0.002	0.275	2.7 to 3.6	-30 to +70	DFN-6 2 x 2.4 x 0.65
TSL25403	20,000	I ² C	550	0.001	0.090	1.7 to 2.0	-30 to +85	QFN-10 2 x 2 x 0.5
TSL25413	60,000	I ² C	550	0.001	0.090	1.7 to 2.0	-30 to +85	QFN-10 2 x 2 x 0.5, Dark

ON Semiconductor®



Part Number	Sensing Range (Lux)	Output Interface	Peak Wave Length (nm)	Power-Down Current (mA)	Supply Current (mA)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
LV0104CS	65k	I ² C	550	0.001	0.07	2.3	-30 to +85	ODCSP-4



Part Number	Sensing Range (Lux)	Output Interface	Peak Wave Length (nm)	Power-Down Current (mA)	Supply Current (mA)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
BH1726NUC	0 to 30,000	I ² C	530	0.0008	0.075	2.3 to 3.6	-40 to +85	WS0N008X2120 (8-pin) 2.1 x 2.0 x 0.6



Part Number	Sensing Range (Lux)	Output Interface	Peak Wave Length (nm)	Power-Down Current (mA)	Supply Current (mA)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
VEML6030	0 to 120000	I ² C Bus	530	0.0005	0.045	2.5 to 3.6	-25 to +85	2.0 x 2.0 x 0.87H Top View
VEML7700-TR	0 to 120000	I ² C Bus	530	0.0005	0.045	2.5 to 3.6	-25 to +85	6.8 x 2.35 x 3.0 Side View

VISHAY

**SENSING
— THE —
POSSIBILITIES**

Vishay's Thermistor and RTD Temperature Sensors deliver **fast, accurate, and stable measurement** for emerging applications of the future.

A WORLD OF SOLUTIONS™

www.vishay.com

© 2019 VISHAY INTERTECHNOLOGY, INC. ALL RIGHTS RESERVED.



Part Number	Output Channel	Output Interface	Output Range	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
TCS34003	RGB + Clear +IR	I ² C	—	2.7 to 3.6	0.235	-40 to +70	DFN-6 2 x 2.4 x 0.65
TCS34303	XYZ + IR	I ² C	—	1.7 to 2.0	0.100	-30 to +85	DFN-8 1.75 x 2.41 x 1
TCS34721	RGB + Clear	I ² C	—	2.7 to 3.6	0.235	-30 to +70	DFN-6 2 x 2.4 x 0.65
TCS34723	RGB + Clear	I ² C	—	2.7 to 3.3	0.235	-30 to +70	DFN-6 2 x 2.4 x 0.65



Part Number	Output Channel	Output Interface	Output Range	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
BH1749NUC	R, G, B, IR	I ² C	0lx to 80,000lx, ± 5% CCT Accuracy	2.3 to 3.6	0.190	-40 to +85	WSON008x2120 (8-Pin) 2.1 x 2.0 x 0.6



Part Number	Output Channel	Output Interface	Output Range	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
VEML6040A30G	R, B, G, W	I ² C Bus	.0056 to 11796 (lx)	2.5 to 3.6	0.2	-40 to +85	2.0 x 1.25 x 1.0H



Murata Sensor Solutions

offers a wide selection of MEMS, ceramic and magnetoresistive options



muRata
INNOVATOR IN ELECTRONICS



Part Number	Photo Current (µA)	Dark Current (µA)	Rise Time (ms)	Fall Time (ms)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
VEMD5010X01	48	2	100	430 to 1100	1	-40 to +110	5 x 4 x 0.9 SMT
VEMD5110X01	48	2	100	790 to 1050	1	-40 to +110	5 x 4 x 0.9 SMT
VEMD5060X01	26	0.2	30	350 to 1070	0.8	-40 to +110	5 x 4 x 0.9 SMT
VEMD5160X01	26	0.2	30	700 to 1050	0.8	-40 to +110	5 x 4 x 0.9 SMT
VEMD5080X01	45	0.2	70	350 to 1100	0.9	-40 to +110	5 x 4 x 0.9 SMT
VEMD5510C	0.6	0.2	70	440 to 700	0.9	-40 to +110	5 x 4 x 0.9 SMT
VEMD2023SLX01	10	1	100	750 to 1050	1	-40 to +100	2.3 x 2.5 x 2.3 Side view, SMT
VEMD2523SLX01	10	1	100	350 to 1120	1	-40 to +100	2.3 x 2.5 x 2.3 Side view, SMT
VEMD8080	28	0.2	70	350 to 1100	1.2	-40 to +85	4.8 x 2.5 x 0.48 SMT

LIGHT - COLOR / UV Sensor



Part Number	Output Interface	Functional Description	Supply Voltage (V)	Maximum-Sensitivity Wave Length	Sensitivity Region	Supply Current	Operating Temperature (°C)	Package Type / Size (mm)
VEML6070	I²C Bus	UV-A sensor	2.7 to 5.5	100 µA	355 nm	280 nm to 400 nm	-40 to +85	2.35 x 1.8 x 1.0


LIGHT - COLOR / Spectral Sensor



Part Number	Output Channel	Output Interface	Output Range	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
AS7341	8 channel VIS + NIR + Clear + Flicker"	I²C	16-bits / channel	1.8	5	-30 to +70	3.1 x 2 x 1 OLGA-8
AS7261	XYZ+NIR	I²C or UART	16-bits / channel	2.7 to 3.6	5	-30 to +70	4.5 x 4.7 LGA
AS7262	6 channel VIS	I²C or UART	16-bits / channel	2.7 to 3.6	5	-30 to +70	4.5 x 4.7 LGA
AS7263	6 channel NIR	I²C or UART	16-bits / channel	2.7 to 3.6	5	-30 to +70	4.5 x 4.7 LGA
AS7264N	XYZ+2blue+NIR	I²C	16-bits / channel	2.7 to 3.6	5	-30 to +70	4.5 x 4.7 LGA
AS7265x	18 channel VIS+NIR	I²C or UART	16-bits / channel	2.7 to 3.6	5	-30 to +70	4.5 x 4.7 LGA

11-Channel Spectral Color Sensor

www.ams.com



AS7341 – 11-Channel Spectral Color Sensor

- Color matching and skin tone measurement
- Enhanced Artificial Intelligence: Search & shop by color (eCommerce boost)
- Optional: Flicker immune camera operation and image optimization (AWB automatic white balancing)
- Mobile phone compatible package

PRELIMINARY INFORMATION

Sensing
is life.

General Description

ams, X-Rite and PANTONE® presents a joint solution to bring accurate color matching directly to smartphones in order to improve retail and ecommerce applications, artificial intelligence and other tools help consumers find the right products.

Research shows that consumers lack confidence in purchasing color-critical items online. This uncertainty is typically due to past experiences which did not meet expectations and a difficulty in communicating color from home to store. Consumers wrongly expect to be able to simply take a photo of the inspiration color with their smartphones and match it to a desired item. However, the wide variety of tones and colors available in home décor, apparel and cosmetics is difficult to accurately reproduce on mobile device displays. Cameras are not precise enough to accurately compare the color between an online product offering and how it will appear in the

consumer's intended physical environment. This makes online color-critical purchase decisions unreliable and limits consumer confidence.

The joint ams and X-Rite solution is the world's first spectral color measurement solution utilizing Pantone Color Standards to be embedded in a mobile device. The miniaturized module is intended for integration in the backside of a smartphone. The module contains an advanced 11-channel spectral sensor and optical components that enable users to measure color of objects in a non-contact manner. The solution will connect to Pantone's world-leading color reference systems using cloud technology. Consumers, brands and retailers will now be able to identify and share product colors, making it easier to search product catalogs and select color-critical items with confidence.

Features

- 8 optical channels distributed over the visible range
- 3 extra channels: Clear, Flicker and NIR channel
- 6 parallel ADCs for signal processing
- Ultra-low-profile package 3.1 x 2 x 1 mm


Benefits

- Spectral information enables highly accurate object color measurements
- Detection & rejection environmental influences such as light sources
- Optimized channel count and signal processing for fast measurements
- Mobile phone compatible package


Applications

- Color matching and skin tone measurement
- Enhanced Artificial Intelligence: Search & shop by color (eCommerce boost)
- Optional: Flicker immune camera operation and image optimization (AWB automatic white balancing)

Spectral Responsivity



Block Diagram



PRODUCT IN DEVELOPMENT

Kevin Jensen
Senior Marketing Manager
ams Sensor Germany GmbH
Göschwitzer Straße 32, 07745 Jena, Germany
Phone +49 3641 2809-9911
kevin.jensen@ams.com

www.ams.com
products@ams.com
© 02/2018 by ams
Subject to change without notice

Headquarters
ams AG
Tobelbader Strasse 30, 8141 Premstaetten, Austria
Phone +43 3136 500-0



MAGNETIC – HALL

Current Sensor	65
Hall Switch – Latch.....	66
Linear Hall IC.....	77
Magnetometer.....	78
AMR Sensors	79

amUN



BOSCH
Invented for life

DIODES
INCORPORATED

infineon

Melexis

MPS

muRata
INNOVATOR IN ELECTRONICS

ROHM
SEMICONDUCTOR

ST
life.augmented



Part Number	Output Interface	Sensing Range (A)	Sensing Accuracy (%)	Bandwidth (kHz)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
TLI4970D025T4XUMA1	16-bit digital SPI output	25 primary current range	1.60	18	3.3	12	-40 to +85	TISON-8; 7 x 7
TLI4970D050T4XUMA1	16-bit digital SPI output	50 primary current range	1.60	18	3.3	12	-40 to +85	TISON-8; 7 x 7
TLI4970D025T5XUMA1	16-bit digital SPI output	25 primary current range	3.50	18	3.3	12	-40 to +85	TISON-8; 7 x 7
TLI4970D050T5XUMA1	16-bit digital SPI output	50 primary current range	3.50	18	3.3	12	-40 to +85	TISON-8; 7 x 7



Part Number	Output Interface	Sensing Range (A)	Sensing Accuracy (%)	Bandwidth (kHz)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
MLX91205KDC-AAL-003	Analog - Diff.	0 to ± 100	1	100	4.5 to 5.5	11	-40 to +125	SOIC8
MLX91205KDC-AAH-003	Analog - Diff.	0 to ± 500	1	100	4.5 to 5.5	11	-40 to +125	SOIC8
MLX91206LDC-CAL-001	Analog	0 to ± 100	1	70	4.5 to 5.5	8	-40 to +150	SOIC8
MLX91206LDC-CAL-002	Analog	0 to ± 100	1	70	4.5 to 5.5	8	-40 to +150	SOIC8
MLX91206LDC-CAL-003	Analog	0 to ± 100	1	70	4.5 to 5.5	8	-40 to +150	SOIC8
MLX91206LDC-CAH-001	Analog	0 to ± 500	1	70	4.5 to 5.5	8	-40 to +150	SOIC8
MLX91206LDC-CAH-002	Analog	0 to ± 500	1	70	4.5 to 5.5	8	-40 to +150	SOIC8
MLX91206LDC-CAH-003	Analog	0 to ± 500	1	70	4.5 to 5.5	8	-40 to +150	SOIC8
MLX91206LDC-CAH-004	Analog	0 to ± 500	1	70	4.5 to 5.5	8	-40 to +150	SOIC8
MLX91206LDC-CAH-021	Analog	0 to ± 500	1	70	4.5 to 5.5	8	-40 to +150	SOIC8
MLX91206LDC-CAH-104	PWM	0 to ± 500	1	70	4.5 to 5.5	8	-40 to +150	SOIC8
MLX91208LDC-CAL-000	Analog	0 to ± 100	1	250	4.5 to 5.5	12	-40 to +150	SOIC8
MLX91208LDC-CAH-000	Analog	0 to ± 500	1	250	4.5 to 5.5	12	-40 to +150	SOIC8
MLX91208LDC-CAV-000	Analog	0 to ± 2000	1	250	4.5 to 5.5	12	-40 to +150	SOIC8
MLX91208LDC-CAV-001	Analog	0 to ± 2000	1	250	4.5 to 5.5	12	-40 to +150	SOIC8
MLX91216LDC-ACH-000	Analog	0 to ± 100	1	250	4.5 to 5.5	12.5	-40 to +150	SOIC8
MLX91216LDC-ACV-000	Analog	0 to ± 500	1	250	4.5 to 5.5	12.5	-40 to +150	SOIC8
MLX91216LDC-ACV-001	Analog	0 to ± 2000	1	250	4.5 to 5.5	12.5	-40 to +150	SOIC8
MLX91207LDC-CAA-005	Analog	0 to ± 1000	1	70	4.5 to 5.5	9	-40 to +150	SOIC8
MLX91207LDC-CAA-007	Analog	0 to ± 2000	1	70	4.5 to 5.5	9	-40 to +150	SOIC8
MLX91207LDC-CAA-015	Analog	0 to ± 2000	1	70	4.5 to 5.5	9	-40 to +150	SOIC8
MLX91209LVA-CAA-000	Analog	0 to ± 500	1	250	4.5 to 5.5	12	-40 to +150	SIP4 VA
MLX91209LVA-CAA-001	Analog	0 to ± 500	1	250	4.5 to 5.5	12	-40 to +150	SIP4 VA
MLX91209LVA-CAA-002	Analog	0 to ± 500	1	250	4.5 to 5.5	12	-40 to +150	SIP4 VA
MLX91217LVA-ACA-000	Analog	0 to ± 500	1	250	4.5 to 5.5	12.5	-40 to +150	SIP4 VA
MLX91217LVA-ACA-003	Analog	0 to ± 500	1	250	4.5 to 5.5	12.5	-40 to +150	SIP4 VA
MLX91217LVA-ACA-005	Analog	0 to ± 500	1	250	4.5 to 5.5	12.5	-40 to +150	SIP4 VA
MLX91210KDC-CAS-101	Analog	0 to ± 25	1	100	4.5 to 5.5	12	-40 to +125	SOIC8
MLX91210KDC-CAS-102	Analog	0 to ± 50	1	100	4.5 to 5.5	12	-40 to +125	SOIC8



Part Number	Output Interface	Sensing Range (A)	Sensing Accuracy (%)	Bandwidth (kHz)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
MLX91210KDC-CAS-104	Analog	0 to ±50	1	100	4.5 to 5.5	12	-40 to +125	SOIC8
MLX91210KDC-CAS-105	Analog	0 to ±50	1	100	4.5 to 5.5	12	-40 to +125	SOIC8
MLX91210KDC-CAS-106	Analog	0 to ±50	1	100	4.5 to 5.5	12	-40 to +125	SOIC8
MLX91210KDF-CAS-101	Analog	0 to ±25	1	100	4.5 to 5.5	12	-40 to +125	SOIC16 WB
MLX91210KDF-CAS-102	Analog	0 to ±50	1	100	4.5 to 5.5	12	-40 to +125	SOIC16 WB
MLX91210KDF-CAS-103	Analog	0 to ±50	1	100	4.5 to 5.5	12	-40 to +125	SOIC16 WB
MLX91210KDF-CAS-104	Analog	0 to ±50	1	100	4.5 to 5.5	12	-40 to +125	SOIC16 WB



Part Number	Output Interface	Sensing Range (A)	Sensing Accuracy (%)	Bandwidth (kHz)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
MCS1801	Ratiometric	12.5, 25	5	100	3.3	8	-40 to +150	SOIC-8 (5 × 4)
MCS1802	Ratiometric	12.5, 25	5	100	5	8	-40 to +150	SOIC-8 (5 × 4)

MAGNETIC – HALL / Hall Switch - Latch



Part Number	Type	Operating Point Bop (mT)	Release Point Brp (mT)	Output Current (mA)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
AH3772	Latch	2.5	-2.5	30	3 to 28	-40 to +125	SOT23, SIP-3
AH3774	Latch	4.0	-4.0	30	3 to 28	-40 to +125	SOT23, SC59, SIP-3
AH3775	Latch	7.0	-7.0	30	3 to 28	-40 to +125	SOT23, SC59, SIP-3
AH3776	Latch	11	-11	30	3 to 28	-40 to +125	SOT23, SIP-3
AH3777	Latch	14	-14	30	3 to 28	-40 to +125	SOT23, SIP-3
AH3781	Latch	2.5	-2.5	30	3 to 28	-40 to +125	SOT23, SIP-3
AH3782	Latch	4.0	-4.0	30	3 to 28	-40 to +125	SOT23, SIP-3
AH3762Q	Automotive Latch	2.5	-2.5	30	3 to 28	-40 to +150	SOT23, SC59, SIP-3
AH3763Q	Automotive Latch	3.0	-3.0	30	3 to 28	-40 to +150	SOT23, SC59, SIP-3
AH3764Q	Automotive Latch	4.0	-4.0	30	3 to 28	-40 to +150	SOT23, SC59, SIP-3
AH3765Q	Automotive Latch	7.0	-7.0	30	3 to 28	-40 to +150	SOT23, SC59, SIP-3
AH3766Q	Automotive Latch	11.0	-11.0	30	3 to 28	-40 to +150	SOT23, SIP-3
AH3767Q	Automotive Latch	14	-14	30	3 to 28	-40 to +150	SOT23, SIP-3
AH3768Q	Automotive Latch	17.5	-17.5	30	3 to 28	-40 to +150	SOT23, SIP-3
AH3769Q	Automotive Latch	22	-22	30	3 to 28	-40 to +150	SOT23, SIP-3
AH1389	Dual Unipolar Switch	+2.5 and -2.5	+2.0 and -2.0	2.5	1.6 to 3.6	-40 to +85	X1-DFN14102-4

Hall Effect Sensors with Market-Leading Performance

HIGH PERFORMANCE HALL EFFECT SENSORS SUPPORT CONSUMER, INDUSTRIAL AND AUTOMOTIVE APPLICATIONS

Combining superior Hall Effect technology, extensive analog design expertise, leading package technology and manufacturing capability, Diodes offer outstanding system solutions.

HALL EFFECT SWITCH

Using core architectures based on a stable patented Hall Effect plate design, Diodes provides three comprehensive Hall Effect switch product families:

- Omnipolar switches
- Unipolar switches
- Latched switches

LINEAR HALL SENSORS

Diodes Linear Hall Sensors provide high linearity outputs whose voltage is proportional to the applied magnetic flux density.

They provide simple compact solutions for analog magnetic flux/field sensing/position detection in consumer and industrial applications.

DIODES ADVANTAGE

- Ultra Low Switch-point Drift Over Full Operating Range
- Wide Selection Of Magnetic Operating Points
- Fast Response Time
- Wide Input Voltage Range 3 – 28V
- Full Device Protections Features:
 - Input/Output Clamp, Output Current Limit, Reverse Blocking
- High ESD (HBM) Capability:
 - Industrial: 6kV
 - Automotive Compliant: 8kV
- Extended Temperature Range:
 - Industrial: -40 – 125°C
 - Automotive Compliant: -40 – 150°C



diodes.com

Part Number	Type	Operating Point Bop (mT)	Release Point Brp (mT)	Output Current (mA)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
AH1887	Dual Unipolar Switch	+3.5 and -3.5	+2.0 and -2.0	1	1.65 to 3.3	-40 to +85	SOT553
AH3360	Unipolar Switch	3.0	2.0	3	1.6 to 3.6	-40 to +85	X1-DFN1216-4, DFN2015-6
AH3372	Unipolar Switch	3.0	2.0	30	3 to 28	-40 to +125	SOT23, SC59, SIP-3
AH3373	Unipolar Switch	5.5	3.5	30	3 to 28	-40 to +125	SOT23, SC59, SIP-3
AH3376	Unipolar Switch	10	8.5	30	3 to 28	-40 to +125	SOT23, SC59, SIP-3
AH3377	Unipolar Switch	11.5	9.0	30	3 to 28	-40 to +125	SOT23, SC59, SIP-3
AH3382	Unipolar Switch	5.5	3.5	30	3 to 28	-40 to +125	SOT23, SC59, SIP-3
AH3362Q	Automotive Unipolar Switch	3.0	2.0	30	3 to 28	-40 to +150	SOT23, SC59, SIP-3
AH3363Q	Automotive Unipolar Switch	5.5	3.5	30	3 to 28	-40 to +150	SOT23, SC59, SIP-3
AH3364Q	Automotive Unipolar Switch	8.0	6.0	30	3 to 28	-40 to +150	SOT23, SIP-3
AH3365Q	Automotive Unipolar Switch	10.0	8.0	30	3 to 28	-40 to +150	SOT23, SIP-3
AH3366Q	Automotive Unipolar Switch	10.0	8.5	30	3 to 28	-40 to +150	SOT23, SC59, SIP-3
AH3367Q	Automotive Unipolar Switch	11.5	9.0	30	3 to 28	-40 to +150	SOT23, SC59, SIP-3
AH3368Q	Automotive Unipolar Switch	15.0	12.5	30	3 to 28	-40 to +150	SOT23, SIP-3
AH3369Q	Automotive Unipolar Switch	17.5	15.0	30	3 to 28	-40 to +150	SOT23, SIP-3
AH3390Q	Automotive Unipolar Switch	21.0	18.5	30	3 to 28	-40 to +150	SOT23, SC59, SIP-3
AH3391Q	Automotive Unipolar Switch	27.5	25.0	30	3 to 28	-40 to +150	SOT23, SIP-3
AH1806	Omnipolar	±3.0	±2.0	2.5	2.5 to 5.5	-40 to +85	SC59, SOT553
AH1807	Omnipolar	±8.0	±6.5	2.5	2.5 to 5.5	-40 to +125	SC59, SOT553, SIP-3
AH1808	Omnipolar	±4.0	±3.0	2.5	2.5 to 5.5	-40 to +85	SC59, SOT553
AH1809	Omnipolar	±13	±11.5	2.5	2.5 to 5.5	-40 to +125	SC59, SOT553, SIP-3
AH1815	Omnipolar	±39.5	±35.5	2.5	2.5 to 5.5	-40 to +125	SC59, SOT553, SIP-3
AH9246	Omnipolar	±1.8	±1.2	2	2.5 to 5.5	-40 to +85	SC59, SIP-3
AH9251	Omnipolar	±6.0	±5.0	2	2.5 to 5.5	-40 to +85	SC59, SIP-3
AH1893	Omnipolar	±3.0	±2.0	3	1.6 to 3.6	-40 to +85	SOT553, X1-DFN1216-4
AH1911	Omnipolar	±6.0	±4.5	1	1.6 to 5.5	-40 to +85	SC59
AH1912	Omnipolar	±3.0	±2.25	1	1.6 to 5.5	-40 to +85	SC59, X1-DFN1216-4
AH1913	Omnipolar	±1.8	±1.1	1	1.6 to 5.5	-40 to +85	SC59, X1-DFN1216-4
AH1921	Omnipolar	±6.0	±4.5	1	1.6 to 5.5	-40 to +85	SC59
AH3572	Omnipolar	±2.0	±1.0	30	3 to 28	-40 to +125	SOT23, SIP-3
AH3574	Omnipolar	±4.0	±2.5	30	3 to 28	-40 to +125	SOT23, SIP-3
AH3582	Omnipolar	±4.0	±2.5	30	3 to 28	-40 to +125	SOT23, SIP-3
AH3562Q	Automotive Omnipolar	±2.0	±1.0	30	3 to 28	-40 to +150	SOT23, SIP-3
AH3563Q	Automotive Omnipolar	±3.0	±2.0	30	3 to 28	-40 to +150	SOT23, SIP-3
AH3564Q	Automotive Omnipolar	±4.0	±2.5	30	3 to 28	-40 to +150	SOT23, SIP-3
AH1894	Omnipolar Switch, Selectable Threshold	±3.0 or ±4.0	±2.0 to ±3.0	3	1.6 to 3.6	-40 to +85	SOT553, X1-DFN1216-4
AH1895	Omnipolar	±6.0	±5.0	3	1.6 to 3.6	-40 to +85	SOT553, X1-DFN1216-4
AH1898	Omnipolar Switch, Selectable Threshold	±3.5 or ±6.0	±2.5 to ±5.0	2.5	1.6 to 3.6	-40 to +85	CSP 0.08 x 0.08
AH1902	Omnipolar	±3.3 or +3.3	±2.3 or +2.3	3	1.6 to 3.6	-40 to +85	X1-DFN1216-4
AH1903	Programmable Omnipolar or Unipolar Switch	±3.3	±2.3	3	1.6 to 3.6	-40 to +85	X1-DFN1216-4



Part Number	Type	Operating Point Bop (mT)	Release Point Brp (mT)	Output Current (mA)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
TLE4913HTSA1	Switch	3.5	2.7	0 to 2	2.4 to 5.5	-40 to +150	SC59
TLE49215UHALA1	Switch	0	0	0 to 50	4.5 to 24	-40 to +170	SSO-4
TLE49462KHTSA1	Switch	2.0	-2.0	0 to 20	2.7 to 24	-40 to +150	SC59
TLE49611MXTMA1	Latch	2.0	-2.0	0 to 25	3 to 32	-40 to +170	SOT23-3
TLE49612MXTSA1	Latch	5.0	-5.0	0 to 25	3 to 32	-40 to +170	SOT23-3
TLE49613MXTMA1	Latch	7.5	-7.5	0 to 25	3 to 32	-40 to +170	SOT23-3
TLE49614MXTSA1	Latch	10.0	-10.0	0 to 25	3 to 32	-40 to +170	SOT23-3
TLE49615MXTMA1	Latch	15.0	-15.0	0 to 25	3 to 32	-40 to +170	SOT23-3
TLE49643KXTSA1	Switch	12.5	9.5	0 to 25	3 to 42	-40 to +170	SC59
TLI4906KHTSA1	Switch	10.0	8.5	0 to 20	2.7 to 18	-40 to +125	SC59
TLI4906LHALA1	Switch	10.0	8.5	0 to 20	2.7 to 18	-40 to +125	SSO-3
TLI49611MXTSA1	Latch	2.0	-2.0	0 to 25	3 to 32	-40 to +125	SOT23-3
TLI49631MXTMA1	Latch	2.0	-2.0	0 to 5	3 to 5.5	-40 to +125	SOT23-3
TL49611TBXALA1	Latch	2.0	-2.0	0 to 25	3 to 26	-40 to +125	T092S
TL49645TBXALA1	Switch	7.5	5.0	0 to 25	3 to 26	-40 to +125	T092S
TLE49631MXTSA1	Latch	2.0	-2.0	0 to 5	3 to 5.5	-40 to +170	SOT23-3
TLE49632MXTSA1	Latch	5.0	-5.0	0 to 5	3 to 5.5	-40 to +170	SOT23-3
TLE49655MXTSA1	Switch	7.5	5.0	0 to 5	3 to 5.5	-40 to +170	SOT23-3

Introducing: A New Line of Current Sensors

Hall Effect Linear Current Sensors for 5 to 50A Applications

MCS1800X Family

Isolated bi-directional Hall effect linear current sensors for AC or DC current sensing. A low resistance conductive path of less than 1mohm minimizes power loss to maximize efficiency.


Up to 50A

1.5% Accuracy

3.3V & 5V versions

- Differential Hall Sensing for immunity to stray fields
- Factory calibrated accuracy from -40°C to 125°C
- <0.8mΩ current sensing resistance
- 200V or 2.4kVRMS isolation voltage versions
- Fast 3.5μs output response time
- 100kHz bandwidth
- Linear output voltage vs. current

For ordering and more information
visit MonolithicPower.com



Part #	VCC (V)	Current Range (A)	Accuracy (%)	Isolation Voltage (V)
Available Soon MCS1800	3.3	$\pm 12.5/25$	5	200
MCS1801	5	$\pm 12.5/25$	5	200
MCS1802	3.3	$\pm 5/10/20/30/40/50$	3	2400
Available Soon MCS1803	5	$\pm 5/10/20/30/40/50$	3	2400
Available Soon MCS1804	3.3	$\pm 5/10/20/30/40/50$	1.5	2400
Available Soon MCS1805	5	$\pm 5/10/20/30/40/50$	1.5	2400





Part Number	Type	Operating Point Bop (mT)	Release Point Brp (mT)	Output Current (mA)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
MLX90224EVA-ABA-000	Dual hall latch	2.5	-2.5	4.5	2.7 to 24	-40 to +85	TSOT
MLX90248ELD-EBA-000	Omnipolar switch	3.5	2.5	0.003	1.5 to 3.6	-40 to +85	UTQFN
MLX90248ESE-EBA-000	Omnipolar switch	3.5	2.5	0.003	1.5 to 3.6	-40 to +85	TSOT
MLX92211LSE-AAA-000	3-wire latch	3	-3	3	2.7 to 24	-40 to +150	TSOT
MLX92211LSE-ACA-000	3-wire latch	3	-3	3	2.7 to 24	-40 to +150	TSOT
MLX92211LSE-ADA-000	3-wire latch	14	-14	3	2.7 to 24	-40 to +150	TSOT
MLX92211LSE-AEA-000	3-wire latch	3	-3	3	2.7 to 24	-40 to +150	TSOT
MLX92211LSE-BAA-003	3-wire latch	0.5	-0.5	3	2.7 to 24	-40 to +150	TSOT
MLX92211LSE-BAA-006	3-wire latch	1.5	-1.5	3	2.7 to 24	-40 to +150	TSOT
MLX92211LSE-BAA-008	3-wire latch	7	-7	3	2.7 to 24	-40 to +150	TSOT
MLX92211LSE-BAA-024	3-wire latch	5	-5	3	2.7 to 24	-40 to +150	TSOT
MLX92211LSE-BAA-037	3-wire latch	8.75	-8.75	3	2.7 to 24	-40 to +150	TSOT
MLX92211LSE-BAA-202	3-wire latch	1.5	-1.5	3	2.7 to 24	-40 to +150	TSOT
MLX92211LSE-BAA-203	3-wire latch	3	-3	3	2.7 to 24	-40 to +150	TSOT
MLX92211LSE-BAA-205	3-wire latch	8.75	-8.75	3	2.7 to 24	-40 to +150	TSOT
MLX92211LUA-AAA-000	3-wire latch	3	-3	3	2.7 to 24	-40 to +150	UA
MLX92211LUA-ADA-000	3-wire latch	14	-14	3	2.7 to 24	-40 to +150	UA
MLX92211LUA-AEA-000	3-wire latch	—	-3	2.2	2.7 to 24	-40 to +150	UA
MLX92211LUA-BAA-015	3-wire latch	0.5	-0.5	3	2.7 to 24	-40 to +150	UA
MLX92212LSE-AAA-000	3-wire latch	2	-2	2.2	2.5 to 5.5	-40 to +150	TSOT
MLX92212LSE-ABA-000	3-wire switch	12	10.5	2.2	2.5 to 5.5	-40 to +150	TSOT
MLX92213ELD-AAA-000	3-wire latch	2	-2	0.036	1.6 to 3.6	-40 to +85	UTQFN
MLX92215LSE-AAA-000	3-wire latch	3	-3	3	2.7 to 24	-40 to +150	TSOT
MLX92215LSE-ACA-000	3-wire latch	3	-3	3	2.7 to 24	-40 to +150	TSOT
MLX92215LUA-AAA-000	3-wire latch	3	-3	3	2.7 to 24	-40 to +150	UA
MLX92221LSE-AAA-001	2-wire latch	12	-12	6	2.7 to 24	-40 to +150	TSOT
MLX92221LSE-AAA-002	2-wire latch	6	-6	6	2.7 to 24	-40 to +150	TSOT
MLX92221LSE-AAA-003	2-wire latch	1.75	-1.75	6	2.7 to 24	-40 to +150	TSOT
MLX92221LSE-BAA-008	2-wire latch	4	-4	3.3	2.7 to 24	-40 to +150	TSOT
MLX92221LUA-AAA-004	2-wire latch	6	-6	6	2.7 to 24	-40 to +150	UA
MLX92221LUA-AAA-005	2-wire latch	1.75	-1.75	6	2.7 to 24	-40 to +150	UA
MLX92221LUA-AAA-006	2-wire latch	0.8	-0.8	6	2.7 to 24	-40 to +150	UA
MLX92221LUA-AAA-007	2-wire latch	12	-12	6	2.7 to 24	-40 to +150	UA
MLX92221LUA-BAA-102	2-wire latch	6	-6	6	2.7 to 24	-40 to +150	UA

Part Number	Type	Operating Point Bop (mT)	Release Point Brp (mT)	Output Current (mA)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
MLX92221LUA-BAA-105	2-wire latch	1.8	-1.8	6	2.7 to 24	-40 to +150	UA
MLX92231LSE-AAA-003	3-wire switch	33	27	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-004	3-wire switch	-5.5	-3.5	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-005	3-wire switch	26	20	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-007	3-wire switch	26	20	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-009	3-wire switch	3.5	2.5	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-010	3-wire switch	10	8.5	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-011	3-wire switch	40	34	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-012	3-wire switch	15	12	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-013	3-wire switch	3.5	2.5	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-014	3-wire switch	5.5	3.5	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-016	3-wire switch	9.72	8.32	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-017	3-wire switch	11.7	10.3	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-018	3-wire switch	16.2	14.2	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-019	3-wire switch	23	21	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-021	3-wire switch	5.5	3.5	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-022	3-wire switch	10	8.5	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-023	3-wire switch	43	41	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-025	3-wire switch	50	48	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-026	3-wire switch	23	21	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-027	3-wire switch	3.5	2.5	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-028	3-wire switch	-3.5	-2.5	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-029	3-wire switch	15	14	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-030	3-wire switch	26	20	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-031	3-wire switch	-13.5	-8.5	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-032	3-wire switch	23	21	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-033	3-wire switch	18	12.5	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-036	3-wire switch	26	24	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-038	3-wire switch	27	26	3	2.7 to 24	-40 to +150	TSOT
MLX92231LSE-AAA-040	3-wire switch	66	50	3	2.7 to 24	-40 to +150	UA
MLX92231LSE-AAA-041	3-wire switch	10.2	8.4	3	2.7 to 24	-40 to +150	UA
MLX92231LSE-AAA-042	3-wire switch	51	41	3	2.7 to 24	-40 to +150	UA
MLX92231LSE-AAA-045	3-wire switch	20	15	3	2.7 to 24	-40 to +150	UA
MLX92231LSE-AAA-046	3-wire switch	13	12	3	2.7 to 24	-40 to +150	UA


Part Number	Type	Operating Point Bop (mT)	Release Point Brp (mT)	Output Current (mA)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
MLX92231LSE-AAA-204	3-wire switch	6.5	5.5	3	2.7 to 24	-40 to +150	UA
MLX92231LSE-ABA-004	3-wire switch	-5.5	-3.5	3	2.7 to 24	-40 to +150	TSOT
MLX92231LUA-AAA-020	3-wire switch	3.5	2.5	3	2.7 to 24	-40 to +150	UA
MLX92231LUA-AAA-034	3-wire switch	5.5	3.5	3	2.7 to 24	-40 to +150	UA
MLX92231LUA-AAA-035	3-wire switch	28.2	26	3	2.7 to 24	-40 to +150	UA
MLX92231LUA-AAA-039	3-wire switch	13.5	8.5	3	2.7 to 24	-40 to +150	UA
MLX92232LSE-AAA-000	Progr. 3-wire latch/switch	-80	80	3	2.7 to 24	-40 to +150	TSOT
MLX92232LSE-AAA-001	Progr. 3-wire latch/switch	-80	80	3	2.7 to 24	-40 to +150	TSOT
MLX92232LSE-AAA-002	Progr. 3-wire latch/switch	-80	80	3	2.7 to 24	-40 to +150	TSOT
MLX92232LSE-AAA-003	Progr. 3-wire latch/switch	-80	80	3	2.7 to 24	-40 to +150	TSOT
MLX92232LSE-AAA-200	Progr. 3-wire latch/switch	-40	40	3	2.7 to 24	-40 to +150	TSOT
MLX92232LUA-AAA-000	Progr. 3-wire latch/switch	-80	80	3	2.7 to 24	-40 to +150	UA
MLX92232LUA-AAA-001	Progr. 3-wire latch/switch	-80	80	3	2.7 to 24	-40 to +150	UA
MLX92232LUA-AAA-002	Progr. 3-wire latch/switch	-80	80	3	2.7 to 24	-40 to +150	UA
MLX92232LUA-AAA-003	Progr. 3-wire latch/switch	-80	80	3	2.7 to 24	-40 to +150	UA
MLX92232LVA-AAA-000	Progr. dual hall latch/switch	-80	80	3	2.7 to 24	-40 to +150	VA
MLX92241LSE-AAA-008	2-wire switch	17	15	6	2.7 to 24	-40 to +150	TSOT
MLX92241LSE-AAA-011	2-wire switch	5.5	3.5	3.3	2.7 to 24	-40 to +150	TSOT
MLX92241LSE-AAA-012	2-wire switch	5.5	3.5	6	2.7 to 24	-40 to +150	TSOT
MLX92241LSE-AAA-013	2-wire switch	9.2	7.2	6	2.7 to 24	-40 to +150	TSOT
MLX92241LSE-AAA-014	2-wire switch	9.2	7.2	3.3	2.7 to 24	-40 to +150	TSOT
MLX92241LSE-AAA-015	2-wire switch	9.2	7.2	6	2.7 to 24	-40 to +150	TSOT
MLX92241LSE-AAA-016	2-wire switch	5.5	3.5	6	2.7 to 24	-40 to +150	TSOT
MLX92241LSE-AAA-017	2-wire switch	9.2	7.2	3.3	2.7 to 24	-40 to +150	TSOT
MLX92241LSE-AAA-018	2-wire switch	9.2	7.2	3.3	2.7 to 24	-40 to +150	TSOT
MLX92241LSE-BAA-007	2-wire switch	15	14	3.3	2.7 to 24	-40 to +150	TSOT
MLX92241LSE-BAA-019	2-wire switch	9.2	7.2	3.3	2.7 to 24	-40 to +150	TSOT
MLX92241LSE-BAA-020	2-wire switch	9.2	7.2	3.3	2.7 to 24	-40 to +150	TSOT
MLX92241LSE-BAA-021	2-wire switch	9.2	7.2	6	2.7 to 24	-40 to +150	TSOT
MLX92241LSE-BAA-022	2-wire switch	-8	-5	3.3	2.7 to 24	-40 to +150	TSOT
MLX92241LSE-BAA-023	2-wire switch	-8	-5	6	2.7 to 24	-40 to +150	TSOT
MLX92241LSE-BAA-024	2-wire switch	8.7	7.3	6	2.7 to 24	-40 to +150	TSOT
MLX92241LSE-BAA-025	2-wire switch	-6	-4	6	2.7 to 24	-40 to +150	TSOT
MLX92241LSE-BAA-027	2-wire switch	10	4	3.3	2.7 to 24	-40 to +150	TSOT

Part Number	Type	Operating Point Bop (mT)	Release Point Brp (mT)	Output Current (mA)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
MLX92241LSE-BAA-029	2-wire switch	9.2	7.2	6	2.7 to 24	-40 to +150	TSOT
MLX92241LUA-AAA-003	2-wire switch	8	5	3.3	2.7 to 24	-40 to +150	UA
MLX92241LUA-AAA-004	2-wire switch	9.2	7.2	6	2.7 to 24	-40 to +150	UA
MLX92241LUA-AAA-005	2-wire switch	9.2	7.2	3.3	2.7 to 24	-40 to +150	UA
MLX92241LUA-AAA-006	2-wire switch	8	5	6	2.7 to 24	-40 to +150	UA
MLX92241LUA-AAA-007	2-wire switch	5.5	3.5	3.3	2.7 to 24	-40 to +150	UA
MLX92241LUA-AAA-028	2-wire switch	20	18	6	2.7 to 24	-40 to +150	TSOT
MLX92241LUA-BAA-026	2-wire switch	8.5	7.5	6	2.7 to 24	-40 to +150	UA
MLX92241LUA-BAA-101	2-wire switch	16	15	6	2.7 to 24	-40 to +150	UA
MLX92241LUA-BAA-102	2-wire switch	3.2	2.8	6	2.7 to 24	-40 to +150	UA
MLX92241LUA-BAA-103	2-wire switch	6	4	3.3	2.7 to 24	-40 to +150	UA
MLX92241LUA-BAA-104	2-wire switch	8	7	6	2.7 to 24	-40 to +150	UA
MLX92241LUA-BAA-106	2-wire switch	4	2.7	6	2.7 to 24	-40 to +150	UA
MLX92241LUA-BAA-107	2-wire switch	3.9	3	6	2.7 to 24	-40 to +150	UA
MLX92241LUA-BAA-108	2-wire switch	7.9	5.3	3.3	2.7 to 24	-40 to +150	UA
MLX92241LUA-BAA-109	2-wire switch	16	12	3.3	2.7 to 24	-40 to +150	UA
MLX92241LUA-BAA-110	2-wire switch	7.9	5.3	6	2.7 to 24	-40 to +150	UA
MLX92241LUA-BAA-111	2-wire switch	3.8	2.6	6	2.7 to 24	-40 to +150	UA
MLX92241LUA-BAA-112	2-wire switch	-3.8	2.6	6	2.7 to 24	-40 to +150	UA
MLX92241LUA-BAA-113	2-wire switch	7.9	5.3	3.3	2.7 to 24	-40 to +150	UA
MLX92241LUA-BAA-114	2-wire switch	7.9	5.3	6	2.7 to 24	-40 to +150	UA
MLX92241LUA-BAA-115	2-wire switch	8	5	3.3	2.7 to 24	-40 to +150	UA
MLX92241LUA-BAA-116	2-wire switch	20	18	6	2.7 to 24	-40 to +150	UA
MLX92242LSE-AAA-000	Progr. 2-wire latch/switch	-100	100	3.3	2.7 to 24	-40 to +150	TSOT
MLX92242LSE-AAA-200	Progr. 2-wire latch/switch	-40	40	3.3	2.7 to 24	-40 to +150	TSOT
MLX92242LUA-AAA-000	Progr. 2-wire latch/switch	-100	100	3.3	2.7 to 24	-40 to +150	UA
MLX92242LUA-AAA-100	Progr. 2-wire latch/switch	-100	100	3.3	2.7 to 24	-40 to +150	UA
MLX92242LUA-AAA-200	Progr. 2-wire latch/switch	-40	40	3.3	2.7 to 24	-40 to +150	TSOT
MLX92242LUA-AAA-300	Progr. 2-wire latch/switch	-40	40	3.3	2.7 to 24	-40 to +150	UA
MLX92251LSE-AAA-000	Dual hall latch	7.5	-7.5	4.5	2.7 to 24	-40 to +150	TSOT
MLX92251LSE-ABA-000	Dual hall latch	2.5	-2.5	4.5	2.7 to 24	-40 to +150	TSOT
MLX92255LSE-AAA-000	Dual hall latch	3	-3	5	2.7 to 24	-40 to +150	TSOT
MLX92256LSE-AAA-000	Dual hall latch	2	-2	3.5	2.7 to 24	-40 to +150	TSOT
MLX92256LSE-ABA-000	Dual hall latch	2	-2	3.5	2.7 to 24	-40 to +150	TSOT

Part Number	Type	Operating Point Bop (mT)	Release Point Brp (mT)	Output Current (mA)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
MLX92291LSE-AAA-003	3-wire switch	4.15	3.15	5	3.3 to 18	-40 to +150	TSOT
MLX92291LSE-AAA-004	3-wire switch	5.5	4.5	5	3.3 to 18	-40 to +150	TSOT
MLX92291LSE-AAA-200	3-wire switch	8.8	8.5	5	3.3 to 18	-40 to +150	TSOT
MLX92291LSE-AAA-201	3-wire switch	8.8	8.5	5	3.3 to 18	-40 to +150	TSOT
MLX92291LSE-AAA-202	3-wire switch	5.4	4.4	5	3.3 to 18	-40 to +150	TSOT
MLX92292LDC-AAA-000	Progr. dual hall latch/switch	-90	90	PROGRAMMABLE	3.3 to 18	-40 to +150	SOIC8
MLX92292LSE-AAA-000	Progr. 3-wire latch/switch	-90	90	PROGRAMMABLE	3.3 to 18	-40 to +150	TSOT
MLX92292LSE-AAA-200	Progr. 3-wire latch/switch	-40	40	PROGRAMMABLE	3.3 to 18	-40 to +150	TSOT
MLX92292LUA-AAA-000	Progr. 3-wire latch/switch	-90	90	PROGRAMMABLE	3.3 to 18	-40 to +150	UA
US1881ESE-AAA-000	3-wire latch	5	-5	3	3.5 to 24	-40 to +85	TSOT
US1881EUA-AAA-000	3-wire latch	5	-5	3	3.5 to 24	-40 to +85	UA
US1881LSE-AAA-000	3-wire latch	5	-5	3	3.5 to 24	-40 to +150	TSOT
US1881LUA-AAA-000	3-wire latch	5	-5	3	3.5 to 24	-40 to +150	UA
US1883LUA-AAA-000	3-wire latch	14	-14	3	3.5 to 24	-40 to +150	UA
US2881ESE-AAA-000	3-wire latch	3	-3	3	3.5 to 24	-40 to +85	TSOT
US2881EUA-AAA-000	3-wire latch	3	-3	3	3.5 to 24	-40 to +85	UA
US2881LSE-AAA-000	3-wire latch	3	-3	3	3.5 to 24	-40 to +150	TSOT
US2881LUA-AAA-000	3-wire latch	3	-3	3	3.5 to 24	-40 to +150	UA
US2882ESE-AAA-000	3-wire latch	3	-3	3	3.5 to 24	-40 to +85	TSOT
US2882EUA-AAA-000	3-wire latch	3	-3	3	3.5 to 24	-40 to +85	UA
US2882LSE-AAA-000	3-wire latch	3	-3	3	3.5 to 24	-40 to +150	TSOT
US2882LUA-AAA-000	3-wire latch	3	-3	3	3.5 to 24	-40 to +150	UA
US2884LSE-AAA-000	3-wire latch	3	-3	3	3.5 to 24	-40 to +150	TSOT
US3881ESE-AAA-000	3-wire latch	5	-5	3	2.2 to 18	-40 to +85	TSOT
US3881EUA-AAA-000	3-wire latch	5	-5	3	2.2 to 18	-40 to +85	UA
US3881LSE-AAA-000	3-wire latch	5	-5	3	2.2 to 18	-40 to +150	TSOT
US3881LUA-AAA-000	3-wire latch	5	-5	3	2.2 to 18	-40 to +150	UA
US4881ESE-AAA-000	3-wire latch	3	-3	3	2.2 to 18	-40 to +85	TSOT
US4881EUA-AAA-000	3-wire latch	3	-3	3	2.2 to 18	-40 to +85	UA
US4881LSE-AAA-000	3-wire latch	3	-3	3	2.2 to 18	-40 to +150	TSOT
US4881LUA-AAA-000	3-wire latch	3	-3	3	2.2 to 18	-40 to +150	UA
US5681ESE-AAA-000	3-wire switch	3.5	5.5	3	3.5 to 24	-40 to +85	TSOT
US5681KSE-AAA-000	3-wire switch	3.5	5.5	3	3.5 to 24	-40 to +125	TSOT
US5682ESE-AAA-000	3-wire switch	3.5	5.5	3	3.5 to 24	-40 to +85	TSOT
US5682KSE-AAA-000	3-wire switch	3.5	5.5	3	3.5 to 24	-40 to +125	TSOT

Part Number	Type	Operating Point Bop (mT)	Release Point Brp (mT)	Output Current (mA)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
US5683ESE-AAA-000	3-wire switch	3.5	5.5	3	3.5 to 24	-40 to +85	TSOT
US5683KSE-AAA-000	3-wire switch	3.5	5.5	3	3.5 to 24	-40 to +125	TSOT
US5781ESE-AAA-000	3-wire switch	7.5	12	3	3.5 to 24	-40 to +85	TSOT
US5781EUA-AAA-000	3-wire switch	7.5	12	3	3.5 to 24	-40 to +85	UA
US5781LSE-AAA-000	3-wire switch	7.5	12	3	3.5 to 24	-40 to +150	TSOT
US5781LUA-AAA-000	3-wire switch	7.5	12	3	3.5 to 24	-40 to +150	UA
US5782ESE-AAA-000	3-wire switch	7.5	12	3	3.5 to 24	-40 to +85	TSOT
US5782LSE-AAA-000	3-wire switch	7.5	12	3	3.5 to 24	-40 to +150	TSOT
US5881ESE-AAA-000	3-wire switch	20	25	3	3.5 to 24	-40 to +85	TSOT
US5881EUA-AAA-000	3-wire switch	20	25	3	3.5 to 24	-40 to +85	UA
US5881KSE-AAA-000	3-wire switch	20	25	3	3.5 to 24	-40 to +125	TSOT
US5881LSE-AAA-000	3-wire switch	20	25	3	3.5 to 24	-40 to +150	TSOT
US5881LUA-AAA-000	3-wire switch	20	25	3	3.5 to 24	-40 to +150	UA

Automotive-Compliant & Industrial Hall Effect Omnipolar Switches



New High-Voltage, High performance automotive and industrial Hall Effect Omnipolar Switch family provides more stable, more flexible and more robust solutions.

- Very Precise and Stable Omnipolar Hall switch points
- Wide operating voltage range, 3V to 28V
- High ESD (8kV for Automotive) rating with Multiple protection functions
- AH356xQ are Automotive-compliant, qualified to AEC-Q100 Grade 0, high-sensitivity omnipolar Hall effect switches that support PPAP documentation.
- AH357x and AH3582 Omnipolar Switches with wide (-40 to +125°C) temperature range to support extended Industrial temperature applications
- Fast Power Up and Response time

DIODES
INCORPORATED



Part Number	Type	Operating Point Bop (mT)	Release Point Brp (mT)	Output Current (mA)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
BU52072GWZ	Omnipolar w/ Polarity Discrimination	2.4	2	0.0044	1.65 to 3.6	-40 to +85	UCSP35L1 (CSP 4-Ball) 0.8 x 0.8 x 0.4
BU52073GWZ	Omnipolar w/ Polarity Discrimination	4.1	3.3	0.0044	1.65 to 3.6	-40 to +85	UCSP35L1 (CSP 4-Ball) 0.8 x 0.8 x 0.4
BU52074GWZ	Omnipolar w/ Polarity Discrimination	6.3	5.4	0.0044	1.65 to 3.6	-40 to +85	UCSP35L1 (CSP 4-Ball) 0.8 x 0.8 x 0.4
BU52092GWZ	Omnipolar	2.4	2	0.0044	1.65 to 3.6	-40 to +85	UCSP35L1 (CSP 4-Ball) 0.8 x 0.8 x 0.4
BU52095GWZ	Omnipolar	9.5	8.6	0.0044	1.65 to 3.6	-40 to +85	UCSP35L1 (CSP 4-Ball) 0.8 x 0.8 x 0.4
BU52097GWZ	Omnipolar	15	14.1	0.0044	1.65 to 3.6	-40 to +85	UCSP35L1 (CSP 4-Ball) 0.8 x 0.8 x 0.4
BU52098GWZ	Omnipolar	24	22.4	0.0044	1.65 to 3.6	-40 to +85	UCSP35L1 (CSP 4-Ball) 0.8 x 0.8 x 0.4
BU52177GXZ	Omnipolar w/ Polarity Discrimination	15	14.1	0.005	1.65 to 3.6	-40 to +85	XCSP30L1 (CSP 4-Ball) 0.65 x 0.65 x 0.33
BU52272NUZ	Omnipolar w/ Polarity Discrimination	2.4	2	0.0044	1.65 to 3.6	-40 to +85	VSON04Z1114A (4-pin) 1.1 x 1.4 x 0.4
BU52273NUZ	Omnipolar w/ Polarity Discrimination	4.1	3.3	0.0044	1.65 to 3.6	-40 to +85	VSON04Z1114A (4-pin) 1.1 x 1.4 x 0.4
BU52274NUZ	Omnipolar w/ Polarity Discrimination	6.3	5.4	0.0044	1.65 to 3.6	-40 to +85	VSON04Z1114A (4-pin) 1.1 x 1.4 x 0.4
BU52472NUZ	Omnipolar w/ Polarity Discrimination	2.4	2	0.0044	1.65 to 3.6	-40 to +85	VSON04Z1114A (4-pin) 1.1 x 1.4 x 0.4
BU52492NUZ	Omnipolar	2.4	2	0.0042	1.65 to 3.6	-40 to +85	VSON04Z1114A (4-pin) 1.1 x 1.4 x 0.4
BU52493NUZ	Omnipolar	4.1	3.3	0.0042	1.65 to 3.6	-40 to +85	VSON04Z1114A (4-pin) 1.1 x 1.4 x 0.4
BU52494NUZ	Omnipolar	6.3	5.4	0.0042	1.65 to 3.6	-40 to +85	VSON04Z1114A (4-pin) 1.1 x 1.4 x 0.4
BU52792GWZ	Omnipolar	2.4	2	0.0032	2.7 to 5.5	-40 to +85	UCSP35L1 (CSP 4-Ball) 0.8 x 0.8 x 0.4

**SENSE THE FUTURE
WITH ROHM**





Part Number	Output Voltage Range (V)	Sensitivity (mV/mT)	Magnetic Field Range (mT)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
AS5304	0 to 5	–	5 to 60	5.0	35.0	-40 to +125	TSSOP-20 6.5 x 6.4 x 1.2
AS5306	0 to 5	–	5 to 60	5.0	30.0	-40 to +125	TSSOP-20 6.5 x 6.4 x 1.2
AS5311	0 to 5	–	10 to 40	3.3 or 5.0	21.0	-40 to +125	TSSOP-20 300 x 10 x 1.3
AS5510	0 to 3.6	-50 to +50	10 to 50	3.0	3.5	-30 to +85	TSSOP-20 6.5 x 6.4 x 1.2



Part Number	Output Voltage Range (V)	Sensitivity (mV/mT)	Magnetic Field Range (mT)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
AH49F	0.8 to ($V_{CC} - 0.8$)	0.210	±80	3 to 8	3	-40 to +105	U-DFN2020-6, SC59, T092
AH8500	1.6 to 3.6	0.225	±43	1.6 to 3.6	12uA @ 20Hz	-40 to +85	U-DFN2020-6
AH8501	1.6 to 3.6	0.210	±40	1.6 to 3.6	12uA @ 20Hz	-40 to +85	U-DFN2020-6
AH8502	1.6 to 3.6	0.225	±43	1.6 to 3.6	13uA	-40 to +85	U-DFN2020-6
AH8503	1.6 to 3.6	0.210	±40	1.6 to 3.6	13uA	-40 to +85	U-DFN2020-6



Part Number	Output Voltage Range (V)	Sensitivity (mV/mT)	Magnetic Field Range (mT)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
TLE4997E2XALA1	5% to 95% of V_{DD}	60 (typical)	-200 to +200	4.5 to 5.5	7.5	-40 to +150	SSO-3
TLE4998P3XALA1	5% to 95% of V_{DD}	60 (typical)	-200 to +200	4.5 to 5.5	6	-40 to +150	SSO-3
TLE4997A8DXUMA1	5% to 95% of V_{DD}	±12.5 to ±300 (programmable)	±50 to ±200 (programmable)	4.5 to 5.5	7.5	-40 to +125	TDSO-8
TLE4997A8XUMA1	5% to 95% of V_{DD}	±12.5 to ±300 (programmable)	±50 to ±200 (programmable)	4.5 to 5.5	7.5	-40 to +125	TDSO-8
TLE4998C3XALA1	5% to 95% of V_{DD}	±8.2 to ±245 (programmable)	±50 to ±200 (programmable)	4.5 to 5.5	8	-40 to +150	SSO-3-10



Part Number	Output Voltage Range (V)	Sensitivity (mV/mT)	Magnetic Field Range (mT)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
MLX90215EVA-AAA-106	5	10.0	20 to 500	5	4	-40 to +85	SIP4
MLX90215LVA-AAA-111	5	10.0	20 to 500	5	4	-40 to +150	SIP4
MLX90251EVA-FAA-000	5	12.5	166 to 400	5	7	-40 to +85	SIP4
MLX90251EVA-FAA-100	5	20.0	71 to 250	5	7	-40 to +85	SIP4
MLX90251EVA-FAA-200	5	36.2	27 to 138	5	7	-40 to +85	SIP4
MLX90251EVA-FAA-300	5	100.0	11 to 50	5	7	-40 to +85	SIP4
MLX90251LVA-FAA-000	5	12.5	166 to 400	5	7	-40 to +150	SIP4
MLX90251LVA-FAA-100	5	20.0	71 to 250	5	7	-40 to +150	SIP4
MLX90251LVA-FAA-200	5	36.2	27 to 138	5	7	-40 to +150	SIP4
MLX90251LVA-FAA-300	5	100.0	11 to 50	5	7	-40 to +150	SIP4
MLX90288LDC-CAB-000	5	7.7	6 to 650	5	8.8	-40 to +150	SOIC8
MLX90290LUA-AAA-500	5	37.6	133 to 133	5	5	-40 to +150	TO-92-3L
MLX90290LUA-AAA-510	5	50.0	100 to 100	5	5	-40 to +150	TO-92-3L
MLX90290LUA-AAA-540	5	200.0	25 to 25	5	5	-40 to +150	TO-92-3L
MLX90290LUA-AAA-622	5	62.5	80 to 80	5	5	-40 to +150	TO-92-3L
MLX90290LSE-AAA-511	5	50.0	100 to 100	5	5	-40 to +150	TSOT-3L
MLX90291KDC-BCA-000	5	12.5	15 to 400	5	8	-40 to +125	SOIC8
MLX90293LDC-ADM-000	5	12.5	7 to 400	5	8	-40 to +150	SOIC8
MLX90293LGO-ADM-000	5	12.5	7 to 400	5	16	-40 to +150	TSSOP16



Part Number	Sensing Range (gauss)	Sensing Axis	Sensitivity (LSB / gauss)	Output Interface	Output Noise (mgauss RMS)	Supply Voltage (V)	Supply Current (µA Max)	Operating Temperature (°C)	Package Type / Size (mm)
BMM150	±13 (x,y-axis) ±25 (z-axis)	X, Y, Z	± 0.01	I ² C and SPI (2 interrupt pins)	x, y-axis: 1.0 µTz- axis: 1.4 µT	V _{DD} 1.62 to 3.6 V _{DDIO} 1.2 to 3.6	170 µA (low-power preset); 500 µA (normal mode)	-40 to +85	CSWLP- (12-pin) 1.56 × 1.56 × 0.6 0.4 mm diagonal ball pitch



Part Number	Sensing Range (gauss)	Sensing Axis	Sensitivity (LSB / z)	Output Interface	Output Noise (mgauss RMS)	Supply Voltage (V)	Supply Current (µA Max)	Operating Temperature (°C)	Package Type / Size (mm)
MLX90393SLW-ABA-011	50 to 500	X, Y, Z, T	5 to 50	SPI, I ² C	–	2.2 to 3.6	3	-20 to +85	QFN16
MLX90393ELW-ABA-011	50 to 500	X, Y, Z, T	5 to 50	SPI, I ² C	–	2.2 to 3.6	3	-20 to +85	QFN16
MLX90393SLW-ABA-012	50 to 500	X, Y, Z, T	5 to 50	SPI, I ² C	–	2.2 to 3.6	3	-20 to +85	QFN16
MLX90393ELW-ABA-012	50 to 500	X, Y, Z, T	5 to 50	SPI, I ² C	–	2.2 to 3.6	3	-20 to +85	QFN16
MLX90393SLW-ABA-013	50 to 500	X, Y, Z, T	5 to 50	SPI, I ² C	–	2.2 to 3.6	3	-20 to +85	QFN16
MLX90393ELW-ABA-013	50 to 500	X, Y, Z, T	5 to 50	SPI, I ² C	–	2.2 to 3.6	3	-20 to +85	QFN16
MLX90393SLW-ABA-014	50 to 500	X, Y, Z, T	5 to 50	SPI, I ² C	–	2.2 to 3.6	3	-20 to +85	QFN16
MLX90393ELW-ABA-014	50 to 500	X, Y, Z, T	5 to 50	SPI, I ² C	–	2.2 to 3.6	3	-20 to +85	QFN16

Part Number	Sensing Range (Gauss)	Sensing Axis	Sensitivity (LSB / Gauss)	Output Interface	Output Noise (mGauss RMS)	Supply Voltage (V)	Supply Current (µA Max)	Operating Temperature (°C)	Package Type / Size (mm)
LIS3MDLTR	±4, ±8, ±12, ±16	X, Y, Z	0.15	I ² C, SPI	3.5	1.9 to 3.6	270	-40 to +85	LGA-12 2 x 2 x 1
LIS2MDLTR	±50	X, Y, Z	1.5	I ² C, SPI	3	1.71 to 3.6	200	-40 to +85	LGA-12 2 x 2 x 0.7 max
IIS2MDCTR	±50	X, Y, Z	1.5	I ² C, SPI	3	1.71 to 3.6	25	-40 to +85	LGA-12 2 x 2 x 0.7 max

MAGNETIC - HALL / AMR Sensors

Part Number	Type	Operating Magnetic Field On (mT)	Operating Magnetic Field off (mT)	Current Consumption	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
MRMS201A-001	Magnetic AMR Sensor	Max 2.5mT	Min 0.5mT	5.0µA	1.6 to 3.5	-40 to +125	2.9 x 2.8 x 1.1
MRMS205A-001	Magnetic AMR Sensor	Max 2.5mT	Min 0.5mT	8.0µA	3.0 to 5.5	-40 to +125	2.9 x 2.8 x 1.1
MRMS501A-001	Magnetic AMR Sensor	Max 2.5mT	Min 0.5mT	3.0µA	1.6 to 3.5	-40 to +125	1.45 x 1.45 x 0.55
MRMS511X-001	Magnetic AMR Sensor	Max 2.0mT	Max 0.8mT	3.0µA	1.6 to 3.5	-40 to +125	1.45 x 1.45 x 0.55

Murata Sensor Solutions

offers a wide selection of MEMS, ceramic and magnetoresistive options

Murata pursues sensing functions, making full use of MEMS, processing technology and magnetoresistive elements, including ceramic material technology, in order to develop highly efficient and highly reliable devices, modules and systems.

Murata Sensor products include MEMS sensors (accelerometers, inclinometers, gyro), IR, ultrasonic, thermistors (PTC & NTC), shock, AMR and rotary position to name a few.

A vast lineup of sensors respond to the various needs of automobile, industrial, wearable, IoT, medical care and health care applications.

So whether you need temperature/current sensing, detection, pressure, distance or angle measuring – **Murata has innovative sensing solutions to enable your next innovation.**





OCCUPANCY – MOTION

Passive Infrared Motion Sensor	81
IR Thermal Sensor Array	83
Radar	83
Time of Flight (3D Image).....	84



Part Number	Lens Type (Field of View Angle)	Detection Distance	# of Detection Zones	Output Type	Detection Sensitivity	Current Consumption (µA)	Supply Voltage (V)	Package Type / Size (mm)
IRA-S210ST01	90	<5 meters	2	Analog	4.6mV	Depends on Driver	2 to 15	T05 can
IRA-S230ST01	90	<5 meters	2	Analog	4.6mV	Depends on Driver	2 to 15	T05 can
IRA-S410ST01	76 x 90	<5 meters	4	Analog	7.0mV	Depends on Driver	2 to 15	T05 can
IRA-S510ST01	88	<5 meters	4	Analog	3.3mV	Depends on Driver	2 to 15	T05 can

Panasonic

Part Number	Lens Type (Field of View Angle)	Detection Distance	# of Detection Zones	Output Type	Detection Sensitivity	Current Consumption (µA)	Supply Voltage	Package Type / Size (mm)
EKMC160111*	Standard (106° x 97°)	5 meters	64	Digital	Standard	170µA	3 to 6 V _{DC}	T0-5 Metal Can (through-hole)
EKMC460111*K	Standard (106° x 97°)	5 meters	64	Digital	High Sensitivity	170µA	3 to 6 V _{DC}	T0-5 Metal Can (through-hole)
EKMC760111*K	Standard (106° x 97°)	5 meters	64	Digital	Low Sensitivity	170µA	3 to 6 V _{DC}	T0-5 Metal Can (through-hole)
EKMC260111*K	Standard (106° x 97°)	5 meters	64	Analog	User Controlled	170µA	3 to 6 V _{DC}	T0-5 Metal Can (through-hole)
EKMB110111*	Standard (106° x 97°)	5 meters	64	Digital	Standard	1µA	2.3 to 4 V _{DC}	T0-5 Metal Can (through-hole)
EKMB120111*	Standard (106° x 97°)	5 meters	64	Digital	Standard	2µA	2.3 to 4 V _{DC}	T0-5 Metal Can (through-hole)
EKMB130111*K	Standard (106° x 97°)	5 meters	64	Digital	Standard	6µA	2.3 to 4 V _{DC}	T0-5 Metal Can (through-hole)
EKMC160311*	Long Distance (108° x 99°)	12 meters	92	Digital	Standard	170µA	3 to 6 V _{DC}	T0-5 Metal Can (through-hole)
EKMC460311*K	Long Distance (108° x 99°)	12 meters	92	Digital	Double Sensitivity	170µA	3 to 6 V _{DC}	T0-5 Metal Can (through-hole)
EKMC760311*K	Long Distance (108° x 99°)	12 meters	92	Digital	Half Sensitivity	170µA	3 to 6 V _{DC}	T0-5 Metal Can (through-hole)
EKMC260311*K	Long Distance (108° x 99°)	12 meters	92	Analog	User Controlled	170µA	3 to 6 V _{DC}	T0-5 Metal Can (through-hole)
EKMB110311*	Long Distance (108° x 99°)	12 meters	92	Digital	Standard	1µA	2.3 to 4 V _{DC}	T0-5 Metal Can (through-hole)
EKMB120311*	Long Distance (108° x 99°)	12 meters	92	Digital	Standard	2µA	2.3 to 4 V _{DC}	T0-5 Metal Can (through-hole)
EKMB130311*	Long Distance (108° x 99°)	12 meters	92	Digital	Standard	6µA	2.3 to 4 V _{DC}	T0-5 Metal Can (through-hole)
EKMC160611*	High Density Long Distance (62° x 62°)	17 meters	128	Digital	Standard	170µA	3 to 6 V _{DC}	T0-5 Metal Can (through-hole)
EKMC460611*K	High Density Long Distance (62° x 62°)*	17 meters	128	Digital	Double Sensitivity	170µA	3 to 6 V _{DC}	T0-5 Metal Can (through-hole)
EKMC760611*K	High Density Long Distance (62° x 62°)	17 meters	128	Digital	Half Sensitivity	170µA	3 to 6 V _{DC}	T0-5 Metal Can (through-hole)
EKMC260611*K	High Density Long Distance (62° x 62°)	17 meters	128	Analog	User Controlled	170µA	3 to 6 V _{DC}	T0-5 Metal Can (through-hole)
EKMB110611*	High Density Long Distance (62° x 62°)	17 meters	128	Digital	Standard	1µA	2.3 to 4 V _{DC}	T0-5 Metal Can (through-hole)
EKMB120611*	High Density Long Distance (62° x 62°)	17 meters	128	Digital	Standard	2µA	2.3 to 4 V _{DC}	T0-5 Metal Can (through-hole)
EKMB130611*K	High Density Long Distance (62° x 62°)	17 meters	128	Digital	Standard	6µA	2.3 to 4 V _{DC}	T0-5 Metal Can (through-hole)
EKMC160511*	Wide Field of View (150° x 35°)	5 meters	104	Digital	Standard	170µA	3 to 6 V _{DC}	T0-5 Metal Can (through-hole)
EKMC460511*K	Wide Field of View (150° x 35°)	5 meters	104	Digital	Double Sensitivity	170µA	3 to 6 V _{DC}	T0-5 Metal Can (through-hole)
EKMC760511*K	Wide Field of View (150° x 35°)	5 meters	104	Digital	Half Sensitivity	170µA	3 to 6 V _{DC}	T0-5 Metal Can (through-hole)
EKMC260511*K	Wide Field of View (150° x 35°)	5 meters	104	Analog	User Controlled	170µA	3 to 6 V _{DC}	T0-5 Metal Can (through-hole)
EKMB110511*	Wide Field of View (150° x 35°)	5 meters	104	Digital	Standard	1µA	2.3 to 4 V _{DC}	T0-5 Metal Can (through-hole)

*Note: 1 = White, 2 = Black, 3 = Pearl White

Panasonic

Part Number	Lens Type (Field of View Angle)	Detection Distance	# of Detection Zones	Output Type	Detection Sensitivity	Current Consumption (μA)	Supply Voltage	Package Type / Size (mm)
EKMB120511*	Wide Field of View (150° x 35°)	5 meters	104	Digital	Standard	2μA	2.3 to 4 V _{DC}	TO-5 Metal Can (through-hole)
EKMB130511*K	Wide Field of View (150° x 35°)	5 meters	104	Digital	Standard	6μA	2.3 to 4 V _{DC}	TO-5 Metal Can (through-hole)
EKMC169111*	Slight Motion (97° x 97°)	2.5 meters	112	Digital	Standard	170μA	3 to 6 V _{DC}	TO-5 Metal Can (through-hole)
EKMC469111*K	Slight Motion (97° x 97°)	2.5 meters	112	Digital	Double Sensitivity	170μA	3 to 6 V _{DC}	TO-5 Metal Can (through-hole)
EKMC769111*K	Slight Motion (97° x 97°)	2.5 meters	112	Digital	Half Sensitivity	170μA	3 to 6 V _{DC}	TO-5 Metal Can (through-hole)
EKMC269111*K	Slight Motion (97° x 97°)	2.5 meters	112	Analog	User Controlled	170μA	3 to 6 V _{DC}	TO-5 Metal Can (through-hole)
EKMB119111*	Slight Motion (97° x 97°)	2.5 meters	112	Digital	Standard	1μA	2.3 to 4 V _{DC}	TO-5 Metal Can (through-hole)
EKMB129111*	Slight Motion (97° x 97°)	2.5 meters	112	Digital	Standard	2μA	2.3 to 4 V _{DC}	TO-5 Metal Can (through-hole)
EKMB139111*K	Slight Motion (97° x 97°)	2.5 meters	112	Digital	Standard	6μA	2.3 to 4 V _{DC}	TO-5 Metal Can (through-hole)
EKMC160411*	Wall Installation (105° x 40°)	12 meters	68	Digital	Standard	170μA	3 to 6 V _{DC}	TO-5 Metal Can (through-hole)
EKMC460411*K	Wall Installation (105° x 40°)	12 meters	68	Digital	Standard	170μA	3 to 6 V _{DC}	TO-5 Metal Can (through-hole)
EKMC760411*K	Wall Installation (105° x 40°)	12 meters	68	Digital	Standard	170μA	3 to 6 V _{DC}	TO-5 Metal Can (through-hole)
EKMC260411*K	Wall Installation (105° x 40°)	12 meters	68	Analog	User Controlled	170μA	3 to 6 V _{DC}	TO-5 Metal Can (through-hole)
EKMB110411*	Wall Installation (105° x 40°)	12 meters	68	Digital	Standard	1μA	2.3 to 4 V _{DC}	TO-5 Metal Can (through-hole)
EKMB120411*	Wall Installation (105° x 40°)	12 meters	68	Digital	Standard	2μA	2.3 to 4 V _{DC}	TO-5 Metal Can (through-hole)
EKMB130411*K	Wall Installation (105° x 40°)	12 meters	68	Digital	Standard	6μA	2.3 to 4 V _{DC}	TO-5 Metal Can (through-hole)
EKMC169311*	Saturn (44° x 44°) Slight Motion (90° x 90°) Standard Motion	2.2 meters	84	Digital	Standard	170μA	3 to 6 V _{DC}	TO-5 Metal Can (through-hole)
EKMC469311*K	Saturn (44° x 44°) Slight Motion (90° x 90°) Standard Motion	2.2 meters	84	Digital	Standard	170μA	3 to 6 V _{DC}	TO-5 Metal Can (through-hole)
EKMC769311*K	Saturn (44° x 44°) Slight Motion (90° x 90°) Standard Motion	2.2 meters	84	Digital	Standard	170μA	3 to 6 V _{DC}	TO-5 Metal Can (through-hole)
EKMC269311*K	Saturn (44° x 44°) Slight Motion (90° x 90°) Standard Motion	2.2 meters	84	Analog	User Controlled	170μA	3 to 6 V _{DC}	TO-5 Metal Can (through-hole)
EKMB119311*	Saturn (44° x 44°) Slight Motion (90° x 90°) Standard Motion	2.2 meters	84	Digital	Standard	1μA	2.3 to 4 V _{DC}	TO-5 Metal Can (through-hole)
EKMB129311*	Saturn (44° x 44°) Slight Motion (90° x 90°) Standard Motion	2.2 meters	84	Digital	Standard	2μA	2.3 to 4 V _{DC}	TO-5 Metal Can (through-hole)
EKMB139311*K	Saturn (44° x 44°) Slight Motion (90° x 90°) Standard Motion	2.2 meters	84	Digital	Standard	6μA	2.3 to 4 V _{DC}	TO-5 Metal Can (through-hole)

*Note: 1 = White, 2 = Black, 3 = Pearl White





Hall Effect Sensors with Market-Leading Performance for Automotive and Industrial Markets



Part Number	Pixel Array	Output Interface	Detection Range (m)	Field of View (deg)	Object Temperature Range (°C)	Current Consumption (mA)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
MLX90621ESF-BAA-000	16 x 4	I ² C	5	120 x 25	-40 to +300	9	2.5 to 3.3	-40 to +85	TO-39 / 5.51(h) x 9.3(d)
MLX90621ESF-BAB-000	16 x 4	I ² C	10	60 x 15	-40 to +300	9	2.5 to 3.4	-40 to +85	TO-39 / 11.15(h) x 9.3(d)
MLX90621ESF-BAD-000	16 x 4	I ² C	12	40 x 10	-40 to +300	9	2.5 to 3.5	-40 to +85	TO-39 / 14.15(h) x 9.3(d)
MLX90640ESF-BAA-000	32 x 24	I ² C	5	110 x 75	-40 to +300	15	2.9 to 3.6	-40 to +85	TO-39 / 5.7(h) x 9.3(d)
MLX90640ESF-BAB-000	32 x 24	I ² C	10	55 x 40	-40 to +300	15	2.9 to 3.6	-40 to +85	TO-39 / 11.25(h) x 9.3(d)
MLX90641ESF-BCA-000	16 x 12 (192)	I ² C	5	110 x 75	-40 to +300	12	3 to 3.6	-40 to +125	TO-39 / 5.7(h) x 9.3(d)
MLX90641ESF-BCB-000	16 x 12 (192)	I ² C	10	55 x 40	-40 to +300	12	3 to 3.6	-40 to +125	TO-39 / 11.25(h) x 9.3(d)
MLX90641KSF-BCA-000	16 x 12 (192)	I ² C	5	110 x 75	-40 to +300	12	3 to 3.6	-40 to +125	TO-39 / 5.7(h) x 9.3(d)
MLX90641KSF-BCB-000	16 x 12 (192)	I ² C	10	55 x 40	-40 to +300	12	3 to 3.6	-40 to +125	TO-39 / 11.25(h) x 9.3(d)

Panasonic

Part Number	Pixel Array	Output Interface	Detection Range (m)	Field of View (deg)	Object Temperature Range (°C)	Current Consumption (mA)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
AMG8833	64 (8 x 8)	I ² C	7	60 x 60	0 to +80	4.5	3.3	-20 to +80	11.6 x 8.0 x 4.3
AMG8834	64 (8 x 8)	I ² C	7	60 x 60	-20 to +100	4.5	3.3	-20 to +80	11.6 x 8.0 x 4.3
AMG8853	64 (8 x 8)	I ² C	7	60 x 60	0 to +80	4.5	5	-20 to +80	11.6 x 8.0 x 4.3
AMG8854	64 (8 x 8)	I ² C	7	60 x 60	-20 to +100	4.5	5	-20 to +80	11.6 x 8.0 x 4.3
AMG8854M01	64 (8 x 8)	I ² C (5-pin connector)	7	35.6 x 35.6	-20 to +100	6	5	-20 to +100	25 x 16 x 6.93

OCCUPANCY – MOTION / Radar



Part Number	Detection Range (m)	Operating Frequency (GHz)	Output Current (mA)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
BGT24AR2E6433XUMA1	80-100 m @ 400 mW	24.00 to 24.25	90	3.3	-40 to +125	VQFN-32
BGT24AR4E6433XUMA1	80-100 m @ 730 mW	24.00 to 24.25	220	3.3	-40 to +125	VQFN-32
BGT24AT2E6433XUMA1	80-100 m @ 1000 mW	24.00 to 24.25	280	3.3	-40 to +125	VQFN-32
BGT24ATR11E6433XUMA1	80-100 m @ 630 mW	24.00 to 24.25	150	3.3	-40 to +125	VQFN-32
BGT24ATR12E6433XUMA1	80-100 m @ 900 mW	24.00 to 24.25	210	3.3	-40 to +125	VQFN-32
BGT24LTR11N16E6327XTSA1	20 m @ 180 mW	24.00 to 24.25	45	3.3	-40 to +85	TSNP-16-9
BGT24MR2E6327XUMA1	40 m @ 500 mW	24.00 to 24.25	90	3.3	-40 to +105	VQFN-32
BGT24MTR11E6327XUMA1	40 m @ 500 mW	24.00 to 26.00	150	3.3	-40 to +105	VQFN-32
BGT24MTR12E6327XUMA1	40 m @ 500 mW	24.00 to 24.25	210	3.3	-40 to +105	VQFN-32

RCS= 1m² for MR, MTR and LTR products; RCS= 10m² for ATR, AT, and AR products; Power rated at continuous wave operation



Part Number	Description	Resolution	Pixel Size (µm)	Frame Rate (fps)	Optical Format	Output Interface	Temperature	Sunlight Robustness	Modulation Frequency	Package Type
MLX75023RTF-BAB-000	Automotive ToF Sensor, without cover tape	320 x 240	15 x 15	150	1/3"	analog	-40 to +105	120klux	12 to 40	GBGA
MLX75023RTF-BAB-001	Automotive ToF Sensor, with cover tape	320 x 240	15 x 15	150	1/3"	analog	-40 to +105	120klux	12 to 40	GBGA
MLX75023STF-BAB-000	ToF Sensor, without cover tap	320 x 240	15 x 15	150	1/3"	analog	-20 to +85	120klux	12 to 40	GBGA
MLX75023STF-BAB-001	ToF Sensor, with cover tap	320 x 240	15 x 15	150	1/3"	analog	-20 to +85	120klux	12 to 40	GBGA
MLX75024RTF-GAA-000	Automotive ToF Sensor, without cover tape	320 x 240	15 x 15	150	1/3"	analog	-40 to +105	120klux	12 to 40	GBGA
MLX75024RTF-GAA-001	Automotive ToF Sensor, with cover tape	320 x 240	15 x 15	150	1/3"	analog	-40 to +105	120klux	12 to 40	GBGA
MLX75024STF-GAA-000	ToF Sensor, without cover tap	320 x 240	15 x 15	150	1/3"	analog	-20 to +85	120klux	12 to 40	GBGA
MLX75024STF-GAA-001	ToF Sensor, with cover tap	320 x 240	15 x 15	150	1/3"	analog	-20 to +85	120klux	12 to 40	GBGA
MLX75123RLA-BAG-000-RE	Automotive ToF Companion Chip	320 x 240	–	150	1/3"	12-bit Parallel with I ² C for control	-40 to +105	120klux	12 to 40	AGFN
MLX75123SLA-BAG-000-RE	ToF Companion Chip	320 x 240	–	150	1/3"	12-bit Parallel with I ² C for control	-40 to +105	120klux	12 to 40	AGFN

*Note: MLX7502x and MLX7512x must be used together, ToF= Time of Flight

Panasonic

Grid-EYE® Infrared Array Sensors

Grid-EYE® Infrared Array Sensor Narrow Angle Type

- Narrow Angle Field of View Of 35.6 Degrees
- Mount on PCB Board
- Module Type
- Environmentally Friendly
- RoHS and REACH Compliant



Grid-EYE® Infrared Array Sensor Unit

- Increase the detection area up to 3.8m squared
- Preloaded firmware capable of detecting up to 8 people
- Tracks direction of movement
- Transmits information via RS485 Modbus protocol





Panasonic

Panasonic's Passive Infrared (PIR) Motion Sensors Product Line Expands Significantly

EKMB and EKMC Series now include Analog Output, New Lenses, and New Sensitivities for Digital Output

Panasonic introduces its PIR Motion Sensors line extension. High density, long distance lens type has a concentrated detection area to more accurately detect movement at longer distances from 12m to 17m for high bay ceiling installations. Slight Motion Type with wide detection area to cover an entire room with one sensor and can pick up small or slight motions at up to 2.5m distances. Analog Output provides the highest level of control and flexibility allowing the user to adjust sensitivity levels for custom applications. Digital Output with High Sensitivity allows objects to be detected more easily at longer distances without needing a larger lens. Digital Output with Low Sensitivity can be used to shorten detection distance as well as reduce the change of false triggering.

Features and Benefits:

- Wide variety of lenses and various sensitivity types all with the same footprint
- All Panasonic PIRs are the same footprint allowing users to interchange Sensors without redesigning the board
- Plug and play solution saves design time. No additional components needed
- Panasonic PIRs include amplifier and comparator circuitry inside a shielded TO-5 Metal can to protect against EMF noise
- High signal to noise ratio to prevent false triggers
- Available in three colors: White, Black, And Pearl White
- RoHS and REACH Compliant

Visit na.industrial.panasonic.com today for details.



SENSORS



OPTICAL COMBO

Ambient Light and Proximity 87

Gesture, Color, Proximity and Ambient Light 89



Part Number	Detection Range (mm)	Output Type	Output Range	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
TSL27721	~45	I ² C (V _{DD})	16-bit	2.4 to 3.6	0.200	-30 to +70	DFN8 2 x 2 x 0.65
TSL27723	~45	I ² C (1.8V)	16-bit	2.7 to 3.6	0.200	-30 to +70	DFN8 2 x 2 x 0.65
TMD27721	~45	I ² C (V _{DD})	16-bit	2.2 to 3.6	0.195	-30 to +85	MOD8 2.36 x 3.94 x 1.35
TMD27723	~45	I ² C (1.8V)	16-bit	2.2 to 3.6	0.195	-30 to +85	MOD8 2.36 x 3.94 x 1.35
TMD27253	~15	I ² C	16-bit	1.7 to 2.0	0.08	-30 to +85	OLGA8 2 x 3.65 x 1
TSL27403	~10	I ² C	16-bit	1.7 to 2.0	0.09	-30 to +85	QFN10 2 x 2 x 0.5
TMD27253	~15	I ² C	16-bit	1.7 to 2.0	0.105	-30 to +85	MOD8 2 x 3.65 x 1



Part Number	Detection Range (mm)	Output Type	Output Range	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
VCNL4010	200	I ² C	16-bit	2.5 to 3.6	0.005	-25 to +85	SMD 3.9 x 3.9 x 0.7
VCNL4020	200	I ² C	16-bit	2.5 to 3.6	0.005	-25 to +85	SMD 4.9 x 2.4 x 0.8
VCNL4020X01	200	I ² C	16-bit	2.5 to 3.6	0.005	-40 to +105	SMD 4.9 x 2.4 x 0.8
VCNL4040M30E	200	I ² C	16-bit	2.5 to 3.6	0.3	-40 to +85	SMD 4.0 x 2.0 x 1.1
VCNL4200	1500	I ² C	12 or 16-bit	2.5 to 3.6	0.35	-40 to +85	SMD 8.0 x 3.0 x 1.8

Bosch MEMS sensors for wearable applications



BOSCH
Invented for life

BMI270

Inertial Measurement Unit

The BMI270 includes intuitive gesture, context and activity recognition with an integrated plug-and-play step counter, which is specially optimized for accurate step counting in wrist-worn devices.

A grayscale background image showing a woman wearing a VR headset, looking upwards with an open mouth. In the background, several robotic arms are visible. In the foreground, there is a car's gear shift and some electronic components on a table.

DIGITAL — AND — ANALOG SENSORS

PROXIMITY 1.5 METER | AMBIENT LIGHT | UV LIGHT
HEART RATE | TRANSMISSIVE | PROXIMITY 0.2 METER
COLOR | IR LIGHT | GESTURES | PRESENCE

www.vishay.com/optoelectronics

© 2019 VISHAY INTERTECHNOLOGY, INC. ALL RIGHTS RESERVED.

A **WORLD OF**
SOLUTIONS™



Part Number	Integrated Gesture Control	Maximum Proximity Range (cm)	ALS Dynamic Range (Lux)	Integrated Color Sensing	Output Interface	Supply Voltage (V)	Temperature Range (°C)	Package Type / Size (mm)
TMG39921	Yes	~15	60,000	Yes	I ² C (V _{DD})	2.4 to 3.6	-30 to +85	MOD8 2 x 3.94 x 1.35
TMG39923	Yes	~15	60,000	Yes	I ² C (1.8V)	2.4 to 3.6	-30 to +85	MOD8 2 x 3.94 x 1.35
TMG49033	Yes	~15	100,000	Yes	I ² C	1.7 to 2.0	-30 to +85	MOD8 2 x 5 x 1
TCS37727	No	~45	60,000	Yes	I ² C	2.7 to 3.6	-30 to +70	DFN 2 x 2.4 x 0.65
TMD49033	No	~15	100,000	Yes	I ² C	1.7 to 2.0	-30 to +85	MOD8 2 x 5 x 1
TMD3725	No	~15	60,000	Yes	I ² C	1.7 to 2.0	-30 to +85	OLGA8 2 x 3.65 x 1
TMD37024VC	No	~15	60,000	Yes	I ² C	1.7 to 2.0	-30 to +85	OLGA8 1.44 x 2.84 x 0.65
TCS3701	No	~15	60,000	Yes	I ² C	1.7 to 2.0	-30 to +70	QFN12 2 x 2.5 x 0.5
TCS3707	No	~15	60,000	Yes	I ² C	1.7 to 2.0	-30 to +70	QFN12 2 x 2.5 x 0.5



Part Number	Integrated Gesture Control	Maximum Proximity Range (cm)	ALS Dynamic Range (Lux)	Integrated Color Sensing	Output Interface	Supply Voltage (V)	Temperature Range (°C)	Package Type / Size (mm)
VCNL4035X01	Yes Drives up to 3 external emitters	60	16 bit Selectable: 262, 524, 1048, 2096, 4192	No	I ² C	2.5 to 3.6	-40 to +105	4.0 x 2.36 x 0.75H



POSITION – SPEED

3D Magnetic Position Sensor	91
Magnetic Rotational Speed Sensor	97
Magnetic Speed Sensor.....	97
Optical Switch.....	98
Industrial Magnetic Rotary Encoder	98
Automotive Certified Magnetic Rotary Encoder.....	98
Industrial Magnetic Linear Encoder.....	99
Magnetic Angular Position Sensor.....	100
Passive Position Sensor.....	102

am 

 **infineon**

Melexis 

MPS

muRata
INNOVATOR IN ELECTRONICS

NXP

VISHAY 

Part Number	Output Channel	Output Type	Magnetic Field Range (mT)	Output Resolution (%VDD/LSBB)	Output Current (mA)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
TLI493DA2B6HTSA1	3D Magnetic	Digital	±160	—	—	2.8 to 3.5	3.4	-40 to +105	TSOP-6
TLE493DA2B6HTSA1	3D Magnetic	Digital	±160	—	—	2.8 to 3.5	3.7	-40 to +125	TSOP-6
TLE493DW2B6A0HTSA1	3D Magnetic	Digital	±160	—	—	2.8 to 3.5	3.4	-40 to +125	TSOP-6
TLE493DW2B6A1HTSA1	3D Magnetic	Digital	±160	—	—	2.8 to 3.5	3.4	-40 to +125	TSOP-6
TLE493DW2B6A2HTSA1	3D Magnetic	Digital	±160	—	—	2.8 to 3.5	3.4	-40 to +125	TSOP-6
TLE493DW2B6A3HTSA1	3D Magnetic	Digital	±160	—	—	2.8 to 3.5	3.4	-40 to +125	TSOP-6

Part Number	Output Channel	Output Type	Magnetic Field Range (gauss)	Output Resolution (%V _{DD} /LSB)	Output Current (mA)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
MLX90316SDC-BCG-000	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 18	6	-20 to +85	SOIC8
MLX90316EDC-BCG-000	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 18	6	-40 to +85	SOIC8
MLX90316KDC-BCG-000	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 18	6	-40 to +125	SOIC8
MLX90316LDC-BCG-000	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 18	6	-40 to +150	SOIC8
MLX90316EGO-BCG-000	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 18	6	-40 to +85	TSSOP16
MLX90316KGO-BCG-000	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 18	6	-40 to +125	TSSOP16
MLX90316LGO-BCG-000	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 18	6	-40 to +150	TSSOP16
MLX90316KDC-BCG-200	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 18	6	-40 to +125	SOIC8
MLX90316KGO-BCG-200	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 18	6	-40 to +125	TSSOP16
MLX90316KDC-BCG-300	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 18	6	-40 to +125	SOIC8
MLX90316KGO-BCG-300	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 18	6	-40 to +125	TSSOP16
MLX90316EDC-BDG-100	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 18	6	-40 to +85	SOIC8
MLX90316KDC-BDG-100	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 18	6	-40 to +125	SOIC8
MLX90316LDC-BDG-100	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 18	6	-40 to +150	SOIC8
MLX90316EGO-BDG-100	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 18	6	-40 to +85	TSSOP16
MLX90316KGO-BDG-100	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 18	6	-40 to +125	TSSOP16
MLX90316LGO-BDG-100	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 18	6	-40 to +150	TSSOP16
MLX90316LDC-BDG-102	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 18	6	-40 to +150	SOIC8
MLX90316LDC-BCS-000	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 18	6	-40 to +150	SOIC8
MLX90324LDC-DBO-000	1	Analog, PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +150	SOIC8
MLX90324LDC-DBO-100	1	Analog, PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +150	SOIC8
MLX90324LGO-DBO-000	1	Analog, PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +150	TSSOP16
MLX90333SDC-BCH-000	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 18	6	-20 to +85	SOIC8
MLX90333EDC-BCH-000	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 5.5	6	-40 to +85	SOIC8
MLX90333EDC-BCH-100	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 5.5	6	-40 to +85	SOIC8
MLX90333EDC-BCT-000	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 5.5	6	-40 to +85	SOIC8

1 gauss = 0.1 mT



Part Number	Output Channel	Output Type	Magnetic Field Range (gauss)	Output Resolution (%V _{DD} /LSB)	Output Current (mA)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
MLX90333KDC-BCH-000	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 5.5	6	-40 to +125	SOIC8
MLX90333KDC-BCH-100	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 5.5	6	-40 to +125	SOIC8
MLX90333KDC-BCT-000	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 5.5	6	-40 to +125	SOIC8
MLX90333LDC-BCH-000	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 5.5	6	-40 to +150	SOIC8
MLX90333LDC-BCH-100	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 5.5	6	-40 to +150	SOIC8
MLX90333LDC-BCT-000	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 5.5	6	-40 to +150	SOIC8
MLX90333EG0-BCH-000	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 5.5	6	-40 to +85	TSSOP16
MLX90333EG0-BCH-100	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 5.5	6	-40 to +85	TSSOP16
MLX90333EG0-BCT-000	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 5.5	6	-40 to +85	TSSOP16
MLX90333KG0-BCH-000	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 5.5	6	-40 to +125	TSSOP16
MLX90333KG0-BCH-100	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 5.5	6	-40 to +125	TSSOP16
MLX90333KG0-BCT-000	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 5.5	6	-40 to +125	TSSOP16
MLX90333LG0-BCH-000	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 5.5	6	-40 to +150	TSSOP16
MLX90333LG0-BCH-100	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 5.5	6	-40 to +150	TSSOP16
MLX90333LG0-BCT-000	3	Analog, PWM, SPI	200 to 700	1	15	4.5 to 5.5	6	-40 to +150	TSSOP16
MLX90340LG0-AAA-000	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +150	TSSOP16
MLX90340LDC-AAA-000	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +150	SOIC8
MLX90340EG0-AAA-000	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +85	TSSOP16
MLX90340EDC-AAA-000	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +85	SOIC8
MLX90340EDC-AAA-200	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +85	SOIC8
MLX90340EDC-AAA-100	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +85	SOIC8
MLX90340EDC-AAA-300	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +85	SOIC8
MLX90340EDC-AAA-400	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +85	SOIC8
MLX90340SDC-AAA-000	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-20 to +85	SOIC8
MLX90340SDC-AAA-200	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-20 to +85	SOIC8
MLX90340SDC-AAA-100	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-20 to +85	SOIC8
MLX90340SDC-AAA-300	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-20 to +85	SOIC8
MLX90340SDC-AAA-400	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-20 to +85	SOIC8
MLX90360EDC-ACD-000	3	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +85	SOIC8
MLX90360EG0-ACD-000	3	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +85	TSSOP16
MLX90360KDC-ACD-000	3	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +125	SOIC8
MLX90360KG0-ACD-000	3	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +125	TSSOP16
MLX90360LDC-ACD-000	3	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +150	SOIC8
MLX90360LG0-ACD-000	3	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +150	TSSOP16
MLX90360LDC-ACD-200	3	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +150	SOIC8
MLX90363EDC-ABB-000	1	SPI	200 to 700	1	15	4.5 to 18	6	-40 to +85	SOIC8

1 gauss = 0.1 mT

Part Number	Output Channel	Output Type	Magnetic Field Range (gauss)	Output Resolution (%V _{DD} /LSB)	Output Current (mA)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
MLX90363EGO-ABB-000	1	SPI	200 to 700	1	15	4.5 to 18	6	-40 to +85	TSSOP16
MLX90363KDC-ABB-000	1	SPI	200 to 700	1	15	4.5 to 18	6	-40 to +125	SOIC8
MLX90363KGO-ABB-000	1	SPI	200 to 700	1	15	4.5 to 18	6	-40 to +125	TSSOP16
MLX90363LDC-ABB-000	1	SPI	200 to 700	1	15	4.5 to 18	6	-40 to +150	SOIC8
MLX90363LGO-ABB-000	1	SPI	200 to 700	1	15	4.5 to 18	6	-40 to +150	TSSOP16
MLX90364LVS-ADD-200	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +150	DMP4
MLX90364LVS-ADD-251	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +150	DMP4
MLX90364LVS-ADD-203	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +150	DMP4
MLX90364LVS-ADE-201	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +150	DMP4
MLX90365EDC-ABD-000	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +85	SOIC8
MLX90365EGO-ABD-000	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +85	TSSOP16
MLX90365KDC-ABD-000	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +125	SOIC8
MLX90365KGO-ABD-000	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +125	TSSOP16
MLX90365LDC-ABD-000	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +150	SOIC8
MLX90365LGO-ABD-000	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +150	TSSOP16
MLX90365LGO-ABE-000	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +150	TSSOP16
MLX90365LDC-ABD-200	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +150	SOIC8
MLX90365LDC-ABE-000	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +150	SOIC8
MLX90366LVS-ADU-250	1	SENT	200 to 700	1	15	4.5 to 18	6	-40 to +150	DMP4
MLX90366LVS-ADU-251	1	SENT	200 to 700	1	15	4.5 to 18	6	-40 to +150	DMP4
MLX90366LVS-ADU-253	1	SENT	200 to 700	1	15	4.5 to 18	6	-40 to +150	DMP4
MLX90367EDC-ABU-000	1	SENT	200 to 700	1	15	4.5 to 18	6	-40 to +85	SOIC8
MLX90367EGO-ABU-000	1	SENT	200 to 700	1	15	4.5 to 18	6	-40 to +85	TSSOP16
MLX90367KDC-ABU-000	1	SENT	200 to 700	1	15	4.5 to 18	6	-40 to +125	SOIC8
MLX90367KGO-ABU-000	1	SENT	200 to 700	1	15	4.5 to 18	6	-40 to +125	TSSOP16
MLX90367LDC-ABU-000	1	SENT	200 to 700	1	15	4.5 to 18	6	-40 to +150	SOIC8
MLX90367LGO-ABU-000	1	SENT	200 to 700	1	15	4.5 to 18	6	-40 to +150	TSSOP16
MLX90367EDC-ABV-000	1	SENT	200 to 700	1	15	4.5 to 18	6	-40 to +85	SOIC8
MLX90367EGO-ABV-000	1	SENT	200 to 700	1	15	4.5 to 18	6	-40 to +85	TSSOP16
MLX90367KDC-ABV-000	1	SENT	200 to 700	1	15	4.5 to 18	6	-40 to +125	SOIC8
MLX90367KGO-ABV-000	1	SENT	200 to 700	1	15	4.5 to 18	6	-40 to +125	TSSOP16
MLX90367LDC-ABV-000	1	SENT	200 to 700	1	15	4.5 to 18	6	-40 to +150	SOIC8
MLX90367LDC-ABX-000	1	SENT	200 to 700	1	15	4.5 to 18	6	-40 to +150	SOIC8
MLX90367LGO-ABV-000	1	SENT	200 to 700	1	15	4.5 to 18	6	-40 to +150	TSSOP16
MLX90367LGO-ABX-000	1	SENT	200 to 700	1	15	4.5 to 18	6	-40 to +150	TSSOP16
MLX90367LGO-ACU-000	1	SENT	200 to 700	1	15	4.5 to 18	6	-40 to +150	TSSOP16

1 gauss = 0.1 mT




Part Number	Output Channel	Output Type	Magnetic Field Range (gauss)	Output Resolution (%V _{DD} /LSB)	Output Current (mA)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
MLX90371GDC-BCC-100	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	SOIC8
MLX90371GDC-BCC-200	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	SOIC8
MLX90371GDC-BCC-300	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	SOIC8
MLX90371GG0-BCC-100	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	TSSOP16
MLX90371GG0-BCC-200	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	TSSOP16
MLX90371GG0-BCC-300	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	TSSOP16
MLX90371GG0-BCC-500	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90371GVS-BCC-100	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90371GVS-BCC-150	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90371GVS-BCC-101	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90371GVS-BCC-151	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90371GVS-BCC-103	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90371GVS-BCC-153	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90371GVS-BCC-200	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90371GVS-BCC-250	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90371GVS-BCC-201	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90371GVS-BCC-251	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90371GVS-BCC-203	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90371GVS-BCC-253	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90371GVS-BCC-300	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90371GVS-BCC-350	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90371GVS-BCC-301	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90371GVS-BCC-351	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90371GVS-BCC-303	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90371GVS-BCC-353	2	Analog, PWM	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90372GDC-ACC-100	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	SOIC8
MLX90372GDC-ACC-200	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	SOIC8
MLX90372GDC-ACC-300	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	SOIC8
MLX90372GG0-ACC-100	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	TSSOP16
MLX90372GG0-ACC-200	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	TSSOP16
MLX90372GG0-ACC-300	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	TSSOP16
MLX90372GG0-ACC-500	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	TSSOP16
MLX90372GVS-ACC-300	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90372GVS-ACC-301	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90372GVS-ACC-303	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90372GVS-ACC-308	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4

1 gauss = 0.1 mT

MLX90340

ANALOG RATIOMETRIC / PWM

TRIAxis® POSITION SENSOR



- ✓ Absolute position sensor - $\pm 1^\circ$ accuracy - 12 bits resolution
- ✓ Programmable linearization algorithm: arbitrary points (4 points) or 17 points piecewise linear output compensation
- ✓ Programmable magnetic mapping XY, XZ, YZ
- ✓ 5 V supply
- ✓ Magnetic field range from 20 to 70 mT
- ✓ SOIC-8 package and redundant TSSOP-16 package
- ✓ Temperature range:
Heavy-duty industrial $[-40 \text{ to } 150^\circ\text{C}]$
Industrial $[-40 \text{ to } 85^\circ\text{C}]$
Consumer $[-20 \text{ to } 85^\circ\text{C}]$
- ✓ Ratiometric Analog output or PWM Open drain/Push-pull output [100 Hz to 1 kHz]
- ✓ 4 different pre-programmed analog version [90, 180, 270, 360°]



Part Number	Output Channel	Output Type	Magnetic Field Range (gauss)	Output Resolution (%V _{DD} /LSB)	Output Current (mA)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
MLX90372GDC-ACE-100	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	SOIC8
MLX90372GDC-ACE-200	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	SOIC8
MLX90372GDC-ACE-300	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	SOIC8
MLX90372GG0-ACE-100	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	TSSOP16
MLX90372GG0-ACE-200	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	TSSOP16
MLX90372GG0-ACE-300	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	TSSOP16
MLX90372GVS-ACE-100	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90372GVS-ACE-101	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90372GVS-ACE-103	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90372GVS-ACE-108	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90372GVS-ACE-200	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90372GVS-ACE-201	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90372GVS-ACE-203	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90372GVS-ACE-208	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90372GVS-ACE-300	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90372GVS-ACE-301	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90372GVS-ACE-303	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90372GVS-ACE-308	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90372GVS-ACE-350	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90372GVS-ACE-357	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90372GVS-ADE-310	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90372GVS-ADE-311	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90372GVS-ADE-313	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90372GVS-ADE-318	2	PWM, SENT	200 to 700	1	15	4.5 to 18	6	-40 to +160	DMP4
MLX90393SLW-ABA-011	2	SPI, I2C	200 to 700	1	15	2.2 to 3.6	6	-20 to +85	QFN16
MLX90393ELW-ABA-011	2	SPI, I2C	200 to 700	1	15	2.2 to 3.6	6	-40 to +85	QFN16
MLX90393SLW-ABA-012	2	SPI, I2C	200 to 700	1	15	2.2 to 3.6	6	-20 to +85	QFN16
MLX90393ELW-ABA-012	2	SPI, I2C	200 to 700	1	15	2.2 to 3.6	6	-40 to +85	QFN16
MLX90393SLW-ABA-013	2	SPI, I2C	200 to 700	1	15	2.2 to 3.6	6	-20 to +85	QFN16
MLX90393ELW-ABA-013	2	SPI, I2C	200 to 700	1	15	2.2 to 3.6	6	-40 to +85	QFN16
MLX90393SLW-ABA-014	2	SPI, I2C	200 to 700	1	15	2.2 to 3.6	6	-20 to +85	QFN16
MLX90393ELW-ABA-014	2	SPI, I2C	200 to 700	1	15	2.2 to 3.6	6	-40 to +85	QFN16
MLX90380LGO-BAB-103	1	sine/cosine	200 to 700	1	15	4.5 to 5.5	6	-40 to +150	TSSOP16
MLX90380LGO-BAB-023	1	sine/cosine	200 to 700	1	15	4.5 to 5.5	6	-40 to +150	TSSOP16
MLX90380LDC-BAB-100	1	sine/cosine	200 to 700	1	15	4.5 to 5.5	6	-40 to +150	SOIC8
MLX90380LDC-BAB-120	1	sine/cosine	200 to 700	1	15	4.5 to 5.5	6	-40 to +150	SOIC8
MLX90380LDC-BAB-010	1	sine/cosine	200 to 700	1	15	4.5 to 5.5	6	-40 to +150	SOIC8

1 gauss = 0.1 mT

Part Number	Typ. Sensing Distance (mm)	Tooth Frequency (Hz)	Target	Output Type	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
MLX90217LUA-CAA-000	1 to 3	800	Gear tooth or lobe	Digital	5	-40 to +150	through hole
MLX90217LUA-CCA-000	1 to 3	800	Gear tooth or lobe	Digital	5	-40 to +150	through hole
MLX90217LVA-BBA-000	1 to 3	800	Gear tooth or lobe	Digital	5	-40 to +150	through hole
MLX90254LVA-BBA-000	1 to 3	800	Gear tooth or lobe	Digital	5	-40 to +150	through hole



Part Number	Typ. Sensing Distance (mm)	Tooth Frequency (Hz)	Target	Output Type	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
KMI17/4	0.5 to 2.8	0 to 20,000	Ferromagnetic gear wheel (passive)	Current	4.5 to 16	-40 to +150	SIP2, SOT453E
KMI23/2	2.4 to 3.2	0 to 2,500	Multipole wheel (active)	Current	6.8 to 16	-40 to +150	SIP2, SOT453E
KMI23/4	2.4 to 3.2	0 to 2,500	Ferromagnetic gear wheel (passive)	Current	6.8 to 16	-40 to +150	SIP2, SOT453E
KMI25/2	2.4 to 3.2	0 to 2,500	Multipole wheel (active)	Digital protocol	6.8 to 16	-40 to +150	SIP3, SOT477A
KMI25/4	2.4 to 3.2	0 to 2,500	Ferromagnetic gear wheel (passive)	Digital protocol	6.8 to 16	-40 to +150	SIP3, SOT477A
KMI16/1	2.4 to 3.2	0 to 25,000	Ferromagnetic gear wheel (passive)	Voltage	4.5 to 16	-40 to +150	SIP3, SOT477A

Part Number	Pre-Induction (mT)	Output Type	Differential Induction (mT)	Supply Current (mA)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
TLE49215UHALA1	-500 to +500	Voltage	-80 to +80	3.8 to 8.8	4.5 to 24	-40 to +170	SSO-4
TLE4922XANFHALA1	-400 to +400	Voltage	-400 to +400	3.5 to 7.0	4.5 to 16	-40 to +155	SSO-4

Part Number	Pre-Induction (mT)	Output Type	Differential Induction (mT)	Supply Current (mA)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
MLX90217LUA-CAA-000	1 to 3	Digital	500	3	5	-40 to +150	Through hole
MLX90217LUA-CCA-000	1 to 3	Digital	500	3	5	-40 to +150	Through hole
MLX90217LVA-BBA-000	1 to 3	Digital	500	3	5	-40 to +150	Through hole
MLX90254LVA-BBA-000	1 to 3	Digital	100	8.5	5	-40 to +150	Through hole

POSITION - SPEED / Optical Switch



Part Number	Slot Width (mm)	Forward Voltage (V)	Peak Wavelength (nm)	Collector Current (ON State) (mA)	Dark Current Max (na)	Operating Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
TCPT1300X01	3	1.2V at IF=15mA	950	0.6	100	2.5 to 5	-40 to +105	SMD, 5.5 x 4 x 4
TCUT1300X01	3	1.2V at IF=15mA	950	0.6 x 2	100	2.5 to 5	-40 to +105	SMD, 5.5 x 4 x 4
TCPT1350X01	3	1.2V at IF=15mA	950	1.6	100	2.5 to 5	-40 to +125	SMD, 5.5 x 4 x 4
TCUT1350X01	3	1.2V at IF=15mA	950	1.6 x 2	100	2.5 to 5	-40 to +125	SMD, 5.5 x 4 x 4
TCPT1600X01	3	1.2V at IF=15mA	950	1.6	100	2.5 to 5	-40 to +105	SMD, 5.5 x 4 x 5.7
TCUT1600X01	3	1.2V at IF=15mA	950	1.6 x 2	100	2.5 to 5	-40 to +105	SMD, 5.5 x 4 x 5.7
TCUT1630X01	3	1.2V at IF=15mA	950	1.3 x 3	100	2.5 to 5	-40 to +105	SMD, 5.5 x 5.85 x 7
TCUT1800X01	3	1.2V at IF=15mA	950	1.3 x 4	100	2.5 to 5	-40 to +105	SMD, 5.5 x 4 x 5.7

POSITION - SPEED / Industrial Magnetic Rotary Encoder



Part Number	Maximum Rotational Angle	Output Type / Interface	Magnetic Field Range (mT)	Output Resolution (deg)	RPM (Max)	Hysteresis (Degree)	Supply Voltage (V)	Supply Current Max. (mA)	Operating Temperature (°C)	Package Type / Size (mm)	Package Type / Size (mm)
AS5050A	360	SPI	30 to 90	0.09 (12-bit)	—	—	3.3	8.5	-40 to +85	QFN16	4 x 4 x 0.85
AS5055A	360	I ² C, SPI, PWM	30 to 90	0.09 (12-bit)	—	—	3.3	8.5	-40 to +85	QFN16	4 x 4 x 0.85
AS5600	360	Analog, I ² C, PWM	30 to 90	12-bit	—	—	3.0 to 3.6 & 4.5 to 5.5	6.5	-40 to +125	SOIC-8	—
AS5600L	360	Analog, I ² C, PWM	30 to 90	12-bit	—	—	5.0	6.5	-40 to +125	SOIC-8, WLCSP	—

POSITION - SPEED / Automotive Certified Magnetic Rotary Encoder



Part Number	Maximum Rotational Angle	Output Type / Interface	Magnetic Field Range (mT)	Output Resolution (deg)	RPM (Max)	Hysteresis (Degree)	Supply Voltage (V)	Supply Current Max. (mA)	Operating Temperature (°C)	Package Type / Size (mm)
AS5200L	360	I ² C, PWM	10 to 90	0.09 (12-bit)	—	—	5.0	7	-40 to +125	MLF16 5x5
AS5172A/B	360	PSI5	10 to 90	0.09 (12-bit)	—	0	4.0 to 16.5	19	-40 to +150	TSSOP 14.5 x 4.4x1.2



Part Number	Maximum Rotational Angle	Output Type / Interface	Magnetic Field Range (mT)	Output Resolution (deg)	RPM (Max)	Hysteresis (Degree)	Supply Voltage (V)	Supply Current Max. (mA)	Operating Temperature (°C)	Package Type / Size (mm)
MAQ470	360	SPI, ABI	20 to 150	± 0.045	150k	—	3.3	12	-40 to +125	QFN16 3 x 3
MAQ430	360	SPI, ABI, UVW	20 to 150	± 0.045	150k	—	3.3	12	-40 to +125	QFN16 3 x 3

* NOTE: SSI= Synchronized Serial Interface
 ABI= A/B Quadrature
 UVW= BLDC Commutation
 PWM= Pulse Width Modulator

Part number	Output Type*	Magnetic Field Range (mT)	Linear Resolution	Speed (Max)	Hysteresis (lsb)	Supply Voltage nom. (V)	Supply Current Max (mA)	Operating Temperature (°C)	Package
AS5304	ABI	5 to 60	25 (µm)	20 meter/sec	1.5	5.0	35	-40 to +125	TSSOP-20
AS5306	ABI	5 to 60	15 (µm)	12 meter/sec	1.5	5.0	30	-40 to +125	TSSOP-20
AS5311	SSI, PWM, ABI	10 to 40	0,488 (µm)	0.65 meter/sec	2	3.3 or 5.0	21	-40 to +125	TSSOP-20
AS5510	I ² C	10 to 50	10-bit	–	0	3.0	3.5	-30 to +85	WLCSP

* NOTE: SSI= Synchronized Serial Interface
 ABI= A/B Quadrature
 UFW= BLDC Commutation
 PWM= Pulse Width Modulator



Check out leading
ams position sensors
in the position sensor
section of this guide.



ams Position Sensors for Angle Sensing

Accurate position measurement:

- Precise position sensing with immunity against stray fields

Long life:

- Robust and wear-free solutions for position sensing in harsh environments

Flexible solution:

- Different outputs are needed and adjustable to any system



Part Number	Supply Voltage (V)	Maximum Rotational Angle	Output Range	Output Type	Temperature Range (°C)	Package Type / Size (mm)
TLE5009E1000FUMA1	3.3	360°	0 to 360°	voltage	-40 to +150	DSO-8
TLE5009E1010FUMA1	3.3	360°	0 to 360°	voltage	-40 to +150	DSO-8
TLE5009E2000FUMA1	5	360°	0 to 360°	voltage	-40 to +150	DSO-8
TLE5009E2010FUMA1	5	360°	0 to 360°	voltage	-40 to +150	DSO-8
TLE5012BE1000XUMA1	5	360°	0 to 360°	voltage	-40 to +150	DSO-8
TLE5012BE3005XUMA1	5	360°	0 to 360°	voltage	-40 to +150	DSO-8
TLE5012BE5000XUMA1	5.0	360°	0 to 360°	voltage	-40 to +150	DSO-8
TLE5012BE9000XUMA1	5.0	360°	0 to 360°	voltage	-40 to +150	DSO-8
TLE5011FUMA1	3.0 to 5.5	360°	0 to 360°	Voltage	-40 to +150	DSO-8
TLI5012BE1000XUMA1	3.0 to 5.5	360°	–	Voltage	-40 to +125	DSO-8
TLE5501E0001XUMA1	2.7 to 5.5	360°	–	Voltage	-40 to +150	DSO-8



Part Number	Supply Voltage (V)	Maximum Rotational Angle	Output Range	Output Type	Temperature Range (°C)	Package Type / Size (mm)
MA302	3.3	360	0-65535	SPI, ABI, UVW	-40 to +125	QFN16 3 x 3
MA702	3.3	360	0-65535	SPI, ABI	-40 to +125	QFN16 3 x 3
MA780	3.3	360	0-65535	SPI	-40 to +125	QFN16 3 x 3
MA800	3.3	360	0-65535	SPI	-40 to +125	QFN16 3 x 3
MA102	3.3	360	0-65535	UVW	-40 to +125	QFN16 3 x 3
MA310	3.3	360	0-65535	SPI, ABI, UVW	-40 to +125	QFN16 3 x 3
MA330	3.3	360	0-65535	SPI, ABI, UVW	-40 to +125	QFN16 3 x 3
MA704	3.3	360	0-65535	SPI, ABI	-40 to +125	QFN16 3 x 3
MA710	3.3	360	0-65535	SPI, ABI	-40 to +125	QFN16 3 x 3

* NOTE: SSI= Synchronized Serial Interface
 ABI= A/B Quadrature
 UVW= BLDC Commutation
 PWM= Pulse Width Modulator

Precision Current Sensors, Magnetic Angle Sensors & More

We know sensors.

[LEARN MORE](#)



Part Number	Supply Voltage (V)	Maximum Rotational Angle	Output Range	Output Type	Temperature Range (°C)	Package Type / Size (mm)
MA730	3.3	360	0 - 65535	SPI, ABI	-40 to +125	QFN16 3 x 3
MA732	3.3	360	0 - 65535	SPI, ABI	-40 to +125	QFN16 3 x 3
MA820	3.3	360	0 - 65535	PWM	-40 to +125	QFN16 3 x 3
MA850	3.3	360	0 - 65535	ABI	-40 to +125	QFN16 3 x 3

* NOTE: SSI= Synchronized Serial Interface
 ABI= A/B Quadrature
 UYW= BLDC Commutation
 PWM= Pulse Width Modulator



Part Number	Supply Voltage (V)	Maximum Rotational Angle	Output Range	Output Type	Temperature Range (°C)	Package Type / Size (mm)
KMA210	4.5 to 5.5	180°	~0 to ~5.0V	1 analog output linear	-40 to +160	SIP-3; SOT-1288
KMA215	4.5 to 5.25	180°	~0 to ~5.0V	1 digital output SAE J2716 SENT	-40 to +160	SIP-3; SOT-1288
KMA220	4.5 to 5.5	180°	~0 to ~5.0V	2 analog outputs; 1 per channel	-40 to +160	SIL-4; SOT-1188-1
KMA221	4.5 to 5.5	180°	~0 to ~5.0V	1 analog output linear	-40 to +160	SIL-4; SOT-1188-1
KMZ60	2.7 to 5.5	180°	0.07 to 0.93 Vcc	Amplified sine / cosine	up to +150	SO-8; SOT-96-1
KMZ41	9 Max.	180°	0.081 peak voltage	Sine / cosine	up to +150	SO-8; SOT96-1
KMZ49	9 Max.	180°	0.067 peak voltage	Sine / cosine	up to +150	SO-8; SOT-96-1
X3G-OH047	9 Max.	180°	0.067 peak voltage	Sine / cosine	up to +150	Double die; sawn wafer on foil
X3G-OH048	9 Max.	180°	0.067 peak voltage	Sine / cosine	up to +150	Single die; sawn wafer on foil
X3T-OH047	9 Max.	180°	0.067 peak voltage	Sine / cosine	up to +150	Double die; taped on reel
X3T-OH048	9 Max.	180°	0.067 peak voltage	Sine / cosine	up to +150	Single die; taped on reel



Part Number	Supply Voltage (V)	Maximum Rotational Angle	Output Range	Output Type	Temperature Range (°C)	Package Type / Size (mm)
981HE	Standard : 5V _{DC} ±10%	360°	0.5V to 4.5V	Analog / PWM	-45 to +125	Throttle type design
34THE	Standard : 5V _{DC} ±10%	3600°	0.05V to 4.95V	Analog / PWM / SPI	-40 to +85	Bush and servo mount
151HE	Standard : 5V _{DC} ±10%	360°	0.5V to 4.5V	Analog / PWM	-45 to +125	Servo mount
RAME027	5VDC ± 0,25V	360°	0.5V to 4.5V	Analog	-25 to +75	Servo mount

POSITION - SPEED / Passive Position Sensor



Part Number	Standard Resistance	Resistance Tolerance	Temperature Coefficient	Max. Voltage (V)	Rotational Life	Operating Temperature (°C)	Package Type / Size (mm)
SV01A103AEA01B00	10k Ω	±30%	500ppm/°C	5V _{DC}	1M cycles	-40 to +85	SMD 11 x 12
SV01A103AEA01R00	10k Ω	±30%	500ppm/°C	5V _{DC}	1M cycles	-40 to +85	SMD 11 x 12
SV03A103AEA01B00	10k Ω	±30%	500ppm/°C	5V _{DC}	300k cycles	-40 to +85	SMD 11 x 12
SV03A103AEA01R00	10k Ω	±30%	500ppm/°C	5V _{DC}	300k cycles	-40 to +85	SMD 11 x 12
SV04A103AEA41R00	10k Ω	±30%	500ppm/°C	5V _{DC}	2M cycles	-40 to +85	SMD 11 x 12



Part Number	Standard Resistance	Resistance Tolerance	Temperature Coefficient	Max. Voltage (V)	Rotational Life	Operating Temperature (°C)	Package Type / Size (mm)
357	1K - 20k	± 20%	± 600 ppm/°C	Depends of total track ohmic value	5,000,000	-55 to +125	Bushing mount
534	100 - 100k	± 5%	20 ppm/°C	14.1 - 447	1,000,000	-55 to +125	Bush and servo mount design
38L	Function of requested stroke : 25mm to 150mm	± 20%	Ohm value: Typical ± 600 ppm/°C Volt ratio: Typically ± 20 ppm/V/V/°C	Depends of total track ohmic value	25,000,000	-55 to +125	Linear sensor smallest size (diameter : 9,52mm)
LMF	Function of requested stroke : 25mm to 1000mm	± 20%	Ohm value: Typical ± 600 ppm/°C Volt ratio: Typically ± 20 ppm/V/V/°C	Depends of total track ohmic value	25,000,000	-55 to +125	Open sensor + Wiper
115L	Function of requested stroke : 25mm to 1000mm	± 20%	Ohm value: Typical ± 600 ppm/°C Volt ratio: Typically ± 20 ppm/V/V/°C	Depends of total track ohmic value	40,000,000	-55 to +125	Linear sensor with integrated connector
UIPMA	4,7 kohms	± 30%	-300 ± 300 ppm/°C	0,1 W/cm of travel	3 000 000 (more on request)	-10 to +50 (more on request)	Ultra Flat (< 3)
PP12SR	4,7 kohms	± 20%	-300 ± 300 ppm/°C	0,5 W max	5000000	-55 to +125	Diameter 12
PP27BS	10 kohms	± 20%	-300 ± 300 ppm/°C	1 W Max	5000000	-55 to +105	Diameter 27
RP12	from 2,2 kohms to 22 kohms for a length from 10 mm to 300 mm	+ -20%	-300 ± 300 ppm/°C	Depends of travel	20000000	-40 to +105	Diameter 12

MagAlpha Rotary Magnetic Angle Sensors

High reliability contactless angle sensing for all rotary applications

MagAlpha Sensor Benefits

Used to measure angle, speed, or position of a rotating shaft


Contactless sensing for high reliability and long endurance

MagAlpha Sensor Applications

Turning knobs in user interfaces (white goods, industrial man-machine interfaces, automotive)

Actuators (HVAC dampers, textile machines, industrial automation, automotive)

Motors (commutation in brushless motors, speed or position control in all types of motor)



- Unique “SpinAxis” measurement technique gives low 10us angle latency at any speed
- Resolutions from 8 up to 14 bit
- Wide magnetic field range support from 15mT to 150mT
- End and side of shaft magnet positioning for easy set up
- Low power consumption: 3.3V, 12mA
- Small package form factor : 3mmx3mm QFN-16 package

Applications	Part	Features
Replacement of 3 Hall switches for BLDC commutation	MA102	UVW output, multi-pole pair support
Human/machine interface Speed <200rpm	MA800	SPI output
	MA820	ABZ output
	MA850	PWM output
	MA704	10 bit high bandwidth
	MA702	12 bit medium bandwidth
	MA710	12 bit for low field side-shaft
All purpose encoder SPI, SSI, ABZ, PWM outputs	MA730	14 bit low bandwidth
	MA732	9-14 bit configurable filter bandwidth
	MAQ470	12 bit Automotive AECQ Grade 1
	MA302	12 bit medium bandwidth
	MA310	12 bit for low field side shaft
All purpose encoder for BLDC Servo Motors SPI, ABZ and UVW outputs	MA330	9-14 bit configurable filter bandwidth
	MAQ430	12 bit Automotive AECQ Grade 1
Low power	MA780	Multiple power modes

For ordering and more information visit MonolithicPower.com





PRESSURE

Pressure Sensor – Analog	105
Pressure Sensor – Digital.....	117
Barometer	121

Amphenol
Advanced Sensors



BOSCH
Invented for life



Melexis



Panasonic

SENSIRION
THE SENSOR COMPANY

ST
life.augmented



Part Number	Pressure Range (kPa)	Pressure Type	Full Scale Output (V)	Accuracy (%FSO)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
FMA-500-T1	5"H2O, 40" H2O	G/V	0.5 to 4.5	±2.5	5 V _{DC}	5	-40 to +125	Pressure Port, 1/8-27 NPT Female
NPR-101	300 PSI	A	0.5 to 4.5	2	5	3	-40 to +140	-
NPC-100T	6 PSI	G	—	±3	6	-	+15 to +40	Ceramic
NPC-120T	6 PSI	G	—	±3	6	-	+15 to +40	Ceramic
NPP-301A-100A	15 PSIA	A	0.06	±0.2	3	-	-40 to +125	SOIC-8
NPP-301A-200A	30 PSIA	A	0.06	±0.2	3	-	-40 to +125	SOIC-8
NPP-301A-700A	100 PSIA	A	0.06	±0.2	3	-	-40 to +125	SOIC-8
NPA-100B-10WG	10" H2O	G	0.1 Typ	±1.5	-	1.5	-40 to +125	SOIC-14, Barb port
NPA-100B-005G	5 PSI	G	0.1 Typ	±1.5	-	1.5	-40 to +125	SOIC-14, Barb port
NPA-100B-015A	15 PSI	A	0.1 Typ	±1.5	-	1.5	-40 to +125	SOIC-14, Barb port
NPA-100B-030A	30PSI	A	0.1 Typ	±1.5	-	1.5	-40 to +125	SOIC-14, Barb port
NPA-100B-10WD	10" H2O	D	0.1 Typ	±1.5	-	1.5	-40 to +125	SOIC-14, Barb port
NPA-100B-001D	1 PSI	D	0.1 Typ	±1.5	-	1.5	-40 to +125	SOIC-14, Barb port
NPA-100B-015D	15 PSI	D	0.1 Typ	±1.5	-	1.5	-40 to +125	SOIC-14, Barb port
NPA-300B-02WD	2" H2O	D	0.5 to 3.0	±1.5	3.3	-	-40 to +125	SOIC-14, Barb port
NPA-300B-05WD	5" H2O	D	0.5 to 3.0	±1.5	3.3	-	-40 to +125	SOIC-14, Barb port
NPA-300B-015G	15 PSI	G	0.5 to 3.0	±1.5	3.3	-	-40 to +125	SOIC-14, Barb port
NPA-300B-030G	30 PSI	G	0.5 to 3.0	±1.5	3.3	-	-40 to +125	SOIC-14, Barb port
NPA-300B-10WD	10" H2O	D	0.5 to 3.0	±1.5	3.3	-	-40 to +125	SOIC-14, Barb port
NPA-300B-001D	1 PSI	D	0.5 to 3.0	±1.5	3.3	-	-40 to +125	SOIC-14, Barb port
NPA-300B-005D	5 PSI	D	0.5 to 3.0	±1.5	3.3	-	-40 to +125	SOIC-14, Barb port
NPA-300B-015D	15 PSI	D	0.5 to 3.0	±1.5	3.3	-	-40 to +125	SOIC-14, Barb port
NPA-500B-02WG	2" H2O	G	0.5 to 4.5	±1.5	5	-	-40 to +125	SOIC-14, Barb port
NPA-500B-05WG	5" H2O	G	0.5 to 4.5	±1.5	5	-	-40 to +125	SOIC-14, Barb port
NPA-500B-02WD	2" H2O	D	0.5 to 4.5	±1.5	5	-	-40 to +125	SOIC-14, Barb port
NPA-500B-05WD	5" H2O	D	0.5 to 4.5	±1.5	5	-	-40 to +125	SOIC-14, Barb port
NPA-500B-10WG	10" H2O	G	0.5 to 4.5	±1.5	5	-	-40 to +125	SOIC-14, Barb port
NPA-500B-001G	1 PSI	G	0.5 to 4.5	±1.5	5	-	-40 to +125	SOIC-14, Barb port
NPA-500B-005G	5 PSI	G	0.5 to 4.5	±1.5	5	-	-40 to +125	SOIC-14, Barb port
NPA-500B-015G	15 PSI	G	0.5 to 4.5	±1.5	5	-	-40 to +125	SOIC-14, Barb port
NPA-500B-030G	30 PSI	G	0.5 to 4.5	±1.5	5	-	-40 to +125	SOIC-14, Barb port
NPA-500B-015A	15 PSI	A	0.5 to 4.5	±1.5	5	-	-40 to +125	SOIC-14, Barb port
NPA-500B-030A	30PSI	A	0.5 to 4.5	±1.5	5	-	-40 to +125	SOIC-14, Barb port
NPA-500B-10WD	10" H2O	D	0.5 to 4.5	±1.5	5	-	-40 to +125	SOIC-14, Barb port
NPA-500B-001D	1 PSI	D	0.5 to 4.5	±1.5	5	-	-40 to +125	SOIC-14, Barb port
NPA-500B-005D	5 PSI	D	0.5 to 4.5	±1.5	5	-	-40 to +125	SOIC-14, Barb port
NPA-500B-015D	15 PSI	D	0.5 to 4.5	±1.5	5	-	-40 to +125	SOIC-14, Barb port

A: Absolute, B: Barometric, D: Differential, G: Gauge

1kPa = 10 mbar = 10 hPa = 0.145 psi = 4.015 in H₂O

Amphenol
Advanced Sensors

Part Number	Pressure Range (kPa)	Pressure Type	Full Scale Output (V)	Accuracy (%FSO)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
NPA-500B-030D	30PSI	D	0.5 to 4.5	±1.5	5	—	-40 to +125	SOIC-14, Barb port
NPC-1210-030G-1-S	30 PSI	G	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-10WG-3-L	10" H2O	G	0.025 to 0.070	±0.1	—	1.5	-40 to +125	8-pin PCB
NPC-1210-001G-3-L	1 PSI	G	0.050 to 0.110	±0.1	—	1.5	-40 to +125	8-pin PCB
NPC-1210-005G-3-L	5 PSI	G	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-015G-3-L	15 PSI	G	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-030G-3-L	30 PSI	G	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-050G-3-L	50 PSI	G	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-100G-3-L	100 PSI	G	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-015A-3-L	15 PSI	A	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-030A-3-L	30 PSI	A	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-050A-3-L	50 PSI	A	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-100A-3-L	100 PSI	A	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-10WD-3-L	10" H2O	D	0.025 to 0.070	±0.1	—	1.5	-40 to +125	8-pin PCB
NPC-1210-001D-3-L	1 PSI	D	0.050 to 0.110	±0.1	—	1.5	-40 to +125	8-pin PCB
NPC-1210-005D-3-L	5 PSI	D	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-015D-3-L	15 PSI	D	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-030D-3-L	30 PSI	D	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-050D-3-L	50 PSI	D	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-100D-3-L	100 PSI	D	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-015G-3-S	15 PSI	G	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-030G-3-S	30 PSI	G	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-050G-3-S	50 PSI	G	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-015A-3-S	15 PSI	A	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-10WD-3-S	10" H2O	D	0.025 to 0.070	±0.1	—	1.5	-40 to +125	8-pin PCB
NPC-1210-015D-3-S	15 PSI	D	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-10WG-3-N	10" H2O	G	0.025 to 0.070	±0.1	—	1.5	-40 to +125	8-pin PCB
NPC-1210-001G-3-N	1 PSI	G	0.050 to 0.110	±0.1	—	1.5	-40 to +125	8-pin PCB
NPC-1210-005G-3-N	5 PSI	G	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-015G-3-N	15 PSI	G	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-030G-3-N	30 PSI	G	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-050G-3-N	50 PSI	G	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-100G-3-N	100 PSI	G	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-015A-3-N	15 PSI	A	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-030A-3-N	30 PSI	A	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-050A-3-N	50 PSI	A	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB
NPC-1210-100A-3-N	100 PSI	A	0.075 to 0.150	±0.5	—	1.5	-40 to +125	8-pin PCB

A: Absolute, B: Barometric, D: Differential, G: Gauge 1kPa = 10 mbar = 10 hPa = 0.145 psi = 4.015 in H₂O

Part Number	Pressure Range (kPa)	Pressure Type	Full Scale Output (V)	Accuracy (%FSO)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
NPC-1220-030A-1-S	30 PSI	A	0.05	±0.1	—	1.5	-40 to +125	8-pin PCB
NPC-1220-005G-3-S	5 PSI	G	0.05	±0.1	—	1.5	-40 to +125	8-pin PCB
NPC-1220-015G-3-S	15 PSI	G	0.05	±0.1	—	1.5	-40 to +125	8-pin PCB
NPC-1220-030G-3-S	30 PSI	G	0.05	±0.1	—	1.5	-40 to +125	8-pin PCB
NPC-1220-050G-3-S	50 PSI	G	0.05	±0.1	—	1.5	-40 to +125	8-pin PCB
NPC-1220-100G-3-S	100 PSI	G	0.05	±0.1	—	1.5	-40 to +125	8-pin PCB
NPC-1220-015A-3-S	15 PSI	A	0.05	±0.1	—	1.5	-40 to +125	8-pin PCB
NPC-1220-030A-3-S	30 PSI	A	0.05	±0.1	—	1.5	-40 to +125	8-pin PCB
NPC-1220-050A-3-S	50 PSI	A	0.05	±0.1	—	1.5	-40 to +125	8-pin PCB
NPC-1220-100A-3-S	100 PSI	A	0.05	±0.1	—	1.5	-40 to +125	8-pin PCB
NPC-1220-005D-3-S	5 PSI	D	0.05	±0.1	—	1.5	-40 to +125	8-pin PCB
NPC-1220-015D-3-S	15 PSI	D	0.05	±0.1	—	1.5	-40 to +125	8-pin PCB
NPC-1220-030D-3-S	30 PSI	D	0.05	±0.1	—	1.5	-40 to +125	8-pin PCB
NPC-1220-050D-3-S	50 PSI	D	0.05	±0.1	—	1.5	-40 to +125	8-pin PCB
NPC-1220-100D-3-S	100 PSI	D	0.05	±0.1	—	1.5	-40 to +125	8-pin PCB
NPC-1220-100G-3-N	100 PSI	G	0.05	±0.1	—	1.5	-40 to +125	8-pin PCB
NPH-8-002.5GH	10" H2O	G	0.25	±0.1	—	1.5	-40 to +125	T0-8
NPH-8-002.5DH	10" H2O	D	0.25	±0.1	—	1.5	-40 to +125	T0-8
NPH-8-007GH	7 kPa	G	0.25	±0.1	—	1.5	-40 to +125	T0-8
NPH-8-007DH	7 kPa	D	0.25	±0.1	—	1.5	-40 to +125	T0-8
NPH-8-030GH	30 kPa	G	0.25	±0.1	—	1.5	-40 to +125	T0-8
NPH-8-030AH	30 kPa	A	0.25	±0.1	—	1.5	-40 to +125	T0-8
NPH-8-030DH	30 kPa	D	0.25	±0.1	—	1.5	-40 to +125	T0-8
NPH-8-100GH	100 kPa	G	0.25	±0.5	—	1.5	-40 to +125	T0-8
NPH-8-100AH	100 kPa	A	0.25	±0.5	—	1.5	-40 to +125	T0-8
NPH-8-100DH	100 kPa	D	0.25	±0.5	—	1.5	-40 to +125	T0-8
NPH-8-200GH	200 kPa	G	0.25	±0.5	—	1.5	-40 to +125	T0-8
NPH-8-200AH	200 kPa	A	0.25	±0.5	—	1.5	-40 to +125	T0-8
NPH-8-200DH	200 kPa	D	0.25	±0.5	—	1.5	-40 to +125	T0-8
NPH-8-700GH	700 kPa	G	0.25	±0.5	—	1.5	-40 to +125	T0-8
NPH-8-700AH	700 kPa	A	0.25	±0.5	—	1.5	-40 to +125	T0-8
NPH-8-700DH	700 kPa	D	0.25	±0.5	—	1.5	-40 to +125	T0-8
NPI-15A-353AH	5000 PSI	A	0.23	±0.3	—	1	-40 to +125	Stainless Steel
NPI-15A-353SH	5000 PSI	G	0.23	±0.3	—	1	-40 to +125	Stainless Steel
NPI-15H-352AH	500 PSI	A	0.23	±0.3	—	1	-40 to +125	Stainless Steel
NPI-15H-702AH	1000 PSI	A	0.23	±0.3	—	1	-40 to +125	Stainless Steel
NPI-15J-352AH	500 PSI	A	0.23	±0.3	—	1	-40 to +125	Stainless Steel

A: Absolute, B: Barometric, D: Differential, G: Gauge

1kPa = 10 mbar = 10 hPa = 0.145 psi = 4.015 in H₂O

Amphenol

Advanced Sensors

Part Number	Pressure Range (kPa)	Pressure Type	Full Scale Output (V)	Accuracy (%FSO)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
NPI-15J-702AH	1000 PSI	A	0.23	±0.3	–	1	-40 to +125	Stainless Steel
NPI-15H-352SH	500 PSI	G	0.23	±0.3	–	1	-40 to +125	Stainless Steel
NPI-15H-702SH	1000 PSI	G	0.23	±0.3	–	1	-40 to +125	Stainless Steel
NPI-15J-352SH	500 PSI	G	0.23	±0.3	–	1	-40 to +125	Stainless Steel
NPI-15J-702SH	1000 PSI	G	0.23	±0.3	–	1	-40 to +125	Stainless Steel
NPI-15A-1K0SV	1000 PSI	G	0.101	±0.3	10	–	-40 to +125	Stainless Steel
NPI-15A-3K0SV	3000 PSI	G	0.101	±0.3	10	–	-40 to +125	Stainless Steel
NPI-15A-5K0SV	5000 PSI	G	0.101	±0.3	10	–	-40 to +125	Stainless Steel
NPI-15H-500AV	500 PSI	A	0.101	±0.3	10	–	-40 to +125	Stainless Steel
NPI-15H-1K0AV	1000 PSI	A	0.101	±0.3	10	–	-40 to +125	Stainless Steel
NPI-15J-500AV	500 PSI	A	0.101	±0.3	10	–	-40 to +125	Stainless Steel
NPI-15J-1K0AV	1000 PSI	A	0.101	±0.3	10	–	-40 to +125	Stainless Steel
NPI-15H-500SV	500 PSI	G	0.101	±0.3	10	–	-40 to +125	Stainless Steel
NPI-15H-1K0SV	1000 PSI	G	0.101	±0.3	10	–	-40 to +125	Stainless Steel
NPI-15J-500SV	500 PSI	G	0.101	±0.3	10	–	-40 to +125	Stainless Steel
NPI-15J-1K0SV	1000 PSI	G	0.101	±0.3	10	–	-40 to +125	Stainless Steel
NPI-19A-021GH	2.5 PSI	G	0.1	±0.3	10	1.5	-10 to +80	Stainless Steel
NPI-19A-031GH	5 PSI	G	0.1	±0.3	10	1.5	-10 to +80	Stainless Steel
NPI-19A-101GH	15 PSI	G	0.1	±0.3	10	1	-10 to +80	Stainless Steel
NPI-19A-201GH	30 PSI	G	0.1	±0.3	10	1	-10 to +80	Stainless Steel
NPI-19A-701GH	100 PSI	G	0.1	±0.3	10	1	-10 to +80	Stainless Steel
NPI-19A-172GH	250 PSI	G	0.1	±0.3	10	1	-10 to +80	Stainless Steel
NPI-19A-101AH	15 PSI	A	0.1	±0.3	10	1	-10 to +80	Stainless Steel
NPI-19A-201AH	30 PSI	A	0.1	±0.3	10	1	-10 to +80	Stainless Steel
NPI-19A-701AH	100 PSI	A	0.1	±0.3	10	1	-10 to +80	Stainless Steel
NPI-19A-172AH	250 PSI	A	0.1	±0.3	10	1	-10 to +80	Stainless Steel
NPI-19H-101GH	15 PSI	G	0.1	±0.3	10	1	-10 to +80	Stainless Steel
NPI-19H-201GH	30 PSI	G	0.1	±0.3	10	1	-10 to +80	Stainless Steel
NPI-19H-101AH	15 PSI	A	0.1	±0.3	10	1	-10 to +80	Stainless Steel
NPI-19A-002GV	2.5 PSI	G	0.1	±0.3	10	1.5	-10 to +80	Stainless Steel
NPI-19A-005GV	5 PSI	G	0.1	±0.3	10	1.5	-10 to +80	Stainless Steel
NPI-19A-015GV	15 PSI	G	0.1	±0.3	10	–	-10 to +80	Stainless Steel
NPI-19A-030GV	30 PSI	G	0.1	±0.3	10	–	-10 to +80	Stainless Steel
NPI-19A-050GV	50 PSI	G	0.1	±0.3	10	–	-10 to +80	Stainless Steel
NPI-19A-100GV	100 PSI	G	0.1	±0.3	10	–	-10 to +80	Stainless Steel
NPI-19A-200GV	200 PSI	G	0.1	±0.3	10	–	-10 to +80	Stainless Steel

A: Absolute, B: Barometric, D: Differential, G: Gauge

1kPa = 10 mbar = 10 hPa = 0.145 psi = 4.015 in H₂O

Part Number	Pressure Range (kPa)	Pressure Type	Full Scale Output (V)	Accuracy (%FSO)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
NPI-19A-300GV	300 PSI	G	0.1	±0.3	10	—	-10 to +80	Stainless Steel
NPI-19A-015AV	15 PSI	A	0.1	±0.3	10	—	-10 to +80	Stainless Steel
NPI-19A-030AV	30 PSI	A	0.1	±0.3	10	—	-10 to +80	Stainless Steel
NPI-19A-050AV	50 PSI	A	0.1	±0.3	10	—	-10 to +80	Stainless Steel
NPI-19A-100AV	100 PSI	A	0.1	±0.3	10	—	-10 to +80	Stainless Steel
NPI-19A-200AV	200 PSI	A	0.1	±0.3	10	—	-10 to +80	Stainless Steel
NPI-19A-300AV	300 PSI	A	0.1	±0.3	10	—	-10 to +80	Stainless Steel
NPI-19J-050GV	50 PSI	G	0.1	±0.3	10	—	-10 to +80	Stainless Steel
NPI-19H-100AV	100 PSI	A	0.1	±0.3	10	—	-10 to +80	Stainless Steel

A: Absolute, B: Barometric, D: Differential, G: Gauge, V: Vacuum Sensor

1kPa = 10 mbar = 10 hPa = 0.145 psi = 4.015 in H₂O

Part Number	Pressure Range (kPa)	Pressure Type	Full Scale Output (V)	Accuracy (%FSO)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
KP215F1701XTMA1	10 to 115	Manifold Air	0.1 to 4.85	±1.4	5	8	-40 to +140	DSOF-8
KP236N6165XTMA1	60 to 165	B	0.1 to 4.85	±1.0	5	8	-40 to +125	DSOF-8
KP236XTMA1	40 to 115	B	0.1 to 4.85	±1.0	5	8	-40 to +125	DSOF-8

A: Absolute, B: Barometric, D: Differential, G: Gauge

1kPa = 10 mbar = 10 hPa = 0.145 psi = 4.015 in H₂O

Part Number	Pressure Range (kPa)	Pressure Type	Full Scale Output (V)	Accuracy (%FSO)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
MLX90809LXG-EAD-000	-1.05 to 0.05bar	D	5	—	4.5 to 5.0	8	-40 to +150	S016 cavity
MLX90809LXG-EAD-003	0 to 1bar	D	5	—	4.5 to 5.0	8	-40 to +150	S016 cavity

A: Absolute, B: Barometric, D: Differential, G: Gauge

1kPa = 10 mbar = 10 hPa = 0.145 psi = 4.015 in H₂O



Part Number	Pressure Range (kPa)	Pressure Type	Full Scale Output (V)	Accuracy (%FSO)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
MPXV10GCxx	0 to 10	D & G	$0.5 V_{DD} + 0.035$	1.00	3.0 to 6.0	6	-40 to +125	SOP & ported SOP
MPXV12xx	0 to 10	D & G	$0.5 V_{DD} + 0.055$	5.00	3.0 to 6.0	6	-40 to +125	SOP; SOP dual port; MPAK; SOP ported
MPXM2051G	0 to 50	A	$0.5 V_{DD} + 0.040$	1.50	10 to 16	6	-40 to +125	MPAK
MPXx2053	0 to 50	D & G	$0.5 V_{DD} + 0.040$	1.50	10 to 16	6	-40 to +125	x=V SOP & ported SOP; x=M MPAK
MPXx2102	0 to 100	A, D & G	$0.5 V_{DD} + 0.040$	1.50	10 to 16	6	-40 to +125	x=V SOP & ported SOP; x=M MPAK
MPXx2202	0 to 200	A, D & G	$0.5 V_{DD} + 0.040$	1.50	10 to 16	6	-40 to +125	x=V SOP & ported SOP; x=M MPAK
MPX2300DT1	0 to 40	D & G	$0.5 V_{DD} + 0.003$	1.50	6.0 to 10	1	+15 to +40	ChipPak package
MPXV(Z)4006	0 to 6	D & G	4.9	2.50	4.75 to 5.25	10	+10 to +60	SOP; SOP dual port; SOP ported
MPXV(Z)5004	0 to 3.92	D & G	4.9	1.50	4.75 to 5.25	10	0 to +85	SOP; SOP dual port; SOP ported
MP3V5004	0 to 3.92	D & G	2.9	1.50	2.7 to 3.3	10	+10 to +60	SOP; SOP dual port; SOP ported
MPXV5010	0 to 10	D & G	4.7	5.00	4.75 to 5.25	5	-40 to +125	SOP; SOP dual port; SOP ported
MPV5010	0 to 10	D & G	4.7	5.00	4.75 to 5.25	5	-40 to +125	SOP; SOP dual port; SOP ported
MP3V5010	0 to 10	D & G	2.9	5.00	2.7 to 3.3	7	-40 to +125	SOP; SOP dual port; SOP ported
MPXV5050VC6U	-50 to 50	V	4.7	2.50	4.75 to 5.25	7	-40 to +125	SOP ported
MPXV5050	0 to 50	D & G	4.7	2.50	4.75 to 5.25	7	-40 to +125	SOP ported & dual port
MPVZ5050	0 to 50	D & G	4.7	2.50	4.75 to 5.25	7	-40 to +125	SOP ported
MP3V5050	0 to 50	V	2.8	2.50	2.7 to 3.3	7	-40 to +125	SOP ported; SOP dual port
MPXV5100	0 to 100	A, D & G	4.7	2.50	4.75 to 5.25	7	-40 to +125	SOP ported & dual port
MPX5500	0 to 500	D	4.7	2.50	4.75 to 5.25	7	-40 to +125	Unibody Packages
MPX5700	0 to 700	A, D & G	4.7	2.50	4.75 to 5.25	7	-40 to +125	Unibody Packages
MPX5700A	15 to 700	A	4.7	2.50	4.75 to 5.25	7	-40 to +125	Unibody Packages
MPX5999	0 to 1000	D	4.7	2.50	4.75 to 5.25	7	-40 to +125	Unibody Packages
MPXHZ6250A	20 to 250	A	4.8	1.50	4.75 to 5.25	6	-40 to +125	SSOP & ported SSOP
MPXH6300A	20 to 304	A	4.9	1.50	4.74 to 5.46	6	-40 to +125	SSOP & ported SSOP
MPXHZ6400A	20 to 400	A	4.8	1.50	4.64 to 5.36	6	-40 to +125	SOP & ported SOP // SSOP & Ported SOP
MPXHV6115 V	-115 to 0	V	4.6	1.50	4.75 to 5.25	6	-40 to +125	SOP & SOP ported
MPXV7002	-2 to 2	V	4.5	6.25	4.75 to 5.25	10	+10 to +60	SOP ported; dual port

A: Absolute, B: Barometric, D: Differential, G: Gauge

1kPa = 10 mbar = 10 hPa = 0.145 psi = 4.015 in H₂O

Part Number	Pressure Range (kPa)	Pressure Type	Full Scale Output (V)	Accuracy (%FSO)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
ADP527x	145.04psi, 1000kpa	Gauge	4.5V, $\pm 0.05V$	$\pm 1.25\%FS$	5 $\pm 0.25V$ DC	Max 10	0 to +50	SMD
ADP526x	72.52psi, 500kpa	Gauge	4.5V, $\pm 0.05V$	$\pm 1.25\%FS$	5 $\pm 0.25V$ DC	Max 10	0 to +50	SMD
ADP525x	29.008psi, 200kpa	Gauge	4.5V, $\pm 0.05V$	$\pm 1.25\%FS$	5 $\pm 0.25V$ DC	Max 10	0 to +50	SMD
ADP524x	14.5038psi, 100kpa	Gauge	4.5V, $\pm 0.05V$	$\pm 1.25\%FS$	5 $\pm 0.25V$ DC	Max 10	0 to +50	SMD
ADP523x	7.252psi, 50kpa	Gauge	4.5V, $\pm 0.05V$	$\pm 1.25\%FS$	5 $\pm 0.25V$ DC	Max 10	0 to +50	SMD
ADP522x	3.626psi, 25kpa	Gauge	4.5V, $\pm 0.05V$	$\pm 1.25\%FS$	5 $\pm 0.25V$ DC	Max 10	0 to +50	SMD
ADP521x	-100kpa	Gauge	4.5V, $\pm 0.05V$	$\pm 1.25\%FS$	5 $\pm 0.25V$ DC	Max 10	0 to +50	SMD
ADP520x	± 100 kPa	Gauge	4.5V, $\pm 0.05V$	$\pm 1.25\%FS$	5 $\pm 0.25V$ DC	Max 10	0 to +50	SMD
ADP51B63	0.870228psi, 6kpa	Gauge	4V(Typical)	$\pm 2.50\%FS$	5 $\pm 0.25V$ DC	Max 10	0 to +70	DIP-8
ADP51B62	0.870228psi, 6kpa	Gauge	4V(Typical)	$\pm 2.50\%FS$	5 $\pm 0.25V$ DC	Max 10	0 to +70	DIP-8
ADP51B61	0.870228psi, 6kpa	Gauge	4V(Typical)	$\pm 2.50\%FS$	5 $\pm 0.25V$ DC	Max 10	0 to +70	DIP-8
ADP51A11	5.80152psi, 40kpa	Gauge	2.4V, $\pm 0.03V$	$\pm 4\%FS$	5 $\pm 0.25V$ DC	Max 3	+5 to +45	DIP-6
ADP517x	145.038psi, 1000kpa	Gauge	4.5V, $\pm 0.05V$	$\pm 1.25\%FS$	5 $\pm 0.25V$ DC	Max 10	0 to +50	DIP-6
ADP516x	72.519psi, 500kpa	Gauge	4.5V, $\pm 0.05V$	$\pm 1.25\%FS$	5 $\pm 0.25V$ DC	Max 10	0 to +50	DIP-6
ADP515x	29.0076psi, 200kpa	Gauge	4.5V, $\pm 0.05V$	$\pm 1.25\%FS$	5 $\pm 0.25V$ DC	Max 10	0 to +50	DIP-6
ADP514x	14.5038psi, 100kpa	Gauge	4.5V, $\pm 0.05V$	$\pm 1.25\%FS$	5 $\pm 0.25V$ DC	Max 10	0 to +50	DIP-6
ADP513x	7.2519psi, 50kpa	Gauge	4.5V, $\pm 0.05V$	$\pm 1.25\%FS$	5 $\pm 0.25V$ DC	Max 10	0 to +50	DIP-6
ADP512x	3.62595psi, 25kpa	Gauge	4.5V, $\pm 0.05V$	$\pm 1.25\%FS$	5 $\pm 0.25V$ DC	Max 10	0 to +50	DIP-6
ADP511x	-100kpa	Gauge	4.5V, $\pm 0.05V$	$\pm 1.25\%FS$	5 $\pm 0.25V$ DC	Max 10	0 to +50	DIP-6
ADP510x	± 100 kPa	Gauge	4.5V, $\pm 0.05V$	$\pm 1.25\%FS$	5 $\pm 0.25V$ DC	Max 10	0 to +50	DIP-6
ADP4xA23	5.80152psi, 40kpa	Gauge	43.5mV, $\pm 22.5mV$	$\pm 0.3\%FS$	5 $\pm 0.25V$ DC	1.5	-5 to +50	DIP-6
ADP4x913	142.238767psi, 980.7kpa	Gauge	65mV, $\pm 25mV$	$\pm 1.0\%$	5 $\pm 0.25V$ DC	1	-20 to +100	DIP-6
ADP4x910	142.238767psi, 980.7kpa	Gauge	65mV, $\pm 25mV$	$\pm 1.0\%$	5 $\pm 0.25V$ DC	1.5	-20 to +100	DIP-6
ADP4x810	120.903677psi, 833.6kpa	Gauge	100mV, $\pm 40mV$	$\pm 0.6\%$	5 $\pm 0.25V$ DC	1.5	-20 to +100	DIP-6
ADP4x710	71.112131psi, 490.3kpa	Gauge	100mV, $\pm 40mV$	$\pm 0.5\%$	5 $\pm 0.25V$ DC	1.5	-20 to +100	DIP-6
ADP4x610	49.777042psi, 343.2kpa	Gauge	100mV, $\pm 40mV$	$\pm 0.3\%$	5 $\pm 0.25V$ DC	1.5	-20 to +100	DIP-6
ADP4x413	14.228228psi, 98.1kpa	Gauge	65mV, $\pm 25mV$	$\pm 1.0\%$	5 $\pm 0.25V$ DC	1	-20 to +100	DIP-6
ADP4*320	7.106862psi, 49kpa	Gauge	100mV, $\pm 40mV$	$\pm 0.3\%$	5 $\pm 0.25V$ DC	1.5	-20 to +100	DIP-6
ADP4x210	4.974803psi, 34.3kpa	Gauge	100mV, $\pm 40mV$	$\pm 0.3\%$	5 $\pm 0.25V$ DC	1.5	-20 to +100	DIP-6
ADP4x010	0.710686psi, 4.9kpa	Gauge	40mV, $\pm 20mV$	$\pm 0.7\%$	5 $\pm 0.25V$ DC	1.5	-20 to +100	DIP-6

A: Absolute, B: Barometric, D: Differential, G: Gauge

1kPa = 10 mbar = 10 hPa = 0.145 psi = 4.015 in H₂O

x = refers to port size and direction



Part Number	Pressure Range (kPa)	Pressure Type	Full Scale Output (V)	Accuracy (%FSO)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
SDP806-500Pa	500	D	10 to 90% VDD	0.02 (±3% of reading)	3.0 to 5.5	3.8	-40 to +85	29 x 12.6 x 18
SDP816-500Pa	500	D	10 to 90% VDD	0.02 (±3% of reading)	3.0 to 5.5	3.8	-40 to +85	29 x 12.6 x 18
SDP806-125Pa	125	D	10 to 90% VDD	0.064 (±3% of reading)	3.0 to 5.5	3.8	-40 to +85	29 x 12.6 x 18
SDP816-125Pa	125	D	10 to 90% VDD	0.064 (±3% of reading)	3.0 to 5.5	3.8	-40 to +85	29 x 12.6 x 18
SDP36	500	D	10 to 90% VDD	0.02 (±3% of reading)	3.0 to 3.6	3.8	-20 to +85	8.5 x 5.4 x 3.5
SDP37	125	D	10 to 90% VDD	0.064 (±3% of reading)	3.0 to 3.6	3.8	-20 to +85	8.5 x 5.4 x 3.5
SDP2000	3500	D	0.25 to 4.5	0.2 (±1.5% of reading)	4.75 to 5.25	5.2	-10 to +60	30.5 x 22.1 x 30

A: Absolute, B: Barometric, D: Differential, G: Gauge

1kPa = 10 mbar = 10 hPa = 0.145 psi = 4.015 in H₂O



AUTHORIZED DISTRIBUTOR

Part Number	Pressure Range (kPa)	Pressure Type	Full Scale Output (V)	Accuracy (%FSO)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
1210A-001D-3L	6.9	D	100 mV	±0.3% Span Non-Linearity	–	1.5	-40 to +125	16.2 x 16.8
1210A-001D-3S	6.9	D	100 mV	±0.3% Span Non-Linearity	–	1.5	-40 to +125	16.2 x 16.8
1210A-001G-3S	6.9	G	100 mV	±0.3% Span Non-Linearity	–	1.5	-40 to +125	16.2 x 16.8
1210A-002D-3L	13.79	D	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	14.7 x 15.2
1210A-002D-3N	13.79	D	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	14.7 x 15.2
1210A-002D-3S	13.79	D	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	14.7 x 15.2
1210A-005D-3L	34.48	D	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	14.7 x 15.2
1210A-005D-3S	34.48	D	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	14.7 x 15.2
1210A-005G-3S	34.48	G	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	14.7 x 15.2
1210A-015A-3L	103.45	A	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	14.7 x 15.2
1210A-015A-3N	103.45	A	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	14.7 x 15.2
1210A-015A-3S	103.45	A	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	14.7 x 15.2
1210A-015D-3L	103.45	D	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	14.7 x 15.2
1210A-015D-3S	103.45	D	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	14.7 x 15.2
1210A-015G-3L	103.45	G	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	14.7 x 15.2
1210A-015G-3S	103.45	G	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	14.7 x 15.2
1210A-030A-3L	206.9	A	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	14.7 x 15.2
1210A-030D-3L	206.9	D	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	14.7 x 15.2
1210A-030D-3S	206.9	D	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	14.7 x 15.2
1210A-100D-3L	689.66	D	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	14.7 x 15.2
1210A-100D-3S	689.66	D	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	14.7 x 15.2
1210A-100G-1S	689.66	G	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	14.7 x 15.2
1210A-100G-3L	689.66	G	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	14.7 x 15.2
1210A-100G-3N	689.66	G	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	14.7 x 15.2
1210A-100G-3S	689.66	G	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	14.7 x 15.2

A: Absolute, B: Barometric, D: Differential, G: Gauge

1kPa = 10 mbar = 10 hPa = 0.145 psi = 4.015 in H₂O

Part Number	Pressure Range (kPa)	Pressure Type	Full Scale Output (V)	Accuracy (%FSO)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
1210A-10WD-3S	2.49	D	40 mV	±0.3% Span Non-Linearity	—	1.5	-40 to +125	14.7 x 15.2
1220A-002D-3S	13.79	D	50 mV	±0.1% Span Non-Linearity	—	—	-40 to +125	14.7 x 15.2
1220A-005D-3L	34.48	D	50 mV	±0.1% Span Non-Linearity	—	—	-40 to +125	14.7 x 15.2
1220A-005D-3S	34.48	D	50 mV	±0.1% Span Non-Linearity	—	—	-40 to +125	14.7 x 15.2
1220A-005G-3N	34.48	G	50 mV	±0.1% Span Non-Linearity	—	—	-40 to +125	14.7 x 15.2
1220A-005G-3S	34.48	G	50 mV	±0.1% Span Non-Linearity	—	—	-40 to +125	14.7 x 15.2
1220A-015A-3L	103.45	A	50 mV	±0.1% Span Non-Linearity	—	—	-40 to +125	14.7 x 15.2
1220A-015A-3S	103.45	A	50 mV	±0.1% Span Non-Linearity	—	—	-40 to +125	14.7 x 15.2
1220A-015D-3L	103.45	D	50 mV	±0.1% Span Non-Linearity	—	—	-40 to +125	14.7 x 15.2
1220A-030G-3N	206.9	G	50 mV	±0.1% Span Non-Linearity	—	—	-40 to +125	14.7 x 15.2
1220A-030G-3S	206.9	G	50 mV	±0.1% Span Non-Linearity	—	—	-40 to +125	14.7 x 15.2
1230-002D-3N	13.79	D	100 mV	±0.1% Span Non-Linearity	—	1.5	-40 to +125	14.7 x 15.2
1230-015A-3L	103.45	A	100 mV	±0.1% Span Non-Linearity	—	1.5	-40 to +125	14.7 x 15.2
1230-015A-3S	103.45	A	100 mV	±0.1% Span Non-Linearity	—	1.5	-40 to +125	14.7 x 15.2
1230-015D-3L	103.45	D	100 mV	±0.1% Span Non-Linearity	—	1.5	-40 to +125	14.7 x 15.2
1230-015D-3S	103.45	D	100 mV	±0.1% Span Non-Linearity	—	1.5	-40 to +125	14.7 x 15.2
1230-030A-3S	206.9	A	100 mV	±0.1% Span Non-Linearity	—	1.5	-40 to +125	14.7 x 15.2
1230-030D-3S	206.9	D	100 mV	±0.1% Span Non-Linearity	—	1.5	-40 to +125	14.7 x 15.2
1230-100D-3S	689.66	D	100 mV	±0.1% Span Non-Linearity	—	1.5	-40 to +125	14.7 x 15.2
1240-015A-3S	103.45	A	50 mV	±0.1% Span Non-Linearity	—	—	-40 to +125	14.7 x 15.2
13A-002G	13.79	G	100 mV	±0.1% Span Non-Linearity	—	1.5	-40 to +125	φ11.4
13A-005G	34.48	G	100 mV	±0.1% Span Non-Linearity	—	1.5	-40 to +125	φ11.4
13A-010G	68.97	G	100 mV	±0.1% Span Non-Linearity	—	1.5	-40 to +125	φ11.4
13A-015A	103.45	A	100 mV	±0.1% Span Non-Linearity	—	1.5	-40 to +125	φ11.4
13A-015G	103.45	G	100 mV	±0.1% Span Non-Linearity	—	1.5	-40 to +125	φ11.4
13A-030G	206.9	G	100 mV	±0.1% Span Non-Linearity	—	1.5	-40 to +125	φ11.4
13A-100G	689.66	G	100 mV	±0.1% Span Non-Linearity	—	1.5	-40 to +125	φ11.4
1451-005G-T	34.48	G	60 mV	±0.25% Non-Linearity	3	—	-40 to +125	7.6 x 7.6
1451-015A-N	103.45	A	60 mV	±0.25% Non-Linearity	3	—	-40 to +125	7.6 x 7.6
1451-015A-T	103.45	A	60 mV	±0.25% Non-Linearity	3	—	-40 to +125	7.6 x 7.6
1451-030A-T	206.9	A	60 mV	±0.25% Non-Linearity	3	—	-40 to +125	7.6 x 7.6
1451-100G-T	689.66	G	60 mV	±0.25% Non-Linearity	3	—	-40 to +125	7.6 x 7.6
1471-015A-T	103.45	A	60 mV	±0.25% Non-Linearity	3	—	-40 to +125	7.6 x 7.6
17-015A	103.45	A	100 mV	±0.1% Span Non-Linearity	—	1.5	-40 to +125	φ11.4
17-015G	103.45	G	100 mV	±0.1% Span Non-Linearity	—	1.5	-40 to +125	φ11.4
17-030A	206.9	A	100 mV	±0.1% Span Non-Linearity	—	1.5	-40 to +125	φ11.4
17-030G	206.9	G	100 mV	±0.1% Span Non-Linearity	—	1.5	-40 to +125	φ11.4

A: Absolute, B: Barometric, D: Differential, G: Gauge

1kPa = 10 mbar = 10 hPa = 0.145 psi = 4.015 in H₂O



AUTHORIZED DISTRIBUTOR

Part Number	Pressure Range (kPa)	Pressure Type	Full Scale Output (V)	Accuracy (%FSO)	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
17-050G	344.83	G	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	φ11.4
17-100G	68.97	G	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	φ11.4
325401000-00	100	A	–	±0.05% or ±0.2% Non-Linearity	5	–	-40 to +125	6.2 x 6.4
325407000-00	700	A	–	±0.05% or ±0.2% Non-Linearity	5	–	-40 to +125	6.2 x 6.4
325412000-00	1200	A	–	±0.05% or ±0.2% Non-Linearity	5	–	-40 to +125	6.2 x 6.4
33A-001D	6.9	D	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	φ11.4
33A-002D	13.79	D	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	φ11.4
33A-005D	34.48	D	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	φ11.4
33A-015D	103.45	D	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	φ11.4
43A-015A	103.45	A	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	φ11.4
4425-001D	6.9	D	100 mV	±0.15% Span Non-Linearity	12	–	-40 to +125	15.2 x 13.7
4425-005D	34.48	D	100 mV	±0.15% Span Non-Linearity	12	–	-40 to +125	15.2 x 13.7
4425-015D	103.45	D	100 mV	±0.15% Span Non-Linearity	12	–	-40 to +125	15.2 x 13.7
4425-100D	689.66	D	100 mV	±0.15% Span Non-Linearity	12	–	-40 to +125	15.2 x 13.7
47-015A	103.45	A	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	φ11.4
47-030A	206.9	A	100 mV	±0.1% Span Non-Linearity	–	1.5	-40 to +125	φ11.4

A: Absolute, B: Barometric, D: Differential, G: Gauge

1kPa = 10 mbar = 10 hPa = 0.145 psi = 4.015 in H₂O



AUTHORIZED DISTRIBUTOR

SENSORS EVERYWHERE

INNOVATIVE SENSOR SOLUTIONS THAT
HELP CUSTOMERS TRANSFORM CONCEPTS
INTO SMART, CONNECTED CREATIONS.

INDUSTRIES & SOLUTIONS



AEROSPACE
& DEFENSE



APPLIANCES



AUTOMATION
& CONTROL



DATA & DEVICES



INDUSTRIAL



INDUSTRIAL & COMMERCIAL
TRANSPORTATION



INTELLIGENT BUILDINGS



MEDICAL



TEST & MEASUREMENT

System Design Center

Learn how you can leverage Future Electronics' System Design Center



Accelerate Time to Revenue

Capitalize on Future Electronics' experience and expertise to go to market quickly

.....



Control Cost

Future Electronics offers highly competitive, highly discounted NRE

.....



Global Expertise

Leverage Future Electronics' pool of global talent in North America, EMEA, and Asia

.....



Embrace Process Driven and Quality Assurance for Exceptional Products

Design exceptional products through rigorous processes and quality assurance

.....



Partnership / Continuity

Develop a partnership with Future Electronics to ensure continuity and success

.....

1 Concept

Define • Create • Develop

▼

2 Design

Engineer • Refine • Document

▼

3 Prototype

Prove • Iterate • Learn

▼

4 Manufacture

Tool • Debug • Support



Engineering Tomorrow's Ideas



Part Number	Pressure Range	Pressure Type	Digital Interface	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
NPA-600B-10WD	10" H2O	D	Serial	5	–	-40 to +125	SOIC-14, Barb port
NPA-600B-001D	1 PSI	D	Serial	5	–	-40 to +125	SOIC-14, Barb port
NPA-600B-005D	5 PSI	D	Serial	5	–	-40 to +125	SOIC-14, Barb port
NPA-600B-015D	15 PSI	D	Serial	5	–	-40 to +125	SOIC-14, Barb port
NPA-600B-030D	30 PSI	D	Serial	5	–	-40 to +125	SOIC-14, Barb port
NPA-700B-02WG	2" H2O	G	I ² C	5	–	-40 to +125	SOIC-14, Barb port
NPA-700B-05WG	5" H2O	G	I ² C	5	–	-40 to +125	SOIC-14, Barb port
NPA-700B-02WD	2" H2O	D	I ² C	5	–	-40 to +125	SOIC-14, Barb port
NPA-700B-05WD	5" H2O	D	I ² C	5	–	-40 to +125	SOIC-14, Barb port
NPA-700B-10WG	10" H2O	G	I ² C	5	–	-40 to +125	SOIC-14, Barb port
NPA-700B-001G	1 PSI	G	I ² C	5	–	-40 to +125	SOIC-14, Barb port
NPA-700B-005G	5 PSI	G	I ² C	5	–	-40 to +125	SOIC-14, Barb port
NPA-700B-015G	15 PSI	G	I ² C	5	–	-40 to +125	SOIC-14, Barb port
NPA-700B-030G	30 PSI	G	I ² C	5	–	-40 to +125	SOIC-14, Barb port
NPA-700B-015A	15 PSI	A	I ² C	5	–	-40 to +125	SOIC-14, Barb port
NPA-700B-030A	30PSI	A	I ² C	5	–	-40 to +125	SOIC-14, Barb port
NPA-700B-10WD	10" H2O	D	I ² C	5	–	-40 to +125	SOIC-14, Barb port
NPA-700B-001D	1 PSI	D	I ² C	5	–	-40 to +125	SOIC-14, Barb port
NPA-700B-005D	5 PSI	D	I ² C	5	–	-40 to +125	SOIC-14, Barb port
NPA-700B-015D	15 PSI	D	I ² C	5	–	-40 to +125	SOIC-14, Barb port
NPA-700B-030D	30PSI	D	I ² C	5	–	-40 to +125	SOIC-14, Barb port

A: Absolute, B: Barometric, D: Differential, G: Gauge

1kPa = 10 mbar = 10 hPa = 0.145 psi = 4.015 in H₂O

Part Number	Pressure Range	Pressure Type	Digital Interface	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
KP253XTMA1	60 to 165	B	SPI	3.135 to 5.25	10	-40 to +125	DSOF-8
KP254XTMA2	40 to 115	B	SPI	3.135 to 5.25	10	-40 to +125	DSOF-8
DPS310XTSA1	300–1200 hPa	B	I ² C and SPI	1.7 to 3.6	1.7 µA for pressure measurement, 1.5µA for Temperature measurement @1Hz sampling rate, Standby: 0.5 µA	-40 to +85	LGA-8 2.0 x 2.5 x 1.0
DPS368XTSA1	300–1200 hPa	B	I ² C and SPI	1.7 to 3.6	1.7 µA for pressure measurement @1Hz sampling rate, Standby: 0.5 µA	-40 to +85	LGA-, 2.0 x 2.5 x 1.1
DPS422XTSA1	300–1200 hPa	B	I ² C and SPI	1.7 to 3.6	1.7 µA for pressure measurement, 2µA for temperature measurement @1Hz sampling rate, Standby: <1 µA	-40 to +85	LGA-8 2.0 x 2.5 x 0.73

A: Absolute, B: Barometric, D: Differential, G: Gauge

1kPa = 10 mbar = 10 hPa = 0.145 psi = 4.015 in H₂O

Infineon XENSIV™ – sensing the world

Discover our broad portfolio at
www.infineon.com/sensors





Part Number	Pressure Range	Pressure Type	Digital Interface	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
MLX90809LXG-EAD-100	-1.2 to 0.05bar	D	SENT	4.5 to 5	8	-40 to +150	S016 cavity
MLX90818LXZ-BAE-015	0.1 to 4bar	A	SENT	4.5 to 5	8	-40 to +150	DFN cavity
MLX90818LXZ-BAE-016	0.1 to 3bar	A	SENT	4.5 to 5	8	-40 to +150	DFN cavity
MLX90818LXZ-BAE-017	0.1 to 4bar	A	SENT	4.5 to 5	8	-40 to +150	DFN cavity

A: Absolute, B: Barometric, D: Differential, G: Gauge

1kPa = 10 mbar = 10 hPa = 0.145 psi = 4.015 in H₂O



Part Number	Pressure Range (Pa)	Pressure Type	Digital Interface	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
SDP800-500Pa	±500	D	I ² C	3.0 to 5.5	3.8	-20 to +80	29 x 12.6 x 18
SDP810-500Pa	±500	D	I ² C	3.0 to 5.5	3.8	-20 to +80	29 x 12.6 x 18
SDP800-125Pa	±125	D	I ² C	3.0 to 5.5	3.8	-20 to +80	29 x 12.6 x 18
SDP810-125Pa	±125	D	I ² C	3.0 to 5.5	3.8	-20 to +80	29 x 12.6 x 18
SDP31	±500	D	I ² C	3.3	3.8	-40 to +85	8.5 x 5.4 x 3.5
SDP32	±125	D	I ² C	3.3	3.8	-40 to +85	8.5 x 5.4 x 3.5

A: Absolute, B: Barometric, D: Differential, G: Gauge

1kPa = 10 mbar = 10 hPa = 0.145 psi = 4.015 in H₂O



Creating Space for Your Ideas

With the World's Smallest Flow Sensor

Sensirion consolidates incomparable accuracy, long-term stability and excellent repeatability in a tiny new device called the SDP3x – the world's smallest flow and differential pressure sensor. It's the perfect choice for cost-sensitive mass production, opening up new possibilities in integration and application.

www.FutureElectronics.com/Sensors

SENSIRION
THE SENSOR COMPANY

Part Number	Pressure Range	Pressure Type	Digital Interface	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
LPS33HWTR	260-1260hPa	A,B	SPI/I ² C	1.7 to 3.6	3 µA	-40 to +85	CCLGA-10L 3.3 x 3.3
LPS22HHTR	260 to 1260 hPa	A, B	SPI, I ² C or MIPI I3CSM interfaces	1.7 to 3.6	4 µA	-40 to +85	HLGA-10L 2.0 x 2.0 x 0.73
LPS22HDTR	261 to 1260 hPa	A, B	SPI/I ² C	1.7 to 3.6V	3 µA	-40 to +85	HLGA-10L 2.0 x 2.0 x 0.76

A: Absolute, B: Barometric, D: Differential, G: Gauge

1kPa = 10 mbar = 10 hPa = 0.145 psi = 4.015 in H₂O

Part Number	Pressure Range (kPa)	Pressure Type	Digital Interface	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
325534008-00	100	A	I ² C	2.2 to 3.6	–	-40 to +125	9 x 9
325534009-00	100	A	I ² C	2.2 to 3.6	–	-40 to +125	9 x 9
325534009-50	100	A	I ² C	2.2 to 3.6	–	-40 to +125	9 x 9
325535009-00	1400	A	I ² C	2.2 to 3.6	–	-40 to +125	9 x 9
325536008-00	100	G	I ² C	2.2 to 3.6	–	-40 to +85	13 x 10.16

A: Absolute, B: Barometric, D: Differential, G: Gauge

1kPa = 10 mbar = 10 hPa = 0.145 psi = 4.015 in H₂O



The **IIS3DHC**, a 3-axis accelerometer optimized for high measurement resolution and stability to ensure accuracy over time and temperature. The IIS3DHC targets precision inclinometers in antenna-positioning mechanisms for communication systems, Structural Health Monitoring (SHM) equipment for keeping buildings and bridges safe, and stabilizers or levelers for a wide variety of industrial platforms. Its long-term accuracy and robustness are also ideal for high-sensitivity tilt and security sensors, as well as image stabilization in high-end Digital Still Cameras (DSCs).

Part Number	Pressure Range kPa	Pressure Type	Digital Interface	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
325536009-00	-100	G	I ² C	2.2 to 3.6	—	-40 to +85	13 x 10.16
325540009-00	100	A	I ² C	2.2 to 3.6	—	-40 to +85	6.2 x 6.4
325540009-50	100	A	I ² C	2.2 to 3.6	—	-40 to +85	6.2 x 6.4
325541009-00	1400	A	I ² C	2.2 to 3.6	—	-40 to +85	6.2 x 6.4
325541009-50	1400	A	I ² C	2.2 to 3.6	—	-40 to +85	6.2 x 6.4
325541010-00	3000	A	I ² C	2.2 to 3.6	—	-40 to +85	6.2 x 6.4
325541030-00	3000	A	I ² C	2.2 to 3.6	—	-40 to +85	6.2 x 6.4
325561000-00	100	A	I ² C	—	—	-40 to +85	4.75 x 4.25
325561000-50	100	A	I ² C	—	—	-40 to +85	4.75 x 4.25
4515-DS5A002DP	2068.96	D	I ² C	5.0	—	-10 to +85	12.5 x 9.9
4515-DS5B002DP	2068.96	D	I ² C	5.0	—	-10 to +85	12.5 x 9.9
4515D0-DS3BK002DPL	2068.96	D	I ² C	3.3	—	-10 to +85	12.5 x 9.9
4515D0-DS3BK004DP	2068.96	D	I ² C	3.3	—	-10 to +85	12.5 x 9.9
4515D0-DS3BK004GP	2068.96	G	I ² C	3.3	—	-10 to +85	12.5 x 9.9
4515D0-DS3BK005DP	2068.96	D	I ² C	3.3	—	-10 to +85	12.5 x 9.9
4515D0-DS3BK005GP	2068.96	G	I ² C	3.3	—	-10 to +85	12.5 x 9.9
4515D0-DS3BK020DPL	2068.96	D	I ² C	3.3	—	-10 to +85	12.5 x 9.9
4515D0-DS3BK030DPL	2068.96	D	I ² C	3.3	—	-10 to +85	12.5 x 9.9
4515D0-DS5BS002DS	2068.96	D	SPI	5.0	—	-10 to +85	12.5 x 9.9
4525D0-DS5AI001DP	2068.96	D	I ² C	5.0	—	-10 to +85	12.5 x 9.9
5525DS0-DB001DS	6.89	D	I ² C	1.8 to 3.6	—	-40 to +125	12.5 x 7.9
5525DS0-SB001GS	6.89	G	I ² C	1.8 to 3.6	—	-40 to +125	12.5 x 7.9
5525DS0-SB005GS	34.48	G	I ² C	1.8 to 3.6	—	-40 to +125	12.5 x 7.9
MS560702BA03-00	200	A	I ² C	1.5 to 3.6	—	-40 to +85	3 x 3 x 0.9
MS560702BA03-50	200	A	I ² C	1.5 to 3.6	—	-40 to +85	3 x 3 x 0.9
MS561101BA03-00	100	A	I ² C	1.8 to 3.6	—	-40 to +85	5 x 3 x 1
MS561101BA03-50	100	A	I ² C	1.8 to 3.6	—	-40 to +85	5 x 3 x 1
MS563702BA03-50	200	A	I ² C	1.5 to 3.6	—	-40 to +85	3 x 3 x 0.9
MS563730BA03-50	3000	A	I ² C	1.5 to 3.6	—	-20 to +85	14.7 x 15.2
MS580301BA01-00	100	A	I ² C	1.8 to 3.6	—	-40 to +125	6.2 x 6.4
MS580302BA01-00	200	A	I ² C	1.8 to 3.6	—	-40 to +85	6.2 x 6.4
MS580305BA01-00	500	A	I ² C	1.8 to 3.6	—	-40 to +85	6.2 x 6.4
MS580314BA01-00	1400	A	I ² C	1.8 to 3.6	—	-40 to +85	6.2 x 6.4

A: Absolute, B: Barometric, D: Differential, G: Gauge

1kPa = 10 mbar = 10 hPa = 0.145 psi = 4.015 in H₂O


BOSCH
 Invented for life

Part Number	Pressure Range	Pressure Type	Digital Interface	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
BMP280	300 to 1100 hPa	B	I ² C and SPI	V _{DDIO} : 1.2 to 3.6 V _{DD} : 1.71 to 3.6	2.74 µA @ 1 Hz	-40 to +85	2.0 × 2.5 × 0.95
BMP388	300 to 1250 hPa	B	I ² C and SPI	V _{DDIO} : 1.2 to 3.6 V _{DD} : 1.65 to 3.6	2.7 µA @ 1 Hz	-40 to +85	2.0 × 2.0 × 0.75

A: Absolute, B: Barometric, D: Differential, G: Gauge


1kPa = 10 mbar = 10 hPa = 0.145 psi = 4.015 in H₂O

Part Number	Pressure Range kPa	Pressure Type	Digital Interface	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
FXPQ3115BV	20 to 115	A	I ² C	1.95 to 3.6	–	-40 to +85	LGA 3 × 5
MPL3115A2	20 to 115	A	I ² C	1.95 to 3.6	–	-40 to +85	LGA 3 × 5
MPXH6101Axx	15 to 105	A	Analog	4.75 to 5.25	7	-40 to +125	SSOP & ported SSOP
MPXHZ6116A6	20 to 115	A	Analog	4.75 to 5.25	6	-40 to +125	SSOP
MPXHZ6130Axx	15 to 130	A	Analog	4.75 to 5.25	6	-40 to +125	SSOP & ported SSOP
MPXHZ6115Axx	15 to 115	A	Analog	4.75 to 5.25	6	-40 to +125	SOP & ported SOP / SSOP & ported SOP
MP3H6115AC6	15 to 115	A	Analog	2.7 to 3.3	4	-40 to +125	Ported SSOP

A: Absolute, B: Barometric, D: Differential, G: Gauge

1kPa = 10 mbar = 10 hPa = 0.145 psi = 4.015 in H₂O

MLX91216/17

**HIGH-SPEED
CURRENT SENSORS**

Melexis
 INSPIRED ENGINEERING



PROXIMITY

Touch Controller – Capacitive	123
Touch Controller – Resistive	123
IR Reflective Proximity Sensor.....	124
Optical Sensor.....	124
Radar Sensor.....	125
Time-of-Flight Laser Range Sensor.....	125



ON Semiconductor®





Part Number	Number of Sensing Channels	Output Interface	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
PCAP02AE	8	I ² C, SPI	2.1 to 3.6	0.0025 @ 2.5 Hz	-40 to +125	QFN-32 5 x 5
PCAP04	6	I ² C, SPI	3.0 to 3.6	0.0023 @ 2.5 Hz	-40 to +85	QFN-24 4 x 4

ON Semiconductor®



Part Number	Number of Sensing Channels	Output Interface	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
LC717A30UR	8	I ² C, SPI	2.6 to 5.5	800	-40 to +105	VCT-28
LC717A00AJ	8	I ² C, SPI	2.6 to 5.5	320 to 740	-45 to +105	SSOP-30
LC717A00AR	8	I ² C, SPI	2.6 to 5.5	320 to 740	-40 to +105	VCT-28
LC717A10AJ	16	I ² C, SPI	2.6 to 5.5	570 to 1300	-40 to +105	SSOP-30
LC717A10AR	16	I ² C, SPI	2.6 to 5.5	570 to 1300	-40 to +105	VCT-28
LC717A10PJ	16	I ² C, SPI	2.6 to 5.5	570 to 1300	-40 to +105	SSOP-30
LC717A30UJ	8	I ² C, SPI	2.6 to 5.5	800	-40 to +105	SSOP-30

PROXIMITY / Touch Controller - Resistive



Part Number	Touch Panel	Resolution	Output Interface	Power Consumption (μA)	Multi-Touch	Proximity Sensing	Package Type / Size (mm)
BU21029GUL	4-Wire	12-bit	I ² C	800	Yes	Yes	VCSP50L2 (CSP 16-Ball) 2.00 x 2.00 x 0.55
BU21029MUV	4-Wire	12-bit	I ² C	800	Yes	Yes	VQFN (20-Pin) 4.00 x 4.00 x 1.00
BU21021GUL	4-Wire	12-bit	I ² C, SPI	400	Yes	Yes	VCSP50L2 (CSP 25-Ball) 2.70 x 2.65 x 0.55
BU21023GUL	4-Wire	10-bit	I ² C, SPI	400	Yes	Yes	VCSP50L2 (CSP 25-Ball) 2.60 x 2.60 x 0.55
BU21023MUV	4-Wire	10-bit	I ² C, SPI	400	Yes	Yes	VQFN (28-Pin) 5.00 x 5.00 x 1.00
BU21025GUL	4-Wire	12-bit	I ² C	120	Yes	Yes	VCSP50L2 (CSP 12-Ball) 2.00 x 1.50 x 0.55

PROXIMITY / IR Relective Proximity Sensor



Part Number	Detection Range Max (cm)	Output Interface	Output Range	Power Consumption (µA)	Multi-Touch	Proximity Sensing	Package Type / Size (mm)
TSL26721	~45	I ² C	16-bit	2.4 to 3.6	0.2	-30 to +70	DFN (2 x 2 x 0.65)
TMD2672	~45	I ² C	16-bit	2.6 to 3.6	0.195	-30 to +85	MOD8(2.36 x 3.94 x 1.35)
TMD2620	~15	I ² C	16-bit	1.7 to 2.0	0.03	-30 to +85	OLGA8 (2 x 3.1 x 1)



Part Number	Detection Range Max (cm)	Output Interface	Output Range	Power Consumption (µA)	Multi-Touch	Proximity Sensing	Package Type / Size (mm)
VCNL3020	20	I ² C	16-bit	2.5 to 3.6	0.002	-30 to +85	SMD - 10
VCNL36687S	20	I ² C	12-bit	1.65 to 1.95	0.16	-30 to +85	SMD 3.05 x 2.0 x 1.0
TSSP4038	200	Analog	High or Low	2.5 to 5.5	0.8	-30 to +85	Through-hole
VCNL4010	200	I ² C	16-bit	2.5 to 3.6	0.005	-30 to +85	SMD 3.9 x 3.9 x 0.7
VCNL4020	200	I ² C	16-bit	2.5 to 3.6	0.005	-30 to +85	SMD 4.9 x 2.4 x 0.8
VCNL4020X01	200	I ² C	16-bit	2.5 to 3.6	0.005	-40 to +105	SMD 4.9 x 2.4 x 0.8
VCNL4040M30E	200	I ² C	16-bit	2.5 to 3.6	0.3	-30 to +85	SMD 4.0 x 2.0 x 1.1
VCNL4200	1500	I ² C	12 or 16-bit	2.5 to 3.6	0.35	-30 to +85	SMD 8.0 x 3.0 x 1.8

PROXIMITY / Optical Sensor



Part Number	Detection Range (mm)	Forward Voltage (V)	Reverse Voltage (V)	Peak Wave-length (nm)	Maximum Dark Current (nA)	Output Current (µA)	Operating Temperature (°C)	Package Type / Size (mm)
RPR-220UC30N	5 to 12	2	10	800	10000	800	-25 to +85	Through-hole 6.4 x 4.9 x 6.5



Part Number	Detection Range (mm)	Forward Voltage (V)	Reverse Voltage (V)	Peak Wave-length (nm)	Maximum Dark Current (nA)	Output Current (µA)	Operating Temperature (°C)	Package Type / Size (mm)
VCNT2020	0.2 to 2.5	1.25 to 1.7	5	940	30	1.6 mA, typical	-25 to +85	SMD 2.5 x 2 x 0.8H
TCND5000	2 to 25	1.2	1.2	940	1	0.12, typical	-40 to +85	SMD 6 x 4.3 x 3.75



Part Number	Transmitting Channels	Receive Channel	Frequency Range (GHz)	TX Output Power (dBm)	RX LNA Gain (dB)	Supply Voltage (V)	Supply Current (mA)	Package Type / Size (mm)
BGT24MTR11E6327XUMA1	1	1	24.00 to 24.25	5 to 15	26	3.3	150	VQFN-32
BGT24MTR12E6327XUMA1	1	2	24.00 to 24.25	6 to 15	26	3.3	210	VQFN-32
BGT24MR2E6327XUMA1	0	2	24.00 to 24.25	–	26	3.3	90	VQFN-32
BGT24AR2E6433XUMA1	0	2	24.00 to 24.25	–	26	3.3	90	VQFN-32
BGT24AR4E6433XUMA1	0	4	24.00 to 24.25	–	26	3.3	220	VQFN-32
BGT24AT2E6433XUMA1	2	0	24.00 to 24.25	7 to 13	26	3.3	280	VQFN-32
BGT24ATR11E6433XUMA1	1	1	24.00 to 24.25	5 to 15	26	3.3	150	VQFN-32
BGT24ATR12E6433XUMA1	1	2	24.00 to 24.25	6 to 15	26	3.3	210	VQFN-32
BGT24LTR11N16E6327XTSA1	1	1	24.00 to 24.25	2 to 10	26	3.3	55	TSNP-16-9

PROXIMITY / Time-of-Flight Laser Range Sensor



Part Number	Detection Range Max (mm)	Output Interface	Output Range	Laser Safety	Supply Voltage (V)	Supply Current (mA)	Operating Temperature (°C)	Package Type /
VL6180XV0NR/1	100	I ² C	16-bit	Class 1 (IEC 60825-1:2007)	2.6 to 3.0	0.3	-20 to +70	LGA-12 Optical 4.8 x 2.8 x 1.0
VL53L0CXV0DH/1	2000	I ² C	16-bit	Class 1 (IEC 60825-1:2014 - 3rd edition)	2.6 to 3.5	20	-20 to +70	Optical LGA12 4.40 x 2.40 x 1.00
VL53L1CXV0FY/1	4000	I ² C	16-bit	Class 1 (IEC 60825-1:2014 - 3rd edition)	2.6 to 3.5	20	-20 to +85	Optical LGA12 4.9 x 2.5 x 1.56

**SENSE, SENSIBILITY,
AND A LOT OF SENSORS**

www.vishay.com



TEMPERATURE

Analog Infrared Thermopile	127
Digital Infrared Thermometer.	128
Temperature Sensor – Analog	131
Temperature Sensor – Digital.	131
Thermistor	133
Thermistor – Inrush Current Limiter	137
PTC Thermistor - Overheat Detection	139
RTD Platinum Element.	139

Amphenol
Advanced Sensors

amun

Melexis

muRata
INNOVATOR IN ELECTRONICS

NXP

ROHM
SEMICONDUCTOR

SENSIRION
THE SENSOR COMPANY

ST
life.augmented


TE
connectivity
AUTHORIZED DISTRIBUTOR

VISHAY

Part Number	Internal Resistance (kOhm)	Resistance T.C. (% degree C)	Thermistor Resistance (kOhm)	Responsivity (V/W)	Noise Voltage (nVrms)	Diaphragm Size (mm)	Operating Temperature (°C)	Package Type / Size (mm)
ZTP-101T	200	0.1	30 ±3%	110 Typical	62	1.5 x 1.5	-20 to +100	T0-39 (T0-5)
ZTP-115	50	0.15	10 ±3%	60 Typical	30	1.0 x 1.0	-20 to +100	T0-39 (T0-5)
ZTP-135SR	60	0.12	100 ±3%	62 Typical	32	1.4 x 1.4	-20 to +100	T0-46 (T0-18)
ZTP-135SR-F1	60	0.12	100 ±3%	38 Typical	32	1.4 x 1.4	-20 to +100	T0-46 (T0-18)
ZTP-135	60	0.12	10 ±3%	60 Typical	32	1.4 x 1.4	-20 to +100	T0-46 (T0-18)
ZTP-135H	60	0.12	100 ±3%	58 Typical	32	1.4 x 1.4	-20 to +100	T0-46 (T0-18)
ZTP-135L	60	0.12	100 ±3%	58 Typical	32	1.4 x 1.4	-20 to +100	T0-46 (T0-18)
ZTP-315	50	0.12	30 ±1%	32 Typical	30	2.6 x 2.6	-20 to +100	T0-46 (T0-18)
ZTP-135BS	60	-0.03 Typical	100 ±3%	54 Typical	32	1.4 x 1.4	-20 to +100	T0-46 (T0-18)
ZTP-148SR	85	0.12	100 ±2%	61 Typical	37	1.0 X 1.0	-20 to +100	T0-46 (T0-18)



Part Number	Internal Resistance (kOhm)	Resistance T.C. (% degree C)	Thermistor Resistance (kOhm)	Responsivity (V/W)	Noise Voltage (nVrms)	Diaphragm Size (mm)	Operating Temperature (°C)	Package Type / Size (mm)
G-TPM0-101	70,000	-0.06%/K	100	7 ±2.1mV	45nV/Hz ½	0.8 x 0.8	-20 to +85	T0-5



**Particulate Matter Sensor
for HVAC and Air Quality Applications**

SENSIRION
THE SENSOR COMPANY



Part Number	Field-of-View (degree)	Object Temperature Range (°C)	Temperature Accuracy (±) (°C)	Measurement Resolution (°C)	Output Interface	Supply Voltage (V)	Quiescent Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
MLX90614KSF-AAA-000	90	-70 to +380	0.5	0.02	SMBus/PWM	4.5 to 5.5	0.006	-40 to +125	T0-39 / 4.1(h) x 9.1(d)
MLX90614KSF-ABA-000	120	-70 to +380	0.5	0.02	SMBus/PWM	4.5 to 5.5	0.006	-40 to +125	T0-39 / 4.1(h) x 9.1(d)
MLX90614KSF-ACC-000	35	-70 to +380	0.5	0.02	SMBus/PWM	4.5 to 5.5	0.006	-40 to +125	T0-39 / 8.1(h) x 10.2(d)
MLX90614ESF-AAA-000	90	-70 to +380	0.5	0.02	SMBus/PWM	4.5 to 5.5	0.006	-40 to +85	T0-39 / 4.1(h) x 9.1(d)
MLX90614ESF-ABA-000	90	-70 to +380	0.5	0.02	SMBus/PWM	4.5 to 5.5	0.006	-40 to +85	T0-39 / 4.1(h) x 9.1(d)
MLX90614ESF-ACA-000	90	-70 to +380	0.5	0.02	SMBus/PWM	4.5 to 5.5	0.006	-40 to +85	T0-39 / 4.1(h) x 9.1(d)
MLX90614ESF-BAA-000	90	-70 to +380	0.5	0.02	SMBus/PWM	2.6 to 3.6	0.006	-40 to +85	T0-39 / 4.1(h) x 9.1(d)
MLX90614ESF-BBA-000	90	-70 to +380	0.5	0.02	SMBus/PWM	2.6 to 3.6	0.006	-40 to +85	T0-39 / 4.1(h) x 9.1(d)
MLX90614ESF-BCA-000	90	-70 to +380	0.5	0.02	SMBus/PWM	2.6 to 3.6	0.006	-40 to +85	T0-39 / 4.1(h) x 9.1(d)
MLX90614ESF-ACC-000	35	-70 to +380	0.5	0.02	SMBus/PWM	4.5 to 5.5	0.006	-40 to +85	T0-39 / 8.1(h) x 10.2(d)

Melexis
INSPIRED ENGINEERING

MLX90641
16X12 PIXEL
**INFRARED (IR)
ARRAY**

FOR MORE INFORMATION: WWW.MELEXIS.COM/MLX90641



ROHM
SEMICONDUCTOR



SENSE THE FUTURE WITH ROHM

CURRENT SENSORS | ACCELEROMETERS | GEOMAGNETIC

HALL ICs | LOW POWER WIRELESS MODULES

PROXIMITY | HEART RATE | COLOR | IR | AMBIENT LIGHT

BAROMETRIC PRESSURE | TEMPERATURE | ENERGY HARVESTING



Part Number	Field-of-View (degree)	Object Temperature Range (°C)	Temperature Accuracy (±) (°C)	Measurement Resolution (°C)	Output Interface	Supply Voltage (V)	Quiescent Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
MLX90614KSF-AAA-000	90	-70 to +380	0.5	0.02	SMBus/PWM	4.5 to 5.5	0.006	-40 to +125	T0-39 / 4.1(h) x 9.1(d)
MLX90614KSF-ABA-000	120	-70 to +380	0.5	0.02	SMBus/PWM	4.5 to 5.5	0.006	-40 to +125	T0-39 / 4.1(h) x 9.1(d)
MLX90614KSF-ACC-000	35	-70 to +380	0.5	0.02	SMBus/PWM	4.5 to 5.5	0.006	-40 to +125	T0-39 / 8.1(h) x 10.2(d)
MLX90614ESF-AAA-000	90	-70 to +380	0.5	0.02	SMBus/PWM	4.5 to 5.5	0.006	-40 to +85	T0-39 / 4.1(h) x 9.1(d)
MLX90614ESF-ABA-000	90	-70 to +380	0.5	0.02	SMBus/PWM	4.5 to 5.5	0.006	-40 to +85	T0-39 / 4.1(h) x 9.1(d)
MLX90614ESF-ACA-000	90	-70 to +380	0.5	0.02	SMBus/PWM	4.5 to 5.5	0.006	-40 to +85	T0-39 / 4.1(h) x 9.1(d)
MLX90614ESF-BAA-000	90	-70 to +380	0.5	0.02	SMBus/PWM	2.6 to 3.6	0.006	-40 to +85	T0-39 / 4.1(h) x 9.1(d)
MLX90614ESF-BBA-000	90	-70 to +380	0.5	0.02	SMBus/PWM	2.6 to 3.6	0.006	-40 to +85	T0-39 / 4.1(h) x 9.1(d)
MLX90614ESF-BCA-000	90	-70 to +380	0.5	0.02	SMBus/PWM	2.6 to 3.6	0.006	-40 to +85	T0-39 / 4.1(h) x 9.1(d)
MLX90614ESF-ACC-000	35	-70 to +380	0.5	0.02	SMBus/PWM	4.5 to 5.5	0.006	-40 to +85	T0-39 / 8.1(h) x 10.2(d)
MLX90614ESF-BCC-000	35	-70 to +380	0.5	0.02	SMBus/PWM	2.6 to 3.6	0.006	-40 to +85	T0-39 / 8.1(h) x 10.2(d)
MLX90614ESF-ACF-000	10	-70 to +380	0.5	0.02	SMBus/PWM	4.5 to 5.5	0.006	-40 to +85	T0-39 / 17.2(h) x 9.1(d)
MLX90614ESF-BCF-000	10	-70 to +380	0.5	0.02	SMBus/PWM	2.6 to 3.6	0.006	-40 to +85	T0-39 / 17.2(h) x 9.1(d)
MLX90614ESF-BCH-000	12	-70 to +380	0.5	0.02	SMBus/PWM	2.6 to 3.6	0.006	-40 to +85	T0-39 / 8.3(h) x 9.1(d)
MLX90614ESF-BCI-000	5	-70 to +380	0.5	0.02	SMBus/PWM	2.6 to 3.6	0.006	-40 to +85	T0-39 / 20.2(h) x 9.1(d)
MLX90614ESF-ACK-000	15	-70 to +380	1	0.02	SMBus/PWM	4.5 to 5.5	0.006	-40 to +85	T0-39 / 8.1(h) x 10.2(d)
MLX90614ESF-BCK-000	15	-70 to +380	1	0.02	SMBus/PWM	2.6 to 3.6	0.006	-20 to +85	T0-39 / 8.1(h) x 10.2(d)
MLX90632SLD-BCB-000	50	-20 to +200	1	0.02	I ² C	3 to 3.6	0.0025	-20 to +85	QFN / 1(h) x 3(d)
MLX90614ESF-DAA-000	90	-70 to +380	0.2	0.02	SMBus/PWM	2.6 to 3.6	0.006	-40 to +85	T0-39 / 4.1(h) x 9.1(d)
MLX90614ESF-DCA-000	90	-70 to +380	0.2	0.02	SMBus/PWM	2.6 to 3.6	0.006	-40 to +85	T0-39 / 4.1(h) x 9.1(d)
MLX90614ESF-DCC-000	35	-70 to +380	0.2	0.02	SMBus/PWM	2.6 to 3.6	0.006	-40 to +85	T0-39 / 8.1(h) x 10.2(d)
MLX90614ESF-DCH-000	12	-70 to +380	0.2	0.02	SMBus/PWM	2.6 to 3.6	0.006	-40 to +85	T0-39 / 8.3(h) x 9.1(d)
MLX90614ESF-DCI-000	5	-70 to +380	0.2	0.02	SMBus/PWM	2.6 to 3.6	0.006	-40 to +85	T0-39 / 20.2(h) x 9.1(d)
MLX90615SSG-DAA-000	100	-40 to +115	0.2	0.02	SMBus/PWM	2.6 to 3.4	0.003	-40 to +85	T0-46 / 2.7(h) x 5.4(d)
MLX90615SSG-DAG-000	80	-40 to +115	0.2	0.02	SMBus/PWM	2.6 to 3.4	0.003	-40 to +85	T0-46 / 2.7(h) x 5.4(d)
MLX90621ESF-BAA-000	120 x 25	-40 to +300	1	0.02	I ² C	2.5 to 3.3	0.009	-40 to +85	T0-39 / 5.51(h) x 9.3(d)
MLX90621ESF-BAB-000	60 x 15	-40 to +300	1	0.02	I ² C	2.5 to 3.4	0.009	-40 to +85	T0-39 / 11.15(h) x 9.3(d)
MLX90621ESF-BAD-000	40 x 10	-40 to +300	1	0.02	I ² C	2.5 to 3.5	0.009	-40 to +85	T0-39 / 14.15(h) x 9.3(d)
MLX90640ESF-BAA-000	110 x 75	-40 to +300	1	0.02	I ² C	2.9 to 3.6	0.015	-40 to +85	T0-39 / 5.7(h) x 9.3(d)
MLX90640ESF-BAB-000	55 x 40	-40 to +300	1	0.02	I ² C	2.9 to 3.6	0.015	-40 to +85	T0-39 / 11.25(h) x 9.3(d)



Part Number	Object Temperature Range (°C)	Temperature Accuracy (±) (°C)	Measurement Resolution (°C)	Output Interface	Supply Voltage (V)	Quiescent Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
G-TPMO-014	-20 to +120	± 5	± 0.1	1 hz	4 to 6	10	-10 to +85	25 X 35
G-TPMO-025	0 to +300	<4	± 0.1	1 hz	3.3	10	-10 to +85	25 X 35



Part Number	Temperature Accuracy ($\pm$) ($^{\circ}\text{C}$)	Sensor Gain (mV/ $^{\circ}\text{C}$)	Supply Voltage (V)	Quiescent Current (μA)	Operating Temperature ($^{\circ}\text{C}$)	Package Type / Size (mm)
BDJ0600AHFV	2.5	N/A, Thermostat Interrupt Output Only, 60C Detect Temp	2.4 to 5.5	7.5	-30 to +100	HVSOF5 (5-pin) 1.6 x 1.6 x 0.6
BDJ0700AHFV	2.5	N/A, Thermostat Interrupt Output Only, 70C Detect Temp	2.4 to 5.5	7.5	-30 to +100	HVSOF5 (5-pin) 1.6 x 1.6 x 0.6
BDJ0800AHFV	2.5	N/A, Thermostat Interrupt Output Only, 80C Detect Temp	2.4 to 5.5	7.5	-30 to +100	HVSOF5 (5-pin) 1.6 x 1.6 x 0.6



Part Number	Temperature Accuracy ($\pm$) ($^{\circ}\text{C}$)	Sensor Gain (mV/ $^{\circ}\text{C}$)	Supply Voltage (V)	Quiescent Current (μA)	Operating Temperature ($^{\circ}\text{C}$)	Package Type / Size (mm)
STLM20W87F	± 0.5	± 0.5	2.4 to 5.5	2.4 to 5.5	-55 to +130	SC70-5, UDFN4
STLM20DD9F	± 0.5	± 0.5	2.4 to 5.5	2.4 to 5.5	-40 to +85	UDFN-4L
LM135	± 1	± 0.5	3.01 máx	—	-55 to +150	To-92, SO-8
LM235	± 1	± 0.5	3.01 máx	—	-40 to +120	To-92, SO-8
LM335	± 1	± 0.5	3.01 máx	—	-40 to +100	To-92, SO-8



Part Number	Temperature Accuracy ($\pm$) ($^{\circ}\text{C}$)	Sensor Gain (mV/ $^{\circ}\text{C}$)	Supply Voltage (V)	Quiescent Current (μA)	Operating Temperature ($^{\circ}\text{C}$)	Package Type / Size (mm)
GA10K3D1031-UL	$\pm 1\%$	-4.40%	—	—	0 to +95	Ring lug
GA100K6D234	$\pm 0.2^{\circ}\text{C}$	-4.68%	—	—	-40 to +125	Leaded
GA10K3435DM010	$\pm 1\%$	-3.87%	—	—	-40 to +125	Overmold probe
GA10K4D25	$\pm 0.2^{\circ}\text{C}$	-4.04%	—	—	-40 to +125	Flag terminal



Part Number	Temperature Accuracy ($\pm$) ($^{\circ}\text{C}$)	Output Interface	Supply Current (mA)	Resolution (bit)	Supply Voltage (V)	Operating Temperature ($^{\circ}\text{C}$)	Package Type / Size (mm)
AS6200	± 0.4 (0 to +65)	I ² C	6 μA @ 4 samples/sec	12	1.8 to 3.6	-40 to +125	WLCSP / 1.5 x 1.0
AS6204	± 0.4 (0 to +65)	I ² C	6 μA @ 4 samples/sec	12	1.8 to 3.6	-40 to +125	WLCSP / 1.5 x 1.0
AS6200C	± 0.2 (-20 to +810)	I ² C	6 μA @ 4 samples/sec	12	1.8 to 3.6	-40 to +125	WLCSP / 1.5 x 1.0



Part Number	Temperature Accuracy (±)(°C)	Output Interface	Supply Current (mA)	Resolution (bit)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
LM75B	2	I ² C	0.3	11	2.8 to 5.5	-55 to +125	SOT96-1, SOT505-1, SOT996-2, SOT1069-2
PCT2075	1	I ² C	0.40	11	2.7 to 5.5	-55 to +125	SOT96-1, SOT505-1, SOT1069-2, SOT1353-1
PCT2202	1	I ² C	0.45	12	1.65 to 1.95	-40 to +125	WLCS6 (0.69 x 1.09 x 0.382)
SA56004X	2	I ² C	0.5	11	3.0 to 3.6	-40 to +125	SOT96-1, SOT505-1, SOT782-1
SE95	1	I ² C	1.00	11, 13	2.8 to 5.5	-55 to +125	SOT96-1, SOT505-1
SE97B	1	I ² C	0.40	11	3.0 to 3.6	-40 to +125	SOT1069-2
SE98A	1	I ² C	0.4	11	1.7 to 3.6	-40 to +125	SOT1069-2
NHS3100	±0.3	NFC, I ² C, SPI	0.4	12	1.72 to 3.6	-40 to +85	HVQFN-24
NHS3100UK	±0.3	NFC, I ² C, SPI	0,003 to 0,15	12	1.72 to 3.6	-40 to +85	WLCSP-25
NHS3100W8	±0.3	NFC, I ² C, SPI	0,003 to 0,15	12	1.72 to 3.6	-40 to +85	W8 (gold bumps on die)
NHS3152	±0.3	NFC, I ² C, SPI	0,003 to 0,15	12	1.72 to 3.6	-40 to +85	HVQFN-24
NHS3152UK	±0.3	NFC, I ² C, SPI	0,003 to 0,15	12	1.72 to 3.6	-40 to +85	WLCSP-25



Part Number	Temperature Accuracy (±)(°C)	Output Interface	Supply Current (mA)	Resolution (bit)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
STS30	±0.3	I ² C	2	16	2.4 to 5.5	-40 to +85	2.5 x 2.5 x 0.9
STS31	±0.2	I ² C	2	16	2.4 to 5.5	-40 to +85	2.5 x 2.5 x 0.9



life.augmented

Part Number	Temperature Accuracy (±)(°C)	Output Interface	Supply Current (mA)	Resolution (bit)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
STTS75	±0.5	I ² C	0.001	9, 10, 11, 12	2.7 to 5.5	-55 to +125	TSSOP8 or S08
STDS75	±0.5	I ² C	0.001	9, 10, 11, 12	2.7 to 5.5	-55 to +125	TSSOP8
STCN75	±0.5	I ² C	0.001	9	2.7 to 5.5	-55 to +125	TSSOP8
STLM75	±0.5	I ² C	0.001	9	2.7 to 5.5	-55 to +125	TSSOP8 or S08
STTS751	±0.5	I ² C / SMBus	0.002	8	3	-40 to +125	UDFN-6L or SOT23-6L
STTS2004	±1	I ² C / SMBus	0.002	9	3	-40 to +125	TDFN8



AUTHORIZED DISTRIBUTOR

Part Number	Temperature Accuracy (±)(°C)	Output Interface	Supply Current (mA)	Resolution (bit)	Supply Voltage (V)	Operating Temperature (°C)	Package Type / Size (mm)
G-NICO-018	±0.1	SPI, I ² C	12.5 uA	—	3.0	-40 to +125	4 X 4
G-NIMO-003	±0.2 to 1	I ² C	18 uA	—	3.0	-40 to +125	2.5 X 2.5

Part Number / Series	R25 (Ohm)	Tolerances	Temperature Coefficient (%/K)	Operating Temperature (°C)	Package Type / Size (mm)
RL0503-xxx	2K to 100K	±1°C	-3.8 to -4.9	-50 to +150	Epoxy coated with insulated leads
03006-xxx	250 to 1M	2% to 10%	-3.34 to -5.26	-50 to +150	Glass encapsulated - MELF
AL03006-xxx	250 to 1M	2% to 10%	-3.34 to -5.26	-50 to +204	DO-35 glass encapsulated
EC95xxx	1K to 100K	±1°C or ±2°C	-4.04 to -4.68	-80 to +150	Epoxy coated chip with 0.008"OD leads
DC95xxx	2K to 100K	±1°C or ±2°C	-4.04 to -4.68	-80 to +150	Epoxy coated chip with 0.012"OD leads
TK95xxx	2K to 100K	±1°C or ±2°C	-4.04 to -4.68	-80 to +150	Epoxy coated chip with insulated leads
MC65xxx	2252 to 100K	±0.05°C or ±0.1°C or ±0.15°C	-4.04 to -4.39	-40 to +105	Epoxy coated with insulated leads
RL10xx	75 to 350K	±10%	-3.42 to -5.23	-50 to +150	Bare discs with uninsulated leads
RL20xx	25 to 100K	±10%	-3.42 to -5.23	-50 to +150	Bare discs with uninsulated leads
RL30xx	10 to 30K	±10%	-3.42 to -5.23	-50 to +150	Bare discs with uninsulated leads
RL40xx	50 to 10K	±10%	-3.83 to -5.18	-50 to +150	Bare discs with uninsulated leads
RLxxxx	1K to 10K	±1°C	-4.50	-50 to +150	Interchangeable discs
DKxxx	2K to 100K	±3% or ±5% or ±10%	-3.89 to -4.36	-40 to +250	Glass encapsulated
THxxx	2K to 100K	±5%	-3.34 to -5.26	-40 to +250	DO-35 glass encapsulated
C100xx	3K to 100K	±2% or ±5% or ±10%	-4.04 to -4.39	-80 to +150	Epoxy Coated
MA100xxx	2252 to 10K	±0.05°C or ±0.1°C or ±0.15°C	4.39	0 to +50	0.030" OD cap with insulated leads
MA300xxx	5K or 10K	±0.1°C or ±0.15°C	4.39	0 to +50	0.375" OD S/S disc with insulated leads
SCxxx	2.3K to 100K	±0.05°C or ±0.1°C or ±0.2°C	-4.04 to -4.39	-40 to +150	0.032" or 0.050" OD cap with insulated leads
NHQxxx	100 to 500K	±5% or ±10%	—	-40 to +125	1206 size
NHQMxxx	40 to 500K	±5% or ±10%	—	-40 to +125	0805 size
NHQMMxxx	30 to 200K	±5% or ±10%	—	-40 to +125	0603 size
NKAxxx	50 to 50K	±1% or ±2% or ±10%	-4.39 to	-40 to +190	Insulated chip and leads
NKxxx	50 to 50K	±1% or ±2% or ±5% or ±10%	-3.74 to -4.39	-40 to +155	Epoxy coated chip
FP07xxx	2K to 270K	±25%	-3.45 to -4.50	-80 to +200	Fast tip with 0.1sec still air response
ABxxx	51 to 20M	±1% to ±25%	-3.26 to -5.47	-40 to +175	0.0125"-0.022" OD with #38 or #40 or #44 AWG Ni/Cu leads
A-1996	2786	—	-4.5	-40 to +190	Twistlock sensor with an integral connector
A-1737	30000	±5%	4.34	-40 to +210	Radial leaded flexible sensor assembly with Molex terminal
GE-1920	2828	±1.3%	-4.39	-40 to +100	Threaded plated steel with integral connector

Amphenol

Advanced Sensors

Part Number / Series	R25 (Ohm)	Tolerances	Temperature Coefficient (%/K)	Operating Temperature (°C)	Package Type / Size (mm)
GE-2102	10K	±1.5%	-4.39	-40 to +120	1/2" hose, nylon inline sensor with integrated connector
GE-2103	10K	±1.5%	-4.39	-40 to +120	1 1/4" hose, nylon inline sensor with integrated connector
GE-1935	10K	±1.5%	-4.39	-40 to +120	3/4" hose, nylon inline sensor with integrated connector
JS6780	2795	±2.5%	-4.46	-40 to 85	Flange mount with harness and connector
GE-1571	2820	±4.86%	-4.5	-40 to 150	Stainless steel probe with harness wires and connector
WTF083B001	2828	±1.3%	-4.39	-40 to +100	Threaded plated steel with integral sealed USCAR connector
GE-1711	10K	±5%	-4.39	-40 to +180 (at housing)	Threaded brass probe with harness wires and Delphi Metri-Pack Connector
GE-1797	10K	±5%	-4.39	-40 to +180 (at housing)	Threaded stainless steel probe with harness wires and Delphi Metri-Pack Connector
GE-1711ATM	10K	±5%	-4.39	-40 to +180 (at housing)	Threaded brass probe with harness wires and Amphenol-Sine ATM Connector
GE-1797ATM	10K	±5%	-4.39	-40 to +180 (at housing)	Threaded stainless steel probe with harness wires and Amphenol-Sine ATM Connector
JS8741A	2.7K	±5%	-4.39	-40 to +120	Spring Clip of Galvanized Steel
JS8741B	10K	±5%	-4.39	-40 to +120	Spring Clip of Galvanized Steel
JS8741C	30K	±5%	-4.39	-40 to +120	Spring Clip of Galvanized Steel
JI-103C1R2-L301	10K	±2% or ±0.2°C	-4.39	-50 to +105	Double insulated chip and leads
JI-103C1R2-L102	10K	±2% or ±0.2°C	-4.39	-50 to +105	Double insulated chip and leads
JI-103C1R2-L252	10K	±2% or ±0.2°C	-4.39	-50 to +105	Double insulated chip and leads
JI-F103WN-L301	10K	±2% or ±0.2°C	-4.39	-50 to +105	Double insulated chip and leads
JI-F103WN-L102	10K	±2% or ±0.2°C	-4.39	-50 to +105	Double insulated chip and leads
JI-F103WN-L252	10K	±2% or ±0.2°C	-4.39	-50 to +105	Double insulated chip and leads

Part Number / Series	R25 (Ohm)	Tolerances	Temperature Coefficient (%/K)	Operating Temperature (°C)	Package Type / Size (mm)
NCU15WB473D6SRC	47k	0.5	-4.56*	-40 to +150	1.0 x 0.5
NCU15WB473E6SRC	47k	3	-4.56*	-40 to +150	1.0 x 0.5
NCU15WB473F6SRC	47k	1	-4.56*	-40 to +150	1.0 x 0.5
NCU15WB473J6SRC	47k	5	-4.56*	-40 to +150	1.0 x 0.5
NCU15WF104D6SRC	100k	0.5	-6.8*	-40 to +150	1.0 x 0.5
NCU15WF104E6SRC	100k	3	-6.8*	-40 to +150	1.0 x 0.5
NCU15WF104F6SRC	100k	1	-6.8*	-40 to +150	1.0 x 0.5
NCU15WF104J6SRC	100k	5	-6.8*	-40 to +150	1.0 x 0.5
NCU15XH103D6SRC	10k	0.5	-5.408*	-40 to +150	1.0 x 0.5
NCU15XH103E6SRC	10k	3	-5.408*	-40 to +150	1.0 x 0.5
NCU15XH103F6SRC	10k	1	-5.408*	-40 to +150	1.0 x 0.5
NCU15XH103J6SRC	10k	5	-5.408*	-40 to +150	1.0 x 0.5
NCU15WB473D60RC	47k	0.5	-6.48*	-40 to +125	1.0 x 0.5
NCU15WB473E60RC	47k	3	-6.48*	-40 to +125	1.0 x 0.5
NCU15WB473F60RC	47k	1	-6.48*	-40 to +125	1.0 x 0.5
NCU15WB473J60RC	47k	5	-6.48*	-40 to +125	1.0 x 0.5
NCU15WF104D60RC	100k	0.5	-6.8*	-40 to +125	1.0 x 0.5
NCU15WF104E60RC	100k	3	-6.8*	-40 to +125	1.0 x 0.5
NCU15WF104F60RC	100k	1	-6.8*	-40 to +125	1.0 x 0.5
NCU15WF104J60RC	100k	5	-6.8*	-40 to +125	1.0 x 0.5
NCU15XH103D60RC	10k	0.5	-5.408*	-40 to +125	1.0 x 0.5
NCU15XH103E60RC	10k	3	-5.408*	-40 to +125	1.0 x 0.5
NCU15XH103F60RC	10k	1	-5.408*	-40 to +125	1.0 x 0.5
NCU15XH103J60RC	10k	5	-5.408*	-40 to +125	1.0 x 0.5

* = approximate value

Part Number / Series	R25 (Ohm)	Tolerance (%)	Max Steady State Current (Amps)	Operating Temperature (°C)	Package Type / Size (mm)
GA100K6MBD1	100K	±0.2°C 0 to 70°C	-4.68	-40 to +125	Leaded
GA100K6MCD1	100K	±0.1°C @ 25°C	-4.68	-40 to +125	Leaded
GA10K3A1A	10K	±0.1°C 0 to 70°C	-4.4	-40 to +125	Leaded
GA10K3A1A-UL	10K	±0.1°C 0 to 70°C	-4.4	-40 to +125	Leaded
GA10K3MBD1	10K	±0.2°C 0 to 70°C	-4.4	-40 to +125	Leaded
GA10K3MCD1	10K	±0.1°C @ 25°C	-4.4	-40 to +125	Leaded
GA10K3D1217	10K	±1% 25°C to 85°C	-4.4	-40 to +125	Pipe mount



Part Number / Series	R25 (Ohm)	Tolerances	Temperature Coefficient (%/K)	Operating Temperature (°C)	Package Type / Size (mm)
NTCS0805	2K2 to 680K	1%, 2%, 3%, 5%	-3.69 to -4.53	-40 to +150	Surface Mount, 0805
NTCS0603	2K to 100K	1%, 2%, 3%, 5%	-3.59 to -4.52	-40 to +150	Surface Mount, 0603
NTCS0402	4K7 to 100K	1%, 2%, 3%, 5%	-3.03 to -4.48	-40 to +150	Surface Mount, 0402
NTCS...SMT	100K to 210K	1%	-3.93	-40 to +150	Surface Mount, 0402, 0603, 0805
NTCSMELF	10K to 100K	5%	-4.38	-40 to +150	Surface Mount, MELF
NTHS1206	6K to 220K	1%, 2%, 3%, 5%, 10%	-3.84 to -4.50	-40 to +125	Surface Mount, 1206
NTHS0805	4.7K to 200K	1%, 2%, 3%, 5%, 10%	-3.84 to -4.50	-40 to +125	Surface Mount, 0805
NTHS0603	6.8K to 220K	1%, 2%, 3%, 5%, 10%	-3.84 to -4.50	-40 to +125	Surface Mount, 0603
NTHS0402	10K to 250K	3%, 5%, 10%	-3.84 to -4.50	-40 to +125	Surface Mount, 0402
NTCC200/300	4.7K to 20K	1%, 2%, 3%, 5%	-3.75 to -4.22	-55 to +175	Wire Bondable Die
NTCLE100	3R3 to 470K	2%, 3%, 5%	-3.22 to -4.97	-40 to +125	Radial Through-Hole
M, C, T	30R to 1M	1%, 5%, 10%; 0.2°C, 0.5°C, 1.0°C	-3.84 to -5.23	-40 to +125	Radial Through-Hole
NTCLE203	2K to 470K	1%, 2%, 3%, 5%	-3.87 to -4.97	-40 to +125	Radial Through-Hole
NTCLE203...SB0	2K06 to 30K	0.5°C	-3.87 to -4.51	-55 to +150	Radial Through-Hole
NTCLE213	2K1 to 100K	1%, 2%, 3%, 5%	-3.85 to -4.57	-55 to +150	Radial Through-Hole
NTCLE201	3K to 10K	0.5°C	-4.37	-40 to +125	Radial Through-Hole
NTCLE300	3K to 10K	0.5°C	-4.37	-40 to +125	Radial Through-Hole
NTCLE305	2K06 to 10K	0.5°C	-3.85 to -4.39	-40 to +125	Radial Through-Hole
NTCLE400	2K2 to 100K	3%	-4.38 to -4.47	-40 to +85	Long Lead Through-Hole
NTCLE413	4K7 to 100K	1%, 3%, 5%	-3.75 to -4.57	-40 to +105	Radial Through-Hole
NTCLE428	4K7 to 100K	1%, 3%, 5%	-3.75 to -4.47	-40 to +105	Radial Through-Hole
NTCLG100	10K to 220K	5%	-4.10 to -4.38	-40 to +200	Axial Through-Hole
NTCALUG01A	4K7 to 100K	1%, 2%, 3%, 5%	-3.75 to -4.57	-40 to +150	Assembly
NTCALUG01T	10K	1%, 2%,	-3.75 to -4.39	-40 to +150	Assembly
NTCALUG02A	4K7 to 100K	1%, 2%, 3%	-3.75 to -4.57	-55 to +125	Assembly
NTCALUG03A	10K to 47K	2%, 3%	-4.10 to -4.39	-40 to +125	Assembly
NTCALUG54A	10K	2%, 3%	-3.75 to -4.39	-40 to +150	Assembly
NTCALUG85A	10K	2%	-3.75 to -4.39	-40 to +150	Assembly
NTCALUG91A	10K	2%, 3%	-3.75 to -4.39	-40 to +150	Assembly
NTCACAP	2K7 to 10K	1%, 2%	-4.39	-55 to +60	Assembly
NTCAFLEX	10K to 122K	1%, 3%	-3.93 to -4.41	-40 to +125	Assembly
NTCAIMME3C90373/ NTCAIMME3C90686	10K	3%	-4.39	-25 to +105	Assembly
NTCASCW	1K to 470K	1%, 2%, 5%	-3.87 to -4.95	-25 to +100	Assembly
NTCLP450	100K	3%	-4.57	-40 to +105	Assembly
PTCSL03	20 to 120	—	—	-40 to +165	Radial Through-Hole
TFPT1206	100R to 10K	0.5%, 1%, 5%	0.41	-55 to +150	Surface Mount, 1206
TFPT0805	100R to 5K	0.5%, 1%, 5%	0.41	-55 to +150	Surface Mount, 0805
TFPT0603	100R to 1K	0.5%, 1%, 5%	0.41	-55 to +150	Surface Mount, 0603

Amphenol

Advanced Sensors

Part Number / Series	R25 (Ohm)	Tolerance (%)	Max Steady State Current (Amps)	Operating Temperature (°C)	Package Type / Size (mm)
CL-11	0.7	25	12	-50 to +175	Epoxy coated disc, PCB mount
CL-21	1.3	25	8	-50 to +175	Epoxy coated disc, PCB mount
CL-30	2.5	25	8	-50 to +175	Epoxy coated disc, PCB mount
CL-40	5	25	6	-50 to +175	Epoxy coated disc, PCB mount
CL-50	7	25	5	-50 to +175	Epoxy coated disc, PCB mount
CL-60	10	25	5	-50 to +175	Epoxy coated disc, PCB mount
CL-70	16	25	4	-50 to +175	Epoxy coated disc, PCB mount
CL-80	47	25	3	-50 to +175	Epoxy coated disc, PCB mount
CL-90	120	25	2	-50 to +175	Epoxy coated disc, PCB mount
CL-101	0.5	25	16	-50 to +175	Epoxy coated disc, PCB mount
CL-110	10	25	3.2	-50 to +175	Epoxy coated disc, PCB mount
CL-120	10	25	1.7	-50 to +175	Epoxy coated disc, PCB mount
CL-130	50	25	1.6	-50 to +175	Epoxy coated disc, PCB mount
CL-140	50	25	1.1	-50 to +175	Epoxy coated disc, PCB mount
CL-150	5	25	4.7	-50 to +175	Epoxy coated disc, PCB mount
CL-160	5	25	2.8	-50 to +175	Epoxy coated disc, PCB mount
CL-170	16	25	2.7	-50 to +175	Epoxy coated disc, PCB mount
CL-180	16	25	1.7	-50 to +175	Epoxy coated disc, PCB mount
CL-190	25	25	2.4	-50 to +175	Epoxy coated disc, PCB mount
CL-200	25	25	1.7	-50 to +175	Epoxy coated disc, PCB mount
CL-210	30	25	1.5	-50 to +175	Epoxy coated disc, PCB mount
CL-11A	0.07	25	12	-50 to +175	Epoxy coated disc, PCB mount
CL-21A	1.3	25	8	-50 to +175	Epoxy coated disc, PCB mount
CL-30A	2.5	25	8	-50 to +175	Epoxy coated disc, PCB mount
CL-40A	5	25	6	-50 to +175	Epoxy coated disc, PCB mount
CL-50A	7	25	5	-50 to +175	Epoxy coated disc, PCB mount
CL-60A	10	25	5	-50 to +175	Epoxy coated disc, PCB mount
CL-70A	16	25	4	-50 to +175	Epoxy coated disc, PCB mount
CL-80A	47	25	3	-50 to +175	Epoxy coated disc, PCB mount
CL-90A	120	25	2	-50 to +175	Epoxy coated disc, PCB mount
CL-101A	0.5	25	16	-50 to +175	Epoxy coated disc, PCB mount
CL-110A	10	25	3.2	-50 to +175	Epoxy coated disc, PCB mount
CL-120A	10	25	1.7	-50 to +175	Epoxy coated disc, PCB mount
CL-130A	50	25	1.6	-50 to +175	Epoxy coated disc, PCB mount
CL-140A	50	25	1.1	-50 to +175	Epoxy coated disc, PCB mount
CL-150A	5	25	4.7	-50 to +175	Epoxy coated disc, PCB mount
CL-160A	5	25	2.8	-50 to +175	Epoxy coated disc, PCB mount

Amphenol

Advanced Sensors

Part Number / Series	R25 (Ohm)	Tolerance (%)	Max Steady State Current (Amps)	Operating Temperature (°C)	Package Type / Size (mm)
CL-170A	16	25	2.7	-50 to +175	Epoxy coated disc, PCB mount
CL-180A	16	25	1.7	-50 to +175	Epoxy coated disc, PCB mount
CL-190A	25	25	2.4	-50 to +175	Epoxy coated disc, PCB mount
CL-200A	25	25	1.7	-50 to +175	Epoxy coated disc, PCB mount
CL-210A	30	25	1.5	-50 to +175	Epoxy coated disc, PCB mount



Part Number / Series	R25 (Ohm)	Tolerance (%)	Max Steady State Current (mA)	Operating Temperature (°C)	Package Type / Size (mm)
PRG18BB101MS1RB	100	20	200	-20 to +75	1.6 x 0.8
PRG18BB221MS1RB	220	20	90	-20 to +75	1.6 x 0.8
PRG18BB330MS1RB	33	20	600	-20 to +75	1.6 x 0.8
PRG18BB470MS1RB	47	20	420	-20 to +75	1.6 x 0.8
PRG18BB471MS1RB	470	20	40	-20 to +75	1.6 x 0.8
PRG21AR420MS1RA	42	20	590	-20 to +75	2.0 x 1.25
PRG21AR100MS5RA	10	20	3750	-40 to +105	2.0 x 1.25
PRG21AR150MS5RA	15	20	2500	-40 to +105	2.0 x 1.25
PRG21AR220MS5RA	22	20	1710	-40 to +105	2.0 x 1.25
PRG21AR4R7MS5RA	4.7	20	8000	-40 to +105	2.0 x 1.25
PRG21AR8R2MS5RA	8.2	20	2440	-40 to +105	2.0 x 1.25
PRG21BC2R2MS5RA	2.2	20	9000	-40 to +85	2.0 x 1.25
PRG21BC3R3MS5RA	3.3	20	7500	-40 to +85	2.0 x 1.25
PRG21BC4R7MS5RA	4.7	20	8000	-40 to +85	2.0 x 1.25
PRG21BC6R8MS5RA	6.8	20	5500	-40 to +85	2.0 x 1.25



Part Number / Series	R25 (Ohm)	Tolerance (%)	Max Steady State Current (Amps)	Operating Temperature (°C)	Package Type / Size (mm)
PTCEL	60 to 500	130 to 140	40	-40 to +105	Radial Through-Hole

TEMPERATURE / PTC Thermistor - Overheat Detection



Part Number / Series	Sensing Temp 1 (°C)	Sensing Temp 2 (°C)	Max Voltage (V)	R25 (ohm)	Operating Temperature (°C)	Package Type / Size (mm)	Grade
PRF18AR471QS5RB	135	150	32	470	-40 to +150	1.6 x 0.8	Automotive
PRF18AS471QS5RB	145	—	32	470	-40 to +150	1.6 x 0.8	Automotive
PRF18BA471QS5RB	125	140	32	470	-40 to +150	1.6 x 0.8	Automotive
PRF18BB471QS5RB	115	130	32	470	-40 to +150	1.6 x 0.8	Automotive
PRF18BB471RS5RB	115	130	32	470	-40 to +150	1.6 x 0.8	Automotive
PRF18BC471QS5RB	105	120	32	470	-40 to +150	1.6 x 0.8	Automotive
PRF18BC471RS5RB	105	120	32	470	-40 to +150	1.6 x 0.8	Automotive
PRF18BD471QS5RB	95	110	32	470	-40 to +150	1.6 x 0.8	Automotive
PRF18BD471RS5RB	95	110	32	470	-40 to +150	1.6 x 0.8	Automotive
PRF18BE471QS5RB	85	100	32	470	-40 to +150	1.6 x 0.8	Automotive
PRF18BE471RS5RB	85	100	32	470	-40 to +150	1.6 x 0.8	Automotive
PRF18BF471QS5RB	75	90	32	470	-40 to +150	1.6 x 0.8	Automotive
PRF18BF471RS5RB	75	90	32	470	-40 to +150	1.6 x 0.8	Automotive
PRF18BG471QS5RB	65	80	32	470	-40 to +150	1.6 x 0.8	Automotive
PRF18BG471RS5RB	65	80	32	470	-40 to +150	1.6 x 0.8	Automotive

TEMPERATURE / RTD Platinum Element



Part Number / Series	R0°C (Ohm)	Tolerance	Supply Current (mA)	Operating Temperature (°C)	Temperature Coefficient (ppm/K)	Package Type / Size (mm)
Exhaust Gas High Temp Sensor CTTS-186019-F02A	200	±1.5°C from 300 to 850°C & ±4.5°C from -40 to +300°C	2.7mA (max)	-40 to +850	—	Stainless steel sheathed sensor with harness leads and connector



Part Number / Series	R0°C (Ohm)	Tolerance	Supply Current (mA)	Operating Temperature (°C)	Temperature Coefficient (ppm/K)	Package Type / Size (mm)
PTS1206	100R, 500R, 1K	0.3°C, 0.6°C	0.1	-55 to +175	3850	Surface Mount, 1206
PTS0805	100R, 500R	0.3°C, 0.6°C	0.1	-55 to +175	3850	Surface Mount, 0805
PTS0603	100R	0.3°C, 0.6°C	0.1	-55 to +175	3850	Surface Mount, 0603



SENSOR EVALUATION TOOLS

Evaluation Tools.....141

Amphenol
Advanced Sensors

amun



BOSCH
Invented for life

infineon

Melexis

muRata
INNOVATOR IN ELECTRONICS

NXP

ROHM
SEMICONDUCTOR

SENSIRION
THE SENSOR COMPANY

ST
life.augmented

VISHAY

Evaluation Board Part Number	Related Part Number / Series	Description
T6613-EVAL	T6613 Series	CO2 Sensor Evaluation Kit
T6615-EVAL	T6615 Series	Dual Channel CO2 Module Evaluation Kit
T6713-EVAL	T6713 Series	CO2 Sensor Module Evaluation Kit
T6713-5k-EVAL	T6713-5k	CO2 Module 0-5000 PPM Evaluation Kit
AAS-AQS-UNO	SM-PWM-01C	Air Quality Evaluation Board (Base & Dust)
AAS-AQS-UNO-RH-CO2	SM-PWM-01C, T9602, T6713	Air Quality Evaluation Board (Base, CO2, RH, T & Dust)
A-2130	CL Series	Inrush Current Limiter Kit



Evaluation Board Part Number	Related Part Number / Series	Description
AS5050A-QF_EK_AB	AS5050A	AS5050A Adaptor Board
AS5055A-QF_EK_AB	AS5055A	AS5055A Adaptor Board
AS5172B-TS_EK_AB	AS5172A/B	AS5172 Adaptor Board
AS5200L-MF_EK_AB	AS5200L	AS52200L Adaptor Board
AS5304-TS_EK_AB	AS5304	AS5304 Adaptor board
AS5306-TS_EK_AB	AS5306	AS5306 Adaptor Board
AS5311-TS_EK_AB	AS5311	AS5311 Adaptor Board
AS5510-S0_EK_AB	AS5510	AS5510 SOIC8 Adapterboard
AS5510-WL_EK_AB	AS5510	AS5510 WLCSP Adapterboard
AS5510-WL_EK_DB	AS5510	AS5510 Demoboard
AS5600L-S0_EK_AB	AS5600L	AS5600L Adapterboard (SOIC8)
AS5600L-WL_EK_AB	AS5600L	AS5600L Adapterboard (WLCSP)
AS6200-WL_DK_ST	AS6200	AS6200 Development Kit
AS6200-WL_EK_AB	AS6200	AS6200 Adaptor Board
AS6200C-WL_EK_AB	AS6200C	Digital temperature sensor eval kit
AS6200C-WL_EK_AB	AS6200C	Digital temperature sensor eval kit
AS7000_DEMOKIT	AS7000	AS7000 Demokit
AS7000_RETROFITBOARD	AS7000	AS7000 Retrofitboard
AS7024_ADD-ON BOARD	AS7024	AS7024 Add-On Board
AS7024-EVALKIT	AS7024	EvalKit for AS7024
AS7024-WRISTBAND	AS7024	Wristband with AS7024
AS7261 DEMO KIT	AS7261	Demo Kit AS7261 - iSPI v3
AS7262 DEMO KIT	AS7262	Demo Kit AS7262 - iSPI v3
AS7263 DEMO KIT	AS7263	Demo Kit AS7263 - iSPI v3
AS7264N DEMO KIT	AS7264N	Demo Kit AS7264N - iSPI v3
AS7265X DEMO KIT	AS7265x	Demo Kit AS7265x Multispect chipset v3



Evaluation Board Part Number	Related Part Number / Series	Description
CCS811-LG_EK_ST	CCS811	CCS811 Evaluation kit
CMV50000_COLOR_EK	CMV50000	CMV50K color evaluation kit
CMV50000_MONO_EK	CMV50000	CMV50K monochrome evaluation kit
CMV8000 EVALUATION K	CMV8000	CMV8000 EVALUATION KIT
EVALBOARD_DRAGSTER	DR16K	EvalBoard Dragster
EVALBOARD_DRAGSTER	DR2K7	EvalBoard Dragster
EVALBOARD_DRAGSTER	DR4K3.5	EvalBoard Dragster
EVALBOARD_DRAGSTER	DR4K7	EvalBoard Dragster
EVALBOARD_DRAGSTER	DR6K7	EvalBoard Dragster
EVALBOARD_DRAGSTER	DR8K3.5	EvalBoard Dragster
EVALBOARD_DRAGSTER	DR8K7	EvalBoard Dragster
ENS210-QF_EK_ST	ENS210	ENS210 Demo Kit
ENS210-QF_EK_ST	ENS210	ENS210 Demo Kit
ENS210-QF_EK_ST	ENS210	ENS210 Demo Kit
NANOUSB2.2	NanEye Module	NanEye USB2.0 Eval Kit
NanEye_FOB_2.0	NanEye Module	NanEye Fiber Optic Box 2.0
NANOUSB2.2	NanEye-Stereo Module	NanEye USB2.0 Eval Kit
NanEye_FOB_2.0	NanEye-Stereo Module	NanEye Fiber Optic Box 2.0
PCAP02-EVA MODULE	PCAP02AE	PCap02-EVA-AD V1.0 plug-in module
PCAP02-EVA-KIT V1.0	PCAP02AE	PCap02-EVA-KIT V1.0
PCAP04-EVA-BOARD	PCAP04	PCap04-EVA-BOARD
PCAP04-EVA-KIT	PCAP04	PCap04-EVA-KIT V1.0
TCS3400-EVM	TCS34003	Evaluation module for the TCS3400
TCS3400-DB	TCS34003	Daughter board for the TCS3400
TCS3400-EVM	TCS34303	Evaluation module for the TCS3400
TCS3400-DB	TCS34303	Daughter board for the TCS3400
TCS3472 EVM REV. 2.0	TCS34721	TCS3472 EVM Rev. 2.0
TCS3472 EVM REV. 2.0	TCS34723	TCS3472 EVM Rev. 2.0
TCS3701-DB	TCS3701	Daughter board for the TCS3701
TCS3701-EVM	TCS3701	Evaluation module for the TCS3701
TMD2620-EVM	TMD2620	Evaluation module for the TMD2620
TMD2620-DB	TMD2620	Daughter board for the TMD2620
TMD2672EVM	TMD2672	TMD2672 Evaluation Module
TMD2725-DB	TMD27253	Daughter board for the TMD2725
TMD2725-EVM	TMD27253	Evaluation module for the TMD2725
TMD2772EVM	TMD27721	TMD2772 Evaluation Module
TMD2772-DB	TMD27721	TMD2772x Daughter Board
TMD2772EVM	TMD27723	TMD2772 Evaluation Module
TMD2772-DB	TMD27723	TMD2772x Daughter Board



Evaluation Board Part Number	Related Part Number / Series	Description
TMD3702VC-DB	TMD37024VC	Daughter board for the TMD3702VC
TMD3702VC-EVM	TMD37024VC	Evaluation module for the TMD3702VC
TMG3992-DB	TMG39921	Daughter Board for the TMG3992x
TMG3992EVM	TMG39921	Evaluation Module for the TMG3992x
TMG3992-DB	TMG39923	Daughter Board for the TMG3992x
TMG3992EVM	TMG39923	Evaluation Module for the TMG3992x
TMG3993EVM	TMG39931	Evaluation Module for the TMG3993xFN
TMG3993EVM	TMG39933	Evaluation Module for the TMG3993xFN
TMG4903 EVM REV. 2.0	TMG49033	TMG4903 EVM Rev. 2.0
TSL2540-DBX	TSL25403	Daughter board for the TSL2540
TSL2540-EVMX	TSL25403	Evaluation module for the TSL2540
TSL2591X EVM	TSL25911	TSL2591x EVM Rev. 3.0
TSL2591X EVM	TSL25913	TSL2591x EVM Rev. 3.0
TSL2740-DB	TSL27403	Daughter board for the TSL2740
TSL2740-EVM	TSL27403	Evaluation module for the TSL2740
TSL2771EVM2	TSL27721	TSL2771x Evaluation Module
TSL2771EVM2	TSL27723	TSL2771x Evaluation Module



Evaluation Board Part Number	Related Part Number / Series	Description
BMA253 shuttle board	BMA253	The BMA253 PCB Shuttle Board (includes BMA253 acceleration sensor)
BMA280 shuttle board	BMA280	The BMA280 PCB Shuttle Board (includes BMA280 acceleration sensor)
BMA423 shuttle board	BMA423	The BMA423 PCB Shuttle Board (includes BMA423 acceleration sensor)
BMA456 shuttle board	BMA456	The BMA456 PCB Shuttle Board (includes BMA456 acceleration sensor)
BMA400 shuttle board	BMA400	The BMA400 PCB Shuttle Board (includes BMA400 acceleration sensor)
BMM150 shuttle board	BMM150	The BMM150 PCB Shuttle Board (includes BMM150 Magnetometer)
BMG250 shuttle board	BMG250	The BMG250 PCB Shuttle Board (includes BMG250 gyroscope)
BMI055 shuttle board	BMI055	The BMI055 PCB Shuttle Board (includes BMI055 Inertial Measurement unit)
BMI085 shuttle board	BMI085	The BMI085 PCB Shuttle Board (includes BMI085 Inertial Measurement unit)
BMI088 shuttle board	BMI088	The BMI088 PCB Shuttle Board (includes BMI088 Inertial Measurement unit)
BMI160 shuttle board	BMI160	The BMI160 PCB Shuttle Board (includes BMI160 Inertial Measurement unit)
BMX055 shuttle board	BMX055	The BMX055 PCB Shuttle Board (includes BMX055 integrated 9-axis sensor)
BMX160 shuttle board	BMX160	The BMX160 PCB Shuttle Board (includes BMX160 integrated 9-axis sensor)
BHA250 shuttle board	BHA250	The BHA250 PCB Shuttle Board (includes BHA250 smart sensor hub)
BHI160 shuttle board	BHI160	The BHI160 PCB Shuttle Board (includes BHI160 smart sensor hub)
BHI260 shuttle board	BHI260	The BHI260 PCB Shuttle Board (includes BHI260 smart sensor hub)

Evaluation Board Part Number	Related Part Number / Series	Description
BN0055 shuttle board	BN0055	The BN0055 PCB Shuttle Board (includes BN0055 absolute orientation sensor)
BMF055 shuttle board	BMF055	The BMF055 PCB Shuttle Board (includes BMF055 custom programmable 9-axis motion sensor)
BMP280 shuttle board	BMP280	The BMP280 PCB Shuttle Board (includes BMP280 pressure sensor)
BMP388 shuttle board	BMP388	The BMP388 PCB Shuttle Board (includes BMP388 pressure sensor)
BME280 shuttle board	BME280	The BME280 PCB Shuttle Board (includes BME280 combined humidity and pressure sensor)
BME680 shuttle board	BME680	The BME680 PCB Shuttle Board (includes BME680 environmental sensor)



Evaluation Board Part Number	Related Part Number / Series	Description
S2GO_CUR-SENSE_TLI4970	TLI4970-D050T4	Infineon's S2Go_CurrentSenseTLI4970 boards offer a unique customer and evaluation experience – the boards are equipped with one TLI4970 current sensor and come with a ready to use Arduino library. Customers can now develop their own system solutions by combining Shield2Go boards together with Infineon My IoT adapters. My IoT adapters are gateways to external hardware solutions like Arduino and Raspberry Pi, which are popular IoT evaluation platforms. All this enables the fastest evaluation and development of IoT system on the market.
TLI4970050 MS2GO	TLI4970-D050T4	The Current Sensor 2GO is a budget-priced evaluation board equipped with a current sensor combined with an ARM® Cortex™-M0 CPU. The Current Sensor 2GO has a complete set of on-board devices, including an on-board debugger. Build your own application and gadget with the Current Sensor 2GO.
S2GO PRESSURE DPS310	DPS310	S2Go_Pressure_DPS310 is an Arduino shield including DPS310. It comes together with Arduino library and it is pin-to-pin compatible with Infineon XMC2Go MCU board and can be easily connected to different Arduino boards by using Infineon Shield 2Go Adapter.
EVAL SHSBV03SPI	DPS310	Shuttle board DPS310 SPI
KIT DPS310 2G SHV02	DPS310	Infineon wireless sensor hub 2.0
EVAL SHNBV01	DPS310	Infineon sensor hub nano hosts one DPS310 barometric pressure sensor and XMC1000 32-bit ARM Cortex-M0 MCU. The sensor hub nano can communicate to PC or Android™ smart phone wirelessly, thanks to integrated Bluetooth™ 4.0 and battery. Infineon sensor hub nano can be used for quick testing and evaluation of DPS310 in the final application and it works as a platform to develop Android apps.
EVAL_IM69D120_FLEXKIT	IM69D120	The flex evaluation kit allows simple and easy evaluation of XENSIV™ MEMS microphone IM69D120. The flex board can be easily connected to audio testing setup. The evaluation kit includes five IM69D120 mounted on flex board and one adapter board.
EVAL_IM69D130_FLEXKIT	IM69D130	The flex evaluation kit allows simple and easy evaluation of XENSIV™ MEMS microphone IM69D130. The flex board can be easily connected to audio testing setup. The evaluation kit includes five IM69D130 mounted on flex board and one adapter board.
S2GO MEMSMIC IM69D	IM69D130	Infineon's Shield2Go boards offer a unique customer and evaluation experience – the boards are equipped with two High-performance digital MEMS Microphone IM69D130 and come with a ready to use Arduino library. Customers can now develop their own system solutions by combining Shield2Go boards together with Infineon My IoT adapters. My IoT adapters are gateways to external hardware solutions like Arduino and Raspberry Pi, which are popular IoT hardware platforms. All this enables the fastest evaluation and development of IoT system.
TLV493D-A1B6 MS2GO	TLV493D-A1B6	The 3D Magnetic Sensor 2GO is a budget-priced evaluation board equipped with a magnetic sensor for three dimensional measurement combined with an ARM® Cortex™-M0 CPU. The 3D Magnetic Sensor 2GO has a complete set of on-board devices, including an on-board debugger. Build your own application and gadget with the 3D Magnetic Sensor 2GO.
SP001491834	All 3D magnetic sensor ICs	Joystick for 3D 2 Go Eval Board
SP001504602	All 3D magnetic sensor ICs	Rotate knob for 3D 2 Go Eval Board

OSSO

Bad to the Bone



Locate Your Furry Friends Anywhere!

No more waiting to feel it in your bones...reduce time spent around the neighborhood locating your furry friends with OSSO! Future Electronics and STMicroelectronics are proud to collaborate on OSSO, an animal tracking device. OSSO uses a GPS module, the Teseo-LIV3F, to provide superior and reliable positioning accuracy to determine precise location.


Combined with a high-performance MEMS sensor fusion and BLE 5.0 compliant IC, the multi-axis sensor systems enables accuracy for highly demanding applications such as indoor navigation and location-based services. OSSO helps you to locate your pet anytime, anywhere. See the exact location of your dog or cat directly on your smart devices.

Features:

- Small and lightweight
- AAA battery
- Real-time tracking with GPS/ GNSS module
- Bluetooth 5.0 compliant IC
- Offline tracking with serial flash

The following STMicroelectronics parts were used to develop OSSO:

- GNSS/GPS module: Teseo-LIV3F
- Bluetooth low energy 5.0 IC: BlueNRG-2
- NFC Tag: M24SR64
- Balun: BALF-NRG-02D3
- Humidity and temperature sensor: HTS221TR
- Gyro/accelerometer MEMS module: LSM6DSLTR
- Synchronous rectifier step-up converter: L6920DB
- LDO: LDS3985





Evaluation Board Part Number	Related Part Number / Series	Description
TLE493D-W2B6 MS2GO	TLE493D-W2B6	The 3D Magnetic Sensor 2GO is a budget-priced evaluation board equipped with a magnetic sensor for three dimensional measurement combined with an ARM® Cortex™-M0 CPU. The 3D Magnetic Sensor 2GO has a complete set of on-board devices, including an on-board debugger. Build your own application and gadget with the 3D Magnetic Sensor 2GO.
TLE493D-A2B6 MS2GO	TLE493D-A2B6	The 3D Magnetic Sensor 2GO is a budget-priced evaluation board equipped with a magnetic sensor for three dimensional measurement combined with an ARM® Cortex™-M0 CPU. The 3D Magnetic Sensor 2GO has a complete set of on-board devices, including an on-board debugger. Build your own application and gadget with the 3D Magnetic Sensor 2GO.
S2GO_3D-SENSE_TLV493D	TLV493D-A1B6	Infineon's S2Go_3DSense_TLV493D boards offer a unique customer and evaluation experience – the boards are equipped with one TLV493D-A1B6 magnetic sensor and come with a ready to use Arduino library. Customers can now develop their own system solutions by combining Shield2Go boards together with Infineon My IoT adapters. My IoT adapters are gateways to external hardware solutions like Arduino and Raspberry Pi, which are popular IoT evaluation platforms. All this enables the fastest evaluation and development of IoT system on the market
ROTATE KNOB 3D 2 GO KIT	TLV493D-A1B6, TLE493D-A2B6 and TLI493D-A2B6	Rotate and push button control element for 3D Magnetic Sensor 2GO Family. For 3D Magnetic Sensors: TLV493D-A1B6, TLE493D-A2B6 and TLI493D-A2B6.
LINEAR-SLIDER 2GO	TLV493D-A1B6, TLE493D-A2B6 and TLI493D-A2B6	Linear Slider Adapter for 3D Magnetic Sensor 2GO Family. For 3D Magnetic Sensors: TLV493D-A1B6, TLE493D-A2B6 and TLI493D-A2B6.
JOYSTICK FOR 3D 2 GO KIT	TLV493D-A1B6, TLE493D-A2B6 and TLI493D-A2B6	Joystick adapter for 3D Magnetic Sensor 2GO Family. For 3D Magnetic Sensors: TLV493D-A1B6, TLE493D-A2B6 and TLI493D-A2B6.
DEMO SENSE2GOL	BGT24LTR11	Evaluation board to perform basic measurements with BGT24LTR11. Kit contains: Application Note and Evaluation PCB.
EVAL BGT24LTR11 BOARD	BGT24LTR11	Evaluation board to perform basic measurements with BGT24LTR11
DEMO DISTANCE2GO	BGT24MTR11	Radar demo board based on the BGT24MTR11– FMCW & Doppler (distance, speed, and direction of movement detection)
KIT_ATV_24GHZ_RADAR	BGTA24ATR12	This development kit allows customers to implement and test 24GHz radar applications as Doppler movement detectors, FSK or FMCW range/position measurement. It comprises a BGT24A transceiver MMIC family, e.g. BGTA24ATR12, and an AURIX™ 32-bit radar microcontroller family, e.g. SAK-TC264DA- 40F200, for high-performance signal processing. The device has an FFT acceleration engine and extended memory for radar image storage.
TLE4997X PROGRAMMER KIT	TLE4997	The kit consists of a PGSSI box (programming interface) and an evaluation board which allows evaluation of the linear Hall TLE 4997 family.
TLE4998X PROGRAMMER KIT	TLE4998	The kit consists of a PGSSI box (programming interface) and an evaluation board which allows evaluation of the linear Hall TLE 4998 family.



Evaluation Board Part Number	Related Part Number / Series	Description
EV75030-V2	MLX75030	Evaluation board for MLX75030 universal active light interface (Includes MLX75030 EvalBoard v2.0; EVB75030BB10, EVB75030LRP11, EVB75030CC95; Evaluation Software (+access to source codes)
EVK75123-60-850-1	MLX75023, MLX75123	Evaluation board for MLX75023 and MLX75123, TOF chipset; 60deg FOV, 850nm VCSELs (Includes EVK75123)
EVK75123-110-850-1	MLX75023, MLX75123	Evaluation board for MLX75023 and MLX75123, TOF chipset; 110deg FOV, 850nm VCSELs (Includes EVK75123)
DVK91205	MLX91205	MLX91205 Development kit (Includes: 1 x MLX91205LB mounted on PCB_EC01; 1 x MLX91205LB mounted on PCB_EC02; 1 x separate MLX91205LB; 3 x separate MLX91205HBs; 1 x separate PCB_EC01; 1 x separate PCB_EC02; 2 x shields U_12)
DVK91206	MLX91206	MLX91206 Development kit (Includes 1 sample each of MLX91206-CAH-001, MLX91206-CAH-002, MLX91206-CAH-003, MLX91206-CAL-001, MLX91206-CAL-002, MLX91206-CAL-003; 1 each of PCB_EC01, PCB_EC02, PCB_EC03; 3 shields U_12)

Evaluation Board Part Number	Related Part Number / Series	Description
DVK91207	MLX91207	MLX91207 Development kit (Includes 2 MLX91207 mounted on PCB; 2 MLX91207; 2 PCB; 1 core for high current; 1 core for low current)
EVB90614	MLX90614	Evaluation Board for MLX90614 Infrared Thermometer Module board (includes supply, USB cable, manual, software)
EVB90640-41	MLX90640, MLX90641	Evaluation Board for MLX90640 and MLX90641 Infrared Thermometer Module board (includes supply, USB cable, 1 sensor, software)
DVK91208	MLX91208	MLX91208 Development kit (Includes 3 samples each of MLX91208-CAH, MLX91208-CAL; 1 each PCB_EC01, PCB_EC02, PCB_EC03; 3 shields U_12; 2 shields R_12)
DVK91209	MLX91209	MLX91209 Development kit (Includes 5 each MLX91209-CA; 3 separated bare PCBs; 3 ferromagnetic cores (Supra 50 SP)
EVB75030-V2	MLX75030	Evaluation board for MLX75030 universal active light interface (Includes MLX75030 EvalBoard v2.0; EVB75030BB10, EVB75030LRP11, EVB75030CC95; Evaluation Software (+access to source codes)
EVK75123-60-850-1	MLX75023, MLX75123	Evaluation board for MLX75023 and MLX75123, TOF chipset; 60deg FOV, 850nm VCSELs (Includes EVK75123)
EVK75123-110-850-1	MLX75023, MLX75123	Evaluation board for MLX75023 and MLX75123, TOF chipset; 110deg FOV, 850nm VCSELs (Includes EVK75123)
DVK91205	MLX91205	MLX91205 Development kit (Includes: 1 x MLX91205LB mounted on PCB_EC01; 1 x MLX91205LB mounted on PCB_EC02; 1 x separate MLX91205LB; 3 x separate MLX91205HBs; 1 x separate PCB_EC01; 1 x separate PCB_EC02; 2 x shields U_12)
DVK91206	MLX91206	MLX91206 Development kit (Includes 1 sample each of MLX91206-CAH-001, MLX91206-CAH-002, MLX91206-CAH-003, MLX91206-CAL-001, MLX91206-CAL-002, MLX91206-CAL-003; 1 each of PCB_EC01, PCB_EC02, PCB_EC03; 3 shields U_12)
DVK91207	MLX91207	MLX91207 Development kit (Includes 2 MLX91207 mounted on PCB; 2 MLX91207; 2 PCB; 1 core for high current; 1 core for low current)
DVK91208	MLX91208	MLX91208 Development kit (Includes 3 samples each of MLX91208-CAH, MLX91208-CAL; 1 each PCB_EC01, PCB_EC02, PCB_EC03; 3 shields U_12; 2 shields R_12)
DVK91209	MLX91209	MLX91209 Development kit (Includes 5 each MLX91209-CA; 3 separated bare PCBs; 3 ferromagnetic cores (Supra 50 SP)
DVK91210 - SOIC8	MLX91210	MLX91210KDC-CAS-101 Evaluation board; SOIC8 [+/-25A full scale] (Includes 1 board populated with sample + 3 extra samples)
DVK91210 - SOIC16	MLX91210	MLX91210KDF-CAS-101 Evaluation board; SOIC16 [+/-25A full scale] (Includes 1 board populated with sample + 3 extra samples)
EVB922xx	MLX92232	MLX92232 Evaluation board (Includes 5 each of MLX92232LUA, MLX92232LSE)
PTC-04	MLX90xxx, MLX91xxx	Programmer for Melexis devices. Includes: main board in metal case; power supply 100W switching adapter; USB and RS232 cable; CD
PTC-04-19-4	MLX90xxx	19" Rack with two supply units and four PTC04 programmers; Universal implementation; Corresponding Daughter boards to be ordered additionally. (Note: When the rack is ordered together with the corresponding PTC04 daughter boards, the latter will be integrated inside the PTC04's by Melexis before shipment)
PTC-04-DB-90316	MLX90xxx	Daughter board for PTC-04 programmer for all Triaxis products
PTC-04-DB-HALL01	MLX90251; MLX90215; MLX90277; MLX90244	Daughter board for PTC-04 programmer
PTC-04-DB-HALL02	MLX90264, MLX90275	Daughter board for mounting in PTC-04 programmer
PTC-04-DB-HALL03	MLX90288, MLX90291, MLX91206, MLX91207	Daughter board for mounting in PTC-04 programmer
PTC-04-DB-HALL05	MLX91208; MLX91209	Daughter board for mounting in PTC-04 programmer
PTC-04-DB-Debug	MLX90xxx, MLX91xxx	Universal debugging daughter board
PTC-04-DB-Calib	MLX90xxx, MLX91xxx	Supporting daughter board for calibration of PTC04 programmer
PTC-04-DB-SPI01	MLX90xxx	Daughter board for PTC-04 programmer for SPI Hall sensors
PTC04-DB-Mupet	MLX90xxx, MLX91xxx	Melexis Universal Program & Test protocol daughter boards



Evaluation Board Part Number	Related Part Number / Series	Description
PTC04-DB-922xx	MLX922xx	Supporting daughter board to interface with the programmable switch & latch family
PTC04_DB_Pressure01	MLX90807, MLX90808	Daughter board for mounting in PTC-04 programmer
PTC04_sensors_multi_calibration_board	MLX90xxx	Extension board for PTC-04 that allows the calibration of sensors in parallel
PTC-testbench-MLX90316	MLX90316	Testbench for MLX90316 (Includes 2 magnets; socket for MLX90316 TestBench; 1 Socket PCB; 1 Connection cable)
PTC-testbench-Magnetic	MLX90277, MLX90251, MLX90215	Testbench for magnetic devices (Includes 3 magnets; sockets for MLX90277, MLX90251, MLX90215 TestBench; 2 Socket PCB's (4SIP, S08, TSSOP16); 1 Connection cable; 3 magnets)
PTC-04-19-1	MLX90xxx, MLX91xxx	1 PTC04 in 19" Rack
PTC-04-19-2	MLX90xxx, MLX91xxx	2 PTC04 in 19" Rack



Evaluation Board Part Number	Related Part Number / Series	Description
MTHMR-N-002A	NTC family	NTC Thermistor Evaluation Board
IMX-070	PIR family	Pyroelectric Infrared Sensor Evaluation Board with Fresnel Lens
MEMS-EVAL-Board	—	MEMS Interface Board
SCA3100-D04-PCB	SCA3100-D04	Sensor Board for SCA3100-D04 Digital Accelerometer 3 Axis Accel Range $\pm 2g$
SCA3100-D07-PCB	SCA3100-D07	Sensor Board for SCA3100-D07 Digital Accelerometer 3 Axis Accel Range $\pm 6g$
SCA3300-PCB	SCA3300-D01	Sensor Board for SCA3300-D01 Digital Accelerometer 3 Axis Accel Range $\pm 1.5g, \pm 3g, \pm 6g$
SCA100T-D01-PCB	SCA100T-D01	Sensor Board for SCA100T-D01 Analog Inclinator, ± 30 deg range
SCA100T-D02-PCB	SCA100T-D02	Sensor Board for SCA100T-D02 Analog Inclinator, ± 90 deg range
SCA103T-D04-PCB	SCA103T-D04	Sensor Board for SCA103T-D04 Analog Inclinator, ± 15 deg range
SCA103T-D05-PCB	SCA103T-D05	Sensor Board for SCA103T-D05 Analog Inclinator, ± 30 deg range
SCC2130-D08-PCB	SCC2130-D08	Sensor Boards for SCC2130-D08 3 Axis Accel Range $\pm 6g$ and X Axis Gyro 125dps
SCC2230-E02-PCB	SCC2130-D08	Sensor Boards for SCC2130-D08 3 Axis Accel Range $\pm 2g$ and X Axis Gyro 125dps



Evaluation Board Part Number	Related Part Number / Series	Description
FRDM-K22F-AGM01	FXOS8700CQ, FXAS21002CQ	Demonstration Kit
FRDM-K64F-AGM01	FXOS8700CQ, FXAS21002CQ	Demonstration Kit
FRDM-STBC-AGM01	FXOS8700CQ, FXAS21002CQ	Shield Board
BRKT-STBC-AGM01	FXOS8700CQ, FXAS21002CQ	Breakout Board
FRDMKL25-A8471	FXLS8471Q	Demonstration Kit
FRDMSTBC-A8471	FXLS8471Q	Shield Board



Evaluation Board Part Number	Related Part Number / Series	Description
BRKTSTBC-A8471	FXLS8471Q	Breakout Board
FRDMKL25-A8491	MMA8491Q	Demonstration Kit
FRDMSTBC-A8491	MMA8491Q	Shield Board
BRKTSTBC-A8491	MMA8491Q	Breakout Board
FRDM-FXS-MULT2-B	FXLS8471Q, FXOS8700CQ, MMA8652Q, FXAS-21002CQ, MPL3115A2	Shield Board
RD-KL25-AGMP01	FXOS8700CQ	Reference Design
FRDM-KL25Z	MMA8451Q	Demonstration Kit
FRDM-KL27Z	MMA8451Q	Demonstration Kit
FRDMSTBC-A8451	MMA8451Q	Shield Board
BRKTSTBC-A8451	MMA8451Q	Breakout Board
FRDM-K64F-AGM04	MMA8652Q, FXAS21002Q	Demonstration Kit
FRDM-STBC-AGM04	MMA8652Q, FXAS21002Q, MAG3110	Shield Board
BRKT-STBC-AGM04	MMA8652Q, FXAS21002Q	Breakout Board
FRDMKL25-P3115	MPL3115A2	Demonstration Kit
FRDMSTBC-P3115	MPL3115A2	Shield Board
BRKTSTBC-P3115	MPL3115A2	Breakout Board
FRDM-K22F-AGMP03	FXLS8962AF, FXAS21002CQ, MPL3115A2	Demonstration Kit
FRDM-STBC-AGMP03	FXLS8962AF, FXAS21002CQ, MPL3115A2	Shield Board
BRKT-STBC-AGMP03	FXLS8962AF, FXAS21002CQ, MPL3115A2	Breakout Board
FRDMKE06DP5004	MPXV5004DP	Demonstration Kit
BRKTSTBCDP5004	MPXV5004DP	Breakout Board
935308627598	935307303515; 935307749012; 935308967005	NHS3100 Starter kit for temperature monitoring (also NHS3100 general starter kit)
935308627598	935307865515; 935307926012	NHS3152 General starter kit

SENSOR EVALUATION TOOLS



Evaluation Board Part Number	Related Part Number / Series	Description
SensorShield-EVK-003	KX224-1053 Accel, BM1383AGLV Barometric Pressure Sensor, BM1422AGMV Geomagnetic Sensor, RPR-0521RS ALS/PROX Sensor, BH1749NUC Color Sensor, BD7411G Hall Switch Sensor, BD1020HFV Temperature Sensor, BH1790GLC HRM Sensor	Sensor Shield Evaluation Platform; Arduino/MBED Interface; 8 Featured Sensors
KX224-I2C-EVK-001	KX224-1053 Accel	Breakout Board for KX224 Accelerometer
BM1383AGLV-EVK-001	BM1383A Barometric Pressure Sensor	Breakout Board for BM1383A Barometric Pressure Sensor
BM1422AGMV-EVK-001	BM1422AGMV Geomagnetic Sensor	Breakout Board for BM1422AGMV Geomagnetic Sensor
RPR-0521RS-EVK-001	RPR-0521RS ALS/PROX	Breakout Board for RPR-0521RS ALS/PROX
BH1749NUC-EVK-001	BH1749NUC Color Sensor	Breakout Board for BH1749NUC Color Sensor
BD7411G-EVK-001	BD7411G Hall Switch Sensor	Breakout Board for BD7411G Hall Switch Sensor
BD1020HFV-EVK-001	BD1020HFV Temperature Sensor	Breakout Board for BD1020HFV Temperature Sensor
BH1790GLC-EVK-001	BH1790GLC HRM Sensor	Breakout Board for BH1790GLC HRM Sensor
BH1792GLC-EVK-001	BH1792GLC HRM Sensor	Breakout Board for BH1792GLC HRM Sensor



Evaluation Board Part Number	Related Part Number / Series	Description
SEK-SCD30	SCD30	Includes 1x SEK Sensor Bridge, 1x SCD30 on FPCB, 1x adapter cable, 1x USB2.0 cable type A- Micro B
SEK-SPS30	SPS30	Includes 1x SEK Sensor Bridge, 1x SPS30 on FPCB, 1x adapter cable, 1x USB2.0 cable type A- Micro B
SEK-SGPC3	SGPC3, SHTxx, STSxx	Includes 1x SEK Sensor Bridge, 2x SGPC3 on FPCB, 1x SHTC3 on FPCB, 1x SHTW2 on FPCB, 1x SHT31-DIS-D, 1x STS31 on FPCB, 2x adapter cable, 1x USB2.0 cable type A- Micro B
SEK-SHTXX/SGP30	SGP3x, SHTxx, STSxx	Includes 1x SEK Sensor Bridge, 1x SGP30 on FPCB, 1x SHTC3 on FPCB, 1x SHTW2 on FPCB, 1x SHT31-DIS-B on FPCB, 1x STS31-DIS on FPCB, 2x adapter cable, 1x USB2.0 cable type A- Micro B
EK-F3x	SFM3000	Includes 1 x I ² C to USB connector, adapter cable to connect to sensor, downloadable software (sensor must be ordered separately)
EK-F4x	SFM4100	Includes 1 x I ² C to USB connector, adapter cable to connect to sensor, downloadable software (sensor must be ordered separately)
EK-P3	SDPxxx	Includes 1x SDP610; works with all digital SDP's
EK-P4	SDP3x only	Includes 1X SDP31 on PCB, 1x USB stick with adapter cable, 1x flow element
EK-P5	SDP8xx only	Includes 1x SDP810-500Pa, 1x sensor cable, 1x USB stick with adapter cable
EK-F3X	SFM3000/3200 only	Includes 1x I ² C to USB connector, adapter cable to connect to sensor, downloadable software (sensor must be sold separately)
SHT31 Smart Gadget Development kit	SHT31	Board with SHT31

Evaluation Board Part Number	Related Part Number / Series	Description
STEVAL-MKI180V1	LIS3DHH	LIS3DHH adapter board for a standard DIL 24 socket
STEVAL-MET001V1	LPS22HB	LPS22HB adapter board for a standard DIL 24 socket
STEVAL-MKI013V1	LIS302DL	Standard DIL 24 socket-compatible adapter board for testing the LIS302DL
STEVAL-MKI015V1	LIS344ALH	Adapter board for the LIS344ALH
STEVAL-MKI092V2	LIS331HHTR	LIS331HH adapter board for standard DIL24 socket
STEVAL-MKI105V1	LIS3DH	LIS3DH adapter board for standard DIL 24 socket
STEVAL-MKI109V2	STM32F103	eMotion: ST MEMS adapters motherboard based on STM32F103, compatible with all ST MEMS adapter boards
STEVAL-MKI110V1	AIS328DQ	AIS328DQ adapter board for standard DIL24 socket
STEVAL-MKI125V1	A3G4250D	A3G4250D adapter board for standard DIL 24 socket
STEVAL-MKI135V1	LIS2DH	LIS2DH adapter board for standard DIL24 socket
STEVAL-MKI136V1	L3GD20H	L3GD20H adapter board for standard DIL 24 socket
STEVAL-MKI137V1	LIS3MDL	LIS3MDL adapter board for standard DIL24 socket
STEVAL-MKI141V2	HTS221	HTS221 humidity sensor adapter board for standard DIL24 socket (full pinout)
STEVAL-MKI151V1	LIS2DH12	LIS2DH12 3-axis accelerometer adapter board for standard DIL 24 socket, compatible with STEVAL-MKI109V2
STEVAL-MKI153V1	H3LIS331DL	H3LIS331DL 3-axis digital accelerometer adapter board for standard DIL 24 socket, compatible with STEVAL-MKI109V2
STEVAL-MKI158V1	AIS3624DQ	AIS3624DQ adapter board for a standard DIL24 socket
STEVAL-MKI159V1	LSM9DS1	LSM9DS1 adapter board for standard DIL24 socket
STEVAL-MKI160V1	LSM6DS3	LSM6DS3 adapter board for standard DIL24 socket
STEVAL-MKI164V1	LIS2HH12	LIS2HH12 adapter board for a standard DIL24 socket
STEVAL-MKI165V1	LPS25HB	LPS25HB adapter board for a standard DIL 24 socket
STEVAL-MKI166V1	H3LIS100DL	H3LIS100DL adapter board for a standard DIL 24 socket
STEVAL-MKI167V1	H3LIS200DL	H3LIS200DL adapter board for a standard DIL 24 socket
STEVAL-MKI168V1	IIS2DH	IIS2DH adapter board for a standard DIL 24 socket
STEVAL-MKI169V1	I3G4250D	I3G4250D adapter board for a standard DIL 24 socket
STEVAL-MKI170V1	IIS328DQ	IIS328DQ adapter board for a standard DIL 24 socket
STEVAL-MKI172V1	LSM303AGR	LSM303AGR adapter board for a standard DIL 24 socket
STEVAL-MKI173V1	LSM303AH	LSM303AH adapter board for standard DIL24 socket
STEVAL-MKI174V1	LIS2DS12	LIS2DS12 adapter board for standard DIL24 socket
STEVAL-MKI175V1	LIS2DE12	LIS2DE12 adapter board for standard DIL24 socket
STEVAL-MKI176V1	LSM6DS3H	LSM6DS3H adapter board for standard DIL24 socket
STEVAL-MKI177V1	LPS35HW	LPS35HW adapter board for a standard DIL24 socket
STEVAL-MKI178V1	LSM6DSL	LSM6DSL adapter board for standard DIL24 socket
X-NUCLE0-CCA02M1	MP34DT01-M	Digital MEMS microphones expansion board based on MP34DT01-M for STM32 Nucleo.
X-NUCLE0-IKS01A2	LSM6DSM, LSM303AGR, LPS22HB, HTS221	Sensors expansion board for Nucleo kit containing motion, pressure, and humidity/temp sensors
STEVAL-STLCS01V1	BlueNRG-MS, LSM6DSM, LSM303AGR, LPS22HB, MP34DT04, BALF-NRG-01D3, LD39115J18R	SensorTile 13mm x 13mm connectable sensor node with plug on bottom side or solder

SENSOR EVALUATION TOOLS



Evaluation Board Part Number	Related Part Number / Series	Description
STEVAL-STLCS02V1	STM32L476, LSM6DSM, LSM303AGR, LPS22HB, MP34DT04, BlueNRG-MS, BALF-NRG-01D3, LD-39115J18R	SensorTile 13mm x 13mm solderable sensor node (no plug)
STEVAL-STLKT01V1	STM32L4; MP34DT04; LSM6DSM; LSM303AGR; LPS22HB; BlueNRG-MS	SensorTile development kit - complete kit with the sensor tile and cradle adapters
STSW-STLKT01	Embedded Software	Embedded software samples for SensorTile
STEVAL-BCNKT01V1	BlueNRG-MS, LSM6DSM, LSM303AGR, LPS22HB, BALF-NRG-01D3, STBC03JR	BlueCoin Starter kit
STSW-BCNKT01	Embedded Software	Embedded software samples for BlueCoin: data streaming via USB and BLE, logging on SD card, gesture recognition,
STEVAL-MKI139V5	MP23AB01DH	Microphone coupon board based on the MP23AB01DH fully differential analog MEMS microphone
STEVAL-MKI155V3	MP34DT01-M	Microphone coupon board based on the MP34DT01-M digital MEMS microphone
B-L475E-IOT01A	IOT Sensor Node	STM32L4 Discovery kit IoT node, low-power wireless, BLE, NFC, Sensors, SubGHz, Wi-Fi
P-NUCLEO-53LOA1	VL53LOX	VL53LOX Nucleo Pack - Includes VL53LOX Expansion board and STM32F401RE Nucleo
X-NUCLEO-53LOA1	VL53LOX	Ranging sensor expansion board based on VL53LOX for STM32 Nucleo



Evaluation Board Part Number	Related Part Number / Series	Description
SensorXplorer	SensorXplorer	Eval kit for I2C Sensor Products
VEML6030-SB	VEML6030	ALS demo board
VEML6040-SB	VEML6040A30G	R,G,B,W demo board
VCNL4040-SB	VCNL4040M3OE	Proximity/ALS demo board
VCNL4020-SB	VCNL4020-GS08	Proximity/ALS demo board
VCNL36687-SB	VCNL36687	Proximity sensor demo board
VCNL4035X01-SB	VCNL4035X01	Proximity/ALS demo board
VCNL4035X01-GES-SB	VCNL4035X01	Gesture demo board
VEML6070-SB	VEML6070	UVA demo board
VCNL4200-SB	VCNL4200	Long Distance Proximity/ALS demo board

Sense • Connect • Control

Get Connected with Future Connectivity Solutions



Empowering IoT Innovation

Wireless connectivity and the Internet of Things can open up new markets, new services and new revenue streams for your company. Let **Future Connectivity Solutions** help you do it!

www.FutureElectronics.com/our-solutions/IoT-solutions



Enabling Smart Agriculture Solutions

Future Connectivity Solutions offers a market-leading portfolio of products and complimentary, innovative devices to enable **Smart Agriculture** design requirements. Optimize crop harvesting and livestock health monitoring through key applications such as:

- Livestock Position and Health Monitoring
- Irrigation Sensing and Control
- Agriculture Products Tracking
- Tractor Positioning and Guidance Systems



Livestock Position and Health Monitoring	GPS/GNSS	Sub-1GHz or LoRa	Bluetooth Low Energy	RFID/NFC	Sensors
Irrigation Sensing and Control	Sub-1GHz or LoRa	Bluetooth Low Energy	RFID/NFC	Sensors	
Agricultural Products Tracking	GPS/GNSS	Sub-1GHz or LoRa	RFID/NFC	Sensors	
Tractor	Cellular	GPS/GNSS	Bluetooth Low Energy	RFID/NFC	Sensors

Enabling Smart Home Solutions

Future Connectivity Solutions offers a market-leading portfolio of products and complimentary, innovative devices to enable **Smart Home** design requirements. Improve home and building comfort, efficiency and security through key applications such as:

- Smart Appliances
- Smart Lighting
- Smart Locks and Doors
- Smart Thermostats



Appliances	Wi-Fi	Bluetooth Low Energy	RFID/NFC	Sensors
Lighting	Sub-1GHz	Bluetooth Low Energy	RFID/NFC	Sensors
Smart Locks/ Door/Alarm	Cellular	RFID/NFC	Sensors	
Thermostat	Thread	Bluetooth Low Energy	RFID/NFC	Sensors

Enabling Smart Industry Solutions

Future Connectivity Solutions offers a market-leading portfolio of products and complimentary, innovative devices to enable **Smart Industry** design requirements. Ensure a safer, more efficient and environmentally friendly factory and workplace through key applications such as:



- Asset Tracking
- Access Control
- Smart Locks and Doors
- Cold Chain Monitoring
- Predictive Maintenance

Asset Tracking	Cellular	GPS/GNSS	Bluetooth Low Energy	RFID/NFC	Sensors
Access Control	Cellular	RFID/NFC	Sensors		
Smart Locks and Doors	Wi-Fi	Bluetooth Low Energy	RFID/NFC	Sensors	
Cold Chain Monitoring	Cellular	Sensors			
Predictive Medicine	Bluetooth Low Energy	W-iFi	LoRa	Sub-GHz	Sensors

Enabling Smart Health Solutions

Future Connectivity Solutions offers a market-leading portfolio of products and complimentary, innovative devices to enable **Smart Health** design requirements. Improve personal and patient health and wellness, medical monitoring and care delivery platforms through key applications such as:



- Wearables
- Hearables
- Glucose Meters
- Smart Pillbox

Wearables	GPS/GNSS	Wi-Fi	Bluetooth Low Energy	RFID/NFC	Sensors
Hearables	NFMI	Bluetooth Low Energy	RFID/NFC	Sensors	
Glucose Meter	Bluetooth Low Energy	RFID/NFC	Sensors		
Smart Pillbox	Cellular	Sensors	Sensors		



From Low Power Sensor to Low Power System


The **LSM6DSOX** contains a 3D MEMS accelerometer and 3D MEMS gyroscope, and tracks complex movements using the machine-learning core at low typical current consumption of just 0.55mA to minimize load on the battery. Relieving this first stage of activity tracking from the main processor saves energy and accelerates motion-based apps such as fitness logging, wellness monitoring, personal navigation, and fall detection.

The machine-learning core works in conjunction with the sensor's integrated finite-state machine logic to handle motion pattern recognition or vibration detection.

Best in class Inertial Measurement Unit (IMU)
Power Consumption (0.55 mA combo mode HP)
10 to 1000 times energy saving by running Machine Learning on Sensor HW (vs. AP)

Simplified and Lean System Concept based on 2 mainstems:

1. Configurable power mode and high speed communication
2. Flexible HW solution running accurate algorithms



life.augmented

www.st.com

SENSOR APPLICATION SELECTOR

Suppliers

	Accelerometer	Acoustic	Air Quality / Gas	Biosensor	Environmental Combo	Flow	Gyro / Angular Rate	Humidity	Image / 3D	Inertial Combo	Light / Color	Magnetic/Hall	Occupancy / Motion	Optical Combo	Position / Speed	Pressure	Proximity	Temperature
Amphenol Advanced Sensors			✓					✓								✓		✓
ams			✓			✓		✓	✓		✓	✓		✓	✓		✓	✓
Bosch Sensortec	✓		✓		✓		✓			✓		✓				✓		
Crocus Technology												✓						
Cypress																	✓	
Diodes												✓						
FLIR									✓									
IDT			✓			✓		✓							✓			
Infineon		✓										✓	✓		✓	✓	✓	
Maxim Integrated				✓		✓												✓
Melexis Technologies									✓			✓	✓		✓	✓		✓
Microchip																		✓
Monolithic Power												✓			✓			
Murata	✓	✓					✓			✓		✓	✓		✓			✓
NXP Semiconductors	✓						✓			✓		✓			✓	✓		✓
ON Semiconductor								✓	✓		✓						✓	✓
Panasonic													✓			✓		
Renesas											✓			✓			✓	
ROHM	✓			✓			✓			✓	✓	✓		✓		✓	✓	✓
Semtech																	✓	
Sensirion			✓			✓		✓								✓		✓
STMicroElectronics	✓	✓					✓	✓		✓		✓				✓	✓	✓
TE Sensor Solutions	✓					✓	✓	✓							✓	✓		✓
Truly									✓									
Vishay											✓	✓		✓	✓		✓	✓



NEBULA IoT

REFERENCE DESIGN BOARD

As an innovative industry leader, Future Electronics has partnered with Cypress and Murata to develop this reference board to assist with our customers' IoT needs.

- Wireless connectivity is supported by the Murata 1DX module which houses the Cypress-based CYW4343W Wi-Fi and Bluetooth Classic (BR/EDR)/BLE chipset radio.
- Nebula contains an STM32F429, an ARM Cortex-M4, with 32 bit RISC core, 2MB Flash and up to 256kB SRAM.
- Nebula supports application development through Cypress' WICED® (Wireless Internet Connectivity for Embedded Devices) platform.
- The board is equipped with 4 different interfaces to access the STM32F429 peripherals to enable developers to create any IoT application: Arduino™ Compatible Shield, mikro BUS™ Socket, Pmod™ Type 2A, USB Device.

- Nebula explores easy hardware expandability through a large number of standardized add-on boards via these connectors.



NEB1DX-01

To purchase a **Nebula board** go to:
www.futureelectronics.com/nebula



www.FutureElectronics.com/Sensors

